

RADIO TEST REPORT

Report ID

REP098185

Project ID

PRJ0078203

Type of assessment:

MPE Calculation report

Applicant:

JDRF Electromag Engineering Inc.

Description of product:

Lighting control system for smart lighting application

Model(s)/HVIN(s):

JDRF-EAS, JDRF-AS, JDRF-EASLB, JDRF-ASLB

Product marketing name (PMN):

Autonomy Sensor

FCC identifier:

FCC ID: 2A22O-JDRFAS

ISED certification number:

IC: 24973-JDRFAS

Specification:

- ◆ FCC 47 CFR Part 1 Subpart I, §1.1307, §1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06
- ◆ ISED Canada RSS-102 Issue 6 (December 2023)

RSS-102 Annex A

ATTESTATION: I attest that the information provided in Annex A is correct; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the applicable RF exposure limits set forth in RSS-102.

Date of issue: **September 8, 2025****Ketav Jani, EMC/RF Specialist**

Prepared by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).

The tests included in this report are within the scope of this accreditation.

The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



Lab locations

Company name	Nemko Canada Inc.		
Facilities	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2
	Tel: +1 613 737 9680 Fax: +1 613 737 9691	Tel: +1 514 694 2684 Fax: +1 514 694 3528	Tel: +1 519 650 4811
Test site registration	Organization	Ottawa	Montreal
	FCC: ISED:	CA2040 2040A-4	CA2041 2040G-5
Website	www.nemko.com		

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of Contents

Table of Contents	3
Section 1 Evaluation summary	4
1.1 MPE calculation for standalone transmission	4

Section 1 Evaluation summary

1.1 MPE calculation for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(d)

(2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1.1-1: Table 1 to §1.1310(e)(1) — Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1500	—	—	f / 300	<6
1500–100000	—	—	5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1500	—	—	f / 1500	<30
1500–100000	—	—	1.0	<30

Notes: f = frequency in MHz, * = Plane-wave equivalent power density.

References, definitions and limits, continued

RSS-102, Section 5.1

Through this standard, ISED adopts Health Canada's RF exposure guideline entitled Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz (Safety Code 6) and its Notice: Localized human exposure limits for radiofrequency fields in the range of 6 GHz to 300 GHz.

Table 1.1-2: Table 7&8 to RSS-102 — RF Field Strength and power density Limits

Frequency range (MHz)	Electric field strength (V/m rms)	Magnetic field strength (A/m rms)	Power density (W/m ²)	Reference Period (minutes)
Limits for controlled-use devices (controlled environment)				
10–20	61.4	0.163	10	6
20–48	129.8 / $f^{0.25}$	0.3444 / $f^{0.25}$	44.72 / $f^{0.5}$	6
48–100	49.33	0.1309	6.455	6
100–6000	15.60 $f^{0.25}$	0.04138 $f^{0.25}$	0.6455 $f^{0.5}$	6
6000–15000	137	0.364	50	6
15000–150000	137	0.364	50	616000 / $f^{1.2}$
150000–300000	0.354 $f^{0.5}$	$9.40 \times 10^{-4} f^{0.5}$	$3.33 \times 10^{-4} f$	616000 / $f^{1.2}$
Limits for r devices used by the general public (uncontrolled environment)				
10–20	27.46	0.0728	2	6
20–48	58.07 / $f^{0.25}$	0.1540 / $f^{0.25}$	8.944 / $f^{0.5}$	6
48–300	22.06	0.05852	1.291	6
300–6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000–15000	61.4	0.163	10	6
15000–150000	61.4	0.163	10	616000 / $f^{1.2}$
150000–300000	0.158 $f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	616000 / $f^{1.2}$

Notes: f = frequency in MHz

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

Prediction frequency	2479 MHz
Antenna type	Chip antenna
Antenna gain	1.5 dBi
Number of antennas	1
Maximum transmitter power	99.58 dB μ V/m (at 3 m)
Prediction distance (declared)	20 cm

1.1.3 MPE calculation

For radiated measurement

Fundamental transmit (prediction) frequency: 2479 MHz
Maximum measured field strength at 3 m: 99.58 dB μ V/m
Transmit duty cycle: 100 %
Maximum calculated average field strength: 99.58 dB μ V/m
Single Antenna gain (typical): 1.50 dBi
Number of antennae: 1
Total system gain: 1.50 dBi

FCC calculations ISED calculations

Uncontrolled environment	
Declared distance:	<u>20</u> cm
Average power density at declared distance:	<u>0.000542</u> mW/cm ² <u>0.005417</u> W/m ²
MPE limit at prediction frequency:	<u>1.000000</u> mW/cm ² <u>10.000000</u> W/m ²
Minimum calculated prediction distance for compliance:	<u>20</u> cm
Margin of Compliance:	<u>32.66</u> dB
	<u>30.04</u> dB

Controlled environment	
Declared distance:	<u>20</u> cm
Average power density at declared distance:	<u>0.000542</u> mW/cm ² <u>0.005417</u> W/m ²
MPE limit at prediction frequency:	<u>5.000000</u> mW/cm ² <u>50.000000</u> W/m ²
Minimum calculated prediction distance for compliance:	<u>20</u> cm
Margin of Compliance:	<u>39.65</u> dB
	<u>37.73</u> dB

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

End of the test report