

RADIO TEST REPORT

Report ID:

REP098184

Project number:

PRJ0078203

Type of assessment:

Final product testing

Type of radio equipment:

Bluetooth Device

Equipment class:

DTS

Applicant:

JDRF Electromag Engineering Inc.

Description of product:

Lighting control system for smart lighting application

Model(s)/HVIN(s):

JDRF-EAS, JDRF-AS, JDRF-EASLB, JDRF-ASLB

Product marketing name (PMN):

Autonomy Sensor

FCC identifier:

FCC ID: 2A22O-JDRFAS

ISED certification number:

IC: 24973-JDRFAS

Specifications:

- ◆ FCC 47 CFR Part 15 Subpart C, §15.247
- ◆ RSS-247, Issue 3, August 2023, Section 5

Date of issue: **September 8, 2025**

Ketav Jani, EMC/RF Specialist

Tested by



Signature

Dhara Patel, EMC/RF Specialist

Reviewed by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).

The tests included in this report are within the scope of this accreditation.

The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



Lab locations

| Company name | Nemko Canada Inc. | | |
|----------------------|---|--|---|
| Facilities | <i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2 | <i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8 | <i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2 |
| | Tel: +1 613 737 9680 Fax: +1 613 737 9691 | Tel: +1 514 694 2684 Fax: +1 514 694 3528 | Tel: +1 519 650 4811 |
| Test site identifier | CA2040 | CA2041 | CA0101 |
| Website | www.nemko.com | | |

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Table of Contents

| | |
|--|-----------|
| Table of Contents | 3 |
| Section 1 Report summary | 4 |
| 1.1 Test specifications | 4 |
| 1.2 Test methods | 4 |
| 1.3 Exclusions | 4 |
| 1.4 Statement of compliance | 4 |
| 1.5 Test report revision history | 4 |
| Section 2 Engineering considerations | 5 |
| 2.1 Modifications incorporated in the EUT for compliance | 5 |
| 2.2 Technical judgment | 5 |
| 2.3 Model variant declaration | 5 |
| 2.4 Deviations from laboratory tests procedures | 5 |
| Section 3 Test conditions | 6 |
| 3.1 Atmospheric conditions | 6 |
| 3.2 Power supply range | 6 |
| Section 4 Information provided by the applicant | 7 |
| 4.1 Disclaimer | 7 |
| 4.2 Applicant / Manufacturer | 7 |
| 4.3 EUT information | 7 |
| 4.4 Radio technical information | 8 |
| 4.5 EUT setup details | 8 |
| Section 5 Summary of test results | 10 |
| 5.1 Testing period | 10 |
| 5.2 Sample information | 10 |
| 5.3 FCC test results | 10 |
| 5.4 ISED test results | 11 |
| Section 6 Test equipment | 12 |
| 6.1 Test equipment list | 12 |
| Section 7 Testing data | 13 |
| 7.1 Variation of power source | 13 |
| 7.2 Number of frequencies | 14 |
| 7.3 Antenna requirement | 16 |
| 7.4 AC power line conducted emissions limits | 17 |
| 7.5 Minimum 6 dB bandwidth for DTS systems | 20 |
| 7.6 Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz | 24 |
| 7.7 Spurious (out-of-band) unwanted emissions | 28 |
| 7.8 Power spectral density for digitally modulated devices | 37 |
| Section 8 Test setup diagrams | 39 |
| 8.1 Radiated emissions set-up for frequencies below 1 GHz | 39 |
| 8.2 Radiated emissions set-up for frequencies above 1 GHz | 39 |
| 8.3 AC mains conducted emissions set-up | 40 |

Section 1 Report summary

1.1 Test specifications

| | |
|--|--|
| FCC 47 CFR Part 15, Subpart C, Clause 15.247 | Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz |
| RSS-247, Issue 3, August 2023, Section 5 | Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices |

1.2 Test methods

| | |
|---|---|
| 558074 D01 15.247 Meas Guidance v05r02 (April 2, 2019) | Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules. |
| RSS-Gen, Issue 5, February 2021 | General Requirements for Compliance of Radio Apparatus |
| ANSI C63.10 v2013 | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |

1.3 Exclusions

None

1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.3 above. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

Determining compliance is based on the results of the compliance measurement, not taking into account measurement uncertainty, in accordance with section 1.3 of ANSI C63.10 v2013.

See "Summary of test results" for full details.

1.5 Test report revision history

Table 1.5-1: Test report revision history

| Revision # | Date of issue | Details of changes made to test report |
|------------|-------------------|--|
| REP098184 | September 8, 2025 | Original report issued |

Section 2 Engineering considerations

2.1 Modifications incorporated in the EUT for compliance

There were no modifications performed to the EUT during this assessment.

2.2 Technical judgment

None

2.3 Model variant declaration

As declared by the applicant, the EUT model JDRF-EAS has been chosen to be representative for all other models in the model family. The model family, and the description of the variations, are as follows:

- JDRF-AS
- JDRF-ASLB
- JDRF-EASLB

All the variants listed above share the same RF path, radio, matching circuit and antenna with no modification. The only differences between the variants are the application (Low bay vs. commercial deployment) and colour.

2.4 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

Section 3 Test conditions

3.1 Atmospheric conditions

| | |
|-------------------|---|
| Temperature | 15 °C – 35 °C |
| Relative humidity | 20 % – 75 % |
| Air pressure | 86 kPa (860 mbar) – 106 kPa (1060 mbar) |

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

3.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 4 Information provided by the applicant

4.1 Disclaimer

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

4.2 Applicant / Manufacturer

| | |
|----------------------|--|
| Applicant name | JDRF Electromag Engineering Inc. |
| Applicant address | 31 lakeshore Road East, Unit 302 Mississauga, Ontario, L5G 4V5 |
| Manufacturer name | Same as applicant |
| Manufacturer address | Same as applicant |

4.3 EUT information

| | |
|---|--|
| Product description | Lighting control system for smart lighting application |
| HVINs/Model numbers | JDRF-EAS (tested), JDRF-AS, JDRF-EASLB, JDRF-ASLB |
| PMN/Model name | Autonomy Sensor |
| Serial number | Prototype |
| Power supply requirements | DC: 24 V from external 100–277 V(AC) LED electronic driver |
| Product description and theory of operation | The Autonomy Sensor is an integrated control and management device that self-organizes, configures, and optimizes an advanced Smart Lighting System. A set of Autonomy Sensors collaborate to provision a secure wireless mesh network, establish Area membership based on physical co-location, and configure motion and daylight groups through the analysis of motion patterns and daylight distribution levels, respectively. No setup or human supervision is required. |
| Operational frequencies | 1. Main core running at 80 MHz max, Radio running at 60 MHz max, DALI communication at max of 2 kHz & On-board Crystal of 32 MHz 2. BLE frequencies between 2400 and 2479 MHz |
| Software details | There is no Software provided at the time of testing, nor it is needed. As for testing, JDRF Electromag Engineering Inc. provided a sample with main application running, and with BLE transmission enabled |
| Hardware Version | PCB-0014 |

4.4 Radio technical information

| | |
|--|---|
| Category of Wideband Data Transmission equipment | <input type="checkbox"/> Frequency Hopping Spread Spectrum (FHSS) equipment <input checked="" type="checkbox"/> Other types of Wideband Data Transmission equipment (e.g. DSSS, OFDM, etc.). |
| Frequency band | 2400–2483.5 MHz |
| Frequency Min | 2402 MHz |
| Frequency Max | 2479 MHz |
| RF power Max, Conducted | 0.0019 W or 2.9 dBm - (Calculated) |
| Field strength, Radiated | 99.58 dB μ V/m @ 3 m - (Measured) |
| Measured BW, 99% OBW | 1.089 MHz |
| Type of modulation | BLE (GFSK) |
| Emission classification | 1K09F1D |
| Transmitter spurious | At 7438.0 MHz, 45.54 dB μ V/m @ 3 m (average) |
| Antenna information | Type: Surface Mount Chip Antenna Manufacturer: Johanson Model: 2450AT18D0100E Antenna gain: 1.5 dBi |

4.5 EUT setup details

4.5.1 Radio exercise details

| | |
|----------------------|--|
| Operating conditions | The applicant provided three samples loaded with special firmware that forces EUT to be continuously transmitting BLE signal. 1. Test sample 1 transmitting at 100% DC at lower channel 2. Test sample 2 transmitting at 100% DC at mid channel 3. Test sample 3 transmitting at 100% DC at high channel. |
| Transmitter state | Transmitter set into continuous mode. |

4.5.2 EUT setup configuration

Table 4.5-1: EUT interface ports

| Description | Qty. |
|---------------|------|
| DC power port | 1 |

Table 4.5-2: Support equipment

| Description | Brand name | Model, Part number, Serial number, Revision level |
|-----------------------|------------|---|
| LED Electronic Driver | Advance | MN: XI040C110V054VPT1, SN: None |

Table 4.5-3: Inter-connection cables

| Cable description | From | To | Length (m) |
|-------------------|-----------------------|-----|------------|
| DC Power Cable | LED Electronic Driver | EUT | 0.3 |




Figure 4.5-1: Radiated testing block diagram

Section 5 Summary of test results

5.1 Testing period

| | | | |
|-----------------|----------------|---------------|--------------|
| Test start date | April 30, 2025 | Test end date | May 24, 2025 |
|-----------------|----------------|---------------|--------------|

5.2 Sample information

| | | | |
|--------------|----------------|---------------------------|--|
| Receipt date | April 28, 2025 | Nemko sample ID number(s) | PRJ00782030002, PRJ00782030003, PRJ00782030004 |
|--------------|----------------|---------------------------|--|

5.3 FCC test results

Table 5.3-1: FCC requirements results

| Part | Test description | Verdict |
|----------------------------------|---|----------------|
| Generic requirements | | |
| §15.207(a) | Conducted limits | Pass |
| §15.31(e) | Variation of power source | Pass |
| §15.31(m) | Number of tested frequencies | Pass |
| §15.203 | Antenna requirement | Pass |
| §15.247(c)(1) | Fixed point-to-point operation with directional antenna gains greater than 6 dBi | Not applicable |
| §15.247(c)(2) | Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams | Not applicable |
| §15.247(d) | Spurious emissions | Pass |
| §15.247(f) | Time of occupancy for hybrid systems | Not applicable |
| DTS specific requirements | | |
| §15.247(a)(2) | Minimum 6 dB bandwidth | Pass |
| §15.247(b)(3) | Maximum peak output power | Pass |
| §15.247(e) | Power spectral density | Pass |

Notes: EUT is an AC powered device.

5.4 ISED test results

Table 5.4-1: ISED requirements results

| Part | Test description | Verdict |
|----------------------------------|--|----------------|
| Generic requirements | | |
| RSS-Gen, 7.3 | Receiver radiated emission limits | Not applicable |
| RSS-Gen, 7.4 | Receiver conducted emission limits | Not applicable |
| RSS-Gen, 6.9 | Operating bands and selection of test frequencies | Pass |
| RSS-Gen, 8.8 | AC powerline conducted emissions limits | Pass |
| RSS-247, 5.5 | Unwanted emissions | Pass |
| DTS specific requirements | | |
| RSS-247, 5.2 (a) | Minimum 6 dB bandwidth | Pass |
| RSS-247, 5.2 (b) | Maximum power spectral density | Pass |
| RSS-247, 5.4 (d) | Transmitter output power and e.i.r.p. requirements for systems employing digital modulation techniques | Pass |
| RSS-247, 5.4 (e) | Transmitter e.i.r.p. requirements for point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band | Not applicable |
| RSS-247, 5.4 (f) | Transmitter requirements for operation in the 2400–2483.5 MHz band with multiple directional beams | Not applicable |

Notes: ¹According to sections 5.2 and 5.3 of RSS-Gen, Issue 5 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.
EUT is an AC powered device.

Section 6 Test equipment

6.1 Test equipment list

Table 6.1-1: Equipment list

| Equipment | Manufacturer | Model no. | Asset no. | Cal cycle | Next cal. |
|-------------------------------|--------------------|-----------|-----------|-----------|-------------------|
| Receiver/spectrum analyzer | Rohde & Schwarz | ESR26 | FA002969 | 1 year | May 31, 2025 |
| 3 m EMI test chamber | TDK | SAC-3 | FA003012 | 1 year | Mar 9, 2026 |
| Flush mount turntable | SUNAR | FM2022 | FA003006 | — | NCR |
| Controller | SUNAR | SC110V | FA002976 | — | NCR |
| Antenna mast | SUNAR | TLT2 | FA003007 | — | NCR |
| Bilog antenna (30–2000 MHz) | SUNAR | JB3 | FA002108 | 1 year | April 8, 2026 |
| Horn antenna (1–18 GHz) | EMCO | 3117 | FA002911 | 1 year | May 31, 2025 |
| Horn antenna (1–18 GHz) | EMCO | 3115 | FA000649 | 1 year | April 16, 2026 |
| Preamp (1–18 GHz) | ETS Lindgren | 124334 | FA002956 | 1 year | April 11, 2026 |
| Horn antenna (18–40 GHz) | EMCO | 3116B | FA002948 | 1 year | May 3, 2027 |
| Preamp 18-40 GHz | None | PA1840 | FA003323 | 1 year | April 11, 2026 |
| 50 Ω coax cable | Huber + Suhner | None | FA003047 | 1 year | July 29, 2025 |
| 50 Ω coax cable | Huber + Suhner | None | FA003402 | 1 year | July 29, 2025 |
| 50 Ω SMA coax cable | Huber + Suhner | None | FA003057 | 1 year | July 29, 2025 |
| Notch filter (2.4–2.4835 GHz) | Microwave circuits | N0324413 | FA003027 | 1 year | NCR |
| Two-line v-network | Rohde & Schwarz | ENV216 | FA002965 | 1 year | November 30, 2025 |
| 50 Ω coax cable | Rohde & Schwarz | None | FA003074 | 1 year | July 29, 2025 |

Note: NCR - no calibration required

All equipment related to the contribution of measurement has been included in this list. Such items include, but are not limited to, cables, attenuators, directional couplers, and pre-amps.

Table 6.1-2: Automation software details

| Test description | Manufacturer of Software | Details |
|-------------------------|--------------------------|--|
| Radio/EMC test software | Rohde & Schwarz | EMC32, Software for EMC Measurements, Version 10.60.00 |

Table 6.1-3: Measurement uncertainty calculations based on equipment list

| Measurement | Measurement uncertainty, ±dB |
|---|---|
| AC power line conducted emissions | 3.01 |
| Radiated spurious emissions (30 MHz to 1 GHz) | 4.27 |
| Radiated spurious emissions (1 GHz to 6 GHz) | 4.74 |
| Radiated spurious emissions (6 GHz to 18 GHz) | 5.04 |
| Radiated spurious emissions (18 GHz to 26 GHz) | 4.47 |
| RF Output power measurement using Spectrum Analyzer | 0.71 |
| Notes: | UKAS Lab 34, TIA-603 and ETSI TR 100 028-1&2 have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products. Measurement uncertainty calculations assume a coverage factor of K = 2 with 95% certainty. |



Section 7 Testing data

7.1 Variation of power source

7.1.1 References, definitions and limits

FCC §15.31 (e):

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

7.1.2 Test summary

| Verdict | Pass | | |
|---------------|----------------|-------------------|----------|
| Test date | April 30, 2025 | Temperature | 24 °C |
| Tested by | Ketav Jani | Air pressure | 980 mbar |
| Test location | Cambridge | Relative humidity | 31 % |

7.1.3 Observations, settings and special notes

The testing was performed as per ANSI C63.10 Section 5.13.

- a) Where the device is intended to be powered from an external power adapter, the voltage variations shall be applied to the input of the adapter provided with the device at the time of sale. If the device is not marketed or sold with a specific adapter, then a typical power adapter shall be used.
- b) For devices, where operating at a supply voltage deviating $\pm 15\%$ from the nominal rated value may cause damages or loss of intended function, test to minimum and maximum allowable voltage per manufacturer's specification and document in the report.
- c) For devices with wide range of rated supply voltage, test at 15% below the lowest and 15% above the highest declared nominal rated supply voltage.
- d) For devices obtaining power from an input/output (I/O) port (USB, firewire, etc.), a test jig is necessary to apply voltage variation to the device from a support power supply, while maintaining the functionalities of the device.
- e) For battery-operated equipment, the equipment tests shall be performed using a variable power supply.

7.1.4 Test data

EUT Power requirements:

If EUT is an AC or a DC powered, was the noticeable output power variation observed?

AC DC Battery

YES NO N/A

If EUT is battery operated, was the testing performed using fresh batteries?

YES NO N/A

If EUT is rechargeable battery operated, was the testing performed using fully charged batteries?

YES NO N/A

7.2 Number of frequencies

7.2.1 References, definitions and limits

FCC §15.31:

(m) Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

RSS-Gen, Clause 6.9:

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

Table 7.2-1: Frequency Range of Operation

| Frequency range over which the device operates (in each band) | Number of test frequencies required | Location of measurement frequency inside the operating frequency range |
|---|-------------------------------------|--|
| 1 MHz or less | 1 | Center (middle of the band) |
| 1–10 MHz | 2 | 1 near high end, 1 near low end |
| Greater than 10 MHz | 3 | 1 near high end, 1 near center and 1 near low end |

Notes: “near” means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

7.2.2 Test summary

| | | | |
|---------------|----------------|-------------------|----------|
| Verdict | Pass | | |
| Test date | April 30, 2025 | Temperature | 24 °C |
| Tested by | Ketav Jani | Air pressure | 980 mbar |
| Test location | Cambridge | Relative humidity | 31 % |

7.2.3 Observations, settings and special notes

ANSI C63.10, Clause 5.6.2.1:

The number of channels tested can be reduced by measuring the center channel bandwidth first and then applying the following relaxations as appropriate:

- For each operating mode, if the measured channel bandwidth on the middle channel is at least 150% of the minimum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.
- For multiple-input multiple-output (MIMO) systems, if the measured channel bandwidth on testing the middle channel exceeds the minimum permitted bandwidth by more than 50% on one transmit chain, then it is not necessary to repeat testing on the other chains.
- If the measured channel bandwidth on the middle channel is less than 50% of the maximum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.

ANSI C63.10, Clause 5.6.2.2:

For devices with multiple operating modes, measurements on the middle channel can be used to determine the worst-case mode(s). The worst-case modes are as follows:

- Band edge requirements—Measurements on the mode with the widest bandwidth can be used to cover the same channel (center frequency) on modes with narrower bandwidth that have the same or lower output power for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- Spurious emissions—Measure the mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- In-band PSD—Measurements on the mode with the narrowest bandwidth can be used to cover all modes within the same modulation family of an equal or lower output power provided the result is less than 50% of the limit.

7.2.4 Test data

Table 7.2-2: Test channels selection

| Start of Frequency range, MHz | End of Frequency range, MHz | Frequency range bandwidth, MHz | Low channel, MHz | Mid channel, MHz | High channel, MHz |
|--------------------------------------|------------------------------------|---------------------------------------|-------------------------|-------------------------|--------------------------|
| 2400 | 2483.5 | 83.5 | 2402 | 2441 | 2479 |

7.3 Antenna requirement

7.3.1 References, definitions and limits

FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

FCC §15.247:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RSS-Gen, Clause 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

7.3.2 Test summary

| Verdict | Pass | | |
|---------------|----------------|-------------------|----------|
| Test date | April 30, 2025 | Temperature | 24 °C |
| Tested by | Ketav Jani | Air pressure | 980 mbar |
| Test location | Cambridge | Relative humidity | 31 % |

7.3.3 Observations, settings and special notes

None

7.3.4 Test data

Must the EUT be professionally installed?

YES NO

Does the EUT have detachable antenna(s)?

YES NO

If detachable, is the antenna connector(s) non-standard?

YES NO N/A

Table 7.3-1: Antenna information

| Antenna type | Manufacturer | Model number | Maximum gain | Connector type |
|----------------------------|--------------|----------------|--------------|-----------------|
| Surface Mount Chip Antenna | Johanson | 2450AT18D0100E | 1.5 dBi | Surface Mounted |

7.4 AC power line conducted emissions limits

7.4.1 References, definitions and limits

FCC §15.207:

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

ANSI C63.10, Clause 6.2:

If the EUT normally receives power from another device that in turn connects to the public utility ac power lines, measurements shall be made on that device with the EUT in operation to demonstrate that the device continues to comply with the appropriate limits while providing the EUT with power. If the EUT is operated only from internal or dedicated batteries, with no provisions for connection to the public utility ac power lines (600 VAC or less) to operate the EUT (such as an adapter), then ac power-line conducted measurements are not required.

For direct current (dc) powered devices where the ac power adapter is not supplied with the device, an "off-the-shelf" unmodified ac power adapter shall be used. If the device is supposed to be installed in a host (e.g., the device is a module or PC card), then it is tested in a typical compliant host.

RSS-Gen, Clause 8.8:

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in table below.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in table below. The more stringent limit applies at the frequency range boundaries.

Table 7.4-1: Conducted emissions limit

| Conducted emissions limit, dB μ V | | |
|---------------------------------------|------------|-----------|
| Frequency of emission, MHz | Quasi-peak | Average** |
| 0.15–0.5 | 66 to 56* | 56 to 46* |
| 0.5–5 | 56 | 46 |
| 5–30 | 60 | 50 |

Notes: * - The level decreases linearly with the logarithm of the frequency.

** - A linear average detector is required.

7.4.2 Test summary

| | | | |
|---------------|----------------|-------------------|----------|
| Verdict | Pass | | |
| Test date | April 30, 2025 | Temperature | 24 °C |
| Tested by | Ketav Jani | Air pressure | 980 mbar |
| Test location | Cambridge | Relative humidity | 31 % |

7.4.3 Observations, settings and special notes

| | |
|-----------------------------------|--|
| Port under test – Coupling device | AC power input – Artificial Mains Network (AMN) |
| EUT power input during test | 24 V _{DC} (via external 100–277 V _{AC} , 50/60 Hz LED electronic driver) |
| EUT setup configuration | Table top |
| Measurement details | A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 10 dB or above the limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement. |
| Additional notes: | <ul style="list-style-type: none"> – The EUT was set up as tabletop configuration per ANSI C63.10-2013 measurement procedure. – The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance. Correction factor (dB) = LISN factor IL (dB) + cable loss (dB) + attenuator (dB) – Emissions that were continuously present for a minimum of 1 second and occurred more than once for every 15 seconds observation period were considered valid emissions. The maximum value of valid emissions has been recorded. |

Receiver settings:

| | |
|----------------------|---|
| Resolution bandwidth | 9 kHz |
| Video bandwidth | 30 kHz |
| Detector mode | Peak and Average (Preview), Quasi-peak and CAverage (Final) |
| Trace mode | Max Hold |
| Measurement time | 100 ms (Preview), 160 ms (Final) |

7.4.4 Test data

Table 7.4-2: Conducted emissions results on phase line

| Frequency, MHz | Quasi-Peak result, dB μ V | Quasi-Peak limit, dB μ V | Quasi-Peak margin, dB | Correction factor, dB |
|----------------|-------------------------------|------------------------------|-----------------------|-----------------------|
| 0.17 | 48.3 | 64.7 | 16.4 | 15.5 |
| 0.22 | 51.5 | 62.9 | 11.4 | 15.5 |
| 6.70 | 46.0 | 60.0 | 14.0 | 15.7 |
| 6.88 | 46.0 | 60.0 | 14.0 | 15.7 |
| 7.06 | 46.0 | 60.0 | 14.0 | 15.7 |


| Frequency, MHz | CAverage result, dB μ V | CAverage limit, dB μ V | CAverage margin, dB | Correction factor, dB |
|----------------|-----------------------------|----------------------------|---------------------|-----------------------|
| 0.18 | 39.6 | 54.5 | 14.9 | 15.5 |
| 0.22 | 38.9 | 52.9 | 14.0 | 15.5 |
| 6.70 | 42.4 | 50.0 | 7.6 | 15.7 |
| 6.88 | 42.3 | 50.0 | 7.7 | 15.7 |
| 7.06 | 40.8 | 50.0 | 9.2 | 15.7 |

Table 7.4-3: Conducted emissions results on neutral line


| Frequency, MHz | Quasi-Peak result, dB μ V | Quasi-Peak limit, dB μ V | Quasi-Peak margin, dB | Correction factor, dB |
|----------------|-------------------------------|------------------------------|-----------------------|-----------------------|
| 0.18 | 51.6 | 64.5 | 12.9 | 15.5 |
| 0.62 | 42.2 | 56.0 | 13.8 | 15.6 |
| 1.52 | 40.9 | 56.0 | 15.1 | 15.6 |
| 6.70 | 48.5 | 60.0 | 11.5 | 15.7 |
| 6.88 | 48.8 | 60.0 | 11.2 | 15.7 |
| 7.06 | 48.0 | 60.0 | 12.0 | 15.7 |

| Frequency, MHz | CAverage result, dB μ V | CAverage limit, dB μ V | CAverage margin, dB | Correction factor, dB |
|----------------|-----------------------------|----------------------------|---------------------|-----------------------|
| 0.18 | 39.7 | 54.5 | 14.8 | 15.5 |
| 0.62 | 37.8 | 46.0 | 8.2 | 15.6 |
| 1.52 | 35.4 | 46.0 | 10.6 | 15.6 |
| 6.70 | 44.8 | 50.0 | 5.2 | 15.7 |
| 6.88 | 44.7 | 50.0 | 5.3 | 15.7 |
| 7.06 | 43.0 | 50.0 | 7.0 | 15.7 |

Test data, continued



Plot 7.4-1: Conducted emissions on phase line



Plot 7.4-2: Conducted emissions on neutral line

7.5 Minimum 6 dB bandwidth for DTS systems

7.5.1 References, definitions and limits

FCC §15.247:

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

RSS-247, Clause 5.2:

DTSs include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902–928 MHz and 2400–2483.5 MHz:

a. The minimum 6 dB bandwidth shall be 500 kHz.

RSS-Gen, Clause 6.7:

6 dB bandwidth is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 6 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

7.5.2 Test summary

| Verdict | Pass | | |
|---------------|--------------|-------------------|----------|
| Test date | May 24, 2025 | Temperature | 23 °C |
| Tested by | Ketav Jani | Air pressure | 985 mbar |
| Test location | Cambridge | Relative humidity | 38 % |

7.5.3 Observations, settings and special notes

The test was performed as per KDB 558074, section 8.2 with reference to ANSI C63.10 subclause 11.8.

Spectrum analyser settings:

| | |
|----------------------|--|
| Resolution bandwidth | 6 dB BW: 100 kHz; 99% OBW: 1–5% of OBW |
| Video bandwidth | ≥3 × RBW |
| Frequency span | 10 MHz |
| Detector mode | Peak |
| Trace mode | Max Hold |

7.5.4 Test data

Table 7.5-1: 99% occupied bandwidth results

| Frequency, MHz | 99% occupied bandwidth, MHz |
|----------------|-----------------------------|
| 2402 | 1.074 |
| 2441 | 1.079 |
| 2479 | 1.089 |

Notes: There is no 99% occupied bandwidth limit in the standard's requirements, the measurement results provided for information purposes only.

Table 7.5-2: 6 dB bandwidth results

| Frequency, MHz | 6 dB bandwidth, kHz | Minimum limit, kHz | Margin, kHz |
|----------------|---------------------|--------------------|-------------|
| 2402 | 720 | 500 | 220 |
| 2441 | 744 | 500 | 244 |
| 2479 | 738 | 500 | 238 |

Test data, continued




Figure 7.5-1: 6 dB bandwidth on low ch.




Figure 7.5-2: 6 dB bandwidth on mid ch.






Figure 7.5-3: 6 dB bandwidth on high ch.


Test data, continued



Date: 24.MAY.2025 17:30:24



Date: 24.MAY.2025 16:35:48



Date: 24.MAY.2025 19:22:09

7.6 Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz

7.6.1 References, definitions and limits

FCC §15.247:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (3) For systems using digital modulation in the 2400–2483.5 MHz band: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (c) Operation with directional antenna gains greater than 6 dBi.
- (1) Fixed point-to-point operation:
 - (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
 - (ii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.
- (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
 - (i) Different information must be transmitted to each receiver.
 - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
 - (A) The directional gain shall be calculated as the sum of $10 \log$ (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
 - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
 - (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
 - (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

References, definitions and limits, continued

RSS-247, Clause 5.4:

Devices shall comply with the following requirements, where applicable:

d. For DTSs employing digital modulation techniques operating in the 2400–2483.5 MHz band,, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

e. Fixed point-to-point systems in the 2400–2483.5 MHz band are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding an e.i.r.p. of 4 W.

f. Transmitters operating in the band 2400–2483.5 MHz, may employ antenna systems that emit multiple directional beams simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers, provided that the emissions comply with the following:

- Different information must be transmitted to each receiver.
- If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit specified in sections 5.4(b) and 5.4(d). However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
- If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the applicable power limit specified in sections 5.4(b) and 5.4(d). If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the applicable limit specified in sections 5.4(b) and 5.4(d). In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the applicable limit specified in sections 5.4(b) and 5.4(d) by more than 8 dB.
- Transmitters that transmit a single directional beam shall operate under the provisions of sections 5.4(b), 5.4(d) and 5.4(e).

7.6.2 Test summary

| Verdict | Pass | | |
|---------------|--------------|-------------------|----------|
| Test date | May 24, 2025 | Temperature | 23 °C |
| Tested by | Ketav Jani | Air pressure | 985 mbar |
| Test location | Cambridge | Relative humidity | 38 % |

7.6.3 Observations, settings and special notes

The test was performed as per KDB 558074, section 8.3 with reference to ANSI C63.10 subclause 11.9.1 (peak power) using method RBW≥DTS bandwidth (Maximum peak conducted output power)

The measurement was performed as a radiated measurement, the EUT has an integrated antenna.

Spectrum analyser settings:

| | |
|----------------------|----------------------------|
| Resolution bandwidth | 3 MHz |
| Video bandwidth | $\geq 3 \times \text{RBW}$ |
| Frequency span | 20 MHz |
| Detector mode | Peak |
| Trace mode | Max Hold |


7.6.4 Test data

Table 7.6-1: Output power and EIRP results (radiated measurement)

| Frequency, MHz | Field strength, dB μ V/m | EIRP, dBm | EIRP limit, dBm | EIRP margin, dB | Antenna gain, dBi | Output power, dBm | Output power limit, dBm | Output power margin, dB |
|-------------------|------------------------------------|-----------|--------------------|--------------------|----------------------|----------------------|-------------------------------|-------------------------------|
| 2402 | 98.8 | 3.6 | 36.0 | 32.4 | 1.5 | 2.1 | 30.0 | 27.9 |
| 2441 | 99.4 | 4.2 | 36.0 | 31.8 | 1.5 | 2.7 | 30.0 | 27.3 |
| 2479 | 99.6 | 4.4 | 36.0 | 31.6 | 1.5 | 2.9 | 30.0 | 27.1 |


Note: EIRP [dBm] = Field Strength [dB μ V/m] – 95.23 [dB]; Output power [dBm] = EIRP [dBm] – Antenna gain [dBi]

Test data, continued




Date: 24.MAY.2025 17:19:47

Figure 7.6-1: Output power on low channel



Date: 24.MAY.2025 16:29:00

Figure 7.6-2: Output power on mid channel



Date: 24.MAY.2025 19:17:42

Figure 7.6-3: Output power on high channel

7.7 Spurious (out-of-band) unwanted emissions

7.7.1 References, definitions and limits

FCC §15.247:

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247, Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RSS-Gen:

8.9 Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table below.

8.10 Restricted frequency bands are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. The following conditions related to the restricted frequency bands apply:

- a The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands.
- b Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table below.
- c Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in table below.

Table 7.7-1: FCC §15.209 and RSS-Gen – Radiated emission limits

| Field strength of emissions | | | |
|-----------------------------|---------|-----------------------------------|-------------------------|
| Frequency, MHz | µV/m | dBµV/m | Measurement distance, m |
| 0.009–0.490 | 2400/F | 67.6 – 20 × log ₁₀ (F) | 300 |
| 0.490–1.705 | 24000/F | 87.6 – 20 × log ₁₀ (F) | 30 |
| 1.705–30.0 | 30 | 29.5 | 30 |
| 30–88 | 100 | 40.0 | 3 |
| 88–216 | 150 | 43.5 | 3 |
| 216–960 | 200 | 46.0 | 3 |
| above 960 | 500 | 54.0 | 3 |

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

References, definitions and limits, continued

Table 7.7-2: ISED restricted frequency bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090–0.110 | 12.57675–12.57725 | 399.9–410 | 7.25–7.75 |
| 0.495–0.505 | 13.36–13.41 | 608–614 | 8.025–8.5 |
| 2.1735–2.1905 | 16.42–16.423 | 960–1427 | 9.0–9.2 |
| 3.020–3.026 | 16.69475–16.69525 | 1435–1626.5 | 9.3–9.5 |
| 4.125–4.128 | 16.80425–16.80475 | 1645.5–1646.5 | 10.6–12.7 |
| 4.17725–4.17775 | 25.5–25.67 | 1660–1710 | 13.25–13.4 |
| 4.20725–4.20775 | 37.5–38.25 | 1718.8–1722.2 | 14.47–14.5 |
| 5.677–5.683 | 73–74.6 | 2200–2300 | 15.35–16.2 |
| 6.215–6.218 | 74.8–75.2 | 2310–2390 | 17.7–21.4 |
| 6.26775–6.26825 | 108–138 | 2483.5–2500 | 22.01–23.12 |
| 6.31175–6.31225 | 149.9–150.05 | 2655–2900 | 23.6–24.0 |
| 8.291–8.294 | 156.52475–156.52525 | 3260–3267 | 31.2–31.8 |
| 8.362–8.366 | 156.7–156.9 | 3332–3339 | 36.43–36.5 |
| 8.37625–8.38675 | 162.0125–167.17 | 3345.8–3358 | |
| 8.41425–8.41475 | 167.72–173.2 | 3500–4400 | Above 38.6 |
| 12.29–12.293 | 240–285 | 4500–5150 | |
| 12.51975–12.52025 | 322–335.4 | 5350–5460 | |

Note: Certain frequency bands listed in Table 7.7-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Table 7.7-3: FCC restricted frequency bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090–0.110 | 16.42–16.423 | 399.9–410 | 4.5–5.15 |
| 0.495–0.505 | 16.69475–16.69525 | 608–614 | 5.35–5.46 |
| 2.1735–2.1905 | 16.80425–16.80475 | 960–1240 | 7.25–7.75 |
| 4.125–4.128 | 25.5–25.67 | 1300–1427 | 8.025–8.5 |
| 4.17725–4.17775 | 37.5–38.25 | 1435–1626.5 | 9.0–9.2 |
| 4.20725–4.20775 | 73–74.6 | 1645.5–1646.5 | 9.3–9.5 |
| 6.215–6.218 | 74.8–75.2 | 1660–1710 | 10.6–12.7 |
| 6.26775–6.26825 | 108–121.94 | 1718.8–1722.2 | 13.25–13.4 |
| 6.31175–6.31225 | 123–138 | 2200–2300 | 14.47–14.5 |
| 8.291–8.294 | 149.9–150.05 | 2310–2390 | 15.35–16.2 |
| 8.362–8.366 | 156.52475–156.52525 | 2483.5–2500 | 17.7–21.4 |
| 8.37625–8.38675 | 156.7–156.9 | 2690–2900 | 22.01–23.12 |
| 8.41425–8.41475 | 162.0125–167.17 | 3260–3267 | 23.6–24.0 |
| 12.29–12.293 | 167.72–173.2 | 3332–3339 | 31.2–31.8 |
| 12.51975–12.52025 | 240–285 | 3345.8–3358 | 36.43–36.5 |
| 12.57675–12.57725 | 322–335.4 | 3600–4400 | Above 38.6 |
| 13.36–13.41 | | | |

7.7.2 Test summary

| | | | |
|---------------|------------------------------|-------------------|--------------------|
| Verdict | Pass | | |
| Test date | April 30, 2025, May 21, 2025 | Temperature | 24 °C, 23 °C |
| Tested by | Ketav Jani | Air pressure | 980 mbar, 970 mbar |
| Test location | Cambridge | Relative humidity | 31 %, 38 % |

7.7.3 Observations, settings and special notes

- As part of the current assessment, the test range of 9 kHz to 10th harmonic has been fully considered and compared to the actual frequencies utilized within the EUT. Since the EUT contains a transmitter in the GHz range, the EUT has been deemed compliant without formal testing in the 9 kHz to 30 MHz test range, therefore formal test results (tabular data and/or plots) are not provided within this test report.
- EUT was set to transmit with 100 % duty cycle.
- Radiated measurements were performed at a distance of 3 m, except for 18 – 25 GHz was performed at a distance of 1 m.
- DTS emissions in non-restricted frequency bands test was performed as per KDB 558074, section 8.5 with reference to ANSI C63.10 subclause 11.11.
- Since fundamental power was tested using the maximum peak conducted output power procedure to demonstrate compliance, the spurious emissions limit is -20 dBc/100 kHz.
- DTS emissions in restricted frequency bands test was performed as per KDB 558074, section 8.6 with reference to ANSI C63.10 subclause 11.12.
- DTS band-edge emission measurements test was performed as per KDB 558074, section 8.7 with reference to ANSI C63.10 subclause 11.13.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

| | |
|-----------------------|----------|
| Resolution bandwidth: | 100 kHz |
| Video bandwidth: | 300 kHz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:

| | |
|-----------------------|----------|
| Resolution bandwidth: | 1 MHz |
| Video bandwidth: | 3 MHz |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

7.7.4 Test data

Table 7.7-4: Radiated field strength measurement results

| Channel | Frequency, MHz | Peak Field strength, dB μ V/m | | Margin, dB | Average Field strength, dB μ V/m | | Margin, dB |
|---------|-------------------|-----------------------------------|-------|---------------|--------------------------------------|-------|---------------|
| | | Measured | Limit | | Measured | Limit | |
| Low | 2390.0 | 60.46 | 74.00 | 13.54 | 38.67 | 54.00 | 15.33 |
| High | 2483.5 | 61.28 | 74.00 | 12.72 | 39.81 | 54.00 | 14.19 |
| High | 7438.0 | 54.81 | 74.00 | 19.19 | 45.54 | 54.00 | 8.46 |

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

Test data, continued




Figure 7.7-1: Radiated spurious emissions 30-1000 MHz low channel




Figure 7.7-2: Radiated spurious emissions 30-1000 MHz mid channel

Test data, continued




Figure 7.7-3: Radiated spurious emissions 30-1000 MHz high channel




Figure 7.7-4: Radiated spurious emissions 1-18 GHz low channel

Test data, continued




Figure 7.7-5: Radiated spurious emissions 1-18 GHz mid channel




Figure 7.7-6: Radiated spurious emissions 1-18 GHz high channel

Test data, continued




Figure 7.7-7: Radiated spurious emissions 18-26 GHz low channel




Figure 7.7-8: Radiated spurious emissions 18-26 GHz mid channel

Test data, continued




Figure 7.7-9: Radiated spurious emissions 18-26 GHz high channel




Figure 7.7-10: Band edge spurious emissions at 2390 MHz Peak






Figure 7.7-11: Band edge spurious emissions at 2390 MHz Average

Test data, continued




Date: 24.MAY.2025 19:40:42

Figure 7.7-12: Band edge spurious emissions at 2483.5 MHz Peak




Date: 24.MAY.2025 19:43:25

Figure 7.7-13: Band edge spurious emissions at 2483.5 MHz Average



Date: 24.MAY.2025 17:58:31

Figure 7.7-14: Non-restricted band edge emissions at 2400 MHz



Date: 24.MAY.2025 19:34:21

Figure 7.7-15: Non-restricted band edge emissions at 2483.5 MHz

7.8 Power spectral density for digitally modulated devices

7.8.1 References, definitions and limits

FCC §15.247:

- (e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
- (f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned-off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RSS-247, Clause 5.2:

DTSSs include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to the bands 902-928 MHz and 2400-2483.5 MHz:

- b. The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

RSS-247, Clause 5.3:

Hybrid systems employ a combination of both frequency hopping and digital transmission techniques and shall comply with the following:

- b. With the frequency hopping turned off, the digital transmission operation shall comply with the power spectral density requirements for digital modulation systems set out in of section 5.2(b) or section 6.2.4 for hybrid devices operating in the band 5725–5850 MHz.

7.8.2 Test summary

| Verdict | Pass | | |
|---------------|--------------|-------------------|----------|
| Test date | May 24, 2025 | Temperature | 23 °C |
| Tested by | Ketav Jani | Air pressure | 985 mbar |
| Test location | Cambridge | Relative humidity | 38 % |

7.8.3 Observations, settings and special notes

Power spectral density test was performed as per KDB 558074, section 8.4 with reference to ANSI C63.10 subclause 11.10.

The test was performed using method PKPSD (peak PSD).

Spectrum analyser settings:


| | |
|-----------------------|-----------------------------|
| Resolution bandwidth: | 3 kHz |
| Video bandwidth: | ≥3 × RBW |
| Frequency span: | 1.5 times the DTS BW (Peak) |
| Detector mode: | Peak |
| Trace mode: | Max Hold |

7.8.4 Test data

Table 7.8-1: PSD results (radiated measurement)


| Frequency, MHz | Field strength, dB μ V/m/3 kHz | EIRPSD, dBm/3 kHz | Antenna gain, dBi | PSD, dBm/3 kHz | PSD limit, dBm/3 kHz | Margin, dB |
|----------------|------------------------------------|-------------------|-------------------|----------------|----------------------|------------|
| 2402 | 85.86 | -9.33 | 1.5 | -10.83 | 8.0 | 18.83 |
| 2441 | 85.74 | -9.49 | 1.5 | -10.99 | 8.0 | 18.99 |
| 2479 | 85.82 | -9.41 | 1.5 | -10.91 | 8.0 | 18.91 |

Note: EIRPSD [dBm/3 kHz] = Field Strength [dB μ V/m/3 kHz] – 95.23 [dB]; PSD [dBm/3 kHz] = EIRP [dBm/3 kHz] – Antenna gain [dB]




Date: 24.MAY.2025 17:36:30

Figure 7.8-1: PSD on low channel



Date: 24.MAY.2025 16:44:27

Figure 7.8-2: PSD on mid channel




Date: 24.MAY.2025 19:27:37


Figure 7.8-3: PSD on high channel

Section 8 Test setup diagrams

8.1 Radiated emissions set-up for frequencies below 1 GHz



8.2 Radiated emissions set-up for frequencies above 1 GHz



8.3 AC mains conducted emissions set-up

