

# FCC RF Exposure

EUT Description: Wireless karaoke speaker

Model No.: TS-S095B

FCC ID: **2A22V-TS-S095B**

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
$$[(\text{max power of channel, including tune - up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1 - g SAR and } \leq 7.5 \text{ for 10 - g extremity SAR,}$$

Where:

$$\text{Result} = P/D^* \sqrt{F}$$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit	SAR Test Exclusion
BT	0.35	0±1	1/1.26	5	0.39651	3.0	Pass

Note:  
PK Output power= conducted power.  
Conducted power see the test report **HK2111234534-E**, antenna gain=0dBi

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.39651 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[  $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})$  ]  $\cdot [\sqrt{f(\text{GHz})}]$

f(GHz) is the RF channel transmit frequency in GHz

Distance=5mm