



RF TEST REPORT

Product Name: Battery Camera

Model Name: BC-BD06-M10, BC-BD06-M10-V0, BC-BD06-M10-V1,
BC-BD06-M10-V2, BC-BD06-M10-V3, BC-BD06-M10-V4,
BC-BD06-M10-V5, BC-BD06-M10-V6, BC-BD06-M10-V7,
BC-BD06-M10-V8, BC-BD06-M10-V9

FCC ID: 2A22Z-W520

Issued For : Botslab Inc.

919 North Market Street, Suite 950, Wilmington, New Castle,
Delaware, USA

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT24K127RF09

Sample Received Date: Nov. 20, 2024

Date of Test: Nov. 20, 2024 ~ Feb. 20, 2025

Date of Issue: Apr. 30, 2025

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Botslab Inc.
Address: 919 North Market Street, Suite 950, Wilmington, New Castle, Delaware, USA
Manufacturer: Botslab Inc.
Address: 919 North Market Street, Suite 950, Wilmington, New Castle, Delaware, USA
Product Name: Battery Camera
Trademark: Botslab
Model Name: BC-BD06-M10, BC-BD06-M10-V0, BC-BD06-M10-V1, BC-BD06-M10-V2, BC-BD06-M10-V3, BC-BD06-M10-V4, BC-BD06-M10-V5, BC-BD06-M10-V6, BC-BD06-M10-V7, BC-BD06-M10-V8, BC-BD06-M10-V9
Sample Status: Normal
Serial Number: LGT2411106-4-4

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	11
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.2 RADIATED EMISSION MEASUREMENT	17
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	30
4.1 LIMIT	30
4.2 TEST PROCEDURE	30
4.3 DEVIATION FROM STANDARD	30
4.4 TEST SETUP	30
4.5 EUT OPERATION CONDITIONS	30
4.6 TEST RESULTS	30
5. POWER SPECTRAL DENSITY TEST	31
5.1 LIMIT	31
5.2 TEST PROCEDURE	31
5.3 DEVIATION FROM STANDARD	31
5.4 TEST SETUP	31
5.5 EUT OPERATION CONDITIONS	31
5.6 TEST RESULTS	31
6. BANDWIDTH TEST	32
6.1 LIMIT	32
6.2 TEST PROCEDURE	32
6.3 DEVIATION FROM STANDARD	32
6.4 TEST SETUP	32
6.5 EUT OPERATION CONDITIONS	32
6.6 TEST RESULTS	32



Table of Contents	Page
7. PEAK OUTPUT POWER TEST	33
7.1 LIMIT	33
7.2 TEST PROCEDURE	33
7.3 DEVIATION FROM STANDARD	33
7.4 TEST SETUP	33
7.5 EUT OPERATION CONDITIONS	33
7.6 TEST RESULTS	33
8. ANTENNA REQUIREMENT	34
8.1 STANDARD REQUIREMENT	34
8.2 EUT ANTENNA	34
APPENDIX I - TEST RESULTS	35
DUTY CYCLE	35
MAXIMUM PEAK CONDUCTED OUTPUT POWER	42
-6DB BANDWIDTH	43
OCCUPIED CHANNEL BANDWIDTH	50
MAXIMUM POWER SPECTRAL DENSITY LEVEL	57
BAND EDGE	64
CONDUCTED RF SPURIOUS EMISSION	73
APPENDIX II - MEASUREMENT PHOTOS	86



Revision History

Rev.	Issue Date	Contents
00	Apr. 30, 2025	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB&99% Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	PSD	$\pm 1.57\text{dB}$
3	Bandwidth	$\pm 0.46\%$
4	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
5	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
6	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
7	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
8	All emissions, radiated >6G	$\pm 5.48\text{dB}$
9	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
10	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Battery Camera	
Trademark:	Botslab	
Model Name:	BC-BD06-M10	
Series Model:	BC-BD06-M10-V0, BC-BD06-M10-V1, BC-BD06-M10-V2, BC-BD06-M10-V3, BC-BD06-M10-V4, BC-BD06-M10-V5, BC-BD06-M10-V6, BC-BD06-M10-V7, BC-BD06-M10-V8, BC-BD06-M10-V9	
Model Difference:	Only differences in model and color.	
Product Description:	Operation Frequency:	802.11b/g/n/ax(20MHz): 2412~2462 MHz 802.11n/ax (40MHz):2422~2452MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ax(OFDMA): BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM
	Number of Channel:	802.11b/g/n/ax(20MHz): 11CH 802.11n/ax(40MHz): 7CH
	Antenna Designation:	FPC
	Antenna Gain(dBi):	4.29dBi
Channel List:	Please refer to the Note 3.	
Rating:	Input: DC 5V 2A	
Battery:	Capacity: 10000mAh Rated Voltage: 3.6V	
Hardware Version:	EVT02	
Software Version:	W520_v1.0.3.6257_20241113	
Connecting I/O Port(s):	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Operation Frequency of channel			
802.11b/g/n/ax(20MHz)		Channel List for 802.11n/ax(40MHz)	
Channel	Frequency	Channel	Frequency
01	2412	03	2422
02	2417	04	2427
03	2422	05	2432
04	2427	06	2437
05	2432	07	2442
06	2437	08	2447
07	2442	09	2452
08	2447		
09	2452		
10	2457		
11	2462		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n/ax(20MHz)		For 802.11n/ax(40MHz)	
Channel	Freq.(MHz)	Channel	Freq.(MHz)
01	2412	03	2422
06	2437	06	2437
11	2462	09	2452



2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0
Mode 10	TX IEEE 802.11ax HE20 CH1	MCS 0
Mode 11	TX IEEE 802.11ax HE20 CH6	MCS 0
Mode 12	TX IEEE 802.11ax HE20 CH11	MCS 0
Mode 13	TX IEEE 802.11n HT40 CH3	MCS 0
Mode 14	TX IEEE 802.11n HT40 CH6	MCS 0
Mode 15	TX IEEE 802.11n HT40 CH9	MCS 0
Mode 16	TX IEEE 802.11 ax HE40 CH3	MCS 0
Mode 17	TX IEEE 802.11 ax HE40 CH6	MCS 0
Mode 18	TX IEEE 802.11 ax HE40 CH9	MCS 0

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode19: Keeping TX + WLAN Link

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) The 802.11ax mode is investigated among different tones(26/52/106/242-tone RU channel), full resource units (RU), partial resourceunits. The partial RU has no higher power than full RU's, thus the full RU is chosen as main testconfiguration.



2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test software Version	Test program: 2.4G WIFI	
SecureCRT_6.5.0.380	Mode Or Modulation type	Power setting
	b	12
	g	9
	n20	8
	n40	8
	ax20	8
	ax40	8

2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	HKF-16	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
LISN	SCHWARZBECK	NNLK 8122	00160	2024.03.09	2025.03.08
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2024.03.09	2025.03.08
Temperature & Humidity	KTJ	TA218B	N.A	2024.03.09	2025.03.08
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
Active loop Antenna	ETS	6502	00049544	2023.10.13	2025.10.12
Spectrum Analyzer	Keysight	N9010B	MY60242508	2024.08.05	2025.08.04
Bilog Antenna(30M-1G)	SCHWARZBECK	VULB 9168	2705	2022.12.12	2025.12.11
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Horn Antenna(18-40G)	A-INFO	LB-180400-KF	J211060273	2022.06.08	2025.06.07
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2024.03.09	2025.03.08
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2024.03.09	2025.03.08
Pre-amplifier(18-40G)	com-mw	LNPA_18-40-01	18050003	2024.03.09	2025.03.08
Antenna Tower	SAEMC	BK-4AT-BS-D	SK2021093008	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2024.03.11	2025.03.10
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9010B	MY60242508	2024.08.05	2025.08.04
Signal Analyzer	Keysight	N9020A	MY50530994	2024.03.09	2025.03.08
RF Automatic Test system	MW	MW100-RFCB	MW220322LG-033	2024.03.09	2025.03.08
Attenuator	eastsheep	90db	N.A	2024.03.09	2025.03.08
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2024.03.11	2025.03.10
Digital multimeter	MASTECH	MS8261	MBGBC83053	2024.03.09	2025.03.08
Testing Software	MTS8310_V2.0.0.0_MW				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 22.1°C
M/N: BC-BD06-M10	Humidity: 60%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-12-03
Test Mode: TX 802.11b 2412	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.182	29.75	10.61	40.36	64.39	-24.03	QP	L1
2*	0.498	29.86	10.57	40.43	56.03	-15.60	QP	L1
3*	0.886	26.78	10.64	37.42	56.00	-18.58	QP	L1
4*	1.670	24.11	10.89	35.00	56.00	-21.00	QP	L1
5*	4.514	19.95	11.11	31.06	56.00	-24.94	QP	L1
6*	15.718	31.16	11.42	42.58	60.00	-17.42	QP	L1
7*	0.182	18.03	10.61	28.64	54.39	-25.76	AV	L1
8*	0.562	21.87	10.57	32.44	46.00	-13.56	AV	L1
9*	0.774	17.31	10.60	27.91	46.00	-18.09	AV	L1
10*	1.434	13.62	10.82	24.44	46.00	-21.56	AV	L1
11*	2.278	10.94	11.05	21.99	46.00	-24.01	AV	L1
12*	17.598	16.55	11.51	28.06	50.00	-21.94	AV	L1



Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 22.1°C
M/N: BC-BD06-M10	Humidity: 60%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-12-03
Test Mode: TX 802.11b 2412	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.166	32.93	10.56	43.49	65.16	-21.67	QP	N
2*	0.562	30.66	10.55	41.21	56.00	-14.79	QP	N
3*	0.994	27.14	10.54	37.68	56.00	-18.32	QP	N
4*	2.062	23.61	10.76	34.37	56.00	-21.63	QP	N
5*	4.202	21.99	10.82	32.81	56.00	-23.19	QP	N
6*	15.826	32.76	11.42	44.18	60.00	-15.82	QP	N
7*	0.194	17.89	10.56	28.45	53.86	-25.41	AV	N
8*	0.586	21.13	10.55	31.68	46.00	-14.32	AV	N
9*	0.910	15.72	10.55	26.27	46.00	-19.73	AV	N
10*	1.754	13.18	10.71	23.89	46.00	-22.11	AV	N
11*	2.274	11.45	10.77	22.22	46.00	-23.78	AV	N
12*	17.126	16.27	11.49	27.76	50.00	-22.24	AV	N



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.6 TEST RESULT

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.




Results of Radiated Emissions (30MHz~1000MHz)

Note:1. All mode has been tested, only shown the worst case data,
2. The peak value is less than the AV limit, so no AV data is displayed.

Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 25°C
M/N: BC-BD06-M10	Humidity: 58%RH
Test Voltage: Battery	Test Data: 2024-12-11
Test Mode: TX 802.11b 2412	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	34.899	37.23	-16.87	20.36	40.00	-19.64	QP	Hor
2*	49.497	36.78	-15.64	21.14	40.00	-18.86	QP	Hor
3*	115.894	35.16	-15.52	19.64	43.50	-23.86	QP	Hor
4*	154.451	36.86	-13.26	23.60	43.50	-19.90	QP	Hor
5*	496.231	37.13	-8.82	28.31	46.00	-17.69	QP	Hor
6*	942.916	36.62	-0.32	36.30	46.00	-9.70	QP	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	45.520	35.86	-15.79	20.07	40.00	-19.93	QP	Ver
2*	137.670	35.16	-14.00	21.16	43.50	-22.34	QP	Ver
3*	156.585	35.58	-12.91	22.67	43.50	-20.83	QP	Ver
4*	445.112	36.31	-9.63	26.68	46.00	-19.32	QP	Ver
5*	772.778	36.35	-3.50	32.85	46.00	-13.15	QP	Ver
6*	954.653	35.27	0.08	35.35	46.00	-10.65	QP	Ver




Results of Radiated Emissions (Above 1000MHz)

Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 24.2°C
M/N: BC-BD06-M10	Humidity: 48%RH
Test Voltage: Battery	Test Data: 2025-02-18
Test Mode: 802.11b 2412	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1654.5000	60.24	-19.50	40.74	74.00	-33.26	PK	Hor
2*	3390.6000	53.87	-8.21	45.66	74.00	-28.34	PK	Hor
3*	5390.2000	55.10	-6.69	48.41	74.00	-25.59	PK	Hor
4*	6733.2000	55.88	-7.88	48.00	74.00	-26.00	PK	Hor
5*	9461.7000	54.87	-7.38	47.49	74.00	-26.51	PK	Hor
6*	13862.6000	50.88	-3.25	47.63	74.00	-26.37	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2147.5000	58.61	-14.28	44.33	74.00	-29.67	PK	Ver
2*	3142.0000	54.22	-8.56	45.66	74.00	-28.34	PK	Ver
3*	5337.1000	54.30	-6.59	47.71	74.00	-26.29	PK	Ver
4*	8095.4000	57.73	-9.53	48.20	74.00	-25.80	PK	Ver
5*	10078.0000	55.12	-6.54	48.58	74.00	-25.42	PK	Ver
6*	13718.1000	50.87	-3.61	47.26	74.00	-26.74	PK	Ver



Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 24.2°C
M/N: BC-BD06-M10	Humidity: 48%RH
Test Voltage: Battery	Test Data: 2025-02-18
Test Mode: 802.11b 2437	
Note:	




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1811.7000	59.03	-17.85	41.18	74.00	-32.82	PK	Hor
2*	2952.9000	54.64	-8.94	45.70	74.00	-28.30	PK	Hor
3*	4910.0000	54.34	-6.04	48.30	74.00	-25.70	PK	Hor
4*	6803.4000	55.94	-7.94	48.00	74.00	-26.00	PK	Hor
5*	9083.5000	56.46	-7.97	48.49	74.00	-25.51	PK	Hor
6*	13932.7000	49.92	-3.07	46.85	74.00	-27.15	PK	Hor




No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1803.2000	59.52	-17.94	41.58	74.00	-32.42	PK	Ver
2*	3010.2000	54.46	-8.75	45.71	74.00	-28.29	PK	Ver
3*	5430.6000	55.48	-6.76	48.72	74.00	-25.28	PK	Ver
4*	7640.6000	56.82	-8.72	48.10	74.00	-25.90	PK	Ver
5*	9565.9000	54.35	-7.21	47.14	74.00	-26.86	PK	Ver
6*	14984.6000	52.24	-3.86	48.38	74.00	-25.62	PK	Ver



Project: LGT24K127	Test Engineer: LiuH
EUT: Battery Camera	Temperature: 24.2°C
M/N: BC-BD06-M10	Humidity: 48%RH
Test Voltage: Battery	Test Data: 2025-02-18
Test Mode: 802.11b 2462	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1694.9000	60.60	-19.08	41.52	74.00	-32.48	PK	Hor
2*	3352.4000	54.24	-8.26	45.98	74.00	-28.02	PK	Hor
3*	4825.0000	54.25	-6.09	48.16	74.00	-25.84	PK	Hor
4*	7685.2000	56.24	-8.84	47.40	74.00	-26.60	PK	Hor
5*	8990.0000	55.43	-8.12	47.31	74.00	-26.69	PK	Hor
6*	13720.2000	50.71	-3.60	47.11	74.00	-26.89	PK	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1830.9000	58.55	-17.64	40.91	74.00	-33.09	PK	Ver
2*	3012.4000	54.67	-8.74	45.93	74.00	-28.07	PK	Ver
3*	4289.5000	53.65	-6.51	47.14	74.00	-26.86	PK	Ver
4*	5927.9000	55.93	-7.31	48.62	74.00	-25.38	PK	Ver
5*	9021.9000	55.75	-8.07	47.68	74.00	-26.32	PK	Ver
6*	13741.5000	50.90	-3.55	47.35	74.00	-26.65	PK	Ver

Remark:

In frequency ranges 18~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.



3.2.7 TEST RESULTS(Band edge Requirements)

Note:1. All mode has been tested, only shown the worst case data,
2. The peak value is less than the AV limit, so no AV data is displayed.

Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
802.11b							
2390.00	13.08	34.10	47.18	74.00	-26.82	PK	Vertical
2390.00	1.80	34.10	35.90	54.00	-18.10	AV	Vertical
2400.00	14.22	34.11	48.33	74.00	-25.67	PK	Vertical
2400.00	2.20	34.11	36.31	54.00	-17.69	AV	Vertical
2390.00	13.15	34.10	47.25	74.00	-26.75	PK	Horizontal
2390.00	1.88	34.10	35.98	54.00	-18.02	AV	Horizontal
2400.00	12.69	34.11	46.80	74.00	-27.20	PK	Horizontal
2400.00	2.13	34.11	36.24	54.00	-17.76	AV	Horizontal
2483.50	13.99	34.44	48.43	74.00	-25.57	PK	Vertical
2483.50	3.07	34.44	37.51	54.00	-16.49	AV	Vertical
2500.00	15.53	34.46	49.99	74.00	-24.01	PK	Vertical
2500.00	3.21	34.46	37.67	54.00	-16.33	AV	Vertical
2483.50	15.01	34.44	49.45	74.00	-24.55	PK	Horizontal
2483.50	1.74	34.44	36.18	54.00	-17.82	AV	Horizontal
2500.00	15.64	34.46	50.10	74.00	-23.90	PK	Horizontal
2500.00	3.54	34.46	38.00	54.00	-16.00	AV	Horizontal
802.11g							
2390.00	12.45	34.10	46.55	74.00	-27.45	PK	Vertical
2390.00	2.05	34.10	36.15	54.00	-17.85	AV	Vertical
2400.00	13.84	34.11	47.95	74.00	-26.05	PK	Vertical
2400.00	1.84	34.11	35.95	54.00	-18.05	AV	Vertical
2390.00	13.00	34.10	47.10	74.00	-26.90	PK	Horizontal
2390.00	1.12	34.10	35.22	54.00	-18.78	AV	Horizontal
2400.00	13.87	34.11	47.98	74.00	-26.02	PK	Horizontal
2400.00	1.45	34.11	35.56	54.00	-18.44	AV	Horizontal
2483.50	14.82	34.44	49.26	74.00	-24.74	PK	Vertical
2483.50	2.45	34.44	36.89	54.00	-17.11	AV	Vertical
2500.00	14.55	34.46	49.01	74.00	-24.99	PK	Vertical
2500.00	3.29	34.46	37.75	54.00	-16.25	AV	Vertical
2483.50	15.24	34.44	49.68	74.00	-24.32	PK	Horizontal
2483.50	1.68	34.44	36.12	54.00	-17.88	AV	Horizontal



2500.00	15.11	34.46	49.57	74.00	-24.43	PK	Horizontal
2500.00	2.90	34.46	37.36	54.00	-16.64	AV	Horizontal
802.11n20							
2390.00	13.28	34.10	47.38	74.00	-26.62	PK	Vertical
2390.00	0.92	34.10	35.02	54.00	-18.98	AV	Vertical
2400.00	13.00	34.11	47.11	74.00	-26.89	PK	Vertical
2400.00	2.31	34.11	36.42	54.00	-17.58	AV	Vertical
2390.00	13.76	34.10	47.86	74.00	-26.14	PK	Horizontal
2390.00	1.61	34.10	35.71	54.00	-18.29	AV	Horizontal
2400.00	13.11	34.11	47.22	74.00	-26.78	PK	Horizontal
2400.00	1.40	34.11	35.51	54.00	-18.49	AV	Horizontal
2483.50	15.09	34.44	49.53	74.00	-24.47	PK	Vertical
2483.50	1.79	34.44	36.23	54.00	-17.77	AV	Vertical
2500.00	14.80	34.46	49.26	74.00	-24.74	PK	Vertical
2500.00	3.56	34.46	38.02	54.00	-15.98	AV	Vertical
2483.50	14.94	34.44	49.38	74.00	-24.62	PK	Horizontal
2483.50	2.93	34.44	37.37	54.00	-16.63	AV	Horizontal
2500.00	14.95	34.46	49.41	74.00	-24.59	PK	Horizontal
2500.00	3.60	34.46	38.06	54.00	-15.94	AV	Horizontal
802.11n40							
2390.00	12.84	34.10	46.94	74.00	-27.06	PK	Vertical
2390.00	1.81	34.10	35.91	54.00	-18.09	AV	Vertical
2400.00	13.96	34.11	48.07	74.00	-25.93	PK	Vertical
2400.00	1.79	34.11	35.90	54.00	-18.10	AV	Vertical
2390.00	12.43	34.10	46.53	74.00	-27.47	PK	Horizontal
2390.00	2.26	34.10	36.36	54.00	-17.64	AV	Horizontal
2400.00	13.10	34.11	47.21	74.00	-26.79	PK	Horizontal
2400.00	2.29	34.11	36.40	54.00	-17.60	AV	Horizontal
2483.50	14.34	34.44	48.78	74.00	-25.22	PK	Vertical
2483.50	2.44	34.44	36.88	54.00	-17.12	AV	Vertical
2500.00	15.84	34.46	50.30	74.00	-23.70	PK	Vertical
2500.00	3.44	34.46	37.90	54.00	-16.10	AV	Vertical
2483.50	15.42	34.44	49.86	74.00	-24.14	PK	Horizontal
2483.50	2.85	34.44	37.29	54.00	-16.71	AV	Horizontal
2500.00	15.39	34.46	49.85	74.00	-24.15	PK	Horizontal
2500.00	2.40	34.46	36.86	54.00	-17.14	AV	Horizontal
802.11ax20							
2390.00	13.15	34.10	47.25	74.00	-26.75	PK	Vertical



2390.00	1.23	34.10	35.33	54.00	-18.67	AV	Vertical
2400.00	13.01	34.11	47.12	74.00	-26.88	PK	Vertical
2400.00	1.32	34.11	35.43	54.00	-18.57	AV	Vertical
2390.00	13.11	34.10	47.21	74.00	-26.79	PK	Horizontal
2390.00	2.12	34.10	36.22	54.00	-17.78	AV	Horizontal
2400.00	13.63	34.11	47.74	74.00	-26.26	PK	Horizontal
2400.00	2.65	34.11	36.76	54.00	-17.24	AV	Horizontal
2483.50	14.80	34.44	49.24	74.00	-24.76	PK	Vertical
2483.50	3.06	34.44	37.50	54.00	-16.50	AV	Vertical
2500.00	15.71	34.46	50.17	74.00	-23.83	PK	Vertical
2500.00	2.98	34.46	37.44	54.00	-16.56	AV	Vertical
2483.50	14.75	34.44	49.19	74.00	-24.81	PK	Horizontal
2483.50	2.82	34.44	37.26	54.00	-16.74	AV	Horizontal
2500.00	14.61	34.46	49.07	74.00	-24.93	PK	Horizontal
2500.00	2.77	34.46	37.23	54.00	-16.77	AV	Horizontal
802.11ax40							
2390.00	13.25	34.10	47.35	74.00	-26.65	PK	Vertical
2390.00	2.11	34.10	36.21	54.00	-17.79	AV	Vertical
2400.00	12.63	34.11	46.74	74.00	-27.26	PK	Vertical
2400.00	1.84	34.11	35.95	54.00	-18.05	AV	Vertical
2390.00	13.75	34.10	47.85	74.00	-26.15	PK	Horizontal
2390.00	1.98	34.10	36.08	54.00	-17.92	AV	Horizontal
2400.00	13.72	34.11	47.83	74.00	-26.17	PK	Horizontal
2400.00	1.54	34.11	35.65	54.00	-18.35	AV	Horizontal
2483.50	15.22	34.44	49.66	74.00	-24.34	PK	Vertical
2483.50	2.64	34.44	37.08	54.00	-16.92	AV	Vertical
2500.00	15.37	34.46	49.83	74.00	-24.17	PK	Vertical
2500.00	3.31	34.46	37.77	54.00	-16.23	AV	Vertical
2483.50	14.38	34.44	48.82	74.00	-25.18	PK	Horizontal
2483.50	2.53	34.44	36.97	54.00	-17.03	AV	Horizontal
2500.00	14.60	34.46	49.06	74.00	-24.94	PK	Horizontal
2500.00	3.03	34.46	37.49	54.00	-16.51	AV	Horizontal
Low measurement frequencies is range from 2310 to 2422 MHz, high measurement frequencies is range from 2452 to 2500 MHz.							



4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2432 MHz Upper Band Edge: 2442 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

4.6 TEST RESULTS

For the measurement records, refer to the appendix I.



5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	$\leq 8 \text{ dBm}$ (RBW $\geq 3 \text{ KHz}$)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

For the measurement records, refer to the appendix I.



6. BANDWIDTH TEST

6.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:


Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth: 100KHz For 99% Bandwidth: 1% to 5% of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 99% Bandwidth: approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

For the measurement records, refer to the appendix I.



7. PEAK OUTPUT POWER TEST

7.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq$ [3 $\times$ RBW].
- Set span $\geq$ [3 $\times$ RBW].
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the

DTS bandwidth:

- Set the RBW = 1 MHz.
- Set the VBW $\geq$ [3 $\times$ RBW].
- Set the span $\geq$ [1.5 $\times$ DTS bandwidth].
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.


PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

For the measurement records, refer to the appendix I.



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA


The EUT antenna is FPC Antenna. It comply with the standard requirement.



APPENDIX I - TEST RESULTS

Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	98.85	0	0.12
NVNT	b	2437	98.85	0	0.12
NVNT	b	2462	99.13	0	0.12
NVNT	g	2412	93.05	0.31	0.73
NVNT	g	2437	93.05	0.31	0.73
NVNT	g	2462	93.18	0.31	0.73
NVNT	n20	2412	92.74	0.33	0.78
NVNT	n20	2437	92.61	0.33	0.78
NVNT	n20	2462	92.74	0.33	0.78
NVNT	n40	2422	86.45	0.63	1.57
NVNT	n40	2437	86.22	0.64	1.57
NVNT	n40	2452	86.45	0.63	1.57
NVNT	ax20	2412	92.58	0.33	1
NVNT	ax20	2437	92.76	0.33	1
NVNT	ax20	2462	92.41	0.34	1
NVNT	ax40	2422	93.99	0.27	1.88
NVNT	ax40	2437	93.99	0.27	1.88
NVNT	ax40	2452	93.99	0.27	1.88





Duty Cycle NVNT g 2412MHz




Duty Cycle NVNT g 2437MHz



Duty Cycle NVNT g 2462MHz









Duty Cycle NVNT ax20 2412MHz




Duty Cycle NVNT ax20 2437MHz



Duty Cycle NVNT ax20 2462MHz







Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	14.8	30	Pass
NVNT	b	2437	14.59	30	Pass
NVNT	b	2462	13.46	30	Pass
NVNT	g	2412	14.26	30	Pass
NVNT	g	2437	13.98	30	Pass
NVNT	g	2462	13.59	30	Pass
NVNT	n20	2412	13.17	30	Pass
NVNT	n20	2437	12.95	30	Pass
NVNT	n20	2462	12.43	30	Pass
NVNT	n40	2422	12.9	30	Pass
NVNT	n40	2437	12.93	30	Pass
NVNT	n40	2452	12.28	30	Pass
NVNT	ax20	2412	13.88	30	Pass
NVNT	ax20	2437	13.77	30	Pass
NVNT	ax20	2462	13.34	30	Pass
NVNT	ax40	2422	13.64	30	Pass
NVNT	ax40	2437	13.64	30	Pass
NVNT	ax40	2452	13.12	30	Pass



-6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	7.619	0.5	Pass
NVNT	b	2437	8.077	0.5	Pass
NVNT	b	2462	9.07	0.5	Pass
NVNT	g	2412	16.303	0.5	Pass
NVNT	g	2437	16.299	0.5	Pass
NVNT	g	2462	15.707	0.5	Pass
NVNT	n20	2412	17.551	0.5	Pass
NVNT	n20	2437	16.543	0.5	Pass
NVNT	n20	2462	15.715	0.5	Pass
NVNT	n40	2422	35.255	0.5	Pass
NVNT	n40	2437	35.463	0.5	Pass
NVNT	n40	2452	35.448	0.5	Pass
NVNT	ax20	2412	17.377	0.5	Pass
NVNT	ax20	2437	18.615	0.5	Pass
NVNT	ax20	2462	17.417	0.5	Pass
NVNT	ax40	2422	36.332	0.5	Pass
NVNT	ax40	2437	36.296	0.5	Pass
NVNT	ax40	2452	36.332	0.5	Pass



Test Graphs

-6dB Bandwidth NVNT b 2412MHz





-6dB Bandwidth NVNT b 2437MHz





-6dB Bandwidth NVNT b 2462MHz
















Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	b	2412	13.096
NVNT	b	2437	13.103
NVNT	b	2462	13.101
NVNT	g	2412	16.58
NVNT	g	2437	16.59
NVNT	g	2462	16.612
NVNT	n20	2412	17.795
NVNT	n20	2437	17.77
NVNT	n20	2462	17.777
NVNT	n40	2422	36.279
NVNT	n40	2437	36.248
NVNT	n40	2452	36.24
NVNT	ax20	2412	19.001
NVNT	ax20	2437	18.957
NVNT	ax20	2462	18.959
NVNT	ax40	2422	37.732
NVNT	ax40	2437	37.72
NVNT	ax40	2452	37.743





OBW NVNT g 2412MHz



OBW NVNT g 2437MHz



OBW NVNT g 2462MHz







OBW NVNT n40 2422MHz





OBW NVNT n40 2437MHz



OBW NVNT n40 2452MHz












Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-9.61	8	Pass
NVNT	b	2437	-8.74	8	Pass
NVNT	b	2462	-10.54	8	Pass
NVNT	g	2412	-15.56	8	Pass
NVNT	g	2437	-14.96	8	Pass
NVNT	g	2462	-15.44	8	Pass
NVNT	n20	2412	-16.18	8	Pass
NVNT	n20	2437	-15.84	8	Pass
NVNT	n20	2462	-15.07	8	Pass
NVNT	n40	2422	-17.6	8	Pass
NVNT	n40	2437	-19.12	8	Pass
NVNT	n40	2452	-19.63	8	Pass
NVNT	ax20	2412	-17.24	8	Pass
NVNT	ax20	2437	-7.2	8	Pass
NVNT	ax20	2462	-8.36	8	Pass
NVNT	ax40	2422	-10.2	8	Pass
NVNT	ax40	2437	-10.86	8	Pass
NVNT	ax40	2452	-10.08	8	Pass

















Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-49.12	-20	Pass
NVNT	b	2462	-58.65	-20	Pass
NVNT	g	2412	-29.17	-20	Pass
NVNT	g	2462	-50.92	-20	Pass
NVNT	n20	2412	-29.56	-20	Pass
NVNT	n20	2462	-49.19	-20	Pass
NVNT	n40	2422	-32.61	-20	Pass
NVNT	n40	2452	-45.32	-20	Pass
NVNT	ax20	2412	-29.42	-20	Pass
NVNT	ax20	2462	-44.69	-20	Pass
NVNT	ax40	2422	-31.95	-20	Pass
NVNT	ax40	2452	-45.58	-20	Pass






Band Edge NVNT b 2462MHz Emission



Band Edge NVNT g 2412MHz Ref



Band Edge NVNT g 2412MHz Emission



Band Edge NVNT g 2462MHz Ref




Band Edge NVNT g 2462MHz Emission



Band Edge NVNT n20 2412MHz Ref














Band Edge NVNT ax40 2422MHz Emission



Band Edge NVNT ax40 2452MHz Ref



Band Edge NVNT ax40 2452MHz Emission





Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-44.89	-20	Pass
NVNT	b	2437	-47.35	-20	Pass
NVNT	b	2462	-46.63	-20	Pass
NVNT	g	2412	-44.62	-20	Pass
NVNT	g	2437	-46.49	-20	Pass
NVNT	g	2462	-45.05	-20	Pass
NVNT	n20	2412	-46.29	-20	Pass
NVNT	n20	2437	-44.78	-20	Pass
NVNT	n20	2462	-44.98	-20	Pass
NVNT	n40	2422	-43.07	-20	Pass
NVNT	n40	2437	-43.63	-20	Pass
NVNT	n40	2452	-42.11	-20	Pass
NVNT	ax20	2412	-45.07	-20	Pass
NVNT	ax20	2437	-44.95	-20	Pass
NVNT	ax20	2462	-45.78	-20	Pass
NVNT	ax40	2422	-43.12	-20	Pass
NVNT	ax40	2437	-43.04	-20	Pass
NVNT	ax40	2452	-29.96	-20	Pass



Test Graphs

Tx. Spurious NVNT b 2412MHz Ref



Tx. Spurious NVNT b 2412MHz Emission



Tx. Spurious NVNT b 2437MHz Ref





Tx. Spurious NVNT b 2437MHz Emission





Tx. Spurious NVNT b 2462MHz Ref



Tx. Spurious NVNT b 2462MHz Emission










Tx. Spurious NVNT n20 2412MHz Ref



Tx. Spurious NVNT n20 2412MHz Emission



Tx. Spurious NVNT n20 2437MHz Ref





Tx. Spurious NVNT n20 2437MHz Emission



Tx. Spurious NVNT n20 2462MHz Ref



Tx. Spurious NVNT n20 2462MHz Emission






Tx. Spurious NVNT n40 2422MHz Ref



Tx. Spurious NVNT n40 2422MHz Emission



Tx. Spurious NVNT n40 2437MHz Ref





Tx. Spurious NVNT n40 2437MHz Emission



Tx. Spurious NVNT n40 2452MHz Ref



Tx. Spurious NVNT n40 2452MHz Emission





Tx. Spurious NVNT ax20 2412MHz Ref



Tx. Spurious NVNT ax20 2412MHz Emission



Tx. Spurious NVNT ax20 2437MHz Ref






Tx. Spurious NVNT ax20 2437MHz Emission



Tx. Spurious NVNT ax20 2462MHz Ref



Tx. Spurious NVNT ax20 2462MHz Emission





Tx. Spurious NVNT ax40 2422MHz Ref



Tx. Spurious NVNT ax40 2422MHz Emission



Tx. Spurious NVNT ax40 2437MHz Ref





Tx. Spurious NVNT ax40 2437MHz Emission



Tx. Spurious NVNT ax40 2452MHz Ref



Tx. Spurious NVNT ax40 2452MHz Emission





APPENDIX II - MEASUREMENT PHOTOS

Note: Please see the attached RF_Test Setup photos for FCC ID&IC.

※※※※※END OF THE REPORT※※※※※