

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10843.000 | 45.77 | -0.31 | 45.46 | 68.30 | -22.84 | peak | P |
| 2 | 13410.000 | 42.77 | 2.11 | 44.88 | 68.30 | -23.42 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11 ax(HE40) Mode 5190MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11693.000 | 42.70 | 1.03 | 43.73 | 68.30 | -24.57 | peak | P |
| 2 * | 14600.000 | 41.22 | 3.24 | 44.46 | 68.30 | -23.84 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|
| 1 | 11200.000 | 44.29 | 0.33 | 44.62 | 68.30 | -23.68 | peak | P |
| 2 * | 14311.000 | 41.91 | 2.94 | 44.85 | 68.30 | -23.45 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5230MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|
| 1 * | 10588.000 | 45.74 | -0.89 | 44.85 | 68.30 | -23.45 | peak | P |
| 2 | 13478.000 | 41.22 | 2.17 | 43.39 | 68.30 | -24.91 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV)
3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10554.000 | 44.58 | -0.97 | 43.61 | 68.30 | -24.69 | peak | P |
| 2 * | 13138.000 | 42.61 | 1.88 | 44.49 | 68.30 | -23.81 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11608.000 | 42.53 | 0.89 | 43.42 | 68.30 | -24.88 | peak | P |
| 2 * | 14957.000 | 41.53 | 3.61 | 45.14 | 68.30 | -23.16 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11319.000 | 43.91 | 0.49 | 44.40 | 68.30 | -23.90 | peak | P |
| 2 * | 14243.000 | 43.46 | 2.86 | 46.32 | 68.30 | -21.98 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE80) Mode 5210MHz (U-NII-1) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10996.000 | 44.52 | 0.05 | 44.57 | 68.30 | -23.73 | peak | P |
| 2 * | 14600.000 | 42.55 | 3.24 | 45.79 | 68.30 | -22.51 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



5745MHz-5825MHz(U-NII-3)

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11a Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11710.000 | 42.96 | 1.05 | 44.01 | 68.30 | -24.29 | peak | P |
| 2 * | 14328.000 | 42.76 | 2.95 | 45.71 | 68.30 | -22.59 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11a Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10843.000 | 44.08 | -0.31 | 43.77 | 68.30 | -24.53 | peak | P |
| 2 * | 14175.000 | 42.97 | 2.80 | 45.77 | 68.30 | -22.53 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11a Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12271.000 | 42.76 | 1.53 | 44.29 | 68.30 | -24.01 | peak | P |
| 2 * | 14345.000 | 43.18 | 2.97 | 46.15 | 68.30 | -22.15 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11a Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10809.000 | 45.20 | -0.39 | 44.81 | 68.30 | -23.49 | peak | P |
| 2 | 14413.000 | 41.53 | 3.04 | 44.57 | 68.30 | -23.73 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11a Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 11200.000 | 44.29 | 0.33 | 44.62 | 68.30 | -23.68 | peak | P |
| 2 | 13172.000 | 42.41 | 1.91 | 44.32 | 68.30 | -23.98 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11a Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10333.000 | 46.07 | -1.48 | 44.59 | 68.30 | -23.71 | peak | P |
| 2 * | 13206.000 | 43.25 | 1.93 | 45.18 | 68.30 | -23.12 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11n(HT20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11285.000 | 44.16 | 0.45 | 44.61 | 68.30 | -23.69 | peak | P |
| 2 * | 14260.000 | 42.31 | 2.89 | 45.20 | 68.30 | -23.10 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11n(HT20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10962.000 | 44.60 | -0.04 | 44.56 | 68.30 | -23.74 | peak | P |
| 2 * | 14107.000 | 42.16 | 2.72 | 44.88 | 68.30 | -23.42 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | |
|----------------------|---|----------------|---------------------------|----------------|----------------|-------------|----------|-----|--|--|--|--|--|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | |
| Ant. Pol. | Horizontal | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | |
| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | | | | | |
| 1 | 13206.000 | 42.19 | 1.93 | 44.12 | 68.30 | -24.18 | peak | P | | | | | |
| 2 * | 14940.000 | 42.11 | 3.59 | 45.70 | 68.30 | -22.60 | peak | P | | | | | |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | |
|----------------------|---|----------------|---------------------------|----------------|----------------|-------------|----------|-----|--|--|--|--|--|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | |
| Ant. Pol. | Vertical | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | |
| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | | | | | |
| 1 * | 10503.000 | 45.49 | -1.09 | 44.40 | 68.30 | -23.90 | peak | P | | | | | |
| 2 | 13206.000 | 42.03 | 1.93 | 43.96 | 68.30 | -24.34 | peak | P | | | | | |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| Temperature: | 23.5°C | | Relative Humidity: | | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|-----------------------------|---------------------------|-----------------------------|-----------------------------|-------------|----------|-----|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|---|-----------|-------|-------|-------|-------|--------|------|---|-----|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Horizontal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10452.000</td> <td>44.86</td> <td>-1.20</td> <td>43.66</td> <td>68.30</td> <td>-24.64</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>13546.000</td> <td>41.90</td> <td>2.22</td> <td>44.12</td> <td>68.30</td> <td>-24.18</td> <td>peak</td> <td>P</td> </tr> </tbody> </table> | | | | | | | | | No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | 1 | 10452.000 | 44.86 | -1.20 | 43.66 | 68.30 | -24.64 | peak | P | 2 * | 13546.000 | 41.90 | 2.22 | 44.12 | 68.30 | -24.18 | peak | P |
| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 10452.000 | 44.86 | -1.20 | 43.66 | 68.30 | -24.64 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 * | 13546.000 | 41.90 | 2.22 | 44.12 | 68.30 | -24.18 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV) 3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Temperature: | 23.5°C | | Relative Humidity: | | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|-----------------------------|---------------------------|-----------------------------|-----------------------------|-------------|----------|-----|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|---|-----------|-------|------|-------|-------|--------|------|---|-----|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Vertical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dB_uV)</th> <th>Factor (dB/m)</th> <th>Level (dB_uV/m)</th> <th>Limit (dB_uV/m)</th> <th>Margin (dB)</th> <th>Detector</th> <th>P/F</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>13172.000</td> <td>42.66</td> <td>1.91</td> <td>44.57</td> <td>68.30</td> <td>-23.73</td> <td>peak</td> <td>P</td> </tr> <tr> <td>2 *</td> <td>14855.000</td> <td>42.63</td> <td>3.51</td> <td>46.14</td> <td>68.30</td> <td>-22.16</td> <td>peak</td> <td>P</td> </tr> </tbody> </table> | | | | | | | | | No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | 1 | 13172.000 | 42.66 | 1.91 | 44.57 | 68.30 | -23.73 | peak | P | 2 * | 14855.000 | 42.63 | 3.51 | 46.14 | 68.30 | -22.16 | peak | P |
| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 13172.000 | 42.66 | 1.91 | 44.57 | 68.30 | -23.73 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 * | 14855.000 | 42.63 | 3.51 | 46.14 | 68.30 | -22.16 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB_uV/m)= Corr. (dB/m)+ Read Level (dB_uV) 3. Margin (dB) = Peak/AVG (dB_uV/m)-Limit PK/AVG(dB_uV/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 11132.000 | 44.81 | 0.24 | 45.05 | 68.30 | -23.25 | peak | P |
| 2 | 14566.000 | 41.62 | 3.21 | 44.83 | 68.30 | -23.47 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12696.000 | 42.81 | 1.67 | 44.48 | 68.30 | -23.82 | peak | P |
| 2 * | 14872.000 | 41.94 | 3.53 | 45.47 | 68.30 | -22.83 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 13240.000 | 43.59 | 1.96 | 45.55 | 68.30 | -22.75 | peak | P |
| 2 * | 14770.000 | 42.35 | 3.42 | 45.77 | 68.30 | -22.53 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11234.000 | 43.80 | 0.38 | 44.18 | 68.30 | -24.12 | peak | P |
| 2 * | 13223.000 | 42.69 | 1.95 | 44.64 | 68.30 | -23.66 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10656.000 | 46.15 | -0.73 | 45.42 | 68.30 | -22.88 | peak | P |
| 2 | 13070.000 | 42.83 | 1.82 | 44.65 | 68.30 | -23.65 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12747.000 | 42.09 | 1.69 | 43.78 | 68.30 | -24.52 | peak | P |
| 2 * | 14838.000 | 42.22 | 3.48 | 45.70 | 68.30 | -22.60 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 13444.000 | 42.64 | 2.14 | 44.78 | 68.30 | -23.52 | peak | P |
| 2 * | 14940.000 | 41.86 | 3.59 | 45.45 | 68.30 | -22.85 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5745MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11251.000 | 44.22 | 0.40 | 44.62 | 68.30 | -23.68 | peak | P |
| 2 * | 14294.000 | 42.40 | 2.92 | 45.32 | 68.30 | -22.98 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------------|--------------------|-----------------------------|-----------------------------|-------------|----------|-----|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|-----|-----------|-------|------|-------|-------|--------|------|---|---|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Horizontal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_uV)</th><th>Factor (dB/m)</th><th>Level (dB_uV/m)</th><th>Limit (dB_uV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1 *</td><td>11183.000</td><td>43.88</td><td>0.31</td><td>44.19</td><td>68.30</td><td>-24.11</td><td>peak</td><td>P</td></tr><tr><td>2</td><td>13223.000</td><td>42.19</td><td>1.95</td><td>44.14</td><td>68.30</td><td>-24.16</td><td>peak</td><td>P</td></tr></tbody></table> | | | | | | | | | No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | 1 * | 11183.000 | 43.88 | 0.31 | 44.19 | 68.30 | -24.11 | peak | P | 2 | 13223.000 | 42.19 | 1.95 | 44.14 | 68.30 | -24.16 | peak | P |
| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 * | 11183.000 | 43.88 | 0.31 | 44.19 | 68.30 | -24.11 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | 13223.000 | 42.19 | 1.95 | 44.14 | 68.30 | -24.16 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-----------------------------|--------------------|-----------------------------|-----------------------------|-------------|----------|-----|-----|-----------------|-----------------------------|---------------|-----------------------------|-----------------------------|-------------|----------|-----|---|-----------|-------|------|-------|-------|--------|------|---|-----|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Vertical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5785MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dB_uV)</th><th>Factor (dB/m)</th><th>Level (dB_uV/m)</th><th>Limit (dB_uV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>13257.000</td><td>42.37</td><td>1.98</td><td>44.35</td><td>68.30</td><td>-23.95</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>14923.000</td><td>42.48</td><td>3.57</td><td>46.05</td><td>68.30</td><td>-22.25</td><td>peak</td><td>P</td></tr></tbody></table> | | | | | | | | | No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | 1 | 13257.000 | 42.37 | 1.98 | 44.35 | 68.30 | -23.95 | peak | P | 2 * | 14923.000 | 42.48 | 3.57 | 46.05 | 68.30 | -22.25 | peak | P |
| No. | Frequency (MHz) | Reading (dB _u V) | Factor (dB/m) | Level (dB _u V/m) | Limit (dB _u V/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 13257.000 | 42.37 | 1.98 | 44.35 | 68.30 | -23.95 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 * | 14923.000 | 42.48 | 3.57 | 46.05 | 68.30 | -22.25 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB _u V/m)= Corr. (dB/m)+ Read Level (dB _u V) 3. Margin (dB) = Peak/AVG (dB _u V/m)-Limit PK/AVG(dB _u V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12118.000 | 42.12 | 1.49 | 43.61 | 68.30 | -24.69 | peak | P |
| 2 * | 14770.000 | 41.69 | 3.42 | 45.11 | 68.30 | -23.19 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE20) Mode 5825MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10843.000 | 44.09 | -0.31 | 43.78 | 68.30 | -24.52 | peak | P |
| 2 * | 14090.000 | 41.46 | 2.70 | 44.16 | 68.30 | -24.14 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11n(HT40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11302.000 | 43.71 | 0.47 | 44.18 | 68.30 | -24.12 | peak | P |
| 2 * | 13733.000 | 42.62 | 2.39 | 45.01 | 68.30 | -23.29 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11n(HT40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12152.000 | 42.58 | 1.49 | 44.07 | 68.30 | -24.23 | peak | P |
| 2 * | 14719.000 | 41.76 | 3.36 | 45.12 | 68.30 | -23.18 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|----------------|---------------------------|----------------|----------------|-------------|----------|-----|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|---|-----------|-------|------|-------|-------|--------|------|---|-----|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Horizontal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>11217.000</td><td>43.05</td><td>0.35</td><td>43.40</td><td>68.30</td><td>-24.90</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>13240.000</td><td>42.19</td><td>1.96</td><td>44.15</td><td>68.30</td><td>-24.15</td><td>peak</td><td>P</td></tr></tbody></table> | | | | | | | | | No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | 1 | 11217.000 | 43.05 | 0.35 | 43.40 | 68.30 | -24.90 | peak | P | 2 * | 13240.000 | 42.19 | 1.96 | 44.15 | 68.30 | -24.15 | peak | P |
| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 11217.000 | 43.05 | 0.35 | 43.40 | 68.30 | -24.90 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 * | 13240.000 | 42.19 | 1.96 | 44.15 | 68.30 | -24.15 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| Temperature: | 23.5°C | | Relative Humidity: | 49% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|----------------|---------------------------|----------------|----------------|-------------|----------|-----|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|---|-----------|-------|------|-------|-------|--------|------|---|-----|-----------|-------|------|-------|-------|--------|------|---|
| Test Voltage: | DC 11.55V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ant. Pol. | Vertical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Test Mode: | TX 802.11n(HT40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>12696.000</td><td>42.28</td><td>1.67</td><td>43.95</td><td>68.30</td><td>-24.35</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>14957.000</td><td>42.61</td><td>3.61</td><td>46.22</td><td>68.30</td><td>-22.08</td><td>peak</td><td>P</td></tr></tbody></table> | | | | | | | | | No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | 1 | 12696.000 | 42.28 | 1.67 | 43.95 | 68.30 | -24.35 | peak | P | 2 * | 14957.000 | 42.61 | 3.61 | 46.22 | 68.30 | -22.08 | peak | P |
| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 12696.000 | 42.28 | 1.67 | 43.95 | 68.30 | -24.35 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 * | 14957.000 | 42.61 | 3.61 | 46.22 | 68.30 | -22.08 | peak | P | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected. 5. No report for the emission which below the prescribed limit. 6. The peak value<average limit, So only show the peak value. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10775.000 | 45.30 | -0.47 | 44.83 | 68.30 | -23.47 | peak | P |
| 2 * | 13954.000 | 42.84 | 2.57 | 45.41 | 68.30 | -22.89 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 13002.000 | 41.52 | 1.76 | 43.28 | 68.30 | -25.02 | peak | P |
| 2 * | 14294.000 | 41.84 | 2.92 | 44.76 | 68.30 | -23.54 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 13325.000 | 42.46 | 2.04 | 44.50 | 68.30 | -23.80 | peak | P |
| 2 * | 14872.000 | 41.50 | 3.53 | 45.03 | 68.30 | -23.27 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|---|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10962.000 | 44.61 | -0.04 | 44.57 | 68.30 | -23.73 | peak | P |
| 2 | 13257.000 | 42.24 | 1.98 | 44.22 | 68.30 | -24.08 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 13206.000 | 42.65 | 1.93 | 44.58 | 68.30 | -23.72 | peak | P |
| 2 * | 14991.000 | 41.58 | 3.65 | 45.23 | 68.30 | -23.07 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5755MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10571.000 | 45.70 | -0.93 | 44.77 | 68.30 | -23.53 | peak | P |
| 2 | 13393.000 | 42.26 | 2.10 | 44.36 | 68.30 | -23.94 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 11693.000 | 44.65 | 1.03 | 45.68 | 68.30 | -22.62 | peak | P |
| 2 | 14158.000 | 42.52 | 2.78 | 45.30 | 68.30 | -23.00 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|--|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE40) Mode 5795MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 * | 10979.000 | 44.56 | -0.01 | 44.55 | 68.30 | -23.75 | peak | P |
| 2 | 13206.000 | 42.11 | 1.93 | 44.04 | 68.30 | -24.26 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 12645.000 | 42.78 | 1.65 | 44.43 | 68.30 | -23.87 | peak | P |
| 2 * | 14345.000 | 42.15 | 2.97 | 45.12 | 68.30 | -23.18 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|----------------------|---|---------------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11710.000 | 42.90 | 1.05 | 43.95 | 68.30 | -24.35 | peak | P |
| 2 * | 14821.000 | 41.39 | 3.47 | 44.86 | 68.30 | -23.44 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.



| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Horizontal | | |
| Test Mode: | TX 802.11ax(HE80) Mode 5775MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 11132.000 | 43.57 | 0.24 | 43.81 | 68.30 | -24.49 | peak | P |
| 2 * | 14906.000 | 42.20 | 3.56 | 45.76 | 68.30 | -22.54 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

| | | | |
|---------------|--|--------------------|-----|
| Temperature: | 23.5°C | Relative Humidity: | 49% |
| Test Voltage: | DC 11.55V | | |
| Ant. Pol. | Vertical | | |
| Test Mode: | TX 802.11ax(HE80) Mode 5775MHz (U-NII-3) (Ant.1+Ant.2) | | |

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | P/F |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-----|
| 1 | 10044.000 | 46.26 | -2.15 | 44.11 | 68.30 | -24.19 | peak | P |
| 2 * | 12152.000 | 43.52 | 1.49 | 45.01 | 68.30 | -23.29 | peak | P |

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value<average limit, So only show the peak value.

-----END OF THE REPORT-----

