

Antenna Test Report

For

Project ET5000BT

Version:

Customer	博陆科	Project	ET5000BT
Band	BT	Color	
Issued by	WWL	Checked by	
Confirmed by		Date	2024.09.18

This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.






一. Test Instrumentation and item(测试设备及项目)


类别 (Class)	测试项目 (Test item)	设备 (Equipment)
1. S parameter	1. 回波损耗(RL) 2. 驻波比 (VSWR) 3.斯密斯原图(Smith chart)	网分 (VNA) : Agilent E5071B R&S ZVB8 Protek A333
2. 耦合测试 (Coupling testing)	1. 发射功率 (MAX Power) 2. 接收灵敏度 (MIN Sens)	1.2G/3G Tester: Agilent 8960 2.The coupling box: TESCOM TC-5060A 3. 3D Chamber: ETS 3D Chamber (5x3x3)
3. 3D 无源测试 (Passive Test)	1. 效率 (Effeciency) 2. 增益 (Gain) 3.辐射方向图 (radiation pattern)	1. 3D Chamber: TEM24 3D Chamber (5x5x5) ETS 3D Chamber (5x3x3) 2. 网分 (VNA) : Agilent E5071B R&S ZVB8
4.3D 有源测试 (Active Test)	1. 3D 功率 (TRP) 2. 3D 灵敏度 (TIS) 3.吞吐率 (Throughput rate)	1. 3D Chamber: TEM24 3D Chamber (5x5x5) ETS 3D Chamber (5x3x3) 2.2G/3G Tester: Agilent 8960 3.4G Tester: MT8820C/CMW500 4.WIFI/BT/NB-iot Tester: CMW500 5. 5G Tester: SP9500-CTS 6.Head: HEAD-P10 (FACE-P10)




深圳市国质信网络通讯有限公司
ShenZhen NQI network communication ltd



二. Chamber coordinate axis (暗室坐标)



This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it propely, without our company and related clients allowed, anybody has no rights to reval it to public.



三. Definitions (定义)

VSWR: Voltage Standing Wave Rate

RL: Return loss

TRP: total radiated power


TIS: total isotropic sensitivity

四. Cell-Phone Photo and Dealing Method (手机图片及环境处理)




This test report belongs to ShenZhen NQI network communication ltd. and related clients to file, please keeping it properly, without our company and related clients allowed, anybody has no rights to reveal it to public.

五. Antenna size



六. Passive Test (无源测试)




Frequency	Antenna gain
2450MHz	1 dBi

This test report belongs to ShenZhen NQi network communication ltd. and related clients to file, please keeping it properly, without our company and related clients allowed, anybody has no rights to reveal it to public.



RL/VSWR (回波损耗/驻波比)



七. TRP&TIS

NQI ANT TRP&TIS parameter Summary of ET5000BT				
	Test	Bluetooth TRP		
	Result	0	39	78
自由空间	TRP (dBm)	6.89	6.99	7.85
	TIS (dBm)	-91.71	-91.3	-93.06
	Test	Bluetooth TRP		
	Result	0	39	78
二代头戴模	TRP (dBm)	5.06	5.55	6.55
	TIS (dBm)	-89.14	-89.44	-90.93