

FCC Radio Test Report

FCC ID: 2A25M-PRE31G

This report concerns: Original Grant

Project No. : 2108C220
Equipment : Pre-install 3.1G
Brand Name : Clobotics
Test Model : Sloth pre3.1G
Series Model : N/A
Applicant : SHANGHAI CLOBOTICS TECHNOLOGY CO., LTD
Address : 555 DongChuan Rd., Building 5, Rm 102A,Minhang Distr., Shanghai, China
Manufacturer : SHANGHAI CLOBOTICS TECHNOLOGY CO., LTD
Address : 555 DongChuan Rd., Building 5, Rm 102A,Minhang Distr., Shanghai, China
Factory : Shenzhen Changkeshun Technology Co.,Ltd
Address : Fl.3-4,Bldg.k,Jinchangda Tech Park,Guanlan St.,Longhua Dist., Shenzhen, China
Date of Receipt : Sep. 09, 2021
Date of Test : Sep. 10, 2021 ~ Oct. 21, 2021
Issued Date : Oct. 26, 2021
Report Version : R01
Test Sample : Engineering Sample No.: DG2021090933 for conducted, DG2021090934 for radiated.
Standard(s) : 47 CFR FCC Part 22 Subpart H
47 CFR FCC Part 2
ANSI/TIA/EIA-603-E-2016
FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Gabriel Zhu

Prepared by : Gabriel Zhu

Steven Lu

Approved by : Steven Lu



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's
Republic of China
Tel: +86-769-8318-3000
Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	8
2 . GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED	12
2.4 DESCRIPTION OF SUPPORT UNITS	12
3 . TEST RESULT	13
3.1 OUTPUT POWER MEASUREMENT	13
3.1.1 LIMIT	13
3.1.2 TEST PROCEDURE	13
3.1.3 TEST SETUP LAYOUT	13
3.1.4 TEST DEVIATION	13
3.1.5 TEST RESULTS	13
3.2 OCCUPIED BANDWIDTH MEASUREMENT	14
3.2.1 TEST PROCEDURE	14
3.2.2 TEST SETUP LAYOUT	14
3.2.3 TEST DEVIATION	14
3.2.4 TEST RESULTS	14
3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	15
3.3.1 LIMIT	15
3.3.2 TEST PROCEDURES	15
3.3.3 TEST SETUP LAYOUT	15
3.3.4 TEST DEVIATION	15
3.3.5 TEST RESULTS	15
3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT	16
3.4.1 LIMIT	16
3.4.2 TEST PROCEDURES	16
3.4.3 TEST SETUP LAYOUT	17
3.4.4 TEST DEVIATION	18
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	18
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	18
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	18
3.5 BAND EDGE MEASUREMENT	19
3.5.1 LIMIT	19

Table of Contents	Page
3.5.2 TEST PROCEDURES	19
3.5.3 TEST SETUP LAYOUT	19
3.5.4 TEST DEVIATION	19
3.5.5 TEST RESULTS	19
3.6 PEAK TO AVERAGE RATIO MEASUREMENT	20
3.6.1 LIMIT	20
3.6.2 TEST PROCEDURES	20
3.6.3 TEST SETUP LAYOUT	20
3.6.4 TEST DEVIATION	20
3.6.5 TEST RESULTS	20
3.7 FREQUENCY STABILITY MEASUREMENT	21
3.7.1 LIMIT	21
3.7.2 TEST PROCEDURES	21
3.7.3 TEST SETUP LAYOUT	21
3.7.4 TEST DEVIATION	21
3.7.5 TEST RESULTS	21
4. LIST OF MEASUREMENT EQUIPMENTS	22
4 . EUT TEST PHOTO	24
APPENDIX A - OUTPUT POWER	27
APPENDIX B - OCCUPIED BANDWIDTH	32
APPENDIX C - CONDUCTED SPURIOUS EMISSIONS	41
APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)	45
APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)	50
APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)	57
APPENDIX G - BAND EDGE	64
APPENDIX H - PEAK TO AVERAGE RATIO	69
APPENDIX I - FREQUENCY STABILITY	78

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Oct. 18, 2021
R01	Modified the comments of TCB.	Oct. 26, 2021

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 22 Subpart H & Part 2			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 22.913(a)(5)	Effective Radiated Power	PASS	-----
2.1049	Occupied Bandwidth	PASS	-----
2.1051 22.917(a)	Conducted Spurious Emissions	PASS	-----
2.1053 22.917(a)	Radiated Spurious Emissions	PASS	-----
22.917(a)	Band Edge Measurements	PASS	-----
-	Peak To Average Ratio	PASS	Record Only
2.1055 22.355	Frequency Stability	PASS	-----

Note:

(1) "N/A" denotes test is not applicable in this test report.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China.
BTL's Test Firm Registration Number for FCC: 357015
BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))
The BTL measurement uncertainty as below table:

A. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
DG-CB03 (3m)	CISPR	9KHz ~ 30MHz	-	2.36
		30MHz ~ 200MHz	V	4.36
		30MHz ~ 200MHz	H	3.32
		200MHz ~ 1,000MHz	V	4.08
		200MHz ~ 1,000MHz	H	3.96
		1GHz ~ 6GHz	-	3.80
		6GHz ~ 18GHz	-	4.82

Test Site	Method	Measurement Frequency Range	U,(dB)
DG-CB03 (1m)	CISPR	18 GHz ~ 26.5 GHz	3.62

B. Other Measurement:

Parameter	Uncertainty
Spectrum Bandwidth	$\pm 3.8 \%$
Maximum Output Power	$\pm 0.95 \text{ dB}$
Power Spectral Density	$\pm 0.86 \text{ dB}$
Frequency Stability	$\pm 0.16 \text{ dB}$
Temperature	$\pm 0.08 \text{ }^{\circ}\text{C}$
Time	$\pm 0.58 \%$
Supply voltages	$\pm 0.3 \%$

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Output Power & ERP	22.2°C	53%	DC 12V	Tate Liu
Occupied Bandwidth	22.2°C	53%	DC 12V	Tate Liu
Conducted Spurious Emissions	22.2°C	53%	DC 12V	Tate Liu
Radiated Spurious Emissions	26°C	52%	DC 12V	Kwok Guo
Band Edge	22.2°C	53%	DC 12V	Tate Liu
Peak To Average Ratio	22.2°C	53%	DC 12V	Tate Liu
Frequency Stability	Normal & Extreme	53%	Normal & Extreme	Tate Liu

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Pre-install 3.1G			
Brand Name	Clobotics			
Test Model	Sloth pre3.1G			
Series Model	N/A			
Model Difference(s)	N/A			
Hardware Version	DH603_MB_V1.0			
Software Version	2.0.7			
Power Source	DC Voltage supplied from External Power Supply.			
Power Rating	DC 12V			
IEMI No.	Radiated	675646644564647		
	Conducted	664547655656558		
Modulation Type	LTE		QPSK,16QAM	
Max. ERP	LTE	Channel Bandwidth (MHz)	QPSK (dBm)	16QAM (dBm)
	Band 5	1.4	18.75	18.00
		3	18.87	18.22
		5	18.81	18.24
		10	18.86	18.57

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

LTE Band 5					
Test Frequency ID	Bandwidth (MHz)	N _{UL}	Frequency of Uplink (MHz)	N _{DL}	Frequency of Downlink (MHz)
Low Range	1.4	20407	824.7	2407	869.7
	3	20415	825.5	2415	870.5
	5	20425	826.5	2425	871.5
	10	20450	829	2450	874
Mid Range	1.4/3/5/10	20525	836.5	2525	881.5
High Range	1.4	20643	848.3	2643	893.3
	3	20635	847.5	2635	892.5
	5	20625	846.5	2625	891.5
	10	20600	844	2600	889

3. Table for Filed Antenna:

Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
N/A	N/A	FPC	N/A	-1.29	LTE Band 5

Note: The antenna gain is provided by the manufacturer.

2.2 DESCRIPTION OF TEST MODES


Following mode(s) is (were) found to be the worst case(s) and selected for the final test.

LTE BAND 5 MODE					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Output Power & ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1RB/3RB/6RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1RB/8RB/15RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1RB/12RB/25RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1RB/25RB/50RB
Occupied Bandwidth	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	6RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	15RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	25RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	50RB
Conducted Spurious Emissions	20407 to 20643	20525	1.4MHz	QPSK	1RB
	20425 to 20625	20525	5MHz	QPSK	1RB
	20450 to 20600	20525	10MHz	QPSK	1RB
Radiated Spurious Emissions	20407 to 20643	20525	1.4MHz	QPSK	1RB
	20425 to 20625	20525	5MHz	QPSK	1RB
	20450 to 20600	20525	10MHz	QPSK	1RB
Band Edge	20407 to 20643	20407, 20643	1.4MHz	QPSK	1RB/6RB
	20415 to 20635	20415, 20635	3MHz	QPSK	1RB/15RB
	20425 to 20625	20425, 20625	5MHz	QPSK	1RB/25RB
	20450 to 20600	20450, 20600	10MHz	QPSK	1RB/50RB
Peak To Average Ratio	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1RB
Frequency Stability	20407 to 20643	20525	1.4MHz	QPSK	1RB
	20415 to 20635	20525	3MHz	QPSK	1RB
	20425 to 20625	20525	5MHz	QPSK	1RB
	20450 to 20600	20525	10MHz	QPSK	1RB

Note:

There is only one transmitting port in the sample, and the output power has MPR backoff mechanism. The output power of 16QAM will be 1dBm smaller than that of QPSK. All bands of band edge had been evaluated. It is found the Bandwidth 5MHz of LTE Band 25 is worst and recorded.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
A	DC Source	TRUE-POWER	GPC30300N	N/A

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	DC Cable	NO	NO	1m

3. TEST RESULT

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMIT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 5.

EIRP / ERP:

EIRP = Output Power + Antenan gain


ERP = EIPR - 2.15dBi

Output Power:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP LAYOUT

Output Power Measurement



3.1.4 TEST DEVIATION

No deviation

3.1.5 TEST RESULTS

Please refer to the APPENDIX A.


3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 4.

1. The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. $RBW = (1\% \sim 5\%) \cdot EBW$
 $VBW \geq 3 \cdot RBW$
4. Set spectrum analyzer with Peak detector.

3.2.2 TEST SETUP LAYOUT



3.2.3 TEST DEVIATION

No deviation

3.2.4 TEST RESULTS

Please refer to the APPENDIX B.

3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

3.3.1 LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.3.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
3. Set spectrum analyzer with Peak detector.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.3.3 TEST SETUP LAYOUT



3.3.4 TEST DEVIATION

No deviation

3.3.5 TEST RESULTS

Please refer to the APPENDIX C.

3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT

3.4.1 LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.


3.4.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.2.


1. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
3. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
4. ERP can be calculated form EIRP by subtracting the gain of dipole, $ERP = EIPR - 2.15\text{dBi}.$
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.4.3 TEST SETUP LAYOUT

Below 30MHz



30MHz to 1000MHz





3.4.4 TEST DEVIATION

No deviation

3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the APPENDIX D.

3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the APPENDIX E.

3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the APPENDIX F.

3.5 BAND EDGE MEASUREMENT

3.5.1 LIMIT


A Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.

1. All measurements were done at low and high operational frequency range.
2. Record the max trace plot into the test report.

3.5.3 TEST SETUP LAYOUT



3.5.4 TEST DEVIATION

No deviation

3.5.5 TEST RESULTS

Please refer to the APPENDIX G.

3.6 PEAK TO AVERAGE RATIO MEASUREMENT

3.6.1 LIMIT


In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.6.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 5.7.

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.6.3 TEST SETUP LAYOUT



3.6.4 TEST DEVIATION

No deviation

3.6.5 TEST RESULTS

Please refer to the APPENDIX H.

3.7 FREQUENCY STABILITY MEASUREMENT

3.7.1 LIMIT


± 1.5 ppm is for base and fixed station. ± 2.5 ppm is for mobile station.

3.7.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 9.

1. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
2. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
3. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
4. The frequency error was recorded frequency error from the communication simulator.

3.7.3 TEST SETUP LAYOUT



3.7.4 TEST DEVIATION

No deviation

3.7.5 TEST RESULTS

Please refer to the APPENDIX I.

4. LIST OF MEASUREMENT EQUIPMENTS

Radiated Spurious Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3231	Apr. 14, 2022
2	Amplifier	Agilent	8449B	3008A02334	Feb. 27, 2022
3	HighPass Filter	Wairwright Instruments Gmbh	WHK 1.5/15G-10ST	11	Feb. 27, 2022
4	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 1710/1785-1690/1805-60/ 12SS	38	Feb. 27, 2022
5	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 824/849-810/863-60/9SS	7	Feb. 27, 2022
6	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 880/915-860/935-60/9SS	14	Feb. 27, 2022
7	Band Reject Filter	Wairwright Instruments Gmbh	WRCG 1850/1910-1830/1930-60/ 10SS	17	Feb. 27, 2022
8	HighPass Filter	Wairwright Instruments Gmbh	WHK3.1/18G-10SS	24	Feb. 27, 2022
9	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
10	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Feb. 28, 2022
11	Receiver	Agilent	N9038A	MY52130039	Mar. 19, 2022
12	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
13	High pass filter	KANGMAIWEI	ZHPF-M3-12.75G-3869	B2015073763	Feb. 07, 2022
14	High pass filter	KANGMAIWEI	ZHPF-M1000-4000-1	B2015073762	Feb. 07, 2022
15	High pass filter	KANGMAIWEI	ZHPF-M6-186-1727	B2015073764	Feb. 07, 2022
16	Cable	emci	LMR-400(30MHz-1GHz) (8m+5m)	N/A	May 20, 2022
17	Cable	mitron	B10-01-01-12M	18072744	Oct. 16, 2021
18	Controller	ETS-Lindgren	2090	N/A	N/A
19	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
20	Loop Antenna	EM	EM-6876-1	230	Oct. 16, 2021
21	Double Ridged Guide Antenna	ETS	3115	75846	Mar. 17, 2022
22	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 30, 2022

Conducted Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
2	EXA Spectrum Analyzer	Agilent	N9010A	MY50520044	Feb. 28, 2022
3	POWER SPLITTER	Mini-Circuits	ZFRSC-123-S+	331000910-1	Feb. 27, 2022
4	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
2*	Multi-output DC Power Supply	GW Instek	GPC-3030DN	EK880675	Jul. 25, 2023
3	POWER SPLITTER	Mini-Circuits	ZFRSC-123-S+	331000910-1	Feb. 27, 2022
4	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
5	Const Temp,& Humidity Chamber	Bell	BTH-50C	20170306001	Feb. 27, 2022

Remark: "N/A" denotes no model name, serial no. or calibration specified.



"*" calibration period of equipment list is three year.



Except * item, all calibration period of equipment list is one year.



4. EUT TEST PHOTO

Radiated Emissions Test Photos

9 kHz to 30 MHz



Radiated Emissions Test Photos**30 MHz to 1 GHz**

Radiated Emissions Test Photos**Above 1 GHz**

APPENDIX A - OUTPUT POWER

Output Power (dBm):

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20407CH	20525CH	20643CH
				824.7MHz	836.5MHz	848.3MHz
5 / 1.4M	QPSK	1	0	22.06	22.02	22.07
		1	2	22.19	22.14	22.18
		1	5	22.08	22.03	22.07
		3	0	22.10	22.12	22.07
		3	1	22.15	22.17	22.12
		3	2	22.10	22.14	22.11
	16QAM	6	0	21.16	21.19	21.19
		1	0	21.04	21.19	21.34
		1	2	21.13	21.34	21.44
		1	5	21.08	21.17	21.36
		3	0	21.19	21.15	21.22
		3	1	21.24	21.19	21.26
		3	2	21.21	21.12	21.23
		6	0	20.27	20.28	20.07

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20415CH	20525CH	20635CH
				825.5MHz	836.5MHz	847.5MHz
5 / 3M	QPSK	1	0	22.05	22.13	22.08
		1	7	22.28	22.31	22.16
		1	14	22.16	22.18	22.06
		8	0	21.18	21.14	21.15
		8	4	21.20	21.19	21.19
		8	7	21.17	21.13	21.12
		15	0	21.14	21.13	21.11
	16QAM	1	0	21.00	21.46	21.05
		1	7	21.18	21.66	21.18
		1	14	21.00	21.52	21.04
		8	0	20.25	20.20	20.12
		8	4	20.26	20.27	20.20
		8	7	20.25	20.19	20.12
		15	0	20.13	20.16	20.04

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20425CH	20525CH	20625CH
				826.5MHz	836.5MHz	846.5MHz
5 / 5M	QPSK	1	0	22.08	22.05	22.02
		1	13	22.25	22.18	22.15
		1	24	22.14	22.07	22.06
		12	0	21.08	21.13	21.14
		12	6	21.19	21.20	21.17
		12	11	21.17	21.17	21.14
		25	0	21.12	21.16	21.10
	16QAM	1	0	21.17	21.51	21.08
		1	13	21.29	21.68	21.16
		1	24	21.21	21.52	21.11
		12	0	20.11	20.23	20.12
		12	6	20.23	20.28	20.15
		12	11	20.22	20.28	20.11
		25	0	20.13	20.18	20.00

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20450CH	20525CH	20600CH
				829.0MHz	836.5MHz	844.0MHz
5 / 10M	QPSK	1	0	22.08	22.18	22.07
		1	25	22.29	22.30	22.21
		1	49	22.09	22.14	22.07
		25	0	21.15	21.22	21.14
		25	13	21.15	21.17	21.10
		25	25	21.15	21.21	21.05
		50	0	21.12	21.21	21.08
	16QAM	1	0	20.98	21.50	21.95
		1	25	21.15	21.62	22.01
		1	49	21.04	21.45	21.65
		25	0	20.14	20.24	20.65
		25	13	20.14	20.19	20.62
		25	25	20.14	20.24	20.54
		50	0	20.11	20.21	20.48

ERP (dBm):

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20407CH	20525CH	20643CH
				824.7MHz	836.5MHz	848.3MHz
5 / 1.4M	QPSK	1	0	18.62	18.58	18.63
		1	2	18.75	18.70	18.74
		1	5	18.64	18.59	18.63
		3	0	18.66	18.68	18.63
		3	1	18.71	18.73	18.68
		3	2	18.66	18.70	18.67
		6	0	17.72	17.75	17.75
	16QAM	1	0	17.60	17.75	17.90
		1	2	17.69	17.90	18.00
		1	5	17.64	17.73	17.92
		3	0	17.75	17.71	17.78
		3	1	17.80	17.75	17.82
		3	2	17.77	17.68	17.79
		6	0	16.83	16.84	16.63

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20415CH	20525CH	20635CH
				825.5MHz	836.5MHz	847.5MHz
5 / 3M	QPSK	1	0	18.61	18.69	18.64
		1	7	18.84	18.87	18.72
		1	14	18.72	18.74	18.62
		8	0	17.74	17.70	17.71
		8	4	17.76	17.75	17.75
		8	7	17.73	17.69	17.68
		15	0	17.70	17.69	17.67
	16QAM	1	0	17.56	18.02	17.61
		1	7	17.74	18.22	17.74
		1	14	17.56	18.08	17.60
		8	0	16.81	16.76	16.68
		8	4	16.82	16.83	16.76
		8	7	16.81	16.75	16.68
		15	0	16.69	16.72	16.60

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20425CH	20525CH	20625CH
				826.5MHz	836.5MHz	846.5MHz
5 / 5M	QPSK	1	0	18.64	18.61	18.58
		1	13	18.81	18.74	18.71
		1	24	18.70	18.63	18.62
		12	0	17.64	17.69	17.70
		12	6	17.75	17.76	17.73
		12	11	17.73	17.73	17.70
		25	0	17.68	17.72	17.66
	16QAM	1	0	17.73	18.07	17.64
		1	13	17.85	18.24	17.72
		1	24	17.77	18.08	17.67
		12	0	16.67	16.79	16.68
		12	6	16.79	16.84	16.71
		12	11	16.78	16.84	16.67
		25	0	16.69	16.74	16.56


LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20450CH	20525CH	20600CH
				829.0MHz	836.5MHz	844.0MHz
5 / 10M	QPSK	1	0	18.64	18.74	18.63
		1	25	18.85	18.86	18.77
		1	49	18.65	18.70	18.63
		25	0	17.71	17.78	17.70
		25	13	17.71	17.73	17.66
		25	25	17.71	17.77	17.61
		50	0	17.68	17.77	17.64
	16QAM	1	0	17.54	18.06	18.51
		1	25	17.71	18.18	18.57
		1	49	17.60	18.01	18.21
		25	0	16.70	16.80	17.21
		25	13	16.70	16.75	17.18
		25	25	16.70	16.80	17.10
		50	0	16.67	16.77	17.04

APPENDIX B - OCCUPIED BANDWIDTH


LTE Band 5_1.4M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20407	824.7	1.0999	20407	824.7	1.303
20525	836.5	1.0840	20525	836.5	1.270
20643	848.3	1.0905	20643	848.3	1.322
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20407	824.7	1.0878	20407	824.7	1.285
20525	836.5	1.0913	20525	836.5	1.286
20643	848.3	1.0944	20643	848.3	1.305

Spectrum Plot

QPSK-20407




QPSK-20525



QPSK-20643




16QAM-20407



16QAM-20525




16QAM-20643




LTE Band 5_3M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20415	825.5	2.6888	20415	825.5	2.972
20525	836.5	2.6883	20525	836.5	2.919
20635	847.5	2.6920	20635	847.5	2.929
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20415	825.5	2.6860	20415	825.5	2.908
20525	836.5	2.6845	20525	836.5	2.912
20635	847.5	2.6841	20635	847.5	2.900

Spectrum Plot


QPSK-20415




QPSK-20525




QPSK-20635




16QAM-20415



16QAM-20525




16QAM-20635




LTE Band 5_5M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20425	826.5	4.5078	20425	826.5	4.918
20525	836.5	4.4923	20525	836.5	4.878
20625	846.5	4.5019	20625	846.5	4.919
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20425	826.5	4.4919	20425	826.5	4.905
20525	836.5	4.4890	20525	836.5	4.918
20625	846.5	4.4938	20625	846.5	4.856

Spectrum Plot


QPSK-20425




QPSK-20525




QPSK-20625



16QAM-20425



16QAM-20525




16QAM-20625




LTE Band 5_10M					
QPSK					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20450	829.0	8.9756	20450	829.0	9.807
20525	836.5	8.9920	20525	836.5	11.40
20600	844.0	8.9718	20600	844.0	9.726
16QAM					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20450	829.0	8.9856	20450	829.0	9.779
20525	836.5	8.9749	20525	836.5	9.733
20600	844.0	8.9612	20600	844.0	9.731

Spectrum Plot


QPSK-20450




QPSK-20525




QPSK-20600




16QAM-20450



16QAM-20525







16QAM-20600






APPENDIX C - CONDUCTED SPURIOUS EMISSIONS

LTE Band 5_1.4M Spectrum Plot

Channel	Frequency(MHz)	Channel	Frequency(MHz)
20525	836.5	20525	836.5
 Date: 23.SEP.2021 05:29:05		 Date: 23.SEP.2021 05:28:40	
Channel	Frequency(MHz)	-	-
20525	836.5	-	-
 Date: 23.SEP.2021 05:26:46		-	



LTE Band 5_10M Spectrum Plot

Channel	Frequency(MHz)	Channel	Frequency(MHz)
20525	836.5	20525	836.5
 Date: 23.SEP.2021 05:29:56		 Date: 23.SEP.2021 05:27:55	
Channel	Frequency(MHz)	-	-
20525	836.5	-	-
 Date: 23.SEP.2021 05:27:07			

APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)

Test Mode	TX Mode
-----------	---------

Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0180	45.71	15.04	60.75	122.50	-61.75	AVG		
2		0.0545	27.95	13.72	41.67	112.88	-71.21	AVG		
3		0.1356	25.46	13.78	39.24	104.96	-65.72	AVG		

Test Mode	TX Mode
-----------	---------


Ant 0°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.3852	37.67	13.64	51.31	95.89	-44.58	AVG		
2	*	2.1440	34.59	12.20	46.79	69.54	-22.75	QP		
3		3.1900	30.24	11.97	42.21	69.54	-27.33	QP		

Test Mode	TX Mode
-----------	---------


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	0.0181	46.32	15.01	61.33	122.45	-61.12	AVG		
2		0.0360	32.76	14.04	46.80	116.48	-69.68	AVG		
3		0.1363	24.85	13.77	38.62	104.92	-66.30	AVG		

Test Mode	TX Mode
-----------	---------

Ant 90°




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.3914	35.68	13.64	49.32	95.75	-46.43	AVG		
2		2.4218	27.51	12.13	39.64	69.54	-29.90	QP		
3	*	3.3281	29.84	11.98	41.82	69.54	-27.72	QP		

APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)


Test Mode	LTE Band 5_TX CH20525_1.4M
-----------	----------------------------

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		46.490	-48.14	-13.97	-62.11	-13.00	-49.11	peak	
2		133.305	-41.00	-12.69	-53.69	-13.00	-40.69	peak	
3	*	183.260	-34.14	-13.22	-47.36	-13.00	-34.36	peak	
4		280.260	-58.41	-12.14	-70.55	-13.00	-57.55	peak	
5		519.850	-53.18	-7.08	-60.26	-13.00	-47.26	peak	
6		759.925	-58.45	-3.07	-61.52	-13.00	-48.52	peak	


Test Mode LTE Band 5_TX CH20525_1.4M



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		95.475	-38.66	-15.24	-53.90	-13.00	-40.90	peak	
2		133.790	-32.42	-12.67	-45.09	-13.00	-32.09	peak	
3	*	178.895	-32.37	-12.71	-45.08	-13.00	-32.08	peak	
4		263.770	-49.40	-12.38	-61.78	-13.00	-48.78	peak	
5		369.015	-51.82	-9.75	-61.57	-13.00	-48.57	peak	
6		839.950	-55.11	-1.90	-57.01	-13.00	-44.01	peak	

Test Mode LTE Band 5_TX CH20525_5M


Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBm	dB	dBm	dBm	dB		
1		46.490	-49.38	-13.97	-63.35	-13.00	-50.35	peak	
2		135.730	-40.32	-12.63	-52.95	-13.00	-39.95	peak	
3	*	182.775	-34.18	-13.16	-47.34	-13.00	-34.34	peak	
4		519.850	-53.92	-7.08	-61.00	-13.00	-48.00	peak	
5		720.155	-57.72	-3.43	-61.15	-13.00	-48.15	peak	
6		880.205	-58.71	-1.39	-60.10	-13.00	-47.10	peak	

Test Mode LTE Band 5_TX CH20525_5M


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		95.960	-38.95	-15.20	-54.15	-13.00	-41.15	peak	
2		152.220	-33.72	-11.67	-45.39	-13.00	-32.39	peak	
3	*	178.895	-32.65	-12.71	-45.36	-13.00	-32.36	peak	
4		251.645	-49.39	-13.13	-62.52	-13.00	-49.52	peak	
5		369.015	-52.15	-9.75	-61.90	-13.00	-48.90	peak	
6		839.950	-56.51	-1.90	-58.41	-13.00	-45.41	peak	

Test Mode LTE Band 5_TX CH20525_10M


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		46.005	-47.92	-13.97	-61.89	-13.00	-48.89	peak	
2		94.990	-40.70	-15.27	-55.97	-13.00	-42.97	peak	
3		136.700	-40.35	-12.62	-52.97	-13.00	-39.97	peak	
4	*	178.895	-35.01	-12.71	-47.72	-13.00	-34.72	peak	
5		519.850	-53.92	-7.08	-61.00	-13.00	-48.00	peak	
6		839.950	-58.95	-1.90	-60.85	-13.00	-47.85	peak	

Test Mode	LTE Band 5_TX CH20525_10M
-----------	---------------------------

Horizontal




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		95.475	-38.67	-15.24	-53.91	-13.00	-40.91	peak	
2		135.245	-32.97	-12.65	-45.62	-13.00	-32.62	peak	
3	*	151.250	-32.96	-11.80	-44.76	-13.00	-31.76	peak	
4		182.290	-32.82	-13.09	-45.91	-13.00	-32.91	peak	
5		279.775	-50.29	-12.17	-62.46	-13.00	-49.46	peak	
6		800.180	-56.96	-2.53	-59.49	-13.00	-46.49	peak	

APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)

Test Mode	LTE Band 5_TX CH20525_1.4M
-----------	----------------------------


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		1650.250	-47.06	-4.95	-52.01	-13.00	-39.01	peak	
2	*	4136.500	-53.83	3.17	-50.66	-13.00	-37.66	peak	

Test Mode	LTE Band 5_TX CH20525_1.4M
-----------	----------------------------


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1675.750	-39.19	-4.76	-43.95	-13.00	-30.95	peak	
2		3346.000	-55.69	1.12	-54.57	-13.00	-41.57	peak	

Test Mode LTE Band 5_TX CH20525_5M


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1675.750	-41.42	-4.76	-46.18	-13.00	-33.18	peak	
2		4174.750	-51.06	3.22	-47.84	-13.00	-34.84	peak	

Test Mode	LTE Band 5_TX CH20525_5M
-----------	--------------------------


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1675.750	-39.35	-4.76	-44.11	-13.00	-31.11	peak	
2		3346.000	-49.26	1.12	-48.14	-13.00	-35.14	peak	

Test Mode LTE Band 5_TX CH20525_10M


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1675.750	-40.14	-4.76	-44.90	-13.00	-31.90	peak	
2		3346.000	-54.51	1.12	-53.39	-13.00	-40.39	peak	
3		4174.750	-50.12	3.22	-46.90	-13.00	-33.90	peak	
4		4952.500	-52.29	5.88	-46.41	-13.00	-33.41	peak	
5		5857.750	-55.50	6.88	-48.62	-13.00	-35.62	peak	

Test Mode LTE Band 5_TX CH20525_10M

Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1675.750	-38.62	-4.76	-43.38	-13.00	-30.38	peak	
2		3346.000	-52.39	1.12	-51.27	-13.00	-38.27	peak	
3		4174.750	-55.24	3.22	-52.02	-13.00	-39.02	peak	

APPENDIX G - BAND EDGE

LTE Band 5_1.4M Spectrum Plot

1RB#0



1RB#5

Channel

20407

Channel

20643





6RB#0

Channel

20407

Channel

20643



LTE Band 5_3M Spectrum Plot

1RB#0



1RB#14

Channel

20415

Channel

20635




15RB#0

Channel

20415

Channel

20635



LTE Band 5_5M Spectrum Plot

1RB#0



1RB#24

Channel

20425

Channel

20625




25RB#0

Channel

20425

Channel

20625



LTE Band 5_10M Spectrum Plot

1RB#0



1RB#49

Channel

20450

Channel

20600




50RB#0

Channel

20450

Channel

20600




APPENDIX H - PEAK TO AVERAGE RATIO


LTE Band 5_1.4M				
QPSK				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20407	824.7	4.19	13	Pass
20525	836.5	4.80	13	Pass
20643	848.3	2.99	13	Pass
16QAM				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20407	824.7	5.04	13	Pass
20525	836.5	5.44	13	Pass
20643	848.3	4.03	13	Pass

LTE Band 5_1.4M Spectrum Plot


QPSK-20407




QPSK-20525




QPSK-20643




16QAM-20407



16QAM-20525




16QAM-20643




LTE Band 5_3M				
QPSK				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20415	825.5	4.08	13	Pass
20525	836.5	4.58	13	Pass
20635	847.5	3.16	13	Pass
16QAM				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20415	825.5	4.99	13	Pass
20525	836.5	5.44	13	Pass
20635	847.5	4.05	13	Pass

LTE Band 5_3M Spectrum Plot

QPSK-20415




QPSK-20525




QPSK-20635




16QAM-20415



16QAM-20525




16QAM-20635




LTE Band 5_5M				
QPSK				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20425	826.5	4.08	13	Pass
20525	836.5	4.44	13	Pass
20625	846.5	3.86	13	Pass
16QAM				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20425	826.5	4.96	13	Pass
20525	836.5	5.37	13	Pass
20625	846.5	4.69	13	Pass

LTE Band 5_5M Spectrum Plot


QPSK-20425




QPSK-20525




QPSK-20625




16QAM-20425



16QAM-20525




16QAM-20625




LTE Band 5_10M				
QPSK				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20450	829.0	3.99	13	Pass
20525	836.5	4.16	13	Pass
20600	844.0	4.80	13	Pass
16QAM				
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	Max. Limit (dB)	Result
20450	829.0	4.96	13	Pass
20525	836.5	5.03	13	Pass
20600	844.0	5.72	13	Pass

LTE Band 5_10M Spectrum Plot


QPSK-20450




QPSK-20525




QPSK-20600




16QAM-20450



16QAM-20525



16QAM-20600



APPENDIX I - FREQUENCY STABILITY

Test Mode	LTE Band 5_CH20525_1.4M
-----------	-------------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	-8.08	-0.009659295	± 2.5
-20	-3.51	-0.004196055	
-10	8.34	0.009970114	
0	2.97	0.003550508	
10	6.83	0.008164973	
20	-3.11	-0.003717872	
30	-5.27	-0.00630006	
40	-3.99	-0.004769874	
50	-3.39	-0.0040526	
Max. Deviation (ppm)	8.34	0.009970114	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
13.2	-1.33	-0.001589958	± 2.5
12	6.43	0.00768679	
10.8	-7.19	-0.008595338	
Max. Deviation (ppm)	-7.19	-0.008595338	

Test Mode	LTE Band 5_CH20525_3M
-----------	-----------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	-6.64	-0.007937836	± 2.5
-20	-1.05	-0.00125523	
-10	-6.76	-0.008081291	
0	-8.21	-0.009814704	
10	-1.82	-0.002175732	
20	-6.10	-0.007292289	
30	6.55	0.007830245	
40	3.16	0.003777645	
50	3.86	0.004614465	
Max. Deviation (ppm)	-8.21	-0.009814704	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
13.2	6.19	0.00739988	± 2.5
12	-7.60	-0.009085475	
10.8	2.13	0.002546324	
Max. Deviation (ppm)	-7.6	-0.009085475	

Test Mode	LTE Band 5_CH20525_5M
-----------	-----------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	-3.72	-0.004447101	± 2.5
-20	8.91	0.010651524	
-10	8.63	0.010316796	
0	3.81	0.004554692	
10	-8.10	-0.009683204	
20	-1.26	-0.001506276	
30	-6.19	-0.00739988	
40	4.29	0.005128512	
50	-2.32	-0.002773461	
Max. Deviation (ppm)	8.91	0.010651524	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
13.2	7.63	0.009121339	± 2.5
12	-7.53	-0.009001793	
10.8	-2.63	-0.003144053	
Max. Deviation (ppm)	7.63	0.009121339	

Test Mode	LTE Band 5_CH20525_10M
-----------	------------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-30	8.54	0.010209205	±2.5
-20	4.98	0.005953377	
-10	3.83	0.004578601	
0	7.78	0.009300658	
10	-7.61	-0.00909743	
20	-6.71	-0.008021518	
30	-3.80	-0.004542738	
40	8.61	0.010292887	
50	3.64	0.004351464	
Max. Deviation (ppm)	8.61	0.010292887	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
13.2	4.87	0.005821877	±2.5
12	4.54	0.005427376	
10.8	-6.71	-0.008021518	
Max. Deviation (ppm)	-6.71	-0.008021518	

End of Test Report