

RF Exposure Evaluation

FCC ID:2A250-K22

1. Client Information

Applicant	:	Deen Smart LLC
Address	:	8350 NW 52nd Terrace Suite 301, Miami, FL, 33166 USA
Manufacturer	:	KK Smart Technology Co., Ltd
Address	:	No. 201, Guanyu Industrial Factory, Shenzhen Da Industrial Zone, No. 51 Cuijing Road, Xiuxin Community, Kengzi Street, Pingshan District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Multifunctional Visual Pore Cleaner Device
HVIN/Models No.	:	K22
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels
	RF Output Power:	802.11b: 8.105dbm (Max) 802.11g: 8.487dbm (Max) 802.11n(HT20): 8.339dbm (Max)
	Antenna Gain:	0.5dBi PCB Antenna
	Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n: up to 150Mbps
Power Supply	:	Input: DC 5V
Software Version	:	V1.6
Hardware Version	:	V1.1
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.		

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$ ≤ 3.0 for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $\sqrt{f_{\text{GHz}}}$ $\leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
2.4G WIFI 802.11 b						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	6.978	7±1	8.0	6.310	1.960	3.0
2.437	8.105	8±1	9.0	7.943	2.480	3.0
2.462	5.691	6±1	7.0	5.012	1.573	3.0
2.4G WIFI 802.11g						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	8.487	8±1	9.0	7.943	2.467	3.0
2.437	8.148	8±1	9.0	7.943	2.480	3.0
2.462	8.214	8±1	9.0	7.943	2.493	3.0
2.4G WIFI 802.11n(HT20)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.412	8.339	8±1	9.0	7.943	2.467	3.0
2.437	8.079	8±1	9.0	7.943	2.480	3.0
2.462	8.081	8±1	9.0	7.943	2.493	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----