



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250600055003

Rev.: 01

Page: 1 of 94

TEST REPORT

Application No.: SUCR2506000550WM
Applicant: COOSEA GROUP (HK) COMPANY LIMITED
Address of Applicant: UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL
Manufacturer: COOSEA GROUP (HK) COMPANY LIMITED
Address of Manufacturer: UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL
EUT Description: Smart Phone
Model No.: MC8B654B
FCC ID: 2A28USL005
Standards: FCC 47 CFR Part 2, Subpart J
FCC 47 CFR Part 15, Subpart C
Date of Receipt: 2025/06/16
Date of Test: 2025/06/17 to 2025/06/28
Date of Issue: 2025/07/04

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Wireless Laboratory

South of No. 6 Plant, No. 1, RunSheng Road, Suzhou Industrial Park,
Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

t (86-512) 6229 2980
www.sgsgroup.com.cn



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 2 of 94

Version

Revision Record			
Version	Description	Date	Remark
01	Original	July 4, 2025	/

Authorized for issue by:				
Tested By				
		Nature Shen / Project Manager		
Approved By				
		Cloud Peng/Technical Manager		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 3 of 94

Contents

Version	2
1 Test Summary	4
2 General Information	5
2.1 Details of Client	5
2.2 Test Location	5
2.3 Test Facility	5
2.4 General Description of EUT	6
2.5 Test Environment	8
2.6 Description of Support Units	8
3 Equipment List	9
4 Measurement Uncertainty (95% confidence levels, k=2)	12
5 Test results and Measurement Data	13
5.1 Antenna Requirement	13
5.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence 14	
5.3 AC Power Line Conducted Emissions	16
5.4 Conducted Output Power	20
5.5 20dB Emission Bandwidth & 99% Occupied Bandwidth	21
5.6 Carrier Frequencies Separation	22
5.7 Hopping Channel Number	23
5.8 Dwell Time	24
5.9 Band-edge for RF Conducted Emissions	25
5.10 Spurious RF Conducted Emissions	26
5.11 Radiated Spurious Emissions	27
5.12 Restricted bands around fundamental frequency	30
6 Photographs - Setup Photos	32
7 Appendix	33



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 4 of 94

1 Test Summary

Test Item	FCC Rule No.	Test Method	Test Result	Result
Antenna Requirement	15.203/15.247(b)	--	Clause 5.1	PASS
AC Power Line Conducted Emission	15.207	ANSI C63.10 (2013) Section 6.2	Clause 5.3	PASS
Conducted Peak Output Power	15.247 (b)(1)	ANSI C63.10 (2013) Section 7.8.5	Clause 5.4	PASS
20dB Emission Bandwidth & 99% Occupied Bandwidth	15.247 (a)(1)	ANSI C63.10 (2013) Section 6.9.2/6.9.3	Clause 5.5	For Report Purpose
Carrier Frequencies Separation	15.247 (a)(1)	ANSI C63.10 (2013) Section 7.8.2	Clause 5.6	PASS
Hopping Channel Number	15.247 (a)(1)	ANSI C63.10 (2013) Section 7.8.3	Clause 5.7	PASS
Dwell Time	15.247 (a)(1)	ANSI C63.10 (2013) Section 7.8.4	Clause 5.8	PASS
Band-edge for RF Conducted Emissions	15.247(d)	ANSI C63.10 (2013) Section 7.8.6	Clause 5.9	PASS
RF Conducted Spurious Emissions	15.247(d)	ANSI C63.10 (2013) Section 7.8.8	Clause 5.10	PASS
Radiated Spurious emissions	15.247(d); 15.205/15.209	ANSI C63.10 (2013) Section 6.4 / 6.5 / 6.6	Clause 5.11	PASS
Restricted bands around fundamental frequency (Radiated Emission)	15.247(d); 15.205/15.209	ANSI C63.10 (2013) Section 6.10.5	Clause 5.12	PASS



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 5 of 94

2 General Information

2.1 Details of Client

Applicant:	COOSEA GROUP (HK) COMPANY LIMITED
Address of Applicant:	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL
Manufacturer:	COOSEA GROUP (HK) COMPANY LIMITED
Address of Manufacturer:	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL

2.2 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	Tizzy Song, Ives Cheng

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 6 of 94

2.4 General Description of EUT

Hardware Version:	1.0
Software Version:	SL005TCV10002
IMEI:	354637280000903
Operation Frequency:	2400MHz~2483.5MHz $f_c = 2402 \text{ MHz} + N * 1 \text{ MHz}$, where: - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 0 to 78.
Bluetooth version:	Bluetooth V5.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Antenna Type:	☐ External, ☒ Integrated
Antenna Gain:	-1.26dBi (Ant2)
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.
RF Cable*:	1dB
Note: 1.Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 7 of 94

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel(CH0)	2402MHz
The Middle channel(CH39)	2441MHz
The Highest channel(CH78)	2480MHz



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 8 of 94

2.5 Test Environment

Environment Parameter	101 kPa Selected Values During Tests	
Relative Humidity	44-46 % RH Ambient	
Value	Temperature(℃)	Voltage(V)
NTNV	22~23	3.8
Remark: NV: Normal Voltage NT: Normal Temperature		

2.6 Description of Support Units

The EUT has been tested as an independent unit.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 9 of 94

3 Equipment List

RF Test Equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	Brilliant-emc	N/A	SUWI-04-08-01	11/9/2022	11/8/2025
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/13/2025	2/12/2026
Measurement Software	Tonscend	TST272 V2.0	SUWI-03-55-03	NCR	NCR
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	5/8/2025	5/7/2026
Temperature Chamber	ESPEC	SU-242	SUWI-01-13-01	5/9/2025	5/8/2026
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-05	1/21/2025	1/20/2026
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/19/2024	11/18/2025
Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/19/2024	11/18/2025
MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/15/2025	1/14/2026
Router	ASUS	GT-AXE11000(FCC ID MSQ-RTAXJF00)	SUWI-03-14-02	NCR	NCR
Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	3/27/2025	3/26/2026
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	11/19/2024	11/18/2025



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 10 of 94

9*6*6 Test Equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/13/2025	2/12/2026
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/20/2025	1/19/2026
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	11/21/2024	11/20/2025
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	VULB 9168	SUWI-01-11-04	8/22/2024	8/21/2026
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	VULB 9163	SUWI-01-11-01	5/7/2025	5/6/2027
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
Active Loop Antenna	SCHWRZBECK MESS- ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/15/2025	1/14/2026
Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/15/2025	1/14/2026
Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/20/2025	1/19/2026
Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	9/10/2024	9/9/2025
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	9/10/2024	9/9/2025
Measurement Software	Tonscend	JS32-RE V4.0.0.0	SUWI-02-09-04	NCR	NCR
Measurement Software	Tonscend	JS32-RSE 4.0.0.1	SUWI-02-09-06	NCR	NCR
Router	PLANET	FSD-803	SUWI-03-14-01	NCR	NCR
Open Switch and Control Unit	ROHDE&SCHWARZ	OSP220	SUWI-03-15-01	NCR	NCR
Multiplier Unit	ROHDE&SCHWARZ	TC-MX60	SUWI-03-16-01	NCR	NCR
Receive Unit	ROHDE&SCHWARZ	TC-RSE60	SUWI-03-16-02	NCR	NCR
Receive Unit	ROHDE&SCHWARZ	TC-RSE90	SUWI-03-16-03	NCR	NCR
Multiplier Unit	ROHDE&SCHWARZ	TC-MX90	SUWI-03-17-01	NCR	NCR
Receive Unit	ROHDE&SCHWARZ	TC-RSE140	SUWI-03-19-01	NCR	NCR
Multiplier Unit	ROHDE&SCHWARZ	TC-MX140	SUWI-03-19-02	NCR	NCR
Receive Unit	ROHDE&SCHWARZ	TC-RSE220	SUWI-03-19-04	NCR	NCR



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 11 of 94

Multiplier Unit	ROHDE&SCHWARZ	TC-MX220	SUWI-03-17-02	NCR	NCR
Receive Unit	ROHDE&SCHWARZ	TC-RSE325	SUWI-03-16-04	NCR	NCR
Multiplier Unit	ROHDE&SCHWARZ	TC-MX325	SUWI-03-17-03	NCR	NCR
Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	2/1/2024	1/31/2025
Measurement Software	ROHDE&SCHWARZ	ELEKTRA V4.20.1	SUWI-02-09-07	NCR	NCR
Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025

Conduction Test Equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	9/10/2024	9/9/2025
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-06	2/13/2025	2/12/2026
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-03	5/8/2025	5/7/2026
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-04	5/8/2025	5/7/2026
Measurement Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	NCR	NCR
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	9/10/2024	9/9/2025
Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025

Remark: NCR=No Calibration Requirement.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 12 of 94

4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	$\pm 0.54\text{dB}$
2	RF power density, conducted	$\pm 1.03\text{dB}$
3	Spurious emissions, conducted	$\pm 0.54\text{dB}$
4	Radio Frequency	1%
5	Duty Cycle	$\pm 0.37\%$
6	Occupied Bandwidth	1%
7	Conduction Emission	$\pm 2.90\text{dB}$ (150kHz to 30MHz)
8	Radiated Emission	$\pm 3.13\text{dB}$ (9k -30MHz)
		$\pm 4.88\text{dB}$ (30M -1GHz)
		$\pm 4.75\text{dB}$ (1GHz to 18GHz)
		$\pm 4.77\text{dB}$ (Above 18GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 13 of 94

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
The antenna is Integrated Antenna and no consideration of replacement. The best case gain of the antenna is -1.26dBi (Ant2). <i>Note:</i> <i>The antenna gain are derived from the gain information report provided by the manufacturer.</i> <i>Remark:</i> <i>As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.</i>	

5.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

5.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

5.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudo random sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.


> Number of shift register stages: 9

> Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

> Longest sequence of zeros: 8 (non-inverted signal)


Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 15 of 94

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the RF system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels. The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003

Rev.: 01

Page: 16 of 94

5.3 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Receiver Setup:	RBW = 9kHz, VBW = 30kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

Test Setup:	
Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel. Adapter + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation at the lowest channel is the worst case. Adapter + Transmitting mode Only the worst case is recorded in the report.
Instruments Used:	Refer to section 3 for details.
Test Results:	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003


Rev.: 01


Page: 18 of 94

Measurement Data


An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.







5.4 Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)&15.247 (b)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.5
Test Setup:	 * Test with power meter (Detector function: Peak
Test Instruments:	Refer to section 3 for details
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Limit:	0.125 watts
Test Results:	Pass
The detailed test data see: Appendix	


5.5 20dB Emission Bandwidth & 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 6.9.2 and 6.9.3
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Limit:	No restriction limits
Test Results:	For Report Purpose
The detailed test data see: Appendix	


5.6 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.2
Test Setup:	
Test Instruments:	Refer to section 3 for details
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Limit:	2/3 of the 20dB bandwidth Remark: the transmission power is less than 0.125W.
Test Results:	Pass
The detailed test data see: Appendix	


5.7 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.3
Test Setup:	
Instruments Used:	Refer to section 3 for details
Test Mode:	Hopping transmitting with all kind of modulation
Limit:	At least 15 channels
Test Results:	Pass
The detailed test data see: Appendix	


5.8 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.4
Test Setup:	
Instruments Used:	Refer to section 3 for details
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass
The detailed test data see: Appendix	

5.9 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 Section 7.8.6
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass
The detailed test data see: Appendix	

5.10 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 Section 7.8.8
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH5 of data type is the worst case of 8DPSK modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass
The detailed test data see: Appendix	

5.11 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 6.4 / 6.5 / 6.6				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Test Frequency:	9kHz ~ 25GHz				
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Distance from antenna to EUT is 1m for measurements >18GHz). - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Test the EUT in the lowest channel, the middle channel, the Highest channel. - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete. - The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported. - The disturbance above 18GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. - At a measurement distance of 1 meter the limit line was increased by $20 \cdot \text{LOG}(3/1) = 9.54 \text{ dB}$.
Test Configuration:	Measurements below 30MHz • RBW = 10 kHz • VBW = 30 kHz • Detector = Peak & Average & Quasi-peak • Trace mode = max hold Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 29 of 94

	• Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz Use duty cycle correction factor method per 15.35(c). Duty cycle = On time / 100 milliseconds On time = $N_1 \cdot L_1 + N_2 \cdot L_2 \dots + N_{N-1} \cdot L_{N-1} + N_N \cdot L_N$ Where N_1 is number of type 1 pulse, L_1 is length of type 1 pulses, etc. Average Value = Peak Value + $20 \cdot \log(\text{Duty cycle})$.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Adapter + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Adapter + Transmitting mode For below 1GHz part, through pre-scan all channels, but only the worst case is recorded in the report.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass
The detailed test data see: Appendix	

5.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 6.10.5		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.
-----------------	---



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 31 of 94

	h. Test the EUT in the lowest channel , the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. j. Repeat above procedures until all frequencies measured was complete.
Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW ≥ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz Use duty cycle correction factor method per 15.35(c). Duty cycle = On time / 100 milliseconds On time = $N_1 \cdot L_1 + N_2 \cdot L_2 \dots + N_{N-1} \cdot L_{N-1} + N_N \cdot L_N$ Where N_1 is number of type 1 pulse, L_1 is length of type 1 pulses, etc. Average Value = Peak Value + 20*log(Duty cycle).
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Adapter + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Adapter + Transmitting mode, Only the worst case is recorded in the report.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass
The detailed test data see: Appendix	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 32 of 94

6 Photographs - Setup Photos

Refer to Appendix A.2 BT&WLAN Setup Photos.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 33 of 94

7 Appendix

1. Bandwidth

1.1 Test Result

1.1.1 OBW

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	99% Occupied Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.766	/	Pass
		2441	DH5	1	0.763	/	Pass
		2480	DH5	1	0.765	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.151	/	Pass
		2441	2DH5	1	1.150	/	Pass
		2480	2DH5	1	1.153	/	Pass
8DPSK	SISO	2402	3DH5	1	1.158	/	Pass
		2441	3DH5	1	1.154	/	Pass
		2480	3DH5	1	1.159	/	Pass

1.1.2 20dB BW

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	20dB Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.805	/	Pass
		2441	DH5	1	0.804	/	Pass
		2480	DH5	1	0.805	/	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	1.276	/	Pass
		2441	2DH5	1	1.273	/	Pass
		2480	2DH5	1	1.274	/	Pass
8DPSK	SISO	2402	3DH5	1	1.273	/	Pass
		2441	3DH5	1	1.263	/	Pass
		2480	3DH5	1	1.265	/	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 34 of 94

1.2 Test Graph


1.2.1 OBW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 35 of 94







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 36 of 94

Pi/4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV




Pi/4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 37 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 38 of 94







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 39 of 94

1.2.2 20dB BW








SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 41 of 94







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 42 of 94

8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV




8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 43 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 44 of 94

2. Maximum Conducted Output Power

2.1 Test Result

2.1.1 Power

Mode	TX Type	Frequency (MHz)	Packet Type	Maximum Peak Conducted Output Power (dBm)		Verdict
				ANT1	Limit	
GFSK	SISO	2402	DH5	11.13	<=30	Pass
		2441	DH5	11.37	<=30	Pass
		2480	DH5	10.97	<=30	Pass
Pi/4DQPSK	SISO	2402	2DH5	10.40	<=20.97	Pass
		2441	2DH5	10.69	<=20.97	Pass
		2480	2DH5	10.35	<=20.97	Pass
8DPSK	SISO	2402	3DH5	10.68	<=20.97	Pass
		2441	3DH5	10.89	<=20.97	Pass
		2480	3DH5	10.43	<=20.97	Pass

Note1: Antenna Gain: Ant1: -1.26dBi;




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 45 of 94

2.2 Test Graph


2.2.1 Power





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 46 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 47 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 48 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 49 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 50 of 94

3. Carrier Frequency Separation

3.1 Test Result

3.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Packet Type	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Verdict
GFSK	SISO	HOPP	DH5	0.980	0.805	≥ 0.805	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	0.996	1.276	≥ 0.851	Pass
8DPSK	SISO	HOPP	3DH5	1.001	1.273	≥ 0.849	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 51 of 94

3.2 Test Graph


3.2.1 Ant1





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 52 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 53 of 94

4. Number of Hopping Frequencies

4.1 Test Result

4.1.1 HoppNum

Mode	TX Type	Frequency (MHz)	Packet Type	Num of Hopping Frequencies		Verdict
				ANT1	Limit	
GFSK	SISO	HOPP	DH5	79	>=15	Pass
Pi/4DQPSK	SISO	HOPP	2DH5	79	>=15	Pass
8DPSK	SISO	HOPP	3DH5	79	>=15	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 54 of 94

4.2 Test Graph


4.2.1 HoppNum





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 55 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 56 of 94

5. Time of Occupancy (Dwell Time)

5.1 Test Result

5.1.1 Ant1

Ant1									
Mode	TX Type	Frequency (MHz)	Packet Type	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	SISO	HOPP	DH1	0.390	31.600	320	124.800	<=400	Pass
			DH3	1.648	31.600	160	263.680	<=400	Pass
			DH5	2.894	31.600	103	298.082	<=400	Pass
Pi/4DQPSK	SISO	HOPP	2DH1	0.394	31.600	321	126.474	<=400	Pass
			2DH3	1.650	31.600	167	275.550	<=400	Pass
			2DH5	2.898	31.600	109	315.882	<=400	Pass
8DPSK	SISO	HOPP	3DH1	0.390	31.600	320	124.800	<=400	Pass
			3DH3	1.646	31.600	165	271.590	<=400	Pass
			3DH5	2.898	31.600	104	301.392	<=400	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 57 of 94

5.2 Test Graph


5.2.1 Ant1





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 58 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 59 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 60 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 61 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 62 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 63 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 64 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 65 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 66 of 94

6. Unwanted Emissions In Non-restricted Frequency Bands

6.1 Test Result

6.1.1 Ref

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)
GFSK	SISO	2402	DH5	1	10.57
		2441	DH5	1	10.83
		2480	DH5	1	10.42
Pi/4DQPSK	SISO	2402	2DH5	1	9.85
		2441	2DH5	1	10.33
		2480	2DH5	1	9.95
8DPSK	SISO	2402	3DH5	1	10.56
		2441	3DH5	1	10.53
		2480	3DH5	1	9.96

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.

6.1.2 CSE

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	10.83	-9.17	Pass
		2441	DH5	1	10.83	-9.17	Pass
		2480	DH5	1	10.83	-9.17	Pass
		HOPP	DH5	1	10.83	-9.17	Pass
					10.83	-9.17	Pass
Pi/4DQPSK	SISO	2402	2DH5	1	10.33	-9.67	Pass
		2441	2DH5	1	10.33	-9.67	Pass
		2480	2DH5	1	10.33	-9.67	Pass
		HOPP	2DH5	1	10.33	-9.67	Pass
					10.33	-9.67	Pass
8DPSK	SISO	2402	3DH5	1	10.56	-9.44	Pass
		2441	3DH5	1	10.56	-9.44	Pass
		2480	3DH5	1	10.56	-9.44	Pass
		HOPP	3DH5	1	10.56	-9.44	Pass
					10.56	-9.44	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2013, the channel contains the maximum PSD level was used to establish the reference level.




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 67 of 94

6.2 Test Graph


6.2.1 Ref





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 68 of 94







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 69 of 94

Pi/4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



Pi/4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 70 of 94

8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV




8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 71 of 94






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 72 of 94

6.2.2 CSE







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 73 of 94

GFSK_DH5_MCH_2441MHz_Ant1_NTNV




GFSK_DH5_HCH_2480MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 74 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 75 of 94







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 76 of 94

Pi/4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV




Pi/4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 77 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 78 of 94






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003


Rev.: 01

Page: 79 of 94

8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV




8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 80 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd


Report No.: SUCR250600055003
Rev.: 01
Page: 81 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 82 of 94





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01


Page: 83 of 94

Radiated Spurious Emissions

Radiated emission below 1GHz

Worst case Mode:

GFSK_Channel 78



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	49.1575	36.34	18.77	-34.18	20.93	40.00	19.07	199	19	Horizontal
2	52.31	34.96	18.34	-34.16	19.14	40.00	20.86	264	19	Horizontal
3	77.045	36.03	15.40	-33.95	17.48	40.00	22.52	185	146	Horizontal
4	139.3675	32.42	18.54	-33.59	17.36	43.50	26.14	231	113	Horizontal
5	174.7725	35.29	17.89	-33.37	19.81	43.50	23.69	187	294	Horizontal
6	203.3875	42.67	15.30	-33.17	24.80	43.50	18.70	191	98	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 84 of 94



Final Data List										
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.1825	45.82	18.10	-34.18	29.74	40.00	10.26	206	162	Vertical
2	41.3975	41.92	18.76	-34.18	26.50	40.00	13.50	199	108	Vertical
3	49.1575	51.88	18.77	-34.18	36.47	40.00	3.53	234	186	Vertical
4	75.59	45.94	15.32	-33.96	27.30	40.00	12.70	187	232	Vertical
5	144.46	35.51	18.55	-33.56	20.51	43.50	22.99	219	179	Vertical
6	197.81	40.52	15.28	-33.22	22.58	43.50	20.92	208	342	Vertical

Remark:


- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:
Value = Reading(dBμV) + AF(dB/m) + Factor(dB):
AF = Antenna Factor(dB/m)
Factor = Cable Factor(dB) - Preamplifier gain(dB)
Margin = Limit(dBμV/m) – Value(dBμV/m)
- 2) All channels have been tested, but only the worst case data displayed in this report.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 85 of 94

Transmitter emission Above 1GHz
GFSK_Channel 00




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4803.75	58.46	31.09	-45.54	44.01	74.00	29.99	Horizontal
2	7405.5	49.17	36.14	-43.40	41.91	74.00	32.09	Horizontal
3	10788	42.03	38.58	-38.52	42.09	74.00	31.91	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 86 of 94

GFSK_Channel 00



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4803.75	57.64	31.09	-45.54	43.19	74.00	30.81	Vertical
2	7869.75	48.44	36.92	-42.67	42.69	74.00	31.31	Vertical
3	11249.25	41.61	38.72	-37.40	42.93	74.00	31.07	Vertical




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 87 of 94

GFSK_Channel 39



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4882.5	57.52	31.21	-45.53	43.20	74.00	30.80	Horizontal
2	7420.5	48.97	36.18	-43.35	41.79	74.00	32.21	Horizontal
3	10277.25	43.56	38.53	-39.18	42.90	74.00	31.10	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 88 of 94

GFSK_Channel 39




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4881.75	55.20	31.21	-45.53	40.88	74.00	33.12	Vertical
2	6669.75	49.13	34.41	-43.97	39.56	74.00	34.44	Vertical
3	10678.5	41.89	38.57	-38.01	42.45	74.00	31.55	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 89 of 94

GFSK_Channel 78



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4959.75	55.34	31.34	-45.60	41.08	74.00	32.92	Horizontal
2	8010	47.75	37.09	-42.25	42.59	74.00	31.41	Horizontal
3	11979	41.68	39.09	-37.52	43.25	74.00	30.75	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 90 of 94

GFSK_Channel 78



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4959.75	53.05	31.34	-45.60	38.79	74.00	35.21	Vertical
2	7462.5	48.05	36.30	-43.24	41.10	74.00	32.90	Vertical
3	11993.25	41.97	39.10	-37.59	43.47	74.00	30.53	Vertical

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:

Level = Reading(dBμV) + AF(dB/m) + Factor(dB):

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier gain(dB)

Margin = Limit(dBμV/m) – Level(dBμV/m)


- 2) All channels have been tested, but only the worst case data displayed in this report.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 91 of 94

Restricted bands around fundamental frequency
GFSK_Channel 00



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2369.8	45.61	26.94	-23.57	48.98	74.00	25.02	Horizontal
2	2388	45.88	26.98	-23.57	49.28	74.00	24.72	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003

Rev.: 01

Page: 92 of 94

GFSK_Channel 00




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2369.41	45.92	26.94	-23.57	49.29	74.00	24.71	Vertical
2	2388.91	46.29	26.98	-23.57	49.70	74.00	24.30	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 93 of 94

GFSK_Channel 78




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.58	46.70	27.17	-23.54	50.32	74.00	23.68	Horizontal
2	2489.26	46.84	27.18	-23.54	50.48	74.00	23.52	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd

Report No.: SUCR250600055003
Rev.: 01
Page: 94 of 94

GFSK_Channel 78



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.8	46.61	27.17	-23.54	50.23	74.00	23.77	Vertical
2	2487.1	47.36	27.17	-23.54	50.99	74.00	23.01	Vertical

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:

Level = Reading(dBμV) + AF(dB/m) + Factor(dB):

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier gain(dB)

Margin = Limit(dBμV/m) – Level(dBμV/m)

---End of Report---