

EMC TEST REPORT

Applicant COOSEA GROUP (HK)

COMPANY LIMITED

FCC ID 2A28USL112


Product Smart Phone

Model SL112A; SL112C

Report No. R2212A1312-E1

Issue Date March 17, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2022)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.



Prepared by: Liu Wei



Approved by: Fan Guangchang

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL:+86-021-50791141/2/3

FAX:+86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment Under Test	5
2.1	Applicant and Manufacturer Information.....	5
2.2	General Information	5
2.3	Applied Standards	7
2.4	Test Mode.....	8
3	Test Case Results	9
3.1	Radiated Emission	9
3.2	Conducted Emission	14
4	Uncertainty Measurement	17
5	Main Test Instruments	18
	ANNEX A: The EUT Appearance.....	19
	ANNEX B: Test Setup Photos.....	20

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: January 28, 2023 ~ March 3, 2023			
Date of Sample Received: January 11, 2023			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA(Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Fan Guangchang

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: <http://www.ta-shanghai.com>

E-mail: fanguangchang@ta-shanghai.com

2 General Description of Equipment Under Test

2.1 Applicant and Manufacturer Information

Applicant	COOSEA GROUP (HK) COMPANY LIMITED
Applicant address	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL, HONG KONG, CHINA
Manufacturer	COOSEA GROUP (HK) COMPANY LIMITED
Manufacturer address	UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL, HONG KONG, CHINA

2.2 General Information

EUT Description			
Device Type	Portable Device		
Model	SL112A; SL112C		
IMEI	351384680003616		
HW Version	1.0		
SW Version	SL112A10010		
Power Rating	DC 3.85V		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	PIFA Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 14	788 ~ 798	758 ~ 768
	LTE Band 30	2305 ~ 2315	2350 ~ 2360
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5G(U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5G(U-NII-2A)	5250 ~ 5350	5250 ~ 5350

	Wi-Fi 5G(U-NII-2C)	5470 ~ 5725	5470 ~ 5725
	Wi-Fi 5G(U-NII-3)	5725 ~ 5850	5725 ~ 5850
	NFC	13.56	13.56
EUT Accessory			
Adapter	Manufacturer: ShenZhen BaiJunDa Electronic Co., Ltd Model:UT-592A-5200ZY		
Battery	Manufacturer: Huizhou Highpower Technology Co., Ltd Model:BL-A50CT		
USB Cable	Manufacturer: Shenzhen Yihuaxing Electronics Co.Ltd. Model:K342-002		
Auxiliary test equipment			
PC	PC Manufacturer: Microsoft Corporation Model: 1724 SN: 032324771953		
<p>Note:</p> <ol style="list-style-type: none"> 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. 2. The customer claims that SL112A and SL112C are only different in model, and the others are the same. This report only tests SL112A. 			

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B(2022)

ANSI C63.4-2014

2.4 Test Mode

Test Mode	
Mode 1	Adapter +USB cable+EUT+ Front camera On
Mode 2	Adapter +USB cable+EUT+ Rear camera On
Mode 3	Adapter + USB cable + EUT + 1KHz(Color bar)
Mode 4	Adapter +USB cable+EUT+ MUSIC PLAYING
Mode 5	USB Copy(EUT with PC) + USB cable
Mode 6	USB Copy(PC with EUT) + USB cable
Mode 7	USB Copy(SD with EUT) + USB cable
Mode 8	USB Copy(EUT with SD) + USB cable

During the test, mode 5 is selected as the worst condition for Radiated Emission, and mode 6 is selected as the worst condition for Conducted Emission. The test data of the worst-case condition was recorded in this report.

3 Test Case Results

3.1 Radiated Emission

Ambient Condition

Temperature	Relative humidity
15°C~35°C	30%~60%

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO



Above 1GHz:

(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC.

Test Setup**Below 1GHz****Above 1GHz**

Note: Area side:2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits**Class B**


Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. The Emissions in the frequency band 18GHz – 40GHz is more than 20dB below the limit are not reported.

The following graphs display the maximum values of horizontal and vertical by software. For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.

A symbol (dBV) in the test plot below means (dB μ V/m)


Mode 5

Radiated Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor(dB)
41.233333	17.73	40.00	22.27	100.0	V	18.0	19.8
57.958000	12.89	40.00	27.11	100.0	V	221.0	19.7
131.121667	18.95	43.50	24.55	100.0	V	66.0	15.2
184.629000	37.26	43.50	6.24	100.0	H	28.0	16.8
289.872333	31.81	46.00	14.19	100.0	H	49.0	20.2
383.985333	28.94	46.00	17.06	100.0	H	0.0	22.5

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)

2. Margin = Limit – Quasi-Peak



Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1446.250000	33.68	---	74.00	40.32	500.0	100.0	H	15.0	-15.9
1567.375000	---	22.89	54.00	31.11	500.0	100.0	V	143.0	-15.2
2521.500000	37.36	---	74.00	36.64	500.0	200.0	V	150.0	-10.5
2549.125000	---	25.63	54.00	28.37	500.0	200.0	V	304.0	-10.4
4185.375000	40.93	---	74.00	33.07	500.0	100.0	H	198.0	-4.5
4238.500000	---	29.53	54.00	24.47	500.0	100.0	V	27.0	-4.4
5583.625000	43.55	---	74.00	30.45	500.0	100.0	V	81.0	-1.2
5840.750000	---	31.96	54.00	22.04	500.0	100.0	H	301.0	-1.1
7562.000000	44.41	---	74.00	29.59	500.0	200.0	H	344.0	0.9
7593.875000	---	32.65	54.00	21.35	500.0	200.0	H	282.0	0.9
9676.375000	---	34.40	54.00	19.60	500.0	100.0	V	0.0	2.1
10596.500000	46.01	---	74.00	27.99	500.0	200.0	V	118.0	2.0

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Peak Margin = Limit -MAX Peak/ Average

3.2 Conducted Emission

Ambient Condition


Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

During the test, EUT is connected to a laptop via a USB cable in the case of Transfer Data mode. The EUT is used as the peripheral equipment of the PC.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.


Limits

Frequency (MHz)	Conducted Limits(dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 [*]	56 to 46 [*]
0.5 - 5	56	46
5 - 30	60	50

^{*}: Decreases with the logarithm of the frequency.

Test Results**Mode 6**

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.18	60.26	---	64.52	4.26	1000.0	9.000	L1	ON	21.0
0.19	---	44.61	54.11	9.50	1000.0	9.000	L1	ON	21.0
0.36	40.41	---	58.64	18.23	1000.0	9.000	L1	ON	20.8
0.72	---	23.88	46.00	22.12	1000.0	9.000	L1	ON	20.4
1.32	---	24.05	46.00	21.95	1000.0	9.000	L1	ON	19.7
2.12	34.08	---	56.00	21.92	1000.0	9.000	L1	ON	19.4
3.99	38.21	---	56.00	17.79	1000.0	9.000	L1	ON	19.2
5.00	---	30.31	46.00	15.69	1000.0	9.000	L1	ON	19.2
5.36	---	33.25	50.00	16.75	1000.0	9.000	L1	ON	19.2
5.44	41.70	---	60.00	18.30	1000.0	9.000	L1	ON	19.2
13.09	31.96	---	60.00	28.04	1000.0	9.000	L1	ON	19.4
13.20	---	25.34	50.00	24.66	1000.0	9.000	L1	ON	19.4

Remark:Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.18	59.85	---	64.52	4.67	1000.0	9.000	N	ON	21.0
0.19	---	44.21	54.11	9.90	1000.0	9.000	N	ON	21.0
0.37	39.74	---	58.59	18.85	1000.0	9.000	N	ON	20.9
0.66	---	25.76	46.00	20.24	1000.0	9.000	N	ON	20.5
1.32	---	25.68	46.00	20.32	1000.0	9.000	N	ON	19.8
2.09	33.22	---	56.00	22.78	1000.0	9.000	N	ON	19.4
5.00	---	31.48	46.00	14.52	1000.0	9.000	N	ON	19.2
5.00	41.41	---	56.00	14.59	1000.0	9.000	N	ON	19.2
5.19	42.03	---	60.00	17.97	1000.0	9.000	N	ON	19.2
5.30	---	34.13	50.00	15.87	1000.0	9.000	N	ON	19.2
12.54	30.50	---	60.00	29.50	1000.0	9.000	N	ON	19.4
15.71	---	26.31	50.00	23.69	1000.0	9.000	N	ON	19.6

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30MHz

4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Radiated Emission 18GHz – 26.5GHz	5.90 dB	1.96
Radiated Emission 26.5GHz – 40GHz	5.92 dB	1.96
Conducted Emission	2.57 dB	2

5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESR	102389	2022-05-25	2023-05-24
Signal Analyzer	R&S	FSV40	101186	2022-05-14	2023-05-13
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2020-05-05	2023-05-04
Horn Antenna	R&S	HF907	102723	2021-07-24	2024-07-23
Horn Antenna	ETS-Lindgren	3160-09	00102643	2021-10-10	2024-10-09
Horn Antenna	STEATITE	QSH-SL-26-40-K-15	16779	2023-01-17	2026-01-16
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2022-12-13	2024-12-09
EMI Test Receiver	R&S	ESR	101667	2022-05-25	2023-05-24
Software	R&S	EMC32	10.35.10	/	/

*****END OF REPORT*****

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B:Test Setup Photos

The Test Setup Photos are submitted separately.