



TEST REPORT



| | | | | |
|--|--|---|--|--|
| Report Number | 90534-21-72-21-PP021 | | | |
| Date of issue | Oct.09.2021 | | | |
| Tested by (+signature) | Duke |  | | |
| Approved by (+signature) | Jason |  | | |
| Testing Laboratory name | SLG-CPC Testlaboratory Co., Ltd. | | | |
| Address | No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117 | | | |
| Applicant's name | NANJING MIDAS TECHNOLOGY CO., LTD | | | |
| Address | Block A, Kechuang Building, Lishui District, Nanjing City, Jiangsu Province | | | |
| Manufacturer's name | NANJING MIDAS TECHNOLOGY CO., LTD | | | |
| Address | Block A, Kechuang Building, Lishui District, Nanjing City, Jiangsu Province | | | |
| Factory's name | NANJING MIDAS TECHNOLOGY CO., LTD | | | |
| Address | Block A, Kechuang Building, Lishui District, Nanjing City, Jiangsu Province | | | |
| Standard(s) | FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C | | | |
| Test item description | Midas-926 Gateway | | | |
| Trade Mark |  | | | |
| Model/Type reference | Midas-926.GB915 | | | |
| FCC ID | 2A293M926GB915 | | | |
| Date of receipt of test item | Sep.07.2021 | | | |
| Date (s) of performance of test: | Sep.08.2021 to Sep.30.2021 | | | |
| Summary of Test Results | Pass | | | |
| The Summary of Test Results based on a technical opinion belongs to the standard(s). | | | | |
| General disclaimer: This report shall not be reproduced except in full, without the written approval of SLG-CPC Testlaboratory Co., Ltd. The test results in the report only apply to the tested sample. | | | | |



Table of Contents

| | | |
|----------|--|-----------|
| 1 | EUT TECHNICAL DESCRIPTION | 3 |
| 2 | SUMMARY OF TEST RESULT | 4 |
| 3 | TEST METHODOLOGY | 5 |
| 3.1 | GENERAL DESCRIPTION OF APPLIED STANDARDS | 5 |
| 3.2 | MEASUREMENT EQUIPMENT USED | 5 |
| 3.3 | DESCRIPTION OF TEST MODES..... | 6 |
| 4 | FACILITIES AND ACCREDITATIONS | 7 |
| 4.1 | FACILITIES..... | 7 |
| 4.2 | LABORATORY ACCREDITATIONS AND LISTINGS..... | 7 |
| 5 | TEST SYSTEM UNCERTAINTY | 8 |
| 6 | SETUP OF EQUIPMENT UNDER TEST..... | 9 |
| 6.1 | RADIO FREQUENCY TEST SETUP 1 | 9 |
| 6.2 | RADIO FREQUENCY TEST SETUP 2 | 9 |
| 6.3 | CONDUCTED EMISSION TEST SETUP | 11 |
| 6.4 | BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM | 12 |
| 6.5 | SUPPORT EQUIPMENT | 12 |
| 7 | Frequency Hopping System Requirements | 13 |
| 7.1 | Standard Applicable | 13 |
| 7.2 | EUT Pseudorandom Frequency Hopping Sequence | 13 |
| 7.3 | Equal Hopping Frequency Use..... | 14 |
| 7.4 | Frequency Hopping System | 14 |
| 8 | TEST REQUIREMENTS | 15 |
| 8.1 | 20DB BANDWIDTH..... | 15 |
| 8.2 | CARRIER FREQUENCY SEPARATION..... | 18 |
| 8.3 | NUMBER OF HOPPING FREQUENCIES | 21 |
| 8.4 | AVERAGE TIME OF OCCUPANCY (DWELL TIME)..... | 23 |
| 8.5 | MAXIMUM PEAK CONDUCTED OUTPUT POWER | 26 |
| 8.6 | CONDUCTED SPURIOUS EMISSION | 29 |
| 8.7 | RADIATED SPURIOUS EMISSION | 34 |
| 8.8 | CONDUCTED EMISSION TEST | 39 |
| 8.9 | ANTENNA APPLICATION | 42 |



1 EUT TECHNICAL DESCRIPTION

| Characteristics | Description |
|--------------------------------------|---|
| Product | Midas-926 Gateway |
| Model Number | Midas-926.GB915 |
| Modulation: | Lora modulation for 915M |
| Operating Frequency Range(s): | 902.3-914.9MHz |
| Number of Channels: | 64 channels |
| Transmit Power Max: | 21.77 dBm |
| Antenna Type | External Antenna |
| Antenna Gain | 3 dBi |
| Power supply | <input checked="" type="checkbox"/> DC supply: DC 5V <input checked="" type="checkbox"/> Adapter supply: Model:AS2401A-0503000US IN PUT:100~240V 50/60Hz 0.8A MAX OUT PUT: 5V 3000mA |
| Temperature Range: | -20°C ~ +55°C |

Note: for more details, please refer to the User's manual of the EUT.



2 SUMMARY OF TEST RESULT

| FCC Part Clause | Test Parameter | Verdict | Remark |
|-----------------------------|--|---------|--------|
| 15.247(a)(1) | 20 dB Bandwidth | PASS | |
| 15.247(a)(1) | Carrier Frequency Separation | PASS | |
| 15.247(a)(1) | Number of Hopping Frequencies | PASS | |
| 15.247(a)(1) | Average Time of Occupancy (Dwell Time) | PASS | |
| 15.247(b)(1) | Maximum Peak Conducted Output Power | PASS | |
| 15.247(c) | Conducted Spurious Emissions | PASS | |
| 15.247(d) 15.209 | Radiated Spurious Emissions | PASS | |
| 15.207 | Conducted Emission | PASS | |
| 15.203 | Antenna Application | PASS | |
| 15.247 (a) (1)/g/h | Frequency Hopping System | PASS | |
| NOTE1: N/A (Not Applicable) | | | |

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2A293M926GB915 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.



3 TEST METHODOLOGY

3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 FCC KDB 558074 D01 15.247 Meas Guidance v05r02

3.2 MEASUREMENT EQUIPMENT USED

| Equipment | Model | Manufacturer | S/N | Cal. Due |
|-------------------------------------|-----------------|--------------|-------------------|------------|
| RF Connected Test | | | | |
| Vector Signal Generator | Rohde & Schwarz | SMBV100B(6G) | 101166 | 2022/07/30 |
| Analog Signal Generator | Rohde & Schwarz | SMB100A(40G) | 181333 | 2022/07/30 |
| Signal Analyzer | Rohde & Schwarz | FSV40 | 101527 | 2022/05/24 |
| Power Analyzer | Rohde & Schwarz | OSP-B157W8 | N/A | 2022/09/23 |
| Wideband Radio Communication Tester | R&S | CMW270 | 101985 | 2022/07/30 |
| Temperature&Humidity test chamber | ESPEC | VC 4018 | / | 2022/04/02 |
| Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | 166898 | 2022/09/07 |
| Radiated Emission Test | | | | |
| EMI Test Receiver | KEYSIGHT | N9010A | MY56070465 | 2021/12/23 |
| EMI Test Receiver | Rohde & Schwarz | FSV40 | 101511 | 2022/05/24 |
| Bilog Antenna | Schwarzbeck | VULB 9163 | 01335 | 2023/04/28 |
| Power Amplifier | EMEC | EM330 | 060676 | 2021/12/23 |
| Cable | Tuyue | F4309 | L-400-NmNm-120 00 | 2021/12/23 |
| Signal Analyzer | Rohde & Schwarz | FSV40 | 101511 | 2022/05/24 |
| Horn Antenna | Schwarzbeck | BBHA9170 | / | 2022/10/09 |
| Power Amplifier | Rohde & Schwarz | SCU-18F | 180118 | 2022/05/17 |
| Active Loop Antenna | ETS LINDGREN | 6512 | 41623 | 2022/04/26 |
| Test Software | Farad | EZ-EMC | Ver.CPC-3A1 | / |
| Conducted Emission Test | | | | |
| LISN | Schwarzbeck | NSLK 8127 | 8127-892 | 2022-03-19 |
| EMI Test Receiver | R&S | ESR3 | 102124 | 2021-12-23 |
| Pulse Limiter | R&S | ESH3-Z2 | 357.8810.52 | 2021-12-22 |
| Test Software | Farad | EZ-EMC | Ver.CPC-3A1 | / |



3.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates Lora modulation were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 915M

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 1 | 902.3 | 33 | 908.7 | ... | ... |
| 2 | 902.5 | 34 | 908.9 | 62 | 914.5 |
| 3 | 902.7 | 35 | 909.1 | 63 | 914.7 |
| ... | ... | ... | ... | 64 | 914.9 |

Test Frequency and channel for 915M

| Lowest Frequency | | Middle Frequency | | Highest Frequency | |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 1 | 902.3 | 33 | 908.7 | 64 | 914.9 |



4 FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

4.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by A2LA
The Certificate Number is 6325.01.

Name of Firm : SLG-CPC Testlaboratory Co., Ltd.
Site Location : No. 11, Wu Song Road, Dongcheng District, Dongguan, Guangdong Province, China 523117



5 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty |
|--------------------------------|-------------------------|
| Radio Frequency | $\pm 1 \times 10^{-5}$ |
| Maximum Peak Output Power Test | $\pm 1.0 \text{dB}$ |
| Conducted Emissions Test | $\pm 2.0 \text{dB}$ |
| Radiated Emission Test | $\pm 2.0 \text{dB}$ |
| Occupied Bandwidth Test | $\pm 1.0 \%$ |
| Band Edge Test | $\pm 3 \text{dB}$ |
| All emission, radiated | $\pm 3 \text{dB}$ |
| Antenna Port Emission | $\pm 3 \text{dB}$ |
| Temperature | $\pm 0.5^\circ\text{C}$ |
| Humidity | $\pm 3 \%$ |


Measurement Uncertainty for a level of Confidence of 95%



6 SETUP OF EQUIPMENT UNDER TEST

6.1 RADIO FREQUENCY TEST SETUP 1

The 915M component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



6.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)


The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a) Radiated Emission Test Set-Up, Frequency Below 30MHz






(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz






6.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.


Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



6.5 SUPPORT EQUIPMENT

| EUT Cable List and Details | | | |
|----------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| DC cable | 1.0 | Unshielded | Without Ferrite |
| | | | |

| Auxiliary Cable List and Details | | | |
|----------------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| | | | |
| | | | |

| Auxiliary Equipment List and Details | | | |
|--------------------------------------|--------------|--------------|---------------|
| Description | Manufacturer | Model | Serial Number |
| Notebook | Lenovo | MPNXB1505007 | MP1XHYV7 |

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



7 FREQUENCY HOPPING SYSTEM REQUIREMENTS

7.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.2 EUT Pseudorandom Frequency Hopping Sequence


The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels.

The hopping sequence is unique for the piconet and is determined by the device address of the master; the phase in the hopping sequence is determined by the clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence





Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

7.3 Equal Hopping Frequency Use

All frequency units participating in the piconet are time and hop-synchronized to the channel.

Example of a 64 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 32, 1, 11, 23, 2, 55, 29, 3, 9, 52, 58, 40, 25, 7, 18, 26, 60, 47, 50, 2, 5, 16, 37, 63, 54, 20, 13, 4, 8, 15, 21, 26, 10, 43, 24, 57, 39, 46, 48, 33, 17, 31, 75, 19, 41, 62, 28, 51, 66, 30, 56, 34, 59, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

7.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses 915M radio which operates in 902-928 MHz band. 915M uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 64 bands in the range 902-928 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All 915M devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.



8 TEST REQUIREMENTS

8.1 20DB BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.1.2 Conformance Limit

No limit requirement.

8.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in 915M mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.


Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Modulation Mode | Channel Number | Channel Frequency (MHz) | Measurement Bandwidth (kHz) | Limit (kHz) | Verdict |
|-----------------|----------------|-------------------------|-----------------------------|-------------|---------|
| Lora | 1 | 902.3 | 215.8 | <500 | PASS |
| | 33 | 908.7 | 204.6 | <500 | PASS |
| | 64 | 914.9 | 201.6 | <500 | PASS |



20dB Bandwidth
Test Model 915M
Channel 1: 902.3MHz Lora Modulation



20dB Bandwidth
Test Model 915M
Channel 33: 908.7MHz Lora Modulation





Test Model

20dB Bandwidth
915M
Channel 64: 914.9MHz

Lora Modulation





8.2 CARRIER FREQUENCY SEPARATION

8.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.2.2 Conformance Limit

Frequency hopping systems operating in the 902-928MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

8.2.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.2.4 Test Procedure

n According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Modulation Mode | Channel Number | Channel Frequency (MHz) | Measurement Bandwidth (kHz) | Limit (kHz) | Verdict |
|-----------------|----------------|-------------------------|-----------------------------|-------------|---------|
| Lora | 1 | 902.3 | 241 | >216 | PASS |
| | 33 | 908.7 | 211 | >205 | PASS |
| | 64 | 914.9 | 212 | >202 | PASS |

Note: Limit = 20dB bandwidth



Test Model

Carrier Frequency Separation

915M

Channel 1: 902.3MHz

Lora Modulation




Test Model

Carrier Frequency Separation

915M

Channel 33: 908.7MHz

Lora Modulation





Test Model

Carrier Frequency Separation

915M

Channel 64: 914.9MHz

Lora Modulation





8.3 NUMBER OF HOPPING FREQUENCIES

8.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (i) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.3.2 Conformance Limit

Frequency hopping systems operating in the 902-928MHz band shall use at least 50 channels.

8.3.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.3.4 Test Procedure

n According to FCC Part 15.247(a)(1)(i)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (902-928MHz)

RBW \geq 100KHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Modulation Mode | Hopping Channel Frequency Range | Quantity of Hopping Channel | Quantity of Hopping Channel limit |
|-----------------|---------------------------------|-----------------------------|-----------------------------------|
| Lora | 902.3-914.9 | 64 | >50 |




Test Model

Number Of Hopping Frequencies

915M

Span: 902-928MHz





8.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

8.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(i) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.4.2 Conformance Limit

For frequency hopping systems operating in the 902-928MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

8.4.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.4.4 Test Procedure

n According to FCC Part15.247(a)(1)(i)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

8.4.5 Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |



915M (Lora,) mode have been tested:

Dwell Time = 36.167ms

Total bins in 20 s =4 Max.

Allowed time = 0.4s

Total time occupancy in 20s = $36.167 * 4 = 144.67$ ms (which is less than 400ms)





Test Model

Average Time Of Occupancy (Dwell Time)

915M

CH 1: 902.3MHz

Lora





8.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.5.1 Applicable Standard

According to FCC Part 15.247(b)(2) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.5.2 Conformance Limit

The max For frequency hopping systems operating in the 902-928 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 902-928 MHz band: 0.125 watts.

8.5.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.5.4 Test Procedure

According to FCC Part15.247(b)(2)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

Set RBW > the 20 dB bandwidth of the emission being measured

Set VBW ³ RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

Test Results

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Operation Mode | Channel Number | Channel Frequency (MHz) | Measurement Level (dBm) | Limit (dBm) | Verdict |
|----------------|----------------|-------------------------|-------------------------|-------------|---------|
| Lora | 1 | 902.3 | 21.44 | 30 | PASS |
| | 33 | 908.7 | 21.77 | 30 | PASS |
| | 64 | 914.9 | 21.20 | 30 | PASS |
| Note: N/A | | | | | |



Test Model Maximum Peak Conducted Output Power
915M
Channel 1: 902.3MHz Lora



Test Model Maximum Peak Conducted Output Power
915M
Channel 33: 908.7MHz Lora





Test Model

Maximum Peak Conducted Output Power

915M

Channel 64: 914.9MHz

Lora





8.6 CONDUCTED SUPRIOS EMISSION

8.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

8.6.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

8.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

n Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW \geq 3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conducted level.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

n Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW \geq 1% of the span=100kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

n Conducted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.

8.6.5 Test Results

All mode have been tested, and the worst result was report as below:



Test Model

Maximum Conducted Level RBW=100kHz

915M

Channel 1: 902.3MHz

Lora




Test Model

Conducted Spurious RF Conducted Emission

915M


Channel 1: 902.3MHz

Lora






Test Model Band-edge Conducted Emissions
915M
Channel 1: 902.3MHz Lora



Test Model Maximum Conducted Level RBW=100kHz
915M
Channel 33: 908.7MHz Lora






Test Model

Conducted Spurious RF Conducted Emission
915M
Channel 33: 908.7MHz


Lora



Test Model

Maximum Conducted Level RBW=100kHz
915M
Channel 64: 914.9MHz

Lora






Test Model

Conducted Spurious RF Conducted Emission
915M
Channel 64: 914.9MHz


Lora



Test Model

Band-edge Conducted Emissions
915M
Channel 64: 914.9MHz

Lora





8.7 RADIATED SPURIOUS EMISSION

8.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

8.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (2) |
| 13.36-13.41 | | | |

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

| Restricted Frequency(MHz) | Field Strength (μ V/m) | Field Strength ($\text{dB}\mu$ V/m) | Measurement Distance |
|---------------------------|-----------------------------|--------------------------------------|----------------------|
| 0.009-0.490 | 2400/F(KHz) | 20 log (μ V/m) | 300 |
| 0.490-1.705 | 24000/F(KHz) | 20 log (μ V/m) | 30 |
| 1.705-30 | 30 | 29.5 | 30 |
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

8.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW ³ RBW

Sweep = auto

Detector function = peak



Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW ³ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW ³ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW ³ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.7.5 Test Results

n Spurious Emission below 30MHz (9KHz to 30MHz)

| | |
|--------------------|-----------|
| Temperature: | 26° C |
| Relative Humidity: | 54% |
| ATM Pressure: | 1011 mbar |

| Freq. (MHz) | Ant.Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
| | | PK | AV | PK | AV | PK | AV |
| -- | -- | -- | -- | -- | -- | -- | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{ dB})$;

Limit line=Specific limits(dBuV) + distance extrapolation factor



n Spurious Emission Above 1GHz (1GHz to 25GHz)
All mode have been tested, and the worst result was report as below:

Test mode: Lora Frequency: Channel 1: 902.3MHz

| Freq. (MHz) | Ant.Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|-----------------|---------------------------|-------|------------------|----|----------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 1805.47 | V | 60.96 | 43.15 | 74 | 54 | -13.04 | -10.85 |
| 3614.19 | V | 59.82 | 48.71 | 74 | 54 | -14.18 | -5.29 |
| 4369.53 | V | 58.96 | 41.77 | 74 | 54 | -15.04 | -12.23 |
| 1807.15 | H | 62.37 | 41.83 | 74 | 54 | -11.63 | -12.17 |
| 3615.35 | H | 59.27 | 45.73 | 74 | 54 | -14.73 | -8.27 |
| 4835.81 | H | 56.64 | 41.01 | 74 | 54 | -17.36 | -12.99 |

Test mode: Lora Frequency: Channel 33: 908.7MHz

| Freq. (MHz) | Ant.Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|-----------------|------------------------|-------|------------------|----|----------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 1820.96 | V | 62.27 | 43.65 | 74 | 54 | -11.73 | -10.35 |
| 3643.02 | V | 62.56 | 41.24 | 74 | 54 | -11.44 | -12.76 |
| 4363.41 | V | 61.52 | 45.70 | 74 | 54 | -12.48 | -8.30 |
| 1818.43 | H | 61.57 | 41.07 | 74 | 54 | -12.43 | -12.93 |
| 3637.97 | H | 62.3 | 41.37 | 74 | 54 | -11.7 | -12.63 |
| 4838.59 | H | 61.22 | 41.70 | 74 | 54 | -12.78 | -12.30 |

Test mode: Lora Frequency: Channel 64: 914.9MHz


| Freq. (MHz) | Ant.Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Over(dB) | |
|----------------|-----------------|---------------------------|-------|------------------|----|----------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 1831.32 | V | 60.94 | 44.58 | 74 | 54 | -13.06 | -9.42 |
| 3665.03 | V | 59.8 | 41.69 | 74 | 54 | -14.2 | -12.31 |
| 4368.87 | V | 61.9 | 45.32 | 74 | 54 | -12.1 | -8.68 |
| 1830.88 | H | 56.18 | 45.00 | 74 | 54 | -17.82 | -9.00 |
| 3662.52 | H | 59.18 | 43.21 | 74 | 54 | -14.82 | -10.79 |
| 4837.62 | H | 63.44 | 47.40 | 74 | 54 | -10.56 | -6.60 |

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Spurious Emission below 1GHz (30MHz to 1GHz)

All mode have been tested, and the worst result was report as below:



*:Maximum data x:Over limit !:over margin

| Reference Only



Site Polarization: **Horizontal** Temperature: 24 °C

Limit: FCC Part15 C 30-1 GHz Power: AC 120V/60 Hz Humidity: 51 %

Mode: Hopping

Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over |
|-----|-----|----------|---------------|----------------|--------------|-------|-----------|
| | | MHz | dBuV | dB | dBuV/m | dB | Detector |
| 1 | | 62.9800 | 52.88 | -24.89 | 27.99 | 40.00 | -12.01 QP |
| 2 | | 97.9000 | 53.25 | -24.83 | 28.42 | 43.50 | -15.08 QP |
| 3 | * | 183.2600 | 58.89 | -26.83 | 32.06 | 43.50 | -11.44 QP |
| 4 | | 240.4900 | 58.81 | -24.89 | 33.92 | 46.00 | -12.08 QP |
| 5 | | 544.1000 | 50.49 | -20.74 | 29.75 | 46.00 | -16.25 QP |
| 6 | | 797.2700 | 47.61 | -15.30 | 32.31 | 46.00 | -13.69 QP |

*:Maximum data x:Over limit !:over margin

| Reference Only



8.8 CONDUCTED EMISSION TEST

8.8.1 Applicable Standard

According to FCC Part 15.207(a)

8.8.2 Conformance Limit

| Conducted Emission Limit | | |
|--------------------------|------------|---------|
| Frequency(MHz) | Quasi-peak | Average |
| 0.15-0.5 | 66-56 | 56-46 |
| 0.5-5.0 | 56 | 46 |
| 5.0-30.0 | 60 | 50 |

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


8.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.8.5 Test Results

Pass

All mode been tested, and the worst result recorded was report as below:




Site: **N** Temperature: 23
 Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz Humidity: 55 %
 Mode: 915 Mode
 Note:

| No. Mk. | Freq. MHz | Reading Level | Correct Factor | Measure- ment | Limit | Over | Detector | Comment |
|---------|--------------|------------------|-------------------|------------------|-------|--------|----------|---------|
| | | dBuV | dB | dBuV | dB | | | |
| 1 | 0.1500 | 42.45 | 10.05 | 52.50 | 66.00 | -13.50 | QP | |
| 2 | 0.1500 | 27.56 | 10.05 | 37.61 | 56.00 | -18.39 | AVG | |
| 3 | 0.1675 | 39.96 | 10.05 | 50.01 | 65.08 | -15.07 | QP | |
| 4 | 0.1675 | 23.70 | 10.05 | 33.75 | 55.08 | -21.33 | AVG | |
| 5 | 0.2220 | 35.67 | 10.05 | 45.72 | 62.74 | -17.02 | QP | |
| 6 | 0.2220 | 22.97 | 10.05 | 33.02 | 52.74 | -19.72 | AVG | |
| 7 | 0.5433 | 31.47 | 10.06 | 41.53 | 56.00 | -14.47 | QP | |
| 8 * | 0.5433 | 26.25 | 10.06 | 36.31 | 46.00 | -9.69 | AVG | |
| 9 | 11.4375 | 23.44 | 10.63 | 34.07 | 60.00 | -25.93 | QP | |
| 10 | 11.4375 | 12.81 | 10.63 | 23.44 | 50.00 | -26.56 | AVG | |
| 11 | 23.6358 | 23.70 | 10.80 | 34.50 | 60.00 | -25.50 | QP | |
| 12 | 23.6358 | 16.61 | 10.80 | 27.41 | 50.00 | -22.59 | AVG | |

*:Maximum data x:Over limit !:over margin

(Reference Only)



Site: **L1** Temperature: 23
 Limit: FCC Part 15C Conduction(QP) Power: AC 120V/60 Hz Humidity: 55 %
 Mode: 915 Mode
 Note:

| No. | Mk. | Freq. MHz | Reading | Correct | Measure- | Limit | Over | Detector | Comment |
|-----|-----|--------------|---------------|--------------|--------------|-------|--------|----------|---------|
| | | | Level dBuV | Factor dB | ment dBuV | | | | |
| 1 | | 0.1539 | 41.40 | 10.05 | 51.45 | 65.79 | -14.34 | QP | |
| 2 | | 0.1539 | 20.62 | 10.05 | 30.67 | 55.79 | -25.12 | AVG | |
| 3 | | 0.1633 | 40.79 | 10.05 | 50.84 | 65.29 | -14.45 | QP | |
| 4 | | 0.1633 | 23.73 | 10.05 | 33.78 | 55.29 | -21.51 | AVG | |
| 5 | | 0.2220 | 33.70 | 10.05 | 43.75 | 62.74 | -18.99 | QP | |
| 6 | | 0.2220 | 18.47 | 10.05 | 28.52 | 52.74 | -24.22 | AVG | |
| 7 | | 0.5611 | 27.57 | 10.07 | 37.64 | 56.00 | -18.36 | QP | |
| 8 | * | 0.5611 | 21.93 | 10.07 | 32.00 | 46.00 | -14.00 | AVG | |
| 9 | | 0.9282 | 22.63 | 10.14 | 32.77 | 56.00 | -23.23 | QP | |
| 10 | | 0.9282 | 16.51 | 10.14 | 26.65 | 46.00 | -19.35 | AVG | |
| 11 | | 12.3179 | 27.16 | 10.78 | 37.94 | 60.00 | -22.06 | QP | |
| 12 | | 12.3179 | 15.98 | 10.78 | 26.76 | 50.00 | -23.24 | AVG | |

*:Maximum data x:Over limit !:over margin

(Reference Only)



8.9 ANTENNA APPLICATION

8.9.1 Antenna Requirement

| Standard | Requirement |
|---------------------|--|
| FCC CRF Part 15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.9.2 Result

PASS.

The EUT has 1 antenna: a External Antenna for 915M with classic model, the gain is 3 dBi;

Note:

- Antenna use a permanently attached antenna which is not replaceable.
- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

----- END OF REPORT -----