

R²L

ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Application For Grant of Certification

47CFR Paragraph 15.247 FHSS and
Industry Canada RSS-GEN Issue 5 and RSS-247 Issue 3
Hardware Version Identification Number
(HVIN): FBRFS23

902-928 MHz (DSSS)
Frequency Hopping Spread Spectrum
License Exempt Intentional Radiator

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23

FireBoard Labs LLC

501 Charlotte
Kansas City, MO 64106

FCC Designation: US5305
ISED Registration: 3041A

Test Report Number: 230818

Test Date: August 18 to September 28, 2023

Authorized Signatory: *Scot D Rogers*
Scot D. Rogers

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
Date: November 29, 2023
Page 1 of 38

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS.....	2
REVISIONS.....	4
EXECUTIVE SUMMARY	5
OPINION / INTERPRETATION OF RESULTS	6
EQUIPMENT TESTED.....	9
Equipment Function	9
Equipment Configuration.....	10
APPLICATION FOR CERTIFICATION.....	11
APPLICABLE STANDARDS.....	12
EQUIPMENT TESTING PROCEDURES	13
AC Line Conducted Emission Test Procedure	13
Radiated Emission Test Procedure.....	13
Antenna Port Conducted Emission Test Procedure.....	13
Diagram 1 Test arrangement for radiated emissions of tabletop equipment.....	14
Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS).....	15
Diagram 3 Test arrangement for Antenna Port Conducted emissions	16
TEST SITE LOCATIONS	16
UNITS OF MEASUREMENTS	17
ENVIRONMENTAL CONDITIONS.....	17
STATEMENT OF MODIFICATIONS AND DEVIATIONS	17
INTENTIONAL RADIATORS.....	18

Antenna Requirements	18
Restricted Bands of Operation.....	18
Table 1 Radiated Emissions in Restricted Frequency Bands.....	19
Summary of Results for Radiated Emissions in Restricted Bands	19
AC Line Conducted Emissions Procedure	20
General Radiated Emissions Procedure	20
Table 2 General Radiated Emissions Data	21
Summary of Results for General Radiated Emissions	21
Operation in the Band 902 - 928 MHz.....	22
Figure 1 Plot of Transmitter Emissions Operation in 902-928 MHz.....	23
Figure 2 Plot of Transmitter Emissions 20-dB Occupied Bandwidth.....	24
Figure 3 Plot of Transmitter Emissions 99% Occupied Bandwidth	25
Figure 4 Plot of Number of Hopping Channels	26
Figure 5 Plot of Channel Separation.....	27
Figure 6 Plot of Dwell time On Channel	28
Figure 7 Plot of Number of Times on Channel over 10 Second Period	29
Figure 8 Plot of Transmitter Emissions Low Band Edge	30
Figure 9 Plot of Transmitter Emissions High Band Edge.....	31
Transmitter Emissions Data.....	32
Table 3 Transmitter Radiated Emissions	32
Table 4 Transmitter Antenna Port Conducted Data.....	33
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	33
ANNEX.....	34
Annex A Measurement Uncertainty Calculations	35
Annex B Test Equipment.....	36
Annex C Laboratory Certificate of Accreditation.....	38

Executive Summary

License Exempt Frequency Hoping Spread Spectrum Intentional Radiator operating under Title 47 of the Code of Federal Regulations (47CFR) Paragraph 15.247 and Industry Canada RSS-247 Issue 3 and RSS-GEN Issue 5, Frequency Hopping Spread Spectrum (FHSS) transmitter operations in the 902-928 MHz frequency band.

Name of Applicant: FireBoard Labs LLC
501 Charlotte
Kansas City, MO 64106

HVIN: FBRFS23

PMN: FBRFS

FCC ID: 2A29A-FBRFS23

IC: 27842-FBRFS23

Operating Frequency Range: 912-918 MHz

Power (dBm)	Power (Watts)	20-dB OBW (kHz)	99% OBW (kHz)
6.6	0.005	21.1	21.1

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Bands 47CFR 15.205, RSS-210 4.1	-8.3	Complies
AC Line Emissions as per 47CFR 15.207, RSS-GEN 8.8	N/A	Complies
Radiated Emissions 47CFR 15.209, RSS-GEN 8.9	-8.8	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-8.3	Complies

Tests performed include:

47CFR

§15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20-dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20-dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(i) For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(2) For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

Rogers Labs, Inc.

4405 West 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 2

FireBoard Labs LLC

HVIN: FBRFS23

Test: 230818

Test to: 47CFR 15C, RSS-Gen RSS-247

File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23

IC: 27842-FBRFS23

SN's: S432RZ64G, S6F32Z64G

Date: November 29, 2023

Page 6 of 38

(c) Operation with directional antenna gains greater than 6 dBi.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Issue 3

5.1 Frequency hopping systems (FHS)

FHSs employ a spread spectrum technology in which the carrier is modulated with coded information in a conventional manner, causing a conventional spreading of the radio frequency (RF) energy around the carrier frequency. The carrier frequency is not fixed, but changes at fixed intervals under the direction of a coded sequence.

FHSs are not required to employ all available hopping frequencies during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the requirements in this section in case the transmitter is presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of frequency hopping equipment and must distribute its transmissions over the minimum number of hopping channels specified in this section.

Incorporation of intelligence into an FHS that enables it to recognize other users of the band and to avoid occupied frequencies is permitted provided that the FHS does it individually and independently chooses or adapts its hopset. The coordination of FHSs in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

The following applies to FHSs in each of the three bands:

a) The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system's radio frequency (RF) bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

b) FHSs shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz

Rogers Labs, Inc.

4405 West 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 2

FireBoard Labs LLC

HVIN: FBRFS23

Test: 230818

Test to: 47CFR 15C, RSS-Gen RSS-247

File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23

IC: 27842-FBRFS23

SN's: S432RZ64G, S6F32Z64G

Date: November 29, 2023

Page 7 of 38



or two thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

c) For FHSs in the band 902-928 MHz: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period. The maximum 20 dB bandwidth of the hopping channel shall be 500 kHz.

d) FHSs operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

e) FHSs operating in the band 5725-5850 MHz shall use at least 75 hopping channels. The maximum 20 dB bandwidth of the hopping channel shall be 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30-second period.

Equipment Tested

Product Marketing Name: FBRFS

FireBoard Labs LLC
501 Charlotte
Kansas City, MO 64106

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT #5 (Integral Antenna)	FBRFS23	S432RZ64G
EUT #6 (Antenna port connector)	FBRFS23	S6F32Z64G
Thermistor Probe	SF311 Food Probe	N/A

- Software version of “typical” product: v1.0 or newer


Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

Antenna: wire (-1.4 dBi)

Equipment Function

The Equipment Under Test (EUT) provides sensor circuitry to monitor probe temperature and wirelessly send data to remote receiver. The design incorporates a radio transceiver providing wireless interface operation with compatible 902-928 MHz devices. The transmitter was tested for compliance as a Frequency Hopping Spread Spectrum device. The design operates from direct current power provided through replaceable AA battery. No other power interface options are provided. The test sample was provided with test software which engaged the transmitter system during testing. The test sample was provided with test software which engaged the transmitter system for testing. The test software provided operation of the transmitter at 100% duty cycle for testing. For testing purposes, the test sample was connected to the probe and powered from new replaceable AA batteries. The equipment was tested for emissions compliance using the available configurations with the worst-case data presented. Test results in this report relate only to the products described in this report.

Equipment Configuration





Application for Certification

(1) Manufacturer: FireBoard Labs LLC
501 Charlotte
Kansas City, MO 64106

(2) Identification: HVIN: FBRFS23 PMN: FBRFS
FCC ID: 2A29A-FBRFS23 IC: 27842-FBRFS23

(3) Instruction Book:
Refer to Exhibit for Instruction Manual.

(4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.

(5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.

(6) Report of Measurements:
Report of measurements follows in this Report.

(7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.

(8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from replaceable AA batteries. The EUT provides no other interface ports than described in this filing.

(9) Transition Provisions of 47CFR 15.37 are not requested.

(10) Not Applicable. The unit is not a scanning receiver.

(11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.

(12) The equipment is not software defined and this section is not applicable.

(13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.

(14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards

The following information is submitted in accordance with the eCFR (electronic Title 47 Code of Federal Regulations) (47CFR), dated August 4, 2023: Part 2, Subpart J, Part 15C Paragraph 15.247, RSS-247 Issue 3, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013. This report documents compliance for the EUT operations as Frequency Hopping Spread Spectrum (FHSS) Transmitter.

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
Date: November 29, 2023
Page 12 of 38

Equipment Testing Procedures

AC Line Conducted Emission Test Procedure

The EUT operates from battery power only. The design offers no provision for connection to the public utility power system and is therefore exempt from AC Line Conducted emissions testing.


Radiated Emission Test Procedure

Radiated emissions testing was performed as required in 47CFR 15C, RSS-247 Issue 3, RSS-GEN and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams one and two showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure

The EUT was assembled as required for operation and placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in this document and specified in ANSI C63.10-2013. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram four showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing. Refer to diagram three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Diagram 1 Test arrangement for radiated emissions of tabletop equipment



1—A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in $50\ \Omega$ loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).


1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.

2—Antenna can be integral or detachable, depending on the EUT (see 6.3.1).

3—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).

4—For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)
Test arrangement for radiated emissions Below 1 GHz



Test arrangement for radiated emissions Above 1 GHz





Diagram 3 Test arrangement for Antenna Port Conducted emissions



Test Site Locations

Conducted EMI	AC line conducted emissions testing was not required as this is a battery powered unit.
Antenna port	Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS

Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096

NVLAP Accreditation Lab code 200087-0

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
Date: November 29, 2023
Page 16 of 38

Units of Measurements

Conducted EMI Data presented in dB μ V; dB referenced to one microvolt

Antenna port Conducted Data is in dBm; dB referenced to one milliwatt

Radiated EMI Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters.

Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

RFS (dB μ V/m @ 3m) = FSM (dB μ V) + A.F. (dB/m) + Losses (dB) - Gain (dB)

Environmental Conditions

Ambient Temperature 23.1° C

Relative Humidity 39%

Atmospheric Pressure 1029.5 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with the 47CFR Part 15C, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted supporting compliance with the requirements of 47CFR, Subpart C, paragraph 15.247, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5.

Antenna Requirements

The EUT incorporates integral non-user accessible system. Production equipment offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Frequency Bands

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Average Margin (dB)	Vertical Average Margin (dB)
2736.0	58.5	40.1	63.5	44.2	54.0	-13.9	-9.8
2745.0	59.0	41.5	64.0	45.7	54.0	-12.5	-8.3
2754.0	59.1	40.8	64.1	45.3	54.0	-13.2	-8.7
3648.0	47.8	34.1	48.7	35.1	54.0	-19.9	-18.9
3660.0	47.1	33.5	47.0	33.9	54.0	-20.5	-20.1
3672.0	46.2	32.6	45.9	32.6	54.0	-21.4	-21.4
4560.0	47.9	34.0	47.4	33.9	54.0	-20.0	-20.1
4575.0	49.2	35.1	48.1	35.1	54.0	-18.9	-18.9
4590.0	50.1	36.4	50.7	36.4	54.0	-17.6	-17.6

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C and RSS-247 Issue 3 Intentional Radiator requirements. The EUT demonstrated a worst-case minimum margin of -8.3 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted Emissions Procedure

The EUT operates from battery power only. The design offers no provision for connection to the public utility power system and is therefore exempt from AC Line Conducted emissions testing.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available modes during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Table 2 General Radiated Emissions Data

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Quasi-Peak (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Quasi-Peak (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Average Margin (dB)	Vertical Average Margin (dB)
39.9	31.7	26.5	37.4	32.3	40.0	-13.6	-8.8
47.9	31.7	26.0	38.8	33.8	40.0	-17.6	-11.9
50.2	27.5	21.4	36.8	30.5	40.0	-18.0	-8.9
66.2	28.8	22.3	33.5	30.5	40.0	-17.4	-9.6
68.2	26.6	21.3	36.6	28.6	40.0	-25.7	-18.0
80.5	26.8	19.9	28.0	22.0	40.0	-26.8	-24.2
131.3	22.0	15.1	22.4	15.9	40.0	-32.3	-31.4
144.1	23.0	17.8	22.8	16.9	40.0	-28.8	-29.6
192.2	22.0	12.6	19.5	13.0	40.0	-34.9	-35.0
365.7	26.0	18.9	22.2	15.8	47.0	-28.5	-31.4
384.0	22.8	16.5	22.3	16.4	47.0	-30.7	-30.6
456.4	23.6	17.6	24.2	17.6	47.0	-29.4	-29.3
500.1	24.9	19.1	24.2	18.6	47.0	-28.0	-28.2
772.0	29.5	23.2	28.6	23.0	47.0	-24.0	-24.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C paragraph 15.209, RSS-247 Issue 3, and RSS-GEN Issue 5 Intentional Radiators. The EUT configuration demonstrated a minimum margin of -8.8 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Rogers Labs, Inc.

4405 West 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 2

FireBoard Labs LLC

HVIN: FBRFS23

Test: 230818

Test to: 47CFR 15C, RSS-Gen RSS-247

File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23

IC: 27842-FBRFS23

SN's: S432RZ64G, S6F32Z64G

Date: November 29, 2023

Page 21 of 38



Operation in the Band 902 - 928 MHz

The requirements and demonstration of compliance with RSS-247 and 47CFR subpart 15.247 are addressed below and as specified in KDB 558074 D01 15.247 Meas Guidance v05r02. Test sample EUT#5 was used during radiated emissions measurements. Test sample EUT#6 was provided for testing antenna port conducted emissions. Test sample EUT#6 was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak power was measured at the antenna port using a spectrum analyzer and/or wideband RF power sensor as described in ANSI C63.10-2013 and KDB 558074. Radiated emission measurements were taken as required in ANSI C63.10-2013 and KDB 558074. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna. Radiated emission testing was performed on sample EUT#5 representative of production equipment with integral antenna. The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dB μ V/m @ 3 meters. Plots were taken of transmitter performance (using sample EUT#5) for reference in this and other documentation displaying compliance with the specifications.

Requirement: Average occupancy time Requirement:

Average time of occupancy on any channel shall not be greater than 400 mS (0.4 seconds) within a 20 second period (0.4 times the number of hopping channels of 61).

Time on channel: The design resides on channel 4 times in a 20 second period. Transmitting each time for 48.3 mS which equates to an average time of occupancy of (4*48.2 mS) 192.8 mS over 20 seconds.

The 192.8 mS average time of occupancy demonstrates compliance with requirement of less than 400 mS in 20 second period. Additional Frequency Hopping details may be found in the operational description exhibits.

Refer to figures one through nine showing plots taken of the 902-928 MHz Frequency Hopping Spread Spectrum operation displaying compliance with the specifications.

Figure 1 Plot of Transmitter Emissions Operation in 902-928 MHz




Figure 2 Plot of Transmitter Emissions 20-dB Occupied Bandwidth





Figure 3 Plot of Transmitter Emissions 99% Occupied Bandwidth



Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision 2

FireBoard Labs LLC
 HVIN: FBRFS23
 Test: 230818
 Test to: 47CFR 15C, RSS-Gen RSS-247
 File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
 IC: 27842-FBRFS23
 SN's: S432RZ64G, S6F32Z64G
 Date: November 29, 2023
 Page 25 of 38

Figure 4 Plot of Number of Hopping Channels




Figure 5 Plot of Channel Separation




Figure 6 Plot of Dwell time On Channel




Figure 7 Plot of Number of Times on Channel over 10 Second Period





Figure 8 Plot of Transmitter Emissions Low Band Edge




Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818 SN:
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
247 Date: November 29, 2023
0818 Page 30 of 38

Figure 9 Plot of Transmitter Emissions High Band Edge



Transmitter Emissions Data

Table 3 Transmitter Radiated Emissions

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Margin (dB)	Vertical Margin (dB)
912.0	--	--	--	--	--	--	--
1824.0	42.8	30.4	43.0	30.4	54.0	-23.6	-23.6
2736.0	58.5	40.1	63.5	44.2	54.0	-13.9	-9.8
3648.0	47.8	34.1	48.7	35.1	54.0	-19.9	-18.9
4560.0	47.9	34.0	47.4	33.9	54.0	-20.0	-20.1
5472.0	49.6	35.8	49.6	35.9	54.0	-18.2	-18.1
6384.0	52.1	38.5	52.3	39.1	54.0	-15.5	-14.9
915.0	--	--	--	--	--	--	--
1830.0	42.6	30.5	42.8	29.9	54.0	-23.5	-24.1
2745.0	59.0	41.5	64.0	45.7	54.0	-12.5	-8.3
3660.0	47.1	33.5	47.0	33.9	54.0	-20.5	-20.1
4575.0	49.2	35.1	48.1	35.1	54.0	-18.9	-18.9
5490.0	51.1	37.1	51.0	37.1	54.0	-16.9	-16.9
6405.0	51.7	38.5	52.4	39.5	54.0	-15.5	-14.5
918.0	--	--	--	--	--	--	--
1836.0	42.4	30.5	43.2	29.9	54.0	-23.5	-24.1
2754.0	59.1	40.8	64.1	45.3	54.0	-13.2	-8.7
3672.0	46.2	32.6	45.9	32.6	54.0	-21.4	-21.4
4590.0	50.1	36.4	50.7	36.4	54.0	-17.6	-17.6
5508.0	52.4	37.6	52.0	37.6	54.0	-16.4	-16.4
6426.0	52.7	39.2	53.8	40.8	54.0	-14.8	-13.2

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Rogers Labs, Inc.

4405 West 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 2

FireBoard Labs LLC

HVIN: FBRFS23

Test: 230818

Test to: 47CFR 15C, RSS-Gen RSS-247

File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23

IC: 27842-FBRFS23

SN's: S432RZ64G, S6F32Z64G

Date: November 29, 2023

Page 32 of 38

Table 4 Transmitter Antenna Port Conducted Data

Frequency MHz	Output Power (dBm)	Output Power (Watts)	99% Occupied Bandwidth (kHz)	20-dB Occupied Bandwidth (kHz)
912.0	6.6	0.005	21.0	20.9
915.0	6.6	0.005	21.1	20.9
918.0	6.5	0.004	21.1	21.1

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15.247, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5. The antenna port conducted output power measured was 0.005 Watts. The unit utilizes 61 hopping channels with an average time of occupancy less than 0.4 seconds over the required time. The EUT worst-case configuration demonstrated minimum radiated harmonic emission margin of -8.3 dB below the limit. No other radiated emissions were found in the restricted bands less than 20 dB below limits than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the limits.



Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Laboratory Certificate of Accreditation

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
Date: November 29, 2023
Page 34 of 38

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

Equipment	Manufacturer	Model (SN)	Band	Cal Date(m/d/y)	Due
<input type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/28/2023	3/28/2024
<input type="checkbox"/> LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08				3/28/2023	3/28/2024
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)9kHz-40 GHz	10/11/2022	10/11/2023	
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/11/2022	10/11/2023
<input type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/11/2022	10/11/2023
<input type="checkbox"/> Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/11/2023
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/11/2022	10/11/2023
<input type="checkbox"/> Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/11/2022	10/11/2024
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/28/2022	3/29/2024
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/11/2022	10/11/2024
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	3/27/2023	3/27/2025
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	6/26/2023	6/26/2024
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/25/2023	1/25/2024
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/11/2022	10/11/2023
<input checked="" type="checkbox"/> Pwr Sensor	Rohde & Schwarz	NRP33T	0.05-33 GHz	8/31/2022	8/31/2023
<input type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	3/28/2023	3/28/2025
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	3/28/2023	3/28/2024
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/28/2023	3/28/2024
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	3/28/2023	3/28/2025
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	3/28/2023	3/28/2025
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	3/28/2023	3/28/2025
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	3/28/2023	3/28/2025
<input checked="" type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	3/28/2023	3/28/2025
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	3/28/2023	3/28/2025
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	3/28/2023	3/28/2025
<input checked="" type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	3/28/2023	3/28/2024
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/28/2023	3/28/2024
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/28/2023	3/28/2024
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/28/2023	3/28/2024
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	3/28/2023	3/28/2024
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A81120N075)		10/11/2022	10/11/2023

List of Test Equipment

Calibration Date (m/d/y) Due

<input type="checkbox"/> Frequency Counter: Leader LDC-825 (8060153)		3/28/2023	3/28/2025
<input type="checkbox"/> ISN: Com-Power Model ISN T-8		3/28/2023	3/28/2024
<input type="checkbox"/> LISN Compliance Design FCC-LISN-2.Mod.cd.(126) .15-30MHz		10/11/2022	10/11/2024
<input type="checkbox"/> LISN: Com-Power Model LI-220A		3/29/2023	3/29/2025
<input type="checkbox"/> LISN: Com-Power Model LI-550C		10/11/2022	10/11/2024
<input type="checkbox"/> Cable Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072) 9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable Huber & Suhner Inc. Sucoflex102ea(L1M)(281183) 9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable Huber & Suhner Inc. Sucoflex102ea(L4M)(281184) 9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)9kHz-40 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> Cable Time Microwave 4M-750HF290-750 (4M) 9kHz-24 GHz	10/11/2022	10/11/2023	
<input type="checkbox"/> RF Filter Micro-Tronics BRC17663 (001) 9.3-9.5 notch 30-1800 MHz	3/28/2023	3/28/2025	
<input type="checkbox"/> RF Filter Micro-Tronics BRC19565 (001) 9.2-9.6 notch 30-1800 MHz	3/28/2023	3/28/2025	
<input type="checkbox"/> Analyzer HP 8562A (3051A05950) 9kHz-125GHz	3/28/2023	3/28/2024	
<input type="checkbox"/> Wave Form Generator Keysight 33512B (MY57400128)		3/29/2022	3/29/2024
<input type="checkbox"/> Antenna: Solar 9229-1 & 9230-1		2/18/2023	2/18/2024
<input type="checkbox"/> CDN: Com-Power Model CDN325E		10/11/2022	10/11/2024
<input type="checkbox"/> Oscilloscope Scope: Tektronix MDO 4104		2/18/2023	2/18/2024
<input type="checkbox"/> EMC Transient Generator HVT TR 3000		2/18/2023	2/18/2024
<input type="checkbox"/> AC Power Source (Ametech, California Instruments)		2/18/2023	2/18/2024
<input type="checkbox"/> Field Intensity Meter: EFM-018		2/18/2023	2/18/2024
<input type="checkbox"/> ESD Simulator: MZ-15		2/18/2023	2/18/2024
<input type="checkbox"/> Injection Clamp Luthi Model EM101		not required	
<input type="checkbox"/> R.F. Power Amp ACS 230-50W		not required	
<input type="checkbox"/> R.F. Power Amp EIN Model: A301		not required	
<input type="checkbox"/> R.F. Power Amp A.R. Model: 10W 1010M7		not required	
<input type="checkbox"/> R.F. Power Amp A.R. Model: 50U1000		not required	
<input type="checkbox"/> Temperature Chamber		not required	
<input checked="" type="checkbox"/> Shielded Room		not required	

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).*

2023-03-16 through 2024-03-31

Effective Dates



For the National Voluntary Laboratory Accreditation Program

A handwritten signature in blue ink that reads "Anna S. Laman".

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 2

FireBoard Labs LLC
HVIN: FBRFS23
Test: 230818
Test to: 47CFR 15C, RSS-Gen RSS-247
File: Fireboard FBRFS23 TstRpt 230818

FCC ID: 2A29A-FBRFS23
IC: 27842-FBRFS23
SN's: S432RZ64G, S6F32Z64G
Date: November 29, 2023
Page 38 of 38