



TEST REPORT

Test Report No.: UL-RPT-RP-13831825-416-FCC

Applicant : InFarm Indoor Urban Farming GmbH
Model No. : Infarm Gateway
FCC ID : Contains 2A2CI-INF001-WF & Contains 2A2CI-INF001-CL
Technology : Bluetooth – Low Energy
Test Standard(s) : FCC Parts 15.207, 15.209(a) & 15.247

For details of applied tests refer to test result summary

1. This test report shall not be reproduced in full or partial, without the written approval of UL International Germany GmbH.
2. The results in this report apply only to the sample tested.
3. The test results in this report are traceable to the national or international standards.
4. **Test Report Version 1.1 supersede Version 1.0 with immediate effect**
Test Report No. UL-RPT-RP-13831825-416-FCC Version 1.1, Issue Date 08 APRIL 2022 replaces
Test Report No. UL-RPT-RP-13831825-416-FCC Version 1.0, Issue Date 31 MARCH 2022, which is no longer valid.
5. Result of the tested sample: **PASS**

Prepared by: Sercan, Usta
Title: Laboratory Engineer
Date: 08 April 2022

Approved by: Ajit, Phadtare
Title: Lead Test Engineer
Date: 08 April 2022



Deutsche
Akkreditierungsstelle
D-PL-19381-02-00

This laboratory is accredited by DAkkS.
The tests reported herein have been performed in
accordance with its' terms of accreditation.

This page has been left intentionally blank.

Table of Contents

1. Customer Information.....	4
1.1. Applicant Information	4
1.2. Manufacturer Information	4
2. Summary of Testing.....	5
2.1. General Information	5
Applied Standards	5
Location	5
Date information	5
2.2. Summary of Test Results	6
2.3. Methods and Procedures	6
2.4. Deviations from the Test Specification	6
3. Equipment Under Test (EUT)	7
3.1. Identification of Equipment Under Test (EUT)	7
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	8
3.5. Support Equipment	8
A. Support Equipment (In-house)	8
B. Support Equipment (Manufacturer supplied)	8
4. Operation and Monitoring of the EUT during Testing	9
4.1. Operating Modes / Worst-case Identification	9
4.2. Configuration and Peripherals	10
5. Measurements, Examinations and Derived Results	11
5.1. General Comments	11
5.2. Test Results	12
5.2.1. Transmitter AC Conducted Spurious Emissions	12
5.2.2. Transmitter Duty Cycle	18
5.2.3. Transmitter Radiated Emissions	20
5.2.4. Transmitter Band Edge Radiated Emissions	31
6. Measurement Uncertainty	35
7. Used equipment	36
8. Report Revision History	37

1. Customer Information

1.1. Applicant Information

Company Name:	InFarm Indoor Urban Farming GmbH
Company Address:	Colditzstr. 30 12099 Berlin, Germany
Company Phone No.:	+49 (0) 30991916590
Company E-Mail:	info@infarm.com
Contact Person:	Ibrahim Oguz Yildirim
Contact E-Mail Address:	ibrahimoguz.yildirim@infarm.com
Contact Phone No.:	+49 (0) 30991916590

1.2. Manufacturer Information

Company Name:	InFarm Indoor Urban Farming GmbH
Company Address:	Colditzstr. 30 12099 Berlin, Germany
Company Phone No.:	+49 (0) 30991916590
Company E-Mail:	info@infarm.com
Contact Person:	Ibrahim Oguz Yildirim
Contact E-Mail Address:	ibrahimoguz.yildirim@infarm.com
Contact Phone No.:	+49 (0) 30991916590

2. Summary of Testing

2.1. General Information

Applied Standards

Specification Reference:	47CFR15.247
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Section 15.247
Specification Reference:	47CFR15.207 and 47CFR15.209
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Sections 15.207 and 15.209

Location

Location of Testing:	UL International Germany GmbH Hedelfinger Str. 61 70327 Stuttgart Germany
Test Firm Registration:	399704

Date information

Order Date:	17 May 2020
EUT arrived:	11 August 2021
Test Dates:	26 August 2021 to 29 November 2021
EUT returned:	-/-

2.2. Summary of Test Results

Clause	Measurement	Complied	Did not comply	Not performed	Not applicable
Part 15.207	Transmitter AC Conducted Emissions	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Part 15.247(a)(2)	Transmitter Minimum 6 dB Bandwidth ⁽²⁾	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Part 15.35(c)	Transmitter Duty Cycle ⁽¹⁾	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Part 15.247(e)	Transmitter Power Spectral Density ⁽²⁾	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Part 15.247(b)(3)	Transmitter Maximum Output Power ⁽²⁾	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Part 15.247(d) & 15.209(a)	Transmitter Radiated Emissions	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Part 15.247(d) & 15.209(a)	Transmitter Band Edge Radiated Emissions	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note(s):

1. The measurement was performed to assist in the calculation of the average measurements.
2. As per applicant's declaration FCC pre-approved radio module is integrated within the EUT therefore, only partial testing is performed.
For further details refer FCC pre-approved radio module's (Model: v1.1 | FCC ID: 2APW6-FIN0110-CM2) | Report No. CCISE190808001 | Ver 00 | Issue Date: 27-Dec-2019 | Centre Testing Shenzhen Zhongjian Nanfang Testing Co., Ltd.

2.3. Methods and Procedures

Reference:	ANSI C63.10-2013
Title:	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Reference:	KDB 558074 D01 DTS Meas Guidance v05r02 April 2, 2019
Title:	Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules
Reference:	KDB 174176 D01 Line Conducted FAQ v01r01 June 3, 2015
Title:	AC Power-Line Conducted Emissions Frequently Asked Questions

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Infarm
Model Name or Number:	Infarm Gateway
Test Sample Serial Number:	100101000221 (RF Test Sample with External SMA Connectors)
Hardware Version Number:	1.1.0
Firmware Version Number:	W15.68.19.p48-15.26.19.p48
FCC ID:	Contains 2A2CI-INF001-WF & Contains 2A2CI-INF001-CL

Brand Name:	MobileMark
Model:	SMW-414 multiband, 4-cable Global Cellular/LTE, WiFi & GPS
Test Sample Serial Number:	N/A
Additional Info:	External Antenna (Acre)

3.2. Description of EUT

The equipment under test was a host product supporting Bluetooth Low Energy (BLE), WiFi 2.4 GHz operations in 2.4 - 2.4835 GHz ISM band, WiFi 5 GHz operations in U-N-II bands and Cellular operations in UMTS Band 2 & 5, LTE Band 2, 4, 5, 7 & 12 bands.

3.3. Modifications Incorporated in the EUT

Following modifications were applied to the EUT during testing.

- In order to avoid unwanted emissions from EUT as part of EUT filtering two ferrites (Manufacturer: Würth Elektronik | Type: 742 717 33 | Passthrough) was placed just outside the EUT's enclosure and near AC/DC power supply on the DC power supply cable.

Therefore, manufacturer must include these additional ferrites on the AC/DC power supply cable; to ensure compliant results.

3.4. Additional Information Related to Testing

Technology Tested:	Bluetooth Low Energy / Digital Transmission System		
Type of Unit:	Transceiver		
Channel Spacing:	2 MHz		
Modulation:	GFSK		
Data Rate:	1 Mbps		
Power Supply Requirement(s):	6 - 24 (V) DC (Used voltage 12 V DC)		
Declared Antenna Gain:	5 dBi		
Antenna Type:	Multiband External Antenna		
Antenna Details:	4-Cable Multiband SMW-414 multiband MobileMark I SMA Connector Cable 2		
Transmit Frequency Range:	2402 MHz to 2480 MHz		
Transmit Channels Tested:	Channel ID	RF Channel	Channel Frequency (MHz)
	Bottom	37	2402
	Middle	17 (Note 1)	2440
	Top	39	2480

(Note 1) For further details refer FCC pre-approved radio module's (Model: v1.1 | FCC ID: 2APW6-FIN0110-CM2) | Report No. CCISE190808001| Ver 00 | Issue Date: 27-Dec-2019 | Centre Testing Shenzhen Zhongjian Nanfang Testing Co., Ltd.

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

A. Support Equipment (In-house)

Item	Description	Brand Name	Model Name or Number	Serial Number
1	Laptop (labtool v2.0.0.93 software installed)	HP	Probook 650 G1	5CG6143YW
2	Ethernet Cable (2m)	N/A	N/A	N/A

B. Support Equipment (Manufacturer supplied)

Item	Description	Brand Name	Model Name or Number	Serial Number
1	AC/DC Power Supply	Phoenix Contact	UNO-PS/1AC/12DC/100W	290299702051P1207 2020/12/17V

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes / Worst-case Identification

The EUT was tested in the following operating mode(s):

Transmitter / Modulated Carrier Continuous Transmissions Mode Bluetooth LE, Worst-case s*:

- BT-LE Test Mode :1 Mbps | PRBS9 | Power Settings: Max

** These worst-case data rates are taken from FCC pre-approved radio module's (Model: v1.1 | FCC ID: 2APW6-FIN0110-CM2) | Report No. CCISE190808001| Ver 00 | Issue Date: 27-Dec-2019 | Centre Testing Shenzhen Zhongjian Nanfang Testing Co., Ltd.

*** In accordance with FCC KDB 996369 D04 Section 3.4 (b) the Host Product testing has been performed on unwanted (spurious) radiated emissions on the worst-case modulation and channel per frequency range as shown in original filing

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- The applicant supplied documents containing the setup instructions and commands
“Setting up direct test mode (DTM) on the balenaFin.pdf” and “Labtool commands guide.pdf”

EUT Power Supply:

- The EUT was powered by 12 V DC power supply via AC/DC adapter.

Test Mode Activation:

- The test modes were activated using labtool v2.0.0.93 software which supplied by customer.
- The EUTs were configured to transmit test modes continuously with maximum power level.

AC Conducted Emissions Measurements:

- The EUT radiated sample was used for AC conducted emissions measurements.
- The Toyo EMI Software EP5/CE Ver 4.0.1. was used for these measurements.
- The AC conducted line emissions measurements were carried out with 120 V AC / 60 Hz & 240 V AC / 60 Hz.

Radiated Measurements:

- In accordance with ANSI C63.26, the EUT allows for the connection of external accessories, including external electrical control signals; hence EUT has been tested with the listed equipment under section 3.5 B which form part of a system. Therefore, were used for radiated spurious emission, measurements.
- Before starting final radiated spurious emission measurements “worst case verification” with the EUT in Standing-position & Laying-position and different positions of the antenna was performed by Lab.
- The EUT in Standing-position was found to be the worst case therefore this report includes relevant results.
- Antenna's 3 input cables connected to EUT directly. 1 GPS port terminated with 50 Ohm termination.
- The radiated spurious emissions below 30 MHz were performed with the EUT positioned on the turn table and rotating 360 degrees while the loop antenna height was set to 80 cm.
- Radiated spurious emissions were performed with the EUT positioned on the turn table and rotating 360 degrees while the antenna height varies from 1 to 4 m over the measurement frequency range.
- R&S® EMC32 V10.60.10 Software was used for the Radiated spurious emission measurements.

Duty Cycle Correction Details:

- As the EUT continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and EUT was transmitting continuously with a constant Duty Cycle of 94.37 % (duty cycle variations are less than $\pm 2\%$). Therefore, a Duty Cycle Correction Factor of 0.25 dB was added to all average measurements, to compute the corrected average values of the emissions that would have been measured had the test been performed at 100% Duty Cycle.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to Section 6 *Measurement Uncertainty* for details.

In accordance with DAkkS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

5.2. Test Results

5.2.1. Transmitter AC Conducted Spurious Emissions

Test Summary:

Test Engineer:	Asim Shahzad	Test Date:	26 & 29 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 7/8		

FCC Reference:	Part 15.207
Test Method Used:	ANSI C63.10 Section 6.2 / FCC KDB 174176 and notes below

Environmental Conditions:


Temperature (°C):	23 & 25.2
Relative Humidity (%):	35 & 34.7

Settings of the Instrument

Detector	Quasi Peak/ Average Peak
-----------------	--------------------------

Note(s):

1. Measurements were performed in shielded room (SR7/ 8 Asset Number 1603671). The EUT was placed at a height of 10 cm above the reference ground plane and in a distance of 40 cm from the vertical ground plane at the edge of the table.
2. Measurement software used: Toyo EMI Software; CE measurement software EP5/CE Ver 4.0.1.
3. The EUT was plugged into a AC/DC Power Supply. The Power Supply was connected to 120 VAC / 60 Hz or 240 V AC / 60 Hz single phase supply via a LISN.
4. In accordance with FCC KDB 174176 Q4, tests were performed with a 240 VAC 60 Hz single phase supply as this was within the voltage range marked on the 100-240 VAC~50/60 Hz power supply.
5. The EUT was configured on BT-LE Test Mode :1 Mbps | PRBS9 | Power Settings: Max | Middle Channel
6. All other emissions shown on the pre-scan plot were investigated. Only the highest 6 emissions have been reported in the tables below in accordance with ANSI C63.10 section 6.2.5.
7. The final measured value, for the given emission, in the table below incorporates the cable loss. Calculation: Level = test receiver reading + path loss (cable attenuation + correction LISN).

Transmitter AC Conducted Spurious Emissions (continued)**Test setup:**

Transmitter AC Conducted Spurious Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel****Results: 120 VAC 60 Hz / Live / Quasi Peak**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.17101	Live	34.30	64.90	30.60	Complied
0.21536	Live	29.10	63.00	33.90	Complied
0.35062	Live	30.70	58.90	28.20	Complied
3.26872	Live	15.00	56.00	41.00	Complied
9.8873	Live	21.20	60.00	38.80	Complied
11.6699	Live	16.00	60.00	44.00	Complied

Results: 120 VAC 60 Hz / Live / Average


Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.17101	Live	21.40	54.90	33.50	Complied
0.21536	Live	19.30	53.00	33.70	Complied
0.35062	Live	32.40	48.90	16.50	Complied
3.26872	Live	12.60	46.00	33.40	Complied
9.8873	Live	15.80	50.00	34.20	Complied
11.6699	Live	11.30	50.00	38.70	Complied

Results: 120 VAC 60 Hz / Neutral / Quasi Peak

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.17676	Neutral	33.70	64.60	30.90	Complied
0.26285	Neutral	28.00	61.30	33.30	Complied
0.35132	Neutral	32.60	58.90	26.30	Complied
0.6549	Neutral	21.10	56.00	34.90	Complied
2.99509	Neutral	18.80	56.00	37.20	Complied
9.01697	Neutral	19.10	60.00	40.90	Complied

Transmitter AC Conducted Spurious Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel****Results: 120 VAC 60 Hz / Neutral / Average**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.17676	Neutral	23.20	54.60	31.40	Complied
0.26285	Neutral	21.90	51.30	29.40	Complied
0.35132	Neutral	23.00	48.90	25.90	Complied
0.6549	Neutral	18.60	46.00	27.40	Complied
2.99509	Neutral	13.30	46.00	32.70	Complied
9.01697	Neutral	14.00	50.00	36.00	Complied

Result: Pass**Plot: 120 VAC 60 Hz / Live and Neutral Line**

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Transmitter AC Conducted Spurious Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel****Results: 240 VAC 60 Hz / Live / Quasi Peak**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.1633	Live	27.10	65.30	38.20	Complied
0.17989	Live	26.30	64.50	38.20	Complied
0.36221	Live	29.90	58.70	28.80	Complied
0.59547	Live	25.80	56.00	30.20	Complied
1.4941	Live	24.20	56.00	31.80	Complied
9.71632	Live	22.50	60.00	37.50	Complied

Results: 240 VAC 60 Hz / Live / Average


Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.1633	Live	17.40	55.30	37.90	Complied
0.17989	Live	16.80	54.50	37.70	Complied
0.36221	Live	23.80	48.70	24.90	Complied
0.59547	Live	20.70	46.00	25.30	Complied
1.4941	Live	19.90	46.00	26.10	Complied
9.71632	Live	17.30	50.00	32.70	Complied

Results: 240 VAC 60 Hz / Neutral / Quasi Peak

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.1633	Neutral	27.10	65.30	38.20	Complied
0.17989	Neutral	26.30	64.50	38.20	Complied
0.36221	Neutral	29.90	58.70	28.80	Complied
0.59547	Neutral	25.80	56.00	30.20	Complied
1.4941	Neutral	24.20	56.00	31.80	Complied
9.71632	Neutral	22.50	60.00	37.50	Complied

Transmitter AC Conducted Spurious Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel****Results: 240 VAC 60 Hz / Neutral / Average**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.16805	Neutral	25.10	55.10	30.00	Complied
0.26414	Neutral	23.20	51.30	28.10	Complied
0.3498	Neutral	28.40	49.00	20.60	Complied
0.58747	Neutral	23.00	46.00	23.00	Complied
1.17217	Neutral	20.00	46.00	26.00	Complied
12.46648	Neutral	11.80	50.00	38.20	Complied

Result: Pass**Plot: 240 VAC 60 Hz / Live and Neutral Line**

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

5.2.2. Transmitter Duty Cycle

Test Summary:

Test Engineer:	Sercan Usta	Test Date:	24 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 1/2		

FCC Reference:	Part 15.35(c)
Test Method Used:	FCC KDB 558074 Section 6.0 referencing ANSI C63.10 Section 11.6

Environmental Conditions:

Temperature (°C):	24.9
Relative Humidity (%):	57.0


Notes:

1. The transmitter duty cycle was measured using a spectrum analyser in the time domain and calculated by using the following calculation:

Duty Cycle (%) = 100 X [On Time (T_{ON})] / [Period(T_{ON}+ T_{OFF}) or 100ms whichever is the lesser]


Duty Cycle Correction Factor= 10 log 1 / [On Time (T_{ON})] / [Period(T_{ON}+ T_{OFF}) or 100ms whichever is the lesser]

Test Setup:



Transmitter Duty Cycle (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**

Pulse On Time (T_{ON}) (ms)	Pulse Period ($T_{ON} + T_{OFF}$) (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
2.949	3.125	94.37	0.25

**Result: Pass**

5.2.3. Transmitter Radiated Emissions

Test Summary:

Test Engineer:	Sercan Usta	Test Date:	16 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 1/2		


FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	FCC KDB 558074 Sections 8.5 & 8.6 referencing ANSI C63.10 Sections 11.11 and 11.12 ANSI C63.10:2013 Sections 6.3 and 6.4
Frequency Range:	9 kHz to 30 MHz

Environmental Conditions:

Temperature (°C):	23.1
Relative Humidity (%):	34.6


Note(s):

1. In accordance with FCC KDB 414788 D01 Radiated Test Site & ANSI C63.10 clause 5.2 an alternative test site that can demonstrate equivalence to a open area test site may be used. Therefore, the measurement was performed in a Semi Anechoic Chamber. (The OATS / SAC comparison data is available upon request).
2. The limits are specified at a test distances of 30 and 300 metres. However, as specified in FCC Section 15.31 (f)(2) & ANSI C63.10 clause 6.4.3, measurements may be performed at a closer distance and the measured level extrapolated to the specified measurement distance using the method described in clauses 6.4.4, specifically sub-clause 6.4.4.1 which specifies that the measured level shall be extrapolated to the specified distance by conservatively presuming that the field strength decays at 40 dB/decade.
3. Therefore, measurements were performed at a measurement distance of 3 m. Therefore, the limit values are extrapolated to a measurement distance of 3 m was measured.
 - 9 kHz- 490 kHz: limits extrapolated from 300 m to 3 m by adding 80 dB at 40 dB /decade.
 - 490 kHz-1705 kHz: limits extrapolated from 30 m to 3 m by adding 40 dB at 40 dB /decade.
4. Measurements below 30 MHz were performed in a semi-anechoic chamber SR1/ 2 (Asset Number 1603665) at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. The measurement loop antenna height was 80 cm.
5. Pre-scans were performed and markers placed on the highest measured levels. The test receiver was set to:
 - Frequency range: 9 kHz-150 kHz : RBW: 300 Hz /VBW: 1 kHz
 - Frequency range: 150 kHz – 30 MHz: RBW: 10 kHz /VBW: 30 kHz
 - Detector: Max-Peak detector
 - Trace Mode: Max Hold
6. The preliminary scans showed similar emission levels below 30 MHz, for each channel & modes of operation. Therefore, final radiated emissions measurements were performed with the EUT set to the middle channel only.
7. All emissions shown on the pre-scans were investigated and found to be > 20 dB below the applicable limits.

Transmitter Radiated Emissions (continued)**Test Setup:**

Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**

Frequency (MHz)	Loop Antenna Orientation	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
All emissions were below the level of the measurement system noise floor.					

Plot: 9 kHz – 30 MHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**Result: Pass**

Transmitter Radiated Emissions (continued)**Test Summary:**

Test Engineer:	Sercan Usta	Test Date:	12 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 1/2		


FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	FCC KDB 558074 Sections 8.5 & 8.6 referencing ANSI C63.10 Sections 11.11 and 11.12 ANSI C63.10:2013 Sections 6.3 and 6.5
Frequency Range:	30 MHz to 1000 MHz

Environmental Conditions:

Temperature (°C):	24.5
Relative Humidity (%):	46.7


Note(s):

1. Measurements below 1 GHz were performed in a semi-anechoic chamber SR1/ 2 (Asset Number 1603665) at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 m to 4 m.
2. Pre-scans were performed and markers placed on the highest measured levels. The test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold.
3. The preliminary scans showed similar emission levels below 1 GHz, for each channel. Therefore, final radiated emissions measurements were performed with the EUT set to the following worst-case modes:
 - BT-LE Test Mode :1 Mbps | PRBS9 | Power Settings: Max | Middle Channel

Test Setup:

Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**

Frequency (MHz)	Antenna Polarization	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
No critical emissions were found					

Plot: 30 MHz – 1 GHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**Result: Pass**

Transmitter Radiated Emissions (continued)**Test Summary:**

Test Engineer:	Sercan Usta	Test Date:	26 August 2021 & 16 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 1/2		


FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	FCC KDB 558074 Sections 8.5 & 8.6 referencing ANSI C63.10 Sections 11.11 and 11.12 ANSI C63.10:2013 Sections 6.3 and 6.6
Frequency Range:	1 GHz to 25 GHz

Environmental Conditions:

Temperature (°C):	23 & 23.4
Relative Humidity (%):	40 & 40.1


Note(s):

1. The emissions shown at frequencies approximately 2.4 GHz to 2.4835 GHz on the 1 GHz to 18 GHz plots are the EUT fundamental for the tested channel.
2. Pre-scans above 1 GHz were performed in a semi-anechoic chamber SR1/ 2 (Asset Number 1603665) with absorber on the floor at a distance of 3 m. The EUT was placed at a height of 1.5 m above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 m above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber SR1/ 2 (Asset Number 1603665) with absorber on the floor at a distance of 3 m. The EUT was placed at a height of 1.5 m above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 m to 4 m.
3. Pre-scans were performed, and a marker placed on the highest measured level of the appropriate plot. The test receiver resolution bandwidth was set to 1 MHz and video bandwidth 3 MHz. The sweep time was set to auto.
4. All emissions shown on the pre-scan plots were investigated and found to be below system noise floor.
5. The preliminary scans showed similar emission levels above 18 GHz, for each channel & modes of operation. Therefore, final radiated emissions measurements were performed with the EUT set to the middle channel only.
6. In accordance with ANSI C63.10-2013 Section 5.3.3 & 6.5.3 measurements above 18 GHz were performed at closer distance (1 m); because at specified measurement distance (3m) for compliance the instrumentation noise floor was typically close to the radiated emission limit.
7. For frequency range between 18 GHz and 25 GHz, no critical emissions were found.

Transmitter Radiated Emissions Test setup**Test Setup:**


Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Bottom Channel**

Frequency (MHz)	Antenna Polarization	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
No critical emissions were found					

Plot: 1 GHz – 18 GHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Bottom Channel**Result: Pass**


Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**

Frequency (MHz)	Antenna Polarization	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
No critical emissions were found					

Plot: 1 GHz – 18 GHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**Result: Pass**


Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Top Channel**

Frequency (MHz)	Antenna Polarization	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
No critical emissions were found					

Plot: 1 GHz – 18 GHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Top Channel**Result: Pass**

Transmitter Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**

Frequency (MHz)	Antenna Polarization	Peak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
All emissions were below the level of the measurement system noise floor.					

Plot: 18 GHz – 25 GHz: BT-LE Mode / 1 Mbps / PRBS9 / Max Power / Middle Channel**Result: Pass**

5.2.4. Transmitter Band Edge Radiated Emissions

Test Summary:

Test Engineer:	Sercan Usta	Test Date:	24 November 2021
Test Sample Serial Number:	100101000221(RF Test Sample with External SMA Connectors)		
Test Site Identification	SR 1/2		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	DTS emissions in non-restricted frequency bands: FCC KDB 558074 Section 8.5 referencing ANSI C63.10:2013 Sections 11.11
	DTS emissions in restricted frequency bands: FCC KDB 558074 Section 8.6 referencing ANSI C63.10:2013 Sections 11.12
	ANSI C63.10:2013 Sections 6.10.4, 6.10.5

Environmental Conditions:


Temperature (°C):	24.9
Relative Humidity (%):	57.0

Note(s):

1. The measurements were in a semi-anechoic chamber SR1/ 2 (Asset Number 1603665) with RF absorbers on the floor at a distance of 3 m. The EUT was placed at a height of 1.5 m above the test chamber floor in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 m to 4 m
2. As the lower band edge falls within a non-restricted band, measurements were performed in accordance with FCC KDB 558074 Section 8.5 referencing ANSI C63.10 Section 11.11. As the maximum peak conducted output power was previously measured, in accordance with ANSI C63.10 Section 11.11.1(a) lower band edge measurement was performed with a peak detector and the -20 dBc limit applied.
3. As the lower band edge falls within a non-restricted band, only peak measurements are required. The test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. The test receiver was left to sweep for a sufficient length of time in order to maximise the carrier level and out-of-band emissions. A marker and corresponding reference level line were placed on the peak of the carrier. Marker frequencies and levels were recorded.
4. The restricted band peak measurements were performed in accordance with ANSI C63.10 Section 11.12.2.4.
5. As the EUT continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), the restricted band average measurements were performed in accordance with ANSI C63.10 Section 11.12.2.5.2.
6. As the upper band edge falls within a restricted band both peak and average measurements were recorded by placing a marker at the edge of the band. For peak measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. For average measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. A RMS detector in linear power averaging mode was used. The test receiver was left to sweep for a sufficient length of time in order to maximise the carrier level and out-of-band emissions. A marker was placed on the band edge spot frequencies and a second marker placed on the highest emission level in the adjacent restricted band of operation (where a higher level emission was present). Marker frequencies and levels were recorded.

Transmitter Band Edge Radiated Emissions (continued)

7. There is a restricted band 10 MHz below the lower band edge. The test receiver was set up as follows: the RBW set to 1 MHz, the VBW set to 3 MHz, with the sweep time set to auto couple. Peak and average measurements were performed with their respective detectors. Markers were placed on the highest point on each trace.
8. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
9. **As the EUT continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and EUT was transmitting continuously with a constant Duty Cycle of 94.37 % (duty cycle variations are less than $\pm 2\%$). Therefore, a Duty Cycle Correction Factor of 0.25 dB was added to all average measurements, to compute the corrected average values of the emissions that would have been measured had the test been performed at 100% Duty Cycle.

Test Setup:

Transmitter Band Edge Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power****Results: Lower Band Edge / Peak**

Frequency (MHz)	Peak Level (dB μ V/m)	-20 dBc Limit (dB μ V/m)	Margin (dB)	Result
2379.56	32.99	42.58	9.59	Complied
2400.00	30.93	42.58	11.65	Complied

Results: 2310 to 2390 MHz Restricted Band / Peak

Frequency (MHz)	Peak Level (dB μ V/m)	Peak Limit (dB μ V/m)	Margin (dB)	Result
2372.69	43.70	74.0	30.3	Complied

Results: 2310 to 2390 MHz Restricted Band / Average

Frequency (MHz)	Average Level (dB μ V/m)	Duty Cycle Correction Factor (dB)	Corrected Average Level ** (dB μ V/m)	Average Limit (dB μ V/m)	Margin (dB)	Result
2316.28	31.34	0.25	31.59	54.0	22.41	Complied




Results: Upper Band Edge / Peak

Frequency (MHz)	Peak Level (dB μ V/m)	Peak Limit (dB μ V/m)	Margin (dB)	Result
2483.50	42.43	74.0	31.57	Complied
2505.81	44.61	74.0	29.39	Complied

Results: Upper Band Edge / Average

Frequency (MHz)	Average Level (dB μ V/m)	Duty Cycle Correction Factor (dB)	Corrected Average Level ** (dB μ V/m)	Average Limit (dB μ V/m)	Margin (dB)	Result
2483.50	31.38	0.25	31.63	54.0	22.37	Complied
2517.47	31.79	0.25	32.04	54.0	21.96	Complied

Result: Pass

Transmitter Band Edge Radiated Emissions (continued)**Results: BT-LE Mode / 1 Mbps / PRBS9 / Max Power****Lower Band Edge Measurement****Upper Band Edge Measurement****2310 MHz to 2390 MHz Restricted Band Plot**

6. Measurement Uncertainty

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	95%	± 2.49 dB
Radiated Spurious Emissions	95%	± 3.10 dB
Band Edge Radiated Emissions	95%	± 3.10 dB
Transmitter Duty Cycle	95%	$\pm 3.4\%$

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

7. Used equipment

Test site: SR 1/2

ID	Manufacturer	Type	Model	Serial	Calibration Date	Cal. Cycle (months)
1	Rohde & Schwarz	Antenna, Loop	HFH2-Z2	831247/012	10/07/2020	36
377	BONN Elektronik	Amplifier, Low Noise Pre	BLMA 0118-1A	025294B	16/07/2021	12
423	Bonn Elektronik	Amplifier, Low Noise Pre	BLMA 1840-1A	55929	16/07/2021	12
460	Deisel	Turntable	DT 4250 S	n/a	n/a	n/a
452	Schwarzbeck	Antenna, Trilog Broadband	VULB 9168	9168-240	02/09/2020	24
496	Rohde & Schwarz	Antenna, log. - periodical	HL050	100297	05/08/2020	36
607	Schwarzbeck	Antenna broadband horn antenna	BBHA 9170	9170-561	15/10/2019	36
587	Maturo	antenna mast, tilting	TAM 4.0-E	011/7180311	n/a	n/a
588	Maturo	Controller	NCD	029/7180311	n/a	n/a
591	Rohde & Schwarz	Receiver	ESU 40	100244/040	28/06/2021	12
669	Rohde & Schwarz	EMI Test Receiver	ESW44	103087	03/02/2022	12
608	Rohde & Schwarz	Switch Matrix	OSP 120	101227	lab verification	n/a
628	Maturo	Antenna mast	CAM 4.0-P	224/19590716	n/a	n/a
629	Maturo	Kippeinrichtung	KE 2.5-R-M	MAT002	n/a	n/a
-/-	Testo	Thermo-Hygrometer	608-H1	01	lab verification	n/a
1603665	Siemens Matsushita Components	semi-anechoic chamber SR1/2	-/-	B83117-A1421-T161	n/a	n/a

Test site: SR 7/8

ID	Manufacturer	Type	Model	Serial	Calibration Date	Cal. Cycle (months)
23	Rohde & Schwarz	Artificial Mains Network	ESH3-Z5	831767/013	14/07/2021	12
349	Rohde & Schwarz	Receiver, EMI Test	ESIB7	836697/009	13/07/2021	12
-/-	Testo	Thermo-Hygrometer	608-H1	08	lab verification	n/a
327	SPS	AC/DC power distribution system	PAS 5000	A2464 00/1 0200	lab verification	n/a

8. Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	37	-	Initial Version
Test Report Version 1.1 supersede Version 1.0 with immediate effect Test Report No. UL-RPT-RP-13831825-416-FCC Version 1.1, Issue Date 08 APRIL 2022 replaces Test Report No. UL-RPT-RP-13831825-416-FCC Version 1.0, Issue Date 31 MARCH 2022, which is no longer valid.			
1.1	as below	as below	Current Version
	1	-	“Infarm Gateway WiFi” replaced with “Infarm Gateway”
	1	-	“2A2CI-INF001-WF” replaced with “Contains 2A2CI-INF001-WF” and “Contains 2A2CI-INF001-CL”
	7	3.1	“Infarm Gateway WiFi” replaced with “Infarm Gateway” “2A2CI-INF001-WF” replaced with “Contains 2A2CI-INF001-WF” and “Contains 2A2CI-INF001-CL”
	7	3.2	Description of EUT updated
	8	3.4	Max power detail deleted

--END of Test Report--