

FCC 47 CFR MPE REPORT

Guangdong Lizi Technology Co., Ltd

Robot Vacuum Cleaner S9-Automatic Dirt Disposal

Model Number: V-RVCLMD28A

Additional Model: V-RVCLMD28B, V-RVCLMD28C, V-RVCLMD28D,

V-RVCLMD28E, V-RVCLMD28F

FCC ID: 2A2DH-RVCLMD28

Prepared for:	Guangdong Lizi Technology Co., Ltd
	Room 1-6, North of 1st Floor, Block A, Shengda Industrial Park, North No. 2,
	Xinxi Four Road, Xiashi Village, Lunjiao Town, Shunde District, Foshan,
	Guangdong, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2107042
Date of Test:	Jun. 15~Jul. 07, 2021
Date of Report:	Jul. 09, 2021

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times $ E ^2$, $ H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times $ E ^2$, $ H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	18.49	70.63	18 ± 2	4.3	2.69
	2437	16.42	43.85	16 ± 2	4.3	2.69
	2462	16.60	45.71	16 ± 2	4.3	2.69
IEEE 802.11g	2412	15.59	36.22	15 ± 2	4.3	2.69
	2437	15.53	35.73	15 ± 2	4.3	2.69
	2462	15.54	35.81	15 ± 2	4.3	2.69
IEEE 802.11n HT20	2412	15.73	37.41	15 ± 2	4.3	2.69
	2437	15.48	35.32	15 ± 2	4.3	2.69
	2462	15.43	34.91	15 ± 2	4.3	2.69
IEEE 802.11n HT40	2422	15.76	37.67	15 ± 2	4.3	2.69
	2437	15.64	36.64	15 ± 2	4.3	2.69
	2452	15.64	36.64	15 ± 2	4.3	2.69

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	20	4.3	2.69	0.05355	1	Complies
IEEE 802.11g	17	4.3	2.69	0.02684	1	Complies
IEEE 802.11n HT20	17	4.3	2.69	0.02684	1	Complies
IEEE 802.11n HT40	17	4.3	2.69	0.02684	1	Complies

End of Test Report