

FCC 47 CFR MPE REPORT

Guangdong Lizi Technology Co., Ltd

Robot Vacuum Cleaner

Model Number: V-RVCLM21A

Additional Model: V-RVCLM21B, V-RVCLM21C, V-RVCLM24A,
V-RVCLM24B, V-RVCLM24C

FCC ID: 2A2DH-V-RVCLM24

Prepared for:	Guangdong Lizi Technology Co., Ltd
	North No. 2, Xinxi Four Road, Xiashi Village, Lunjiao Town,
	Shunde District, Foshan, Guangdong, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2109320
Date of Test:	Aug. 03~Sep. 24, 2021
Date of Report:	Sep. 27, 2021

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11 b	2412	17.32	53.9511	17±1	1	1.259
	2442	16.86	48.5289	17±1	1	1.259
	2462	16.92	49.2040	17±1	1	1.259
IEEE 802.11 g	2412	21.66	146.5548	22±1	1	1.259
	2442	22.12	162.9296	22±1	1	1.259
	2462	22.94	196.7886	23±1	1	1.259
IEEE 802.11 n HT20	2412	21.62	145.2112	22±1	1	1.259
	2442	22.07	161.0646	22±1	1	1.259
	2462	22.93	196.3360	23±1	1	1.259
IEEE 802.11 n HT40	2422	21.00	125.8925	21±1	1	1.259
	2437	21.79	151.0080	22±1	1	1.259
	2452	22.21	166.3413	22±1	1	1.259

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11 b	18	1	1.259	0.0158	1	Complies
IEEE 802.11 g	24	1	1.259	0.0629	1	Complies
IEEE 802.11 n HT20	24	1	1.259	0.0629	1	Complies
IEEE 802.11 n HT40	23	1	1.259	0.0500	1	Complies

End of Test Report