



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

TEST REPORT

Report No.: CQASZ20230400482E-01

Applicant: Shenzhen Piocreat 3d Technology Co., Ltd.

Address of Applicant: Room 1308, Building No. 3, Jincheng Industrial Area, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China, 518109

Equipment Under Test (EUT):

Product: 3D Printer

Model No.: D158, D160

Test Model No.: D158

Brand Name: N/A

FCC ID: 2A2DOD158D160

Standards: 47 CFR Part 15, Subpart C

Date of Receipt: 2023-04-06

Date of Test: 2023-04-06 to 2023-04-23

Date of Issue: 2023-05-05

Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20230400482E-01	Rev.01	Initial report	2023-05-05

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	PASS
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10-2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10-2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2013	PASS
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10-2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
4.4 TEST ENVIRONMENT AND MODE	8
4.5 DESCRIPTION OF SUPPORT UNITS	9
4.6 TEST LOCATION	9
4.7 TEST FACILITY	9
4.8 STATEMENT OF THE MEASUREMENT UNCERTAINTY	10
4.9 DEVIATION FROM STANDARDS	10
4.10 ABNORMALITIES FROM STANDARD CONDITIONS	10
4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
4.12 EQUIPMENT LIST	11
5 TEST RESULTS AND MEASUREMENT DATA	12
5.1 ANTENNA REQUIREMENT	12
5.2 CONDUCTED EMISSIONS	13
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	19
Test Result	20
Note: Duty cycle correction factor details please see section 4.4.	错误! 未定义书签。
When Duty cycle >98%, D.C.F is not required.	20
Test Graphs	21
5.4 6dB OCCUPIED BANDWIDTH	26
Test Result	27
Test Graphs	28
5.5 POWER SPECTRAL DENSITY	33
Test Result	34
Test Graphs	35
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	40
Test Result	41
5.6.1 Test Graphs	42
5.7 RF CONDUCTED SPURIOUS EMISSIONS	45
Test Result	46
Test Graphs	47
5.8 RADIATED SPURIOUS EMISSIONS	61
5.8.1 Radiated emission below 1GHz	64
5.8.2 Transmitter emission above 1GHz	68
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	74
6 PHOTOGRAPHS - EUT TEST SETUP	79
6.1 RADIATED SPURIOUS EMISSION	79
6.2 CONDUCTED EMISSION	82
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	83

4 General Information

4.1 Client Information

Applicant:	Shenzhen Piocreat 3d Technology Co., Ltd.
Address of Applicant:	Room 1308, Building No. 3, Jincheng Industrial Area, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China, 518109
Manufacturer:	Shenzhen Piocreat 3d Technology Co., Ltd.
Address of Manufacturer:	Room 1308, Building No. 3, Jincheng Industrial Area, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China, 518109
Factory:	Shenzhen Piocreat 3d Technology Co., Ltd.
Address of Factory:	Room 1308, Building No. 3, Jincheng Industrial Area, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China, 518109

4.2 General Description of EUT

Product Name:	3D Printer
Model No.:	D158, D160
Test Model No.:	D158
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Power Supply:	Model No.:K65S240250E1 Input:100-240V~50/60Hz 1.8A Output:24V 2.5A 60W
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☒ Mobile ☐ Portable

Test Software of EUT:	adb
Antenna Type:	FPC antenna
Antenna Gain:	2.24dBi

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.
Run Software:	

```

管理员: C:\WINDOWS\system32\cmd.exe

adb get-state           - prints: offline | bootloader | device
adb get-serialno        - prints: <serial-number>
adb status-window       - continuously print device status for a specified device
adb remount             - remounts the /system partition on the device read-write
adb reboot [bootloader|recovery] - reboots the device, optionally into the bootloader or recovery program
adb reboot-bootloader   - reboots the device into the bootloader
adb root                - restarts the adbd daemon with root permissions
adb usb                 - restarts the adbd daemon listening on USB
adb tcpip <port>        - restarts the adbd daemon listening on TCP on the specified port
networking:
adb ppp <tty> [parameters] - Run PPP over USB.
Note: you should not automatically start a PPP connection.
<tty> refers to the tty for PPP stream. Eg. dev:/dev/omap_csmi_tty1
[parameters] - Eg. defaultroute debug dump local notty usepeerdns

adb sync notes: adb sync [ <directory> ]
<localdir> can be interpreted in several ways:

- If <directory> is not specified, both /system and /data partitions will be updated.

- If it is "system" or "data", only the corresponding partition
  is updated.

environmental variables:
ADB_TRACE               - Print debug information. A comma separated list of the following values
                          1 or all, adb, sockets, packets, rx, usb, sync, sysdeps, transport, jdwp
ANDROID_SERIAL          - The serial number to connect to. -s takes priority over this if given.
ANDROID_LOG_TAGS        - When used with the logcat option, only these debug tags are printed.

C:\Users\REF>AS
  
```

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 4742.01)

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• FCC Registration No.: 522263

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.9 Deviation from Standards

None.

4.10 Abnormalities from Standard Conditions

None.

4.11 Other Information Requested by the Customer

None.

4.12 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2022/09/09	2023/09/08
Spectrum analyzer	R&S	FSU26	CQA-038	2022/09/09	2023/09/08
Spectrum analyzer	R&S	FSU40	CQA-075	2022/09/09	2023/09/08
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2022/09/09	2023/09/08
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2022/09/09	2023/09/08
Preamplifier	EMCI	EMC184055SE	CQA-089	2022/09/09	2023/09/08
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/09/16	2024/09/15
Bilog Antenna	R&S	HL562	CQA-011	2021/09/16	2024/09/15
Horn Antenna	R&S	HF906	CQA-012	2021/09/16	2024/09/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/09/16	2024/09/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2022/09/09	2023/09/08
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2022/09/09	2023/09/08
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2022/09/09	2023/09/08
Antenna Connector	CQA	RFC-01	CQA-080	2022/09/09	2023/09/08
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2022/09/09	2023/09/08
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2022/09/09	2023/09/08
Power meter	R&S	NRVD	CQA-029	2022/09/09	2023/09/08
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2022/09/09	2023/09/08
EMI Test Receiver	R&S	ESR7	CQA-005	2022/09/09	2023/09/08
LISN	R&S	ENV216	CQA-003	2022/09/09	2023/09/08
Coaxial cable	CQA	N/A	CQA-C009	2022/09/09	2023/09/08
DC power	KEYSIGHT	E3631A	CQA-028	2022/09/09	2023/09/08

Test software:


	Manufacturer	Software brand
Radiated Emissions test software	Tonscend	JS1120-3
Conducted Emissions test software	Audix	e3
RF Conducted test software	Audix	e3

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is:Removable . This is either permanently attachment or a unique coupling that satisfies the requirement.	

5.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Setup:			

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

1#

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.170	26.28	9.66	35.94	54.96	-19.02	Average	Line
2	0.170	39.86	9.66	49.52	64.96	-15.44	QP	Line
3	0.195	26.42	9.62	36.04	53.82	-17.78	Average	Line
4	0.195	35.17	9.62	44.79	63.82	-19.03	QP	Line
5	0.405	26.73	9.61	36.34	47.75	-11.41	Average	Line
6	0.405	31.09	9.61	40.70	57.75	-17.05	QP	Line
7 PP	0.510	28.48	9.71	38.19	46.00	-7.81	Average	Line
8 QP	0.510	36.91	9.71	46.62	56.00	-9.38	QP	Line
9	0.790	24.06	9.84	33.90	46.00	-12.10	Average	Line
10	0.790	32.59	9.84	42.43	56.00	-13.57	QP	Line
11	1.320	24.62	10.48	35.10	46.00	-10.90	Average	Line
12	1.320	34.73	10.48	45.21	56.00	-10.79	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




	Freq	Read		Limit	Over		
	MHz	Level	Factor	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.155	25.14	9.69	34.83	55.73	-20.90	Average
2	0.155	39.86	9.69	49.55	65.73	-16.18	QP
3	0.225	25.94	9.57	35.51	52.63	-17.12	Average
4	0.225	42.35	9.57	51.92	62.63	-10.71	QP
5 PP	0.540	28.64	9.74	38.38	46.00	-7.62	Average
6 QP	0.540	36.43	9.74	46.17	56.00	-9.83	QP
7	1.140	22.44	9.71	32.15	46.00	-13.85	Average
8	1.140	33.09	9.71	42.80	56.00	-13.20	QP
9	2.275	21.56	9.75	31.31	46.00	-14.69	Average
10	2.275	27.32	9.75	37.07	56.00	-18.93	QP
11	2.970	16.81	9.77	26.58	46.00	-19.42	Average
12	2.970	31.06	9.77	40.83	56.00	-15.17	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

2#

Live Line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.170	24.65	9.66	34.31	54.96	-20.65	Average	Line
2	0.170	35.52	9.66	45.18	64.96	-19.78	QP	Line
3	0.195	24.18	9.62	33.80	53.82	-20.02	Average	Line
4	0.195	33.43	9.62	43.05	63.82	-20.77	QP	Line
5	0.405	19.83	9.61	29.44	47.75	-18.31	Average	Line
6	0.405	30.86	9.61	40.47	57.75	-17.28	QP	Line
7	0.530	25.29	9.73	35.02	46.00	-10.98	Average	Line
8 PP	0.530	38.16	9.73	47.89	56.00	-8.11	QP	Line
9 AV	0.790	25.51	9.84	35.35	46.00	-10.65	Average	Line
10	0.790	32.40	9.84	42.24	56.00	-13.76	QP	Line
11	20.125	25.31	9.85	35.16	50.00	-14.84	Average	Line
12	20.125	36.89	9.85	46.74	60.00	-13.26	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:





		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.225	24.75	9.57	34.32	52.63	-18.31	Average	Neutral
2	0.225	33.84	9.57	43.41	62.63	-19.22	QP	Neutral
3 PP	0.495	27.22	9.70	36.92	46.08	-9.16	Average	Neutral
4 QP	0.495	35.87	9.70	45.57	56.08	-10.51	QP	Neutral
5	0.695	23.34	9.90	33.24	46.00	-12.76	Average	Neutral
6	0.695	31.13	9.90	41.03	56.00	-14.97	QP	Neutral
7	2.970	18.67	9.77	28.44	46.00	-17.56	Average	Neutral
8	2.970	28.87	9.77	38.64	56.00	-17.36	QP	Neutral
9	20.430	28.29	9.86	38.15	50.00	-11.85	Average	Neutral
10	20.430	34.94	9.86	44.80	60.00	-15.20	QP	Neutral
11	27.395	29.20	10.08	39.28	50.00	-10.72	Average	Neutral
12	27.395	37.17	10.08	47.25	60.00	-12.75	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	<i>Setup for Power meter measurement method</i>  <i>Setup for Spectrum analyser measurement method</i> 
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass


Test Result

Test Mode	Antenna	Frequency [MHz]	Measured Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	6.09	≤30	PASS
		2437	7.59	≤30	PASS
		2462	7.64	≤30	PASS
11G	Ant1	2412	1.56	≤30	PASS
		2437	3.67	≤30	PASS
		2462	3.64	≤30	PASS
11N20SISO	Ant1	2412	1.51	≤30	PASS
		2437	3.11	≤30	PASS
		2462	3.65	≤30	PASS


Note:

When Duty cycle >98%, D.C.F is not required.

Test Graphs




11B_Ant1_2462




Date: 14 APR 2023 03:43:08


11G_Ant1_2412



Date: 14 APR 2023 03:45:45




11N20SISO_Ant1_2412




Date: 14 APR 2023 03:55:35


11N20SISO_Ant1_2437



Date: 14 APR 2023 03:57:26




5.4 6dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass


Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.08	0.5	PASS
		2437	9.28	0.5	PASS
		2462	9.68	0.5	PASS
11G	Ant1	2412	12.56	0.5	PASS
		2437	13.80	0.5	PASS
		2462	13.80	0.5	PASS
11N20SISO	Ant1	2412	12.60	0.5	PASS
		2437	11.32	0.5	PASS
		2462	12.56	0.5	PASS

Test Graphs




11B Ant1_2462




Date: 14 APR 2023 03:42:55

11G Ant1_2412




Date: 14 APR 2023 03:45:31

11G_Ant1_2437




Date: 14 APR 2023 03:49:40

11G_Ant1_2462




Date: 14 APR 2023 03:53:25

11N20SISO_Ant1_2412




Date: 14 APR 2023 03:55:22


11N20SISO_Ant1_2437



Date: 14 APR 2023 03:57:13



5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass


Test Result

TestMode	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-21.47	≤8.00	PASS
	2437	-20.02	≤8.00	PASS
	2462	-19.47	≤8.00	PASS
11G	2412	-24.03	≤8.00	PASS
	2437	-22.24	≤8.00	PASS
	2462	-21.41	≤8.00	PASS
11N20SISO	2412	-24.8	≤8.00	PASS
	2437	-22.99	≤8.00	PASS
	2462	-21	≤8.00	PASS


Note:

When Duty cycle >98%, D.C.F is not required.

Test Graphs




11B_Ant1_2462




Date: 14 APR 2023 03:43:16

11G_Ant1_2412




Date: 14 APR 2023 03:45:53

11G_Ant1_2437




Date: 14 APR 2023 03:50:02

11G_Ant1_2462




Date: 14 APR 2023 03:53:47

11N20SISO_Ant1_2412




Date: 14 APR 2023 03:55:44


11N20SISO_Ant1_2437



Date: 14 APR 2023 03:57:35




5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test Result

TestMode	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	-3.77	-45.28	≤ -33.77	PASS
	High	2462	-2.15	-49.38	≤ -32.15	PASS
11G	Low	2412	-8.26	-49.73	≤ -38.26	PASS
	High	2462	-5.55	-49.33	≤ -35.55	PASS
11N20SISO	Low	2412	-8.15	-50.26	≤ -38.15	PASS
	High	2462	-6.46	-48.42	≤ -36.46	PASS

5.6.1 Test Graphs



11G_Ant1_Low_2412



Date: 14 APR 2023 03:46:03

11G_Ant1_High_2462



Date: 14 APR 2023 03:53:57

11N20SISO_Ant1_Low_2412




Date: 14 APR 2023 03:55:54

11N20SISO_Ant1_High_2462



Date: 14 APR 2023 04:00:40


5.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


Test Result

TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	-3.83	-3.83	---	PASS
		30~1000	-3.83	-54.58	≤ -33.83	PASS
		1000~26500	-3.83	-55.26	≤ -33.83	PASS
	2437	Reference	-2.49	-2.49	---	PASS
		30~1000	-2.49	-54.12	≤ -32.49	PASS
		1000~26500	-2.49	-54.91	≤ -32.49	PASS
	2462	Reference	-2.50	-2.50	---	PASS
		30~1000	-2.50	-55.3	≤ -32.5	PASS
		1000~26500	-2.50	-54.83	≤ -32.5	PASS
11G	2412	Reference	-7.74	-7.74	---	PASS
		30~1000	-7.74	-55.93	≤ -37.74	PASS
		1000~26500	-7.74	-54.97	≤ -37.74	PASS
	2437	Reference	-5.82	-5.82	---	PASS
		30~1000	-5.82	-55.28	≤ -35.82	PASS
		1000~26500	-5.82	-55.52	≤ -35.82	PASS
	2462	Reference	-5.56	-5.56	---	PASS
		30~1000	-5.56	-54.99	≤ -35.56	PASS
		1000~26500	-5.56	-54.49	≤ -35.56	PASS
11N20SISO	2412	Reference	-7.75	-7.75	---	PASS
		30~1000	-7.75	-55.08	≤ -37.75	PASS
		1000~26500	-7.75	-55.35	≤ -37.75	PASS
	2437	Reference	-5.81	-5.81	---	PASS
		30~1000	-5.81	-54.11	≤ -35.81	PASS
		1000~26500	-5.81	-54.96	≤ -35.81	PASS
	2462	Reference	-5.62	-5.62	---	PASS
		30~1000	-5.62	-54.77	≤ -35.62	PASS
		1000~26500	-5.62	-54.99	≤ -35.62	PASS

Test Graphs




11B_Ant1_2412_1000~26500




Date: 14 APR 2023 03:38:27

11B_Ant1_2437_0~Reference




Date: 14 APR 2023 03:40:20

11B_Ant1_2437_30~1000




Date: 14 APR 2023 03:40:27

11B_Ant1_2437_1000~26500




Date: 14 APR 2023 03:40:49

11B_Ant1_2462_0~Reference




Date: 14 APR 2023 03:43:36

11B_Ant1_2462_30~1000




Date: 14 APR 2023 03:43:42

11B_Ant1_2462_1000~26500




Date: 14 APR 2023 03:44:04

11G_Ant1_2412_0~Reference




Date: 14 APR 2023 03:46:12

11G_Ant1_2412_30~1000




Date: 14 APR 2023 03:46:19

11G_Ant1_2412_1000~26500




Date: 14 APR 2023 03:46:41

11G_Ant1_2437_0~Reference




Date: 14 APR 2023 03:50:11

11G_Ant1_2437_30~1000




Date: 14 APR 2023 03:50:17

11G_Ant1_2437_1000~26500




Date: 14 APR 2023 03:50:40

11G_Ant1_2462_0~Reference




Date: 14 APR 2023 03:54:06

11G_Ant1_2462_30~1000




Date: 14 APR 2023 03:54:13

11G_Ant1_2462_1000~26500




Date: 14 APR 2023 03:54:35

11N20SISO_Ant1_2412_0~Reference




Date: 14 APR 2023 03:56:03

11N20SISO_Ant1_2412_30~1000




Date: 14 APR 2023 03:56:09

11N20SISO_Ant1_2412_1000~26500




Date: 14 APR 2023 03:56:32

11N20SISO_Ant1_2437_0~Reference




Date: 14 APR 2023 03:57:43

11N20SISO_Ant1_2437_30~1000




Date: 14 APR 2023 03:57:50

11N20SISO_Ant1_2437_1000~26500





Date: 14 APR 2023 03:58:12

11N20SISO_Ant1_2462_0~Reference



11N20SISO_Ant1_2462_30~1000





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.