




**11G\_Ant1\_2412\_30~1000**



Date: 17.APR.2025 18:55:50

**11G\_Ant1\_2412\_1000~26500**



Date: 17.APR.2025 18:56:01

**11G\_Ant1\_2437\_0~Reference**




**11G\_Ant1\_2462\_0~Reference**



Date: 17.APR.2025 18:58:52

**11G\_Ant1\_2462\_30~1000**



Date: 17.APR.2025 18:58:56

**11G\_Ant1\_2462\_1000~26500**




**11N20SISO\_Ant1\_2412\_1000~26500**



Date: 17.APR.2025 19:00:31

**11N20SISO\_Ant1\_2437\_0~Reference**



Date: 17.APR.2025 19:03:20

**11N20SISO\_Ant1\_2437\_30~1000**



**11N20SISO\_Ant1\_2462\_30~1000**


Date: 17.APR.2025 19:04:46

**11N20SISO\_Ant1\_2462\_1000~26500**





Date: 17.APR.2025 19:04:57

**Remark:**

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

## 5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					


**Test Setup:**

**Figure 1. Below 30MHz**

**Figure 2. 30MHz to 1GHz**

**Figure 3. Above 1 GHz**
**Test Procedure:**

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
Note: For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	<p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case .</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

### 5.9.1 Radiated emission below 1GHz

30MHz~1GHz
Vertical



Freq	Read			Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos	
	Freq	Level	Factor							
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	deg	
1	45.22	18.22	12.95	31.17	40.00	-8.83	Peak	VERTICAL	100	6
2	155.36	23.61	10.05	33.66	43.50	-9.84	Peak	VERTICAL	100	95
3	199.99	20.27	13.02	33.29	43.50	-10.21	Peak	VERTICAL	100	72
4	350.48	17.84	19.00	36.84	46.00	-9.16	Peak	VERTICAL	100	76
5	420.58	17.28	19.63	36.91	46.00	-9.09	Peak	VERTICAL	100	35
6 pp	900.15	10.69	29.29	39.98	46.00	-6.02	Peak	VERTICAL	100	254


#### Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

**Horizontal**


	Read			Limit	Over	Over	APOS	TPOS
	Freq	Level	Factor					
	MHz	dB <sub>uV</sub>	dB/m	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB		
1 pp	199.99	24.55	13.02	37.57	43.50	-5.93	Peak	HORIZONTAL
2	220.62	21.01	13.64	34.65	46.00	-11.35	Peak	HORIZONTAL
3	272.28	16.30	17.00	33.30	46.00	-12.70	Peak	HORIZONTAL
4	302.48	16.62	17.83	34.45	46.00	-11.55	Peak	HORIZONTAL
5	550.95	14.10	22.33	36.43	46.00	-9.57	Peak	HORIZONTAL
6	906.48	10.81	28.70	39.51	46.00	-6.49	Peak	HORIZONTAL

**Remark:**

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

**5.9.2 Transmitter emission above 1GHz**

Test mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits	Over (dB)	Detector Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V		
4824.000	53.23	-4.26	48.97	74	-25.03	peak	H	1.5	235
4824.000	36.89	-4.26	32.63	54	-21.37	AVG	H	1.5	73
7236.000	51.18	1.18	52.36	74	-21.64	peak	H	1.5	85
7236.000	38.25	1.18	39.43	54	-14.57	AVG	H	1.5	2
4824.000	56.19	-4.26	51.93	74	-22.07	peak	V	1.5	10
4824.000	39.75	-4.26	35.49	54	-18.51	AVG	V	1.5	288
7236.000	51.25	1.18	52.43	74	-21.57	peak	V	1.5	67
7236.000	35.65	1.18	36.83	54	-17.17	AVG	V	1.5	239

Test mode:		802.11b(1Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits	Over (dB)	Detector or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V		
4874.000	51.55	-4.12	47.43	74	-26.57	peak	H	1.5	30
4874.000	37.22	-4.12	33.10	54	-20.90	AVG	H	1.5	146
7311.000	49.49	1.46	50.95	74	-23.05	peak	H	1.5	163
7311.000	35.00	1.46	36.46	54	-17.54	AVG	H	1.5	246
4874.000	52.99	-4.12	48.87	74	-25.13	peak	V	1.5	111
4874.000	36.03	-4.12	31.91	54	-22.09	AVG	V	1.5	282
7311.000	49.80	1.46	51.26	74	-22.74	peak	V	1.5	273
7311.000	36.63	1.46	38.09	54	-15.91	AVG	V	1.5	83

Test mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
		(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.66	-4.03	48.63	74	-25.37	peak	H	1.5	96
4924.000	38.82	-4.03	34.79	54	-19.21	AVG	H	1.5	358
7386.000	49.86	1.66	51.52	74	-22.48	peak	H	1.5	254
7386.000	37.55	1.66	39.21	54	-14.79	AVG	H	1.5	128
4924.000	53.33	-4.03	49.30	74	-24.70	peak	V	1.5	118
4924.000	38.83	-4.03	34.80	54	-19.20	AVG	V	1.5	137
7386.000	49.76	1.66	51.42	74	-22.58	peak	V	1.5	210
7386.000	36.75	1.66	38.41	54	-15.59	AVG	V	1.5	345

**Remark:**

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Over (dB)	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V		
4824.000	53.05	-4.26	48.79	74	-25.21	peak	H	1.5	152
4824.000	36.77	-4.26	32.51	54	-21.49	AVG	H	1.5	196
7236.000	50.82	1.18	52.00	74	-22.00	peak	H	1.5	192
7236.000	38.33	1.18	39.51	54	-14.49	AVG	H	1.5	313
4824.000	56.10	-4.26	51.84	74	-22.16	peak	V	1.5	272
4824.000	39.72	-4.26	35.46	54	-18.54	AVG	V	1.5	306
7236.000	50.29	1.18	51.47	74	-22.53	peak	V	1.5	64
7236.000	36.34	1.18	37.52	54	-16.48	AVG	V	1.5	241

Test mode:		802.11g(6Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Over (dB)	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V		
4874.000	52.88	-4.12	48.76	74	-25.24	peak	H	1.5	200
4874.000	36.31	-4.12	32.19	54	-21.81	AVG	H	1.5	49
7311.000	48.53	1.46	49.99	74	-24.01	peak	H	1.5	114
7311.000	35.86	1.46	37.32	54	-16.68	AVG	H	1.5	185
4874.000	53.69	-4.12	49.57	74	-24.43	peak	V	1.5	292
4874.000	36.63	-4.12	32.51	54	-21.49	AVG	V	1.5	259
7311.000	48.50	1.46	49.96	74	-24.04	peak	V	1.5	48
7311.000	35.93	1.46	37.39	54	-16.61	AVG	V	1.5	277

Test mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
		(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.85	-4.03	48.82	74	-25.18	peak	H	1.5	262
4924.000	37.31	-4.03	33.28	54	-20.72	AVG	H	1.5	294
7386.000	50.31	1.66	51.97	74	-22.03	peak	H	1.5	156
7386.000	37.77	1.66	39.43	54	-14.57	AVG	H	1.5	290
4924.000	54.86	-4.03	50.83	74	-23.17	peak	V	1.5	32
4924.000	37.72	-4.03	33.69	54	-20.31	AVG	V	1.5	184
7386.000	49.99	1.66	51.65	74	-22.35	peak	V	1.5	225
7386.000	36.91	1.66	38.57	54	-15.43	AVG	V	1.5	178

**Remark:**

- 1) The 6Mbps of rate of 802.11g is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11n20(6.5Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
4824.000	53.62	-4.26	49.36	74	-24.64	peak	H	1.5	123
4824.000	37.94	-4.26	33.68	54	-20.32	AVG	H	1.5	31
7236.000	50.61	1.18	51.79	74	-22.21	peak	H	1.5	33
7236.000	37.28	1.18	38.46	54	-15.54	AVG	H	1.5	151
4824.000	55.19	-4.26	50.93	74	-23.07	peak	V	1.5	94
4824.000	39.75	-4.26	35.49	54	-18.51	AVG	V	1.5	41
7236.000	51.66	1.18	52.84	74	-21.16	peak	V	1.5	239
7236.000	36.97	1.18	38.15	54	-15.85	AVG	V	1.5	124

Test mode:		802.11n20(6.5Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
4874.000	53.07	-4.12	48.95	74	-25.05	peak	H	1.5	65
4874.000	35.98	-4.12	31.86	54	-22.14	AVG	H	1.5	11
7311.000	49.16	1.46	50.62	74	-23.38	peak	H	1.5	121
7311.000	36.70	1.46	38.16	54	-15.84	AVG	H	1.5	208
4874.000	52.77	-4.12	48.65	74	-25.35	peak	V	1.5	266
4874.000	36.55	-4.12	32.43	54	-21.57	AVG	V	1.5	138
7311.000	50.00	1.46	51.46	74	-22.54	peak	V	1.5	240
7311.000	36.16	1.46	37.62	54	-16.38	AVG	V	1.5	341

Test mode:		802.11n20(6.5Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
		(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
4924.000	51.83	-4.03	47.80	74	-26.20	peak	H	1.5	66
4924.000	37.63	-4.03	33.60	54	-20.40	AVG	H	1.5	51
7386.000	50.60	1.66	52.26	74	-21.74	peak	H	1.5	324
7386.000	37.30	1.66	38.96	54	-15.04	AVG	H	1.5	146
4924.000	55.17	-4.03	51.14	74	-22.86	peak	V	1.5	235
4924.000	38.77	-4.03	34.74	54	-19.26	AVG	V	1.5	21
7386.000	51.13	1.66	52.79	74	-21.21	peak	V	1.5	196
7386.000	36.38	1.66	38.04	54	-15.96	AVG	V	1.5	138

**Remark:**

- 1) The MCS0 of rate of 802.11n20 is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

## 5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	<p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz:</p> <p>Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and</p>
-----------------	--

	<p>then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <ul style="list-style-type: none"> <li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case .</li> <li>i. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates.</p> <p>Transmitting mode.</p>
Final Test Mode:	<p>Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case.</p> <p>Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20).</p> <p>Only the worst case is recorded in the report.</p>
Test Results:	Pass

**Test data:**

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
2390.000	58.52	-9.2	49.32	74	-24.68	peak	H	1.5	121
2390.000	44.07	-9.2	34.87	54	-19.13	AVG	H	1.5	105
2400.000	59.32	-9.39	49.93	74	-24.07	peak	H	1.5	243
2400.000	46.50	-9.39	37.11	54	-16.89	AVG	H	1.5	28
2390.000	59.23	-9.2	50.03	74	-23.97	peak	V	1.5	317
2390.000	44.28	-9.2	35.08	54	-18.92	AVG	V	1.5	27
2400.000	60.23	-9.39	50.84	74	-23.16	peak	V	1.5	161
2400.000	45.98	-9.39	36.59	54	-17.41	AVG	V	1.5	198

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
2483.500	58.42	-9.29	49.13	74	-24.87	peak	H	1.5	181
2483.500	44.09	-9.29	34.80	54	-19.20	AVG	H	1.5	274
2483.500	57.44	-9.29	48.15	74	-25.85	peak	V	1.5	1
2483.500	45.59	-9.29	36.30	54	-17.70	AVG	V	1.5	92

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Over (dB)	Detector Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V	(m)	(Degree)
2390.000	58.65	-9.2	49.45	74	-24.55	peak	H	1.5	24
2390.000	44.11	-9.2	34.91	54	-19.09	AVG	H	1.5	262
2400.000	59.58	-9.39	50.19	74	-23.81	peak	H	1.5	111
2400.000	46.85	-9.39	37.46	54	-16.54	AVG	H	1.5	21
2390.000	58.57	-9.2	49.37	74	-24.63	peak	V	1.5	15
2390.000	44.27	-9.2	35.07	54	-18.93	AVG	V	1.5	351
2400.000	60.18	-9.39	50.79	74	-23.21	peak	V	1.5	199
2400.000	46.23	-9.39	36.84	54	-17.16	AVG	V	1.5	238

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Over (dB)	Detector Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V	(m)	(Degree)
2483.500	58.09	-9.29	48.80	74	-25.20	peak	H	1.5	118
2483.500	43.96	-9.29	34.67	54	-19.33	AVG	H	1.5	328
2483.500	57.87	-9.29	48.58	74	-25.42	peak	V	1.5	131
2483.500	45.56	-9.29	36.27	54	-17.73	AVG	V	1.5	356

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Over	Detector Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
		(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
2390.000	58.79	-9.2	49.59	74	-24.41	peak	H	1.5	74
2390.000	44.24	-9.2	35.04	54	-18.96	AVG	H	1.5	296
2400.000	59.84	-9.39	50.45	74	-23.55	peak	H	1.5	207
2400.000	46.80	-9.39	37.41	54	-16.59	AVG	H	1.5	252
2390.000	58.54	-9.2	49.34	74	-24.66	peak	V	1.5	141
2390.000	44.82	-9.2	35.62	54	-18.38	AVG	V	1.5	294
2400.000	59.96	-9.39	50.57	74	-23.43	peak	V	1.5	232
2400.000	46.43	-9.39	37.04	54	-16.96	AVG	V	1.5	6

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Over	Detector Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
		(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V	(m)	(Degree)
2483.500	58.20	-9.29	48.91	74	-25.09	peak	H	1.5	9
2483.500	44.00	-9.29	34.71	54	-19.29	AVG	H	1.5	319
2483.500	58.30	-9.29	49.01	74	-24.99	peak	V	1.5	149
2483.500	45.92	-9.29	36.63	54	-17.37	AVG	V	1.5	38

**Note:**


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

## 6 Photographs - EUT Test Setup

### 6.1 Radiated Spurious Emission


9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



## 6.2 Conducted Emission



## 7 Photographs - EUT Constructional Details

HALOT-X1

