



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN2400-PCB136GX

Product Name: Antenna

Specification For Approval

Date: 2024.1.15

Version: 1.0

客户名称

Customer:

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN2400-PCB136GX

规格描述

Description :

2.4G PCB 天线 1.13mm 灰色线 L=70mm+IPEX

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制 作	路婷	TESTED BY 检 测	
CHECKED BY 审 核	胡超	CHECKED BY 审 核	
Q.C.DEPT. 品 管	方伟明	Q.C.DEPT. 品 管	
APPROVED BY 核 准	韦佳	APPROVEDBY 核 准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN2400-PCB136GX

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2024.1.15	初版	

Product Number: AN2400-PCB136GX

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500 MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	3.74dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	OD1.13mm ,gray
Connector Type 连接器规格	I-PEX
C. Environmental	
Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number:AN2400-PCB136GX

Product Name: Antenna



2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C;Duration: 5 seconds 温度 260±5° C;持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待测物规范;频率偏移≤5%	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面处理	Directive DUT specification 符合待测物规范	PASS
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 温度 35°C; 湿度≥95%;盐水浓度≥5%; 测试 24H	1. No Visual Damage 2. Frequency Tol.≤5% 无明显外观不良;频率偏移≤5%	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2400-PCB136GX

Product Name: Antenna

3. Antenna - S Parameter Test Data




Product Number:AN2400-PCB136GX


Product Name: Antenna

4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	3.12	3.31	3.40	3.47	3.65	3.74	3.50	3.48	3.36	3.28	3.15
Efficiency (%)	50.61	51.47	52.58	52.13	53.50	54.56	53.60	52.45	53.49	52.53	51.31



5. Mechanical Drawing See attached files



HF	☐
RoHS2.0	☒
REACH	☐
CONFIDENTIAL	

SIGN	DATE	DESCRIPTION	APPROVER
☒			
☒			
☒			

Note:
1.Mark * is important dimension;"Cpk "Identify for process control(CpK ≥ 1.33).
2.Tolerance:Unmarked tolerance refer to the standard tolerance please.

4	ANS08-45-576	Spring	CU		1
3	CR-113-ZP-A	I-PEX	Cu	Au Plated	1
2	CB-113GS	Coaxial Cable		Gray	1
1	AN2400-PCB3011	PCB	FR4	Black T=0.6mm	1
No.	Part Number	Name	Material	Finish	Q'ty

		Tengxiang Electronics Co., Ltd.		http://www.tenxiang.cn			
东莞腾祥电子有限公司				TEL:86-769-81873082			
				FAX:86-769-82663788			
TITLE: 2.4G /Antenna							
PART NO.: AN2400-PCB136GX			CUSTOMER P/N: /				
APP BY	CHK BY	RF BY	DES BY		Tolerance		
YCX	HC	WJ	SY		UNITS: mm	X.X ±0.5	
2023.01.15	2023.01.15	2023.01.15	2023.01.15		SCALE: 1/1	X.XX ±0.2	
				REVISION: A	X° ±1		

产品包装规范


PACKING CRITERION

Date: 2024.01.15

Page: 1 of 1


Part Number : AN2400-PCB136GX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。



8000pcs/Carton

3. SEALING。



APPROVED BY : YCX CHECKED BY : HC DESIGNED BY : SY Y