



TEST REPORT

Test Report No. : UL-RPT-RP13722490-216A

Customer : Laurastar SA
Model No. / HVIN : IGGI 600
PMN : IGGI
FCC ID : 2A2EQIGGI600
ISED Certification No. : IC: 27483-IGGI600
Technology : *Bluetooth – Low Energy*
Test Standard(s) : FCC Parts 15.207, 15.209(a) & 15.247
Innovation, Science and Economic Development Canada
RSS-247 Issue 2 February 2017
RSS-Gen Issue 5 February 2021
Test Laboratory : UL International (UK) Ltd, Basingstoke, Hampshire, RG24 8AH,
United Kingdom

1. This test report shall not be reproduced except in full, without the written approval of UL International (UK) Ltd.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 1.0.

Date of Issue: 23 September 2021

Checked by:

Ben Mercer
Lead Project Engineer, Radio Laboratory

Company Signatory:

Sarah Williams
RF Operations Leader, Radio Laboratory



5772

The *Bluetooth*® word mark and logos are owned by the *Bluetooth* SIG, Inc. and any use of such marks by UL International (UK) Ltd is under licence. Other trademarks and trade names are those of their respective owners.

UL International (UK) LTD

Unit 1-3 Horizon, Kingsland Business Park, Wade Road, Basingstoke, Hampshire, RG24 8AH, UK
Telephone: +44 (0)1256 312000
Facsimile: +44 (0)1256 312001

Customer Information

Company Name:	Laurastar SA
Address:	Route de Montreux 149 Case Postale 320 Châtel-St-Denis, 1618 Switzerland

Report Revision History

Version Number	Issue Date	Revision Details	Revised By
1.0	23/09/2021	Initial Version	Ben Mercer

Table of Contents

Customer Information.....	2
Report Revision History	2
Table of Contents.....	3
1 Attestation of Test Results.....	4
1.1 Description of EUT	4
1.2 General Information	4
1.3 Summary of Test Results	5
1.4 Deviations from the Test Specification	5
2 Summary of Testing.....	6
2.1 Facilities and Accreditation	6
2.2 Methods and Procedures	6
2.3 Calibration and Uncertainty	7
2.4 Test and Measurement Equipment	8
3 Equipment Under Test (EUT)	10
3.1 Identification of Equipment Under Test (EUT)	10
3.2 Modifications Incorporated in the EUT	10
3.3 Additional Information Related to Testing	11
3.4 Description of Available Antennas	11
3.5 Description of Test Setup	12
4 Antenna Port Test Results	16
4.1 Transmitter Duty Cycle	16
4.2 Transmitter 99% Occupied Bandwidth	17
4.3 Transmitter Minimum 6 dB Bandwidth	19
4.4 Transmitter Maximum Peak Output Power	21
5 Radiated Test Results.....	24
5.1 Transmitter Radiated Emissions <1 GHz	24
5.2 Transmitter Radiated Emissions >1 GHz	26
5.3 Transmitter Band Edge Radiated Emissions	29
6 AC Power Line Conducted Emissions Test Results.....	32
6.1 Transmitter AC Conducted Spurious Emissions	32

1 Attestation of Test Results

1.1 Description of EUT

The equipment under test was a fabric steamer incorporating a *Bluetooth* LE radio.

1.2 General Information

Specification Reference:	47CFR15.247
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) – Section 15.247
Specification Reference:	47CFR15.207 and 47CFR15.209
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) – Sections 15.207 and 15.209
Specification Reference:	RSS-Gen Issue 5 February 2021
Specification Title:	General Requirements for Compliance of Radio Apparatus
Specification Reference:	RSS-247 Issue 2 February 2017
Specification Title:	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
FCC Site Registration:	621311
ISEDC Site Registration:	20903
FCC Lab. Designation No.:	UK2011
ISEDC CABID:	UK0001
Location of Testing:	Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, G24 8AH, United Kingdom
Test Dates:	04 May 2021 to 18 May 2021

1.3 Summary of Test Results

FCC Reference (47CFR)	ISED Canada Reference	Measurement	Result
N/A	RSS-Gen 6.7	Transmitter 99% Occupied Bandwidth	✓
Part 15.247(a)(2)	RSS-Gen 6.7 / RSS-247 5.2(a)	Transmitter Minimum 6 dB Bandwidth	✓
Part 15.247(b)(3)	RSS-Gen 6.12 / RSS-247 5.4(d)	Transmitter Maximum Peak Output Power	✓
Part 15.247(e)	RSS-247 5.4(b)	Transmitter Power Spectral Density	Note 1
Part 15.247(d) & 15.209(a)	RSS-Gen 6.13 / RSS-247 5.5	Transmitter Band Edge Conducted Emissions	✓
Part 15.247(d) & 15.209(a)	RSS-Gen 6.13 / RSS-247 5.5	Transmitter Radiated Emissions	✓
Part 15.247(d) & 15.209(a)	RSS-Gen 6.13 / RSS-247 5.5	Transmitter Band Edge Radiated Emissions	✓
Part 15.207	RSS-Gen 8.8	Transmitter AC Conducted Emissions	✓

Key to Results

✓ = Complied ✘ = Did not comply

Note(s):

1. In accordance with ANSI C63.10 Section 11.10.1, PSD measurements are not required if the maximum conducted output power is less than the PSD limit of 8 dBm / 3 kHz. The PSD level is therefore deemed to be equal to the measured output power.

1.4 Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

2 Summary of Testing

2.1 Facilities and Accreditation

The test site and measurement facilities used to collect data are located at Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom. The following table identifies which facilities were utilised for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

Site 1	X
Site 2	
Site 17	

UL International (UK) Ltd is accredited by the United Kingdom Accreditation Service (UKAS). UKAS is one of the signatories to the International Laboratory Accreditation Co-operation (ILAC) Arrangement for the mutual recognition of test reports. The tests reported herein have been performed in accordance with its terms of accreditation.

2.2 Methods and Procedures

Reference:	ANSI C63.10-2013
Title:	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Reference:	KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Title:	Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules
Reference:	KDB 174176 D01 Line Conducted FAQ v01r01 June 3, 2015
Title:	AC Power-Line Conducted Emissions Frequently Asked Questions

2.3 Calibration and Uncertainty

Measuring Instrument Calibration

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

Measurement Uncertainty & Decision Rule

Overview

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

Decision Rule

The decision rule applied is based upon the accuracy method criteria. The measurement uncertainty is met and the result is considered in conformance with the requirement criteria if the observed value is within the prescribed limit.

Measurement Uncertainty

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
Duty Cycle	2.4 GHz to 2.4835 GHz	95%	±1.14 %
99% Occupied Bandwidth	2.4 GHz to 2.4835 GHz	95%	±3.92 %
Minimum 6 dB Bandwidth	2.4 GHz to 2.4835 GHz	95%	±4.59 %
Conducted Maximum Peak Output Power	2.4 GHz to 2.4835 GHz	95%	±1.13 dB
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±3.30 dB
Radiated Spurious Emissions	1 GHz to 25 GHz	95%	±2.94 dB
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±1.96 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

2.4 Test and Measurement Equipment

Test Equipment Used for Transmitter Conducted Tests

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2002	Thermohygrometer	Testo	608-H1	45041825	10 Dec 2021	12
A3118	Attenuator	AtlanTecRF	AN18-10	237378#2	Calibrated before use	-
M2033	Signal Analyser	Rohde & Schwarz	FSV13	101667	24 Jul 2021	12
G0642	Signal Generator	Rohde & Schwarz	SMBV100B	100890	25 Jul 2021	24

Test Equipment Used for Transmitter Radiated Emissions Tests

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2040	Thermohygrometer	Testo	608-H1	45124934	10 Dec 2021	12
K0001	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Oct 2021	12
M2044	Test Receiver	Rohde & Schwarz	ESU26	100122	03 Sep 2021	12
A3154	Pre-Amplifier	Com Power	PAM-118A	551126	25 Jul 2021	12
A3179	Pre-Amplifier	Hewlett Packard	8449B	3008A00934	29 Sep 2021	12
A3141	Pre-Amplifier	Hewlett Packard	BBV 9718 B	00021	29 Sep 2021	12
A2896	Pre-Amplifier	Schwarzbeck	BBV 9721	9721 - 023	16 Feb 2022	12
A3165	Antenna	ETS-Lindgren	6502	00224383	21 Sep 2021	12
A553	Antenna	Chase	CBL6111A	1593	21 Sep 2021	12
A3138	Antenna	Schwarzbeck	BBHA 9120 B	00702	06 Oct 2021	12
A3139	Antenna	Schwarzbeck	HWRD750	00027	06 Oct 2021	12
A2895	Antenna	Schwarzbeck	BBHA 9170	9170-728	16 Feb 2022	12
A2523	Attenuator	AtlanTecRF	AN18W5-10	832827#1	03 Feb 2022	12
A3085	Low Pass Filter	AtlanTecRF	AFL-02000	18051600014	03 Feb 2022	12
A3093	High Pass Filter	AtlanTecRF	AFH-03000	18051800077	03 Feb 2022	12
A3095	High Pass Filter	AtlanTecRF	AFH-07000	18051600012	03 Feb 2022	12

Test Equipment Used for Transmitter Band Edge Radiated Emissions Tests

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2040	Thermohygrometer	Testo	608-H1	45124934	10 Dec 2021	12
K0001	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Oct 2021	12
M2044	Test Receiver	Rohde & Schwarz	ESU26	100122	03 Sep 2021	12
A3179	Pre-Amplifier	Hewlett Packard	8449B	3008A00934	29 Sep 2021	12
A3138	Antenna	Schwarzbeck	BBHA 9120 B	00702	06 Oct 2021	12
A2523	Attenuator	AtlanTecRF	AN18W5-10	832827#1	03 Feb 2022	12

Test and Measurement Equipment (continued)**Test Equipment Used for Transmitter AC Conducted Spurious Emissions:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2037	Thermohygrometer	Testo	608-H1	45124925	09 Dec 2021	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	03 Aug 2021	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	21 Apr 2022	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	14 Dec 2021	12

Test Measurement Software/Firmware Used:

Name	Version	Release Date
Rohde & Schwarz EMC32	6.30.0	2018

3 Equipment Under Test (EUT)

3.1 Identification of Equipment Under Test (EUT)

Brand Name:	Laurastar
Model Name or Number / HVIN:	IGGI 600
PMN:	IGGI
Test Sample Serial Number:	201029/231428 (<i>Conducted sample #1</i>)
Hardware Version:	1132-32-MBO-10-0
Software Version:	1.4.0 – Test Mode
FCC ID:	2A2EQIGGI600
ISED Canada Certification Number:	IC: 27483-IGGI600

Brand Name:	Laurastar
Model Name or Number / HVIN:	IGGI 600
PMN:	IGGI
Test Sample Serial Number:	201029/234175 (<i>Radiated sample #1</i>)
Hardware Version:	1132-32-MBO-10-0
Firmware Version:	1.4.0 – Test Mode
FCC ID:	2A2EQIGGI600
ISED Canada Certification Number:	IC: 27483-IGGI600

3.2 Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.3 Additional Information Related to Testing

Technology Tested:	Bluetooth Low Energy (Digital Transmission System)		
Type of Unit:	Transceiver		
Channel Spacing:	2 MHz		
Modulation:	GFSK		
Data Rate: LE	1 Mbps		
Power Supply Requirement(s):	Nominal	120 VAC	
Maximum Conducted Output Power:	3.9 dBm		
Transmit Frequency Range:	2402 MHz to 2480 MHz		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	37	2402
	Middle	17	2440
	Top	39	2480

3.4 Description of Available Antennas

The radio utilizes an integrated antenna, with the following maximum gain:

Frequency Range (MHz)	Antenna Gain (dBi)
2400-2480	5.3

3.5 Description of Test Setup

Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	Test Laptop
Brand Name:	Lenovo
Model Name or Number:	ThinkPad L470
Serial Number:	PF10T3HL

Description:	Test Laptop
Brand Name:	Lenovo
Model Name or Number:	ThinkPad L480
Serial Number:	PF1EHZPL

Description:	USB 2.0 Isolator
Brand Name:	Not marked or stated
Model Name or Number:	Not marked or stated
Serial Number:	Not marked or stated

Description:	TTI-232R-3V3 USB cable
Brand Name:	Not marked or stated
Model Name or Number:	Not marked or stated
Serial Number:	Not marked or stated

Description:	Isolation Transformer
Brand Name:	Not marked or stated
Model Name or Number:	Not marked or stated
Serial Number:	17991/5

Operating Modes



The EUT was tested in the following operating mode(s):


- Transmitting at maximum power in *Bluetooth LE* mode with modulation, maximum possible data length available.

Configuration and Peripherals

The EUT was tested in the following configuration(s):

- The EUT was controlled with a test laptop and a third-party test software application using commands supplied by the customer. Channels, packet lengths and other settings were then set using this software application as required. The customer supplied a document containing the setup instructions 'NRF_BLE_Certif.pptx'.
- For conducted measurements, the EUT was powered from a 120 VAC 60 Hz mains supply via an isolation transformer.
- For radiated measurements, the EUT was powered from a 120 VAC 60 Hz single phase mains supply.
- Transmitter radiated spurious emissions tests were performed with the EUT in the orientation that produced the worst case with respect to emissions. There were no active ports to terminate.

Test Setup Diagrams**Conducted Tests:****Test Setup for Transmitter Conducted Tests****Test Setup for Transmitter AC Conducted Spurious Emissions**

Test Setup Diagrams (continued)**Radiated Tests:****Test Setup for Transmitter Radiated Emissions**

4 Antenna Port Test Results

4.1 Transmitter Duty Cycle

Test Summary:

Test Engineers:	Raghavendra Katti & Chanthu Thevarajah	Test Date:	18 May 2021
Test Sample Serial Number:	201029/231428		

FCC Reference:	Part 15.35(c)
ISED Canada Reference:	RSS-Gen 8.2
Test Method Used:	FCC KDB 558074 Section 6 referencing ANSI C63.10 Section 11.6

Environmental Conditions:

Temperature (°C):	25
Relative Humidity (%):	38

Note(s):


1. In order to assist with the determination of the average level of spurious emissions field strength, measurements were made of duty cycle to determine the transmission duration and the silent period time of the transmitter. The transmitter duty cycle was measured using a spectrum/signal analyser in the time domain and calculated by using the following calculation:

$10 \log (1 / (\text{On Time} / [\text{Period or } 100 \text{ ms whichever is the lesser}]))$.

duty cycle: $10 \log (1 / (391.300 \mu\text{s} / 626.090 \mu\text{s})) = 2.0 \text{ dB}$

Results:

Pulse Duration (μs)	Period (μs)	Duty Cycle (dB)
391.300	626.090	2.0



4.2 Transmitter 99% Occupied Bandwidth

Test Summary:

Test Engineers:	Raghavendra Katti & Chanthu Thevarajah	Test Date:	18 May 2021
Test Sample Serial Number:	201029/231428		

FCC Reference:	N/A
ISED Canada Reference:	RSS-Gen 6.7
Test Method Used:	RSS-Gen 6.7 and Notes below

Environmental Conditions:




Temperature (°C):	25
Relative Humidity (%):	38

Note(s):

1. The 99% emission bandwidth was measured using the signal analyser occupied bandwidth function. The resolution bandwidth was set in the range of 1% to 5% of the occupied bandwidth and the video bandwidth set to 3 times the resolution bandwidth. The span was set to capture all products of the modulation process including emission skirts.
2. The signal analyser resolution bandwidth was set to 30 kHz and video bandwidth 100 kHz. A peak detector was used, sweep time was set to auto and the trace mode was Max Hold. The span was set to 5 MHz. The signal analyser function set the measurements to be made at 99% of the emission bandwidth. The results are given in the tables below.
3. The signal analyser was connected to the RF port on the EUT using suitable attenuation and coax cable.

Transmitter 99% Occupied Bandwidth (continued)**Results:**

Channel	99% Occupied Bandwidth (kHz)
Bottom	1056.440
Middle	1056.440
Top	1056.440

**Bottom Channel****Middle Channel****Top Channel**

4.3 Transmitter Minimum 6 dB Bandwidth

Test Summary:

Test Engineers:	Raghavendra Katti & Chanthu Thevarajah	Test Date:	18 May 2021
Test Sample Serial Number:	201029/231428		

FCC Reference:	Part 15.247(a)(2)
ISED Canada Reference:	RSS-Gen 6.7 / RSS-247 5.2(a)
Test Method Used:	FCC KDB 558074 Section 8.2 referencing ANSI C63.10 Section 11.8.1

Environmental Conditions:


Temperature (°C):	25
Relative Humidity (%):	38

Note(s):

1. 6 dB DTS bandwidth tests were performed using a signal analyser in accordance with ANSI C63.10 Section 11.8.1 Option 1 measurement procedure. The signal analyser resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and the trace mode was Max Hold. The DTS bandwidth was measured at 6 dB down from the peak of the signal.
2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and coax cable.

Transmitter Minimum 6 dB Bandwidth (continued)**Results:**

Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)	Result
Bottom	694.600	≥500	194.600	Complied
Middle	687.400	≥500	187.400	Complied
Top	687.400	≥500	187.400	Complied

**Bottom Channel****Middle Channel****Top Channel**

4.4 Transmitter Maximum Peak Output Power

Test Summary:

Test Engineers:	Raghavendra Katti & Chanthu Thevarajah	Test Date:	18 May 2021
Test Sample Serial Number:	201029/231428		

FCC Reference:	Part 15.247(b)(3)
ISED Canada Reference:	RSS-Gen 6.12 / RSS-247 5.4(d)
Test Method Used:	FCC KDB 558074 Section 8.3.1.1 referencing ANSI C63.10 Section 11.9.1.1 and Notes below

Environmental Conditions:

Temperature (°C):	25
Relative Humidity (%):	38




Note(s):

1. Conducted power tests were performed using a signal analyser in accordance with ANSI C63.10 Section 11.9.1.1 with the $RBW \geq DTS$ bandwidth procedure.
2. The signal analyser resolution bandwidth was set to 1 MHz and video bandwidth of 3 MHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. The span was set to 3 MHz. A marker was placed at the peak of the signal and the results recorded in the tables below.
3. The signal analyser was connected to the RF port on the EUT using suitable attenuation and coax cable. An RF level offset was entered on the signal analyser to compensate for the loss of the attenuator and coax cable.
4. The conducted power was added to the declared antenna gain to obtain the EIRP.

Transmitter Maximum Peak Output Power (continued)**Results:**

Channel	Conducted Peak Power (dBm)	Conducted Peak Power Limit (dBm)	Margin (dB)	Result
Bottom	3.9	30.0	26.1	Complied
Middle	3.8	30.0	26.2	Complied
Top	3.7	30.0	26.3	Complied

Channel	Conducted Peak Power (dBm)	Declared Antenna Gain (dBi)	EIRP (dBm)	De Facto EIRP Limit (dBm)	Margin (dB)	Result
Bottom	3.9	5.3	9.2	36.0	26.8	Complied
Middle	3.8	5.3	9.1	36.0	26.9	Complied
Top	3.7	5.3	9.0	36.0	27.0	Complied

Transmitter Maximum Peak Output Power (continued)**Results:****Bottom Channel****Top Channel****Middle Channel**

5 Radiated Test Results

5.1 Transmitter Radiated Emissions <1 GHz

Test Summary:

Test Engineer:	Jose Bayona	Test Dates:	05 May 2021 & 06 May 2021
Test Sample Serial Number:	201029/234175		

FCC Reference:	Parts 15.247(d) & 15.209(a)
ISED Canada Reference:	RSS-Gen 6.13 & 8.9 / RSS-247 5.5
Test Method Used:	ANSI C63.10 Sections 5.2, 5.3, 6.3, 6.4 and 6.5
Frequency Range	9 kHz to 1000 MHz

Environmental Conditions:

Temperature (°C):	22 to 23
Relative Humidity (%):	32 to 33




Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. All emissions shown on the pre-scans were investigated and found to be ambient, or > 20 dB below the appropriate limit or below the noise floor of the measurement system. Therefore the highest peak noise floor reading of the measuring receiver was recorded in the table below.
3. Measurements below 30 MHz were performed in a semi-anechoic chamber (Asset Number K0001) at 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. The limit was extrapolated to 3 metres in accordance with ANSI C63.10 Section 6.4.4.2. Correlation data between the semi-anechoic chamber and an open-field test site is available upon request.
4. Measurements between 30 MHz and 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres..
5. Pre-scans were performed and markers placed on the highest measured levels. The test receiver was configured as follows: For 9 kHz to 150 kHz, the resolution bandwidth was set to 300 Hz and video bandwidth 1 kHz. A peak detector was used and trace mode was Max Hold. For 150 kHz to 30 MHz, the resolution bandwidth was set to 10 kHz and video bandwidth 30 kHz, trace mode was Max Hold. For 30 MHz to 1 GHz, the resolution bandwidth was set to 120 kHz and video bandwidth 500 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold.

Transmitter Radiated Emissions (continued)

Results: Peak / Middle Channel

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
1000.000	Horizontal	34.5	54.0	19.5	Complied



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

5.2 Transmitter Radiated Emissions >1 GHz

Test Summary:

Test Engineer:	Jose Bayona	Test Dates:	04 May 2021 & 05 May 2021
Test Sample Serial Number:	201029/234175		

FCC Reference:	Parts 15.247(d) & 15.209(a)
ISED Canada Reference:	RSS-Gen 6.13 & 8.9 / RSS-247 5.5
Test Method Used:	FCC KDB 558074 Sections 8.1 c)3), 8.5 & 8.6 referencing ANSI C63.10 Sections 6.3, 6.6, 11.11 & 11.12
Frequency Range	1 GHz to 25 GHz

Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	32 to 34

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. All other emissions shown on the pre-scans were investigated and found to be ambient, or > 20 dB below the appropriate limit or below the noise floor of the measurement system.
3. The emission shown on the 1 GHz to 3 GHz plot is the EUT fundamental.
4. *In accordance with ANSI C63.10 Section 6.6.4.3, Note 1, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.
5. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT.
6. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 1.5 m above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
7. Pre-scans were performed and a marker placed on the highest measured level of the appropriate plot. The test receiver resolution bandwidth was set to 1 MHz and video bandwidth 3 MHz. The sweep time was set to auto. Peak and average measurements were performed with their own appropriate detectors during the pre-scan measurements.
8. The reference level for the emission in the non-restricted band was established by following ANSI C63.10 Section 11.11.2 procedure.

Transmitter Radiated Emissions (continued)**Results: Bottom Channel / Peak**

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4657.244	Horizontal	51.3	54.0*	2.7	Complied
4804.625	Horizontal	53.8	54.0*	0.2	Complied
4836.788	Horizontal	54.6	74.0	19.4	Complied

Results: Bottom Channel / Average

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4836.667	Horizontal	40.8	54.0	13.2	Complied

Results: Middle Channel / Peak

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4657.244	Horizontal	54.5	74.0	19.5	Complied
4880.417	Horizontal	54.5	74.0	19.5	Complied
4934.615	Horizontal	52.6	54.0*	1.4	Complied
7320.713	Vertical	55.9	74.0	18.1	Complied

Results: Middle Channel / Average

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4657.244	Horizontal	43.9	54.0	10.1	Complied
4880.016	Horizontal	51.6	54.0	2.4	Complied
7320.086	Vertical	50.8	54.0	3.2	Complied





Results: Top Channel / Peak

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
4657.096	Horizontal	51.3	54.0*	2.7	Complied
4960.569	Horizontal	53.8	54.0*	0.2	Complied
4986.167	Horizontal	51.4	54.0*	2.6	Complied
7440.585	Vertical	57.2	74.0	16.8	Complied

Results: Top Channel / Average

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
7439.912	Vertical	53.3	54.0	0.7	Complied

Transmitter Radiated Emissions (continued)



5.3 Transmitter Band Edge Radiated Emissions

Test Summary:

Test Engineer:	Jose Bayona	Test Date:	05 May 2021
Test Sample Serial Number:	201029/234175		

FCC Reference:	Parts 15.247(d) & 15.209(a)
ISED Canada Reference:	RSS-Gen 6.13 / RSS-247 5.5
Test Method Used:	KDB 558074 Section 8.7 referencing ANSI C63.10 Sections 11.11, 11.12 & 11.13

Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	32

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. As the lower band edge is adjacent to a non-restricted band, only peak measurements are required. In accordance with ANSI C63.10 Section 11.11.1, the test method in Section 11.11.3 was followed: the test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. The test receiver was left to sweep for a sufficient length of time in order to maximise the carrier level and out-of-band emissions. A marker and corresponding reference level line were placed on the peak of the carrier. As the maximum peak conducted output power was measured using an peak detector in accordance with ANSI C63.10 Section 11.9.1.1 an out-of-band limit line was placed 20 dB (ANSI C63.10 Section 11.11.1(a)) below the peak level. A marker was placed on the band edge spot frequencies. Marker frequency and levels were recorded.
3. As the upper band edge is adjacent to a restricted band, both peak and average measurements were recorded by placing a marker at the edge of the band. For peak measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. For average measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. An RMS detector was used, sweep time was set to auto and trace mode was Max Hold. A marker was placed on the band edge spot frequencies and a second marker placed on the highest emission level in the adjacent restricted band of operation (where a higher level emission was present). Marker frequencies and levels were recorded.
4. There is a restricted band 10 MHz below the lower band edge. The test receiver was set up as follows: the RBW set to 1 MHz, the VBW set to 3 MHz, with the sweep time set to auto couple. Peak and average measurements were performed with peak and RMS detectors respectively. Markers were placed on the highest point on each trace.
5. * -20 dBc limit.

Transmitter Band Edge Radiated Emissions (continued)**Results: Peak**

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2400.000	Horizontal	44.0	69.6*	25.6	Complied
2483.500	Horizontal	58.0	74.0	16.0	Complied

Results: Average


Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2483.500	Horizontal	49.8	54.0	4.2	Complied

Results: 2310 MHz to 2390 MHz Restricted Band / Peak

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2353.462	Horizontal	52.9	74.0	21.1	Complied

Results: 2310 MHz to 2390 MHz Restricted Band / Average

Frequency (MHz)	Antenna Polarity	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Result
2351.410	Horizontal	47.0	54.0	7.0	Complied

Transmitter Band Edge Radiated Emissions (continued)**Results:**

6 AC Power Line Conducted Emissions Test Results

6.1 Transmitter AC Conducted Spurious Emissions

Test Summary:

Test Engineer:	Alison Johnston	Test Date:	07 May 2021
Test Sample Serial Number:	201029/234175		

FCC Reference:	Part 15.207
ISED Canada Reference:	RSS-Gen 8.8
Test Method Used:	ANSI C63.10 Section 6.2 / FCC KDB 174176 and notes below

Environmental Conditions:

Temperature (°C):	23
Relative Humidity (%):	30

Note(s):

1. The EUT was connected AC Power. The AC was connected to 120 VAC 60 Hz single phase supply via a LISN.
2. The EUT was plugged into a USB cable which is connected to a laptop computer. The computer hosted the terminal interface to control the EUT.
3. A pulse limiter was fitted between the LISN and the test receiver.
4. Pre-scans were performed and markers placed on the highest live and neutral measured levels. Final measurements were performed on the marker frequencies and the results entered into the tables below.

Transmitter AC Conducted Spurious Emissions (continued)**Results: Live / Quasi Peak / 120 VAC 60 Hz**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.564000	Live	39.7	56.0	16.3	Complied
0.640500	Live	38.4	56.0	17.6	Complied
2.184000	Live	36.7	56.0	19.3	Complied
3.691500	Live	38.6	56.0	17.4	Complied
7.237500	Live	46.2	60.0	13.8	Complied
8.142000	Live	48.1	60.0	11.9	Complied

Results: Live / Average / 120 VAC 60 Hz


Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.411000	Live	34.2	47.6	13.4	Complied
0.487500	Live	34.7	46.2	11.5	Complied
0.640500	Live	33.3	46.0	12.7	Complied
4.744500	Live	34.0	46.0	12.0	Complied
7.309500	Live	41.5	50.0	8.5	Complied
8.218500	Live	42.2	50.0	7.8	Complied

Results: Neutral / Quasi Peak / 120 VAC 60 Hz

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.564000	Neutral	38.3	56.0	17.7	Complied
0.640500	Neutral	38.3	56.0	17.7	Complied
3.471000	Neutral	37.8	56.0	18.2	Complied
3.853500	Neutral	37.1	56.0	18.9	Complied
7.021500	Neutral	45.8	60.0	14.2	Complied
8.227500	Neutral	47.8	60.0	12.2	Complied

Results: Neutral / Average / 120 VAC 60 Hz

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.415500	Neutral	35.3	47.5	12.2	Complied
0.492000	Neutral	34.3	46.1	11.8	Complied
0.640500	Neutral	33.5	46.0	12.5	Complied
4.681500	Neutral	34.4	46.0	11.6	Complied
7.246500	Neutral	40.9	50.0	9.1	Complied
7.849500	Neutral	42.5	50.0	7.5	Complied

Transmitter AC Conducted Spurious Emissions (continued)**Results: 120 VAC 60 Hz**

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

--- END OF REPORT ---