

TEST REPORT

FCC ID. :	2A2HT-MARKSMAN	
Test Report No..... :	TCT210616E015	
Date of issue..... :	Sep. 02, 2021	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Targetvision LLC	
Address..... :	1835 County Rd. 130 Pearland, TEXAS 77581, United States	
Manufacturer's name ... :	Targetvision LLC	
Address..... :	1835 County Rd. 130 Pearland, TEXAS 77581, United States	
Standard(s)	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013	
Test item description	THE MARKSMAN 300 YARD TARGET CAMERA	
Trade Mark	LONGSHOT	
Model/Type reference..... :	MARKSMAN	
Rating(s)..... :	Adapter Information: MODEL: JY15-168-080-UD INPUT: AC 100-240V, 50/60Hz, 0.4A OUTPUT: DC 16.8V, 800mA Rechargeable Li-ion Battery DC 14.8V	
Date of receipt of test item	Jun. 16, 2021	
Date (s) of performance of test..... :	See dates for each test case	
Tested by (+signature) ... :	Rleo	
Check by (+signature).... :	Beryl Zhao	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Operation Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units.....	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
4.3. Measurement Uncertainty.....	8
5. Test Results and Measurement Data	9
5.1. Antenna requirement	9
5.2. Conducted Emission.....	10
5.3. Maximum Conducted (Average) Output Power	14
5.4. Emission Bandwidth	15
5.5. Power Spectral Density.....	17
5.6. Conducted Band Edge and Spurious Emission Measurement	19
5.7. Radiated Spurious Emission Measurement.....	21
Appendix A: Test Result of Conducted Test	
Appendix B: Photographs of Test Setup	
Appendix C: Photographs of EUT	

1. General Product Information

1.1. EUT description

Test item description	THE MARKSMAN 300 YARD TARGET CAMERA
Model/Type reference.....	MARKSMAN
Sample Number.....	TCT210616E015-0101
Operation Frequency	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel Separation.....	5MHz
Number of Channel	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Modulation Technology	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n: Orthogonal Frequency Division Multiplexing(OFDM)
Data speed	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: Up to 300Mbps
Antenna Type.....	Internal Antenna
Antenna Gain.....	5dBi
Rating(s).....	Adapter Information: MODEL: JY15-168-080-UD INPUT: AC 100-240V, 50/60Hz, 0.4A OUTPUT: DC 16.8V, 800mA Rechargeable Li-ion Battery DC 14.8V
Remark.....	/

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Operation Frequency

For 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--

For 802.11n (HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (HT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	25.0 °C	25.0 °C
Humidity:	55 % RH	55 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Software:		
Software Information:	MT7620 QA V1.0.6.0	
Power Level:	14	
Test Mode:		
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations	
The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.		

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: TCT Testing Industrial Park Fuqiao 5th Industrial Zone, Fuhai Street, Bao'an District Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:

FCC Part15 C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

E.U.T Antenna:

The WIFI antennas are internal antennas, and the best case gains of the both antennas are 5dBi.



5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Charging + transmitting with modulation														
Test Procedure:	1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jul. 07, 2022
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Mar. 11, 2022
Line-5	TCT	CE-05	N/A	Jul. 07, 2022
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **L1** Temperature: 27.6 (°C)
Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz Humidity: 43 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1739	40.40	9.42	49.82	64.77	-14.95	QP	
2		0.1739	19.56	9.42	28.98	54.77	-25.79	AVG	
3		0.3820	31.10	9.29	40.39	58.24	-17.85	QP	
4		0.3820	16.08	9.29	25.37	48.24	-22.87	AVG	
5		1.0180	29.60	9.40	39.00	56.00	-17.00	QP	
6		1.0180	13.35	9.40	22.75	46.00	-23.25	AVG	
7	*	2.0339	33.20	9.51	42.71	56.00	-13.29	QP	
8		2.0339	18.78	9.51	28.29	46.00	-17.71	AVG	
9		6.1340	29.50	9.63	39.13	60.00	-20.87	QP	
10		6.1340	15.17	9.63	24.80	50.00	-25.20	AVG	
11		27.8700	31.40	10.04	41.44	60.00	-18.56	QP	
12		27.8700	20.05	10.04	30.09	50.00	-19.91	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 27.6 (°C)
 Limit: FCC Part 15C Conduction(QP) Power: AC 120 V/60 Hz Humidity: 43 %

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1	*	0.1779	43.60	9.38	52.98	64.58	-11.60	QP	
2		0.1779	22.05	9.38	31.43	54.58	-23.15	AVG	
3		0.2340	37.20	9.34	46.54	62.31	-15.77	QP	
4		0.2340	16.12	9.34	25.46	52.31	-26.85	AVG	
5		0.4139	30.10	9.29	39.39	57.57	-18.18	QP	
6		0.4139	9.22	9.29	18.51	47.57	-29.06	AVG	
7		1.9819	26.20	9.45	35.65	56.00	-20.35	QP	
8		1.9819	13.13	9.45	22.58	46.00	-23.42	AVG	
9		5.5819	31.20	9.57	40.77	60.00	-19.23	QP	
10		5.5819	13.72	9.57	23.29	50.00	-26.71	AVG	
11		28.5620	31.10	10.05	41.15	60.00	-18.85	QP	
12		28.5620	23.04	10.05	33.09	50.00	-16.91	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

5.3. Maximum Conducted (Average) Output Power

5.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 v05r02, KDB662911 D01 v02r01
Limit:	30dBm
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Measure the conducted output power and record the results in the test report.
Test Result:	PASS

5.3.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 18, 2022
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Jul. 18, 2022
Antenna Connector	TCT	RFC-01	N/A	Jul. 18, 2022

5.3.3. Test Data

Configuration IEEE 802.11b/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Average) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	21.64	23.68	27.99	PASS
Middle	22.49	23.49	27.99	PASS
Highest	22.20	23.32	27.99	PASS

Configuration IEEE 802.11g/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Average) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	22.01	23.96	27.99	PASS
Middle	22.84	23.73	27.99	PASS
Highest	22.66	23.43	27.99	PASS

Configuration IEEE 802.11n(H20)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	21.85	23.57	25.80	27.99	PASS
Middle	23.03	23.67	26.37	27.99	PASS
Highest	22.27	22.93	25.62	27.99	PASS

Configuration IEEE 802.11n(H40)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Average) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	22.84	24.19	26.58	27.99	PASS
Middle	23.18	23.95	26.59	27.99	PASS
Highest	23.13	23.84	26.51	27.99	PASS


Note: $G_{ANT} = 5\text{dBi}$, Array Gain= $10\log(N_{ANT}/N_{SS}) = 3.01\text{dBi}$

Directional Gain= $G_{ANT} + \text{Array Gain} = 8.01\text{dBi} > 6\text{dBi}$, So limit= $30-(8.01-6)=27.99\text{dBm}$

Refer to Appendix A: Test Result of Conducted Test

5.4. Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB 558074 D01 v05r02
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 3. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 18, 2022
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Jul. 18, 2022
Antenna Connector	TCT	RFC-01	N/A	Jul. 18, 2022

5.5. Power Spectral Density

5.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB 558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 4. Detector = RMS, Sweep time = auto couple. 5. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 18, 2022
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Jul. 18, 2022
Antenna Connector	TCT	RFC-01	N/A	Jul. 18, 2022

5.5.3. Test data

Configuration IEEE 802.11b/ Antenna 0, Antenna 1				
Test channel	AVG Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-10.61	-3.75	5.99	PASS
Middle	-9.02	-4.67	5.99	PASS
Highest	-8.77	-4.75	5.99	PASS

Configuration IEEE 802.11g/ Antenna 0, Antenna 1				
Test channel	AVG Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-11.49	-5.77	5.99	PASS
Middle	-11.49	-6.16	5.99	PASS
Highest	-12.05	-6.26	5.99	PASS

Configuration IEEE 802.11n (HT20)/ Antenna 0, Antenna 1					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-12.12	-5.64	-4.76	5.99	PASS
Middle	-11.49	-6.19	-5.07	5.99	PASS
Highest	-12.02	-7.00	-5.81	5.99	PASS

Configuration IEEE 802.11n (HT40)/ Antenna 0, Antenna 1					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-14.36	-9.33	-8.14	5.99	PASS
Middle	-13.96	-9.68	-8.30	5.99	PASS
Highest	-14.75	-10.05	-8.78	5.99	PASS

Note:

$G_{ANT} = 5\text{dBi}$, Array Gain= $10\log(\text{NANT}) = 3.01\text{dBi}$

Directional Gain= $G_{ANT} + \text{Array Gain} = 8.01\text{dBi} > 6\text{dBi}$, So limit= $8 - (8.01 - 6) = 5.99\text{dBm/3kHz}$

Refer to Appendix A: Test Result of Conducted Test

5.6. Conducted Band Edge and Spurious Emission Measurement

5.6.1. Test Specification


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


5.6.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jul. 18, 2022
RF Cable (9KHz-26.5GHz)	TCT	RE-06	N/A	Jul. 18, 2022
Antenna Connector	TCT	RFC-01	N/A	Jul. 18, 2022


5.7. Radiated Spurious Emission Measurement

5.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209					
Test Method:	ANSI C63.10: 2013					
Frequency Range:	9 kHz to 25 GHz					
Measurement Distance:	3 m					
Antenna Polarization:	Horizontal & Vertical					
Operation mode:	Transmitting mode with modulation					
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark	
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
Peak		1MHz	10Hz	Average Value		
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)	
	0.009-0.490		2400/F(KHz)		300	
	0.490-1.705		24000/F(KHz)		30	
	1.705-30		30		30	
	30-88		100		3	
	88-216		150		3	
	216-960		200		3	
	Above 960		500		3	
	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)	Detector
	Above 1GHz		500		3	Average
		5000		3	Peak	
Test setup:	For radiated emissions below 30MHz					
						
	30MHz to 1GHz					



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test results:	PASS


5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jul. 07, 2022
Spectrum Analyzer	R&S	FSQ40	200061	Jul. 07, 2022
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Mar. 11, 2022
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Apr. 08, 2022
Pre-amplifier	HP	8447D	2727A05017	Jul. 07, 2022
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 05, 2022
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 04, 2022
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 04, 2022
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Apr. 10, 2023
Antenna Mast	Keleto	RE-AM	N/A	N/A
Coaxial cable	SKET	RC_DC18G-N	N/A	Apr. 08, 2022
Coaxial cable	SKET	RC-DC18G-N	N/A	Apr. 08, 2022
Coaxial cable	SKET	RC-DC40G-N	N/A	Jul. 07, 2022
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

5.7.3. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:



Site #2

Polarization: **Horizontal**

Temperature: 24.2(C)


Limit: FCC Part 15C RE_3m

Power: DC 14.8 V

Humidity: 49 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	145.3506	21.61	13.29	34.90	43.50	-8.60	QP	P	
2	290.0172	15.94	13.96	29.90	46.00	-16.10	QP	P	
3	487.3149	14.68	19.12	33.80	46.00	-12.20	QP	P	
4	531.9633	16.32	19.98	36.30	46.00	-9.70	QP	P	
5 *	580.7026	20.60	20.90	41.50	46.00	-4.50	QP	P	
6 !	824.5968	14.89	25.41	40.30	46.00	-5.70	QP	P	

Vertical:



Site #2

Polarization: **Vertical**

Temperature: 24.2(C)

Limit: FCC Part 15C RE_3m

Power: DC 14.8 V

Humidity: 49 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	43.8119	21.18	13.92	35.10	40.00	-4.90	QP	P	
2	143.3260	24.13	13.27	37.40	43.50	-6.10	QP	P	
3	338.4000	14.51	15.09	29.60	46.00	-16.40	QP	P	
4 !	435.5898	23.58	18.02	41.60	46.00	-4.40	QP	P	
5 *	531.9635	22.02	19.98	42.00	46.00	-4.00	QP	P	
6	580.7024	18.00	20.90	38.90	46.00	-7.10	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (Lowest channel and n(HT40)) was submitted only.

3. Freq. = Emission frequency in MHz

Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

Limit (dBuV/m) = Limit stated in standard


Margin (dB) = Measurement (dBuV/m) – Limits (dBuV/m)

* is meaning the worst frequency has been tested in the test frequency range.

Test Result of Radiated Spurious at Band edges

Lowest channel 2412:

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 25(°C)


Limit: FCC part 15 (PK)

Power: DC 14.8V

Humidity: 55 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	51.16	-13.15	38.01	74.00	-35.99	peak
2	2390.000	47.35	-13.15	34.20	54.00	-19.80	AVG
3	2400.000	69.84	-13.12	56.72	74.00	-17.28	peak
4 *	2400.000	63.52	-13.12	50.40	54.00	-3.60	AVG

Vertical:




Site: Polarization: **Vertical** Temperature: 25(°C)
 Limit: FCC part 15 (PK) Power: DC 14.8 V Humidity: 55 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	53.56	-13.05	40.51	74.00	-33.49	peak
2	2390.000	49.29	-13.05	36.24	54.00	-17.76	AVG
3	2400.000	68.81	-13.02	55.79	74.00	-18.21	peak
4 *	2400.000	63.09	-13.02	50.07	54.00	-3.93	AVG

Note: Measurements were conducted in all two channels (high, low) and all modulation (802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode 802.11n(HT40)

Highest channel 2462:

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 25(°C)


Limit: FCC part 15 (PK)

Power: DC 14.8 V

Humidity: 55 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.500	69.60	-12.84	56.76	74.00	-17.24	peak
2 *	2483.500	65.27	-12.84	52.43	54.00	-1.57	AVG

Vertical:



Site: Polarization: **Vertical** Temperature: 25(°C)
 Limit: FCC part 15 (PK) Power: DC 14.8 V Humidity: 55 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2390.000	53.56	-13.05	40.51	74.00	-33.49	peak
2	2390.000	49.29	-13.05	36.24	54.00	-17.76	AVG
3	2400.000	68.81	-13.02	55.79	74.00	-18.21	peak
4 *	2400.000	63.09	-13.02	50.07	54.00	-3.93	AVG

Note:

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
3. Measurements were conducted in all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode 802.11n(HT40)) was submitted only.

Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	48.16	---	0.75	48.91	---	74	54	-5.09
7236	H	39.97	---	9.87	49.84	---	74	54	-4.16
---	H	---	---	---	---	---	---	---	---
4824	V	47.43	---	0.75	48.18	---	74	54	-5.82
7236	V	40.05	---	9.87	49.92	---	74	54	-4.08
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	48.37	---	0.97	49.34	---	74	54	-4.66
7311	H	40.32	---	9.83	50.15	---	74	54	-3.85
---	H	---	---	---	---	---	---	---	---
4874	V	48.87	---	0.97	49.84	---	74	54	-4.16
7311	V	40.98	---	9.83	50.81	---	74	54	-3.19
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	48.99	---	1.18	50.17	---	74	54	-3.83
7386	H	38.85	---	10.07	48.92	---	74	54	-5.08
---	H	---	---	---	---	---	---	---	---
4924	V	49.04	---	1.18	50.22	---	74	54	-3.78
7386	V	39.21	---	10.07	49.28	---	74	54	-4.72
---	V	---	---	---	---	---	---	---	---

Note:

- Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
- Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
- Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- 802.11b is SISO mode and the worst case Antenna (ANT1) was submitted only.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	48.23	---	0.75	48.98	---	74	54	-5.02
7236	H	40.05	---	9.87	49.92	---	74	54	-4.08
---	H	---	---	---	---	---	---	---	---
4824	V	47.17	---	0.75	47.92	---	74	54	-6.08
7236	V	40.18	---	9.87	50.05	---	74	54	-3.95
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	48.76	---	0.97	49.73	---	74	54	-4.27
7311	H	40.38	---	9.83	50.21	---	74	54	-3.79
---	H	---	---	---	---	---	---	---	---
4874	V	48.97	---	0.97	49.94	---	74	54	-4.06
7311	V	40.85	---	9.83	50.68	---	74	54	-3.32
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	47.52	---	1.18	48.70	---	74	54	-5.30
7386	H	39.21	---	10.07	49.28	---	74	54	-4.72
---	H	---	---	---	---	---	---	---	---
4924	V	46.84	---	1.18	48.02	---	74	54	-5.98
7386	V	40.07	---	10.07	50.14	---	74	54	-3.86
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---”in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11b is SISO mode and the worst case Antenna (ANT1) was submitted only.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	49.35	---	0.75	50.10	---	74	54	-3.90
7236	H	40.26	---	9.87	50.13	---	74	54	-3.87
---	H	---	---	---	---	---	---	---	---
4824	V	47.37	---	0.75	48.12	---	74	54	-5.88
7236	V	40.14	---	9.87	50.01	---	74	54	-3.99
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	47.33	---	0.97	48.30	---	74	54	-5.70
7311	H	40.02	---	9.83	49.85	---	74	54	-4.15
---	H	---	---	---	---	---	---	---	---
4874	V	47.25	---	0.97	48.22	---	74	54	-5.78
7311	V	40.06	---	9.83	49.89	---	74	54	-4.11
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	48.46	---	1.18	49.64	---	74	54	-4.36
7386	H	40.17	---	10.07	50.24	---	74	54	-3.76
---	H	---	---	---	---	---	---	---	---
4924	V	47.96	---	1.18	49.14	---	74	54	-4.86
7386	V	40.32	---	10.07	50.39	---	74	54	-3.61
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11n(HT20) is MIMO mode.

Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4844	H	45.72	---	0.75	46.47	---	74	54	-7.53
7266	H	38.63	---	9.87	48.50	---	74	54	-5.50
---	H	---	---	---	---	---	---	---	---
4824	V	44.95	---	0.75	45.70	---	74	54	-8.30
7236	V	35.77	---	9.87	45.64	---	74	54	-8.36
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	43.17	---	0.97	44.14	---	74	54	-9.86
7311	H	34.77	---	9.83	44.60	---	74	54	-9.40
---	H	---	---	---	---	---	---	---	---
4874	V	44.30	---	0.97	45.27	---	74	54	-8.73
7311	V	37.85	---	9.83	47.68	---	74	54	-6.32
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4904	H	45.59	---	1.18	46.77	---	74	54	-7.23
7356	H	36.82	---	10.07	46.89	---	74	54	-7.11
---	H	---	---	---	---	---	---	---	---
4904	V	43.89	---	1.18	45.07	---	74	54	-8.93
7356	V	36.27	---	10.07	46.34	---	74	54	-7.66
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown "---" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. 802.11n(HT40) is MIMO mode.

Appendix A: Test Result of Conducted Test

Antenna 0 DTS Bandwidth

Test Result

Test Mode	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	2412	10.160	2406.920	2417.080	0.5	PASS
	2437	10.160	2431.920	2442.080	0.5	PASS
	2462	10.080	2456.960	2467.040	0.5	PASS
11G	2412	16.520	2403.760	2420.280	0.5	PASS
	2437	16.440	2428.760	2445.200	0.5	PASS
	2462	16.440	2453.760	2470.200	0.5	PASS
11N20SISO	2412	17.120	2403.440	2420.560	0.5	PASS
	2437	17.160	2428.400	2445.560	0.5	PASS
	2462	17.600	2453.200	2470.800	0.5	PASS
11N40SISO	2422	36.080	2404.160	2440.240	0.5	PASS
	2437	36.480	2418.760	2455.240	0.5	PASS
	2452	36.480	2433.760	2470.240	0.5	PASS

Test Graphs

11B 2412




11B 2437




11B 2462




11G 2412



11G 2437




11G 2462




11N20SISO 2412




11N20SISO 2437




11N20SISO 2462




11N40SISO 2422



11N40SISO 2437



11N40SISO 2452




Maximum conducted output power

Test Result


Test Mode	Channel	Conducted Power [dBm]	Correction Factor [dB]	Total Power [dBm]	Limit [dBm]	Verdict
11B	2412	21.54	0.10	21.64	<=30	PASS
	2437	22.39	0.10	22.49	<=30	PASS
	2462	22.10	0.10	22.20	<=30	PASS
11G	2412	21.43	0.58	22.01	<=30	PASS
	2437	22.26	0.58	22.84	<=30	PASS
	2462	22.08	0.58	22.66	<=30	PASS
11N20SISO	2412	21.24	0.61	21.85	<=30	PASS
	2437	22.41	0.62	23.03	<=30	PASS
	2462	21.66	0.61	22.27	<=30	PASS
11N40SISO	2422	21.66	1.18	22.84	<=30	PASS
	2437	22.00	1.18	23.18	<=30	PASS
	2452	21.95	1.18	23.13	<=30	PASS

Test Graphs


11B 2412




11B 2437




11B 2462




11G 2412




11G 2437




11G 2462




11N20SISO 2412




11N20SISO 2437




11N20SISO 2462




11N40SISO 2422



11N40SISO 2437



11N40SISO 2452



Maximum power spectral density

Test Result

Test Mode	Channel	Result [dBm/10kHz]	Result [dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-5.38	-10.61	<=8	PASS
	2437	-3.79	-9.02	<=8	PASS
	2462	-3.54	-8.77	<=8	PASS
11G	2412	-6.26	-11.49	<=8	PASS
	2437	-6.26	-11.49	<=8	PASS
	2462	-6.82	-12.05	<=8	PASS
11N20SISO	2412	-6.89	-12.12	<=8	PASS
	2437	-6.26	-11.49	<=8	PASS
	2462	-6.79	-12.02	<=8	PASS
11N40SISO	2422	-9.13	-14.36	<=8	PASS
	2437	-8.73	-13.96	<=8	PASS
	2452	-9.52	-14.75	<=8	PASS

Note: Compensate 10dB is for Exchange rate of RBW

Exchange rate of RBW = $10 \cdot \log_{10}(\text{Reference bandwidth}/\text{RBW at measurement}) = -5.23[\text{dB}]$

where Reference bandwidth = 3KHz

Test Graphs

11B 2412




11B 2437




11B 2462




11G 2412




11G 2437




11G 2462




11N20SISO 2412




11N20SISO 2437




11N20SISO 2462




11N40SISO 2422



11N40SISO 2437



11N40SISO 2452



Band edge measurements

Test Result

Test Mode	Ch Name	Channel	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	11.46	-26.45	<=-18.54	PASS
	High	2462	12.03	-34.05	<=-17.97	PASS
11G	Low	2412	9.78	-25.01	<=-20.22	PASS
	High	2462	10.60	-28.68	<=-19.4	PASS
11N20SISO	Low	2412	9.83	-25.04	<=-20.17	PASS
	High	2462	10.71	-29.74	<=-19.29	PASS
11N40SISO	Low	2422	7.12	-25.84	<=-22.88	PASS
	High	2452	7.35	-25.15	<=-22.65	PASS