



RF EXPOSURE EVALUATION

FCC ID:2A2J3-SR09

Product Name	:	Smart Ring
Model Name	:	SR09W US9, SR09W, SR06, SR06W, SR03, SR09N,SR09N US6,SR09N US7,SR09N US8,SR09N US9,SR09N US10,SR09N US11,SR09N US12,SR09N US13,SR09 US6, SR09 US7, SR09 US8, SR09 US9, SR09 US10, SR09 US11, SR09 US12, SR09 US13, SR09W US6, SR09W US7, SR09W US8, SR09W US9, SR09W US10, SR09W US11, SR09W US12, SR09W US13
Bluetooth Version	:	BT BLE
Operating frequency	:	2402-2480MHz
Numbers of Channel	:	40 channels For DTS
Antenna Type	:	PCB Antenna
Antenna Gain	:	0.95 dBi
Type of Modulation	:	GFSK
Power supply	:	Input:5V,1A
Hardware Version	:	N/A
Software Version	:	V1.0.0



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \times \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g SAR extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is $\leq 50\text{mm}$ and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is $< 5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion. Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2480	1.34	1.34 ± 1	1.713957	5	0.539829	3	BLE

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

Signature

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu

Manager

Date: 2023-09-07