

## SPECIFICATION

|                                                                       |
|-----------------------------------------------------------------------|
| <b>PART NO: LA31H2450-A27</b><br><b>CUSTOMER PART NO:</b>             |
| <b>CUSTOMER APPROVED BY: Validation Date</b><br><b>APPROVED DATE:</b> |

RoHS Compliant Parts

66 Zhengyuan Road, Jiaxing Economic Development Zone,  
Jiaxing, Zhejiang Province, China

No.66 ZhengyuanRoad, Economic Development Zone,Jiaxing ,Zhejiang,China

TEL : 0086-573-83651818

FA X : 0086-573-83651858

|                                    |                                               |                              |
|------------------------------------|-----------------------------------------------|------------------------------|
| Fit the Prepared by:               | Review of the Checked by:                     | Approved by the Approved by: |
| Sample delivery date is Forme d On | Product version, Document Version<br>( V1.5 ) |                              |

## Catalogue

|                                                                                     |       |
|-------------------------------------------------------------------------------------|-------|
| Specifications version change record Version rejigger track record.....             | 3     |
| 1. An Overview of the Introduction.....                                             | 4     |
| 2. Model Part Number.....                                                           | 4     |
| 3. External size and test plate pad size Dimension s.....                           | 4 ~ 5 |
| 4. Test circuit and matching circuit Evaluation B oard and Matching Circuits.....   | 5     |
| 5. Electrical performance: Electrical Characteristics.....                          | 6     |
| 6. Characteristic curve: Characteristic curve.....                                  | 6     |
| 7. Direction diagram, the Radiation Pattern.....                                    | 7~8   |
| 8. Reliability test, after the allowable error of Post Dependability Tolerance..... | 9     |
| 9. Reliability test: Dependability Test.....                                        | 9~10  |
| 10. Reflow welding temperature is Reflow Soldering Standard Condition.....          | 10    |
| 11. Packaging size: Packaging and Dimensions.....                                   | 11    |

## Version change record

| Version                                                                                                                                                                                                                                                                                                                                           | Change the record                                                                                                                                                                                | Prepared       | Approve       | Date       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------|------------|
| V1.0                                                                                                                                                                                                                                                                                                                                              | initial issue                                                                                                                                                                                    | Luo Chang mast | Tang ambition | 2015.8.11  |
| V1.1                                                                                                                                                                                                                                                                                                                                              | More adapted with thickness                                                                                                                                                                      | Cai Zhuang     | Lu Guanyu     | 2016.10.11 |
| V1.2                                                                                                                                                                                                                                                                                                                                              | Change the product dimensional tolerance value                                                                                                                                                   | Luo Chang mast | Lu Guanyu     | 2017.05.24 |
| V1.3                                                                                                                                                                                                                                                                                                                                              | Description of modified reliability test 8.1~8.4                                                                                                                                                 | Pan Feng       | Lu Guanyu     | 2017.11.07 |
| V1.4                                                                                                                                                                                                                                                                                                                                              | Modify the reliability item 9.4 content<br>Update the reflow weld temperature curve chart<br><br>11.1 Correction of product packaging display direction 11.3 Product storage condition is MSL: 1 | Pan Feng       | Lu Guanyu     | 2018.07.31 |
| V1.5                                                                                                                                                                                                                                                                                                                                              | Correct product bottom electrode width from 0.5- -> 0.7                                                                                                                                          | Pan Feng       | Lu Guanyu     | 2019.01.22 |
|                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                  |                |               |            |
|                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                  |                |               |            |
| remarks:<br>1. When changing the electrical performance index of the product, the version number should be replaced (V1.0 to V2.0, V3.0...);<br>2. When changing the product test method (including the reliability test conditions), or changing the use conditions, the current version number plus series (V1.0 changes to V1.1, V1.2... ..) 。 |                                                                                                                                                                                                  |                |               |            |

## Specification

## 1. An Overview of the INTRODUCTION


"Jiali" microwave multi-layer ceramic antenna LA series products are designed for WLAN, W iFi, Bluetooth, PHS, mobile phone multi-frequency antenna, FM and other small volume SMD chip design.

"GLEAD" Microwave Multi-Layer Ceramic Antenna LA series are designed to be used in WLAN 、WiFi 、Bluetooth 、PHS 、Multiple-band Mobile phone antenna, FM, etc and compact size SMD chip design.


## 2. Model # Part Number

|    |    |   |      |       |                     |
|----|----|---|------|-------|---------------------|
| LA | 31 | H | 2450 | - A27 | Product Name: A27   |
|    |    |   |      |       | Antenna Frequency:  |
|    |    |   |      |       | Design Series       |
|    |    |   |      |       | Size: 3.21.60.6     |
|    |    |   |      |       | Multi-layer Antenna |


## 3. Exsize and test plate size Dimensions (Unit: mm)



## Specification



## 4. Evaluation Board and Matching Circuits




## Specification

## 5. Electrical Characteristics

| No . | I. Item (Project)                                | Specifications (Feature)                |
|------|--------------------------------------------------|-----------------------------------------|
| 5.1  | Central Frequency Center Frequency (No matching) | 2545MHz                                 |
|      | (With the matching circuit test) After Matching  | 2450 MHz                                |
| 5.2  | Band Width Pass-band width                       | 100 MHz typ.                            |
| 5.3  | Peak Gain, Peak gain                             | 5.62 dBi                                |
| 5.4  | V.S.W. R (inBW), in Bobbi                        | $\leq 2.0$                              |
| 5.5  | Polarization Polarization mode                   | Linear Linearity                        |
| 5.6  | Azimuth Beam width Azimuth angle                 | The Omni-directional is omnidirectional |
| 5.7  | Impedance Impedance                              | 50 $\Omega$                             |



## 6. Characteristic curve,




## Specification

## 7. Radiation Pattern &amp; Efficiency


coordinates :



## X-Z Plane




## X-Y Plane




## Specification

## Y-Z Plane



## 3D Radiation Pattern



| Frequency<br>(MHz) | 2400  | 2450  | 2500  |
|--------------------|-------|-------|-------|
| Avg.Gain<br>(dBi)  | -1.56 | -1.28 | -1.15 |
| Peck Gain<br>(dBi) | 5.62  | 5.54  | 4.48  |
| Efficiency<br>(%)  | 71.8  | 73.5  | 75.6  |

## Specification

**8 Post Dependability Tolerance**

The allowable deviation from the start reading after the reliability test is shown in the table below

Post Dependability Tolerance (Refer to the table )

| No . | I. Item (Project)                  | Post Dependability Tolerance<br>(Additional error is allowed after reliability test) |
|------|------------------------------------|--------------------------------------------------------------------------------------|
| 8.1  | Central Frequency Center frequency | $\pm 5$ MHz                                                                          |
| 8.2  | Band Width Pass-band width         | $\pm 5$ MHz                                                                          |
| 8.3  | Gain gain                          | $\pm 0.1$ dBi                                                                        |
| 8.4  | V.S.W. R (inBW), in Bobbi          | $\pm 0.1$                                                                            |

**9 Dependability Test**

Base condition:

Temperature range

$25 \pm 5^{\circ}\text{C}$

Relative humidity range Relative Humidity range 55~75%RH working temperature Operating  
Temperature range  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$  reserve temperature Storage Temperature range  $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

**9.1, Vibration Resist**

At a vibration frequency of 10 to 55 Hz with an amplitude of 1.5mm along the X.Y. After 2 hours of vibration, each test conforms to Table 8.1~8.4.

The device should satisfy the electrical characteristics specified in paragraph 8.1~8.4 after applied to the vibration of 10 to 55Hz with amplitude of 1.5mm for 2 hours each in X , Y and Z directions .

**9.2 Drop Shock**

At the height of 100cm, fall on the wooden floor for 3 times before the test meets Table 8.1~8.4.

The device should satisfy the electrical characteristics specified in paragraph 8.1~8.4 after dropping onto the hard wooden board from the height of 100cm for 3 times each facet of the 3 dimensions of the device .

**9.3 Solder Heat Proof**

After preheat of  $120\sim 150^{\circ}\text{C}$  for 120 seconds,  $3 \pm 0.5$  seconds,  $3 \pm 0.5$  seconds, or  $300^{\circ}\text{C} -10^{\circ}\text{C}$ , without damage to the welding surface.

The device should be satisfied after preheating at  $120^{\circ}\text{C} \sim 150^{\circ}\text{C}$  for 120 seconds and dipping in soldering Sn at  $255^{\circ}\text{C} +10^{\circ}\text{C}$  for  $5 \pm 0.5$  seconds , or electric iron  $300^{\circ}\text{C} -10^{\circ}\text{C}$  for  $3 \pm 0.5$  seconds , without damage.


**9.4 Adhesive Strength of Termination**

5N (0603) on product electrode terminals; 10N ( $> 0603$ ) horizontal thrust for  $10 \pm 1$  seconds without obvious visual damage and electrode displacement.

The device have no remarkable damage or removal of the termination after horizontal force of 5N( $\leq 0603$ ); 10N( $> 0603$ )with  $10 \pm 1$  seconds .

## Specification

## 9.5 Bending Resist Test



Welded the product in the middle of the PCB board of  $1.6 \pm 0.2\text{mm}$  according to the drawing, apply the force by the arrow direction:  $1\text{mm} / \text{S}$ , bending distance:  $1.5\text{mm}$ , keep  $5 \pm 1\text{S}$ , the product metal layer does not fall off. Weld the product to the center part of the PCB with the thickness  $1.6 \pm 0.2\text{mm}$  as the illustration shows, and keep exerting force arrow-ward on it at speed of  $1\text{mm} / \text{S}$ , and hold for  $5 \pm 1\text{S}$  at the position of  $1.5\text{mm}$  bending distance, so far, any peeling off of the

product metal coating should not be detected.

## 9.6 Moisture Proof

If in a temperature of  $60 \pm 2^\circ\text{C}$  with 96 hours relative humidity of 90~95%, and restored for 1 to 2 hours in room temperature, the test is in accordance with Table 8.1~8.4.

The device should satisfy the electrical characteristics specified in paragraph 8.1~8.4 after exposed to the temperature  $60 \pm 2^\circ\text{C}$  and the relative humidity 90~95% RH for 96 hours and 1~2 hours recovery time under normal condition.

## 9.7 High Temperature Endurance

Place for  $96 \pm 2$  hours in an incubator at  $85 \pm 5^\circ\text{C}$  and recover for 1 to 2 hours at room temperature before testing. Compliance with Table 8.1~8.4.

The device should satisfy the electrical characteristics specified in paragraph 8.1~8.4 after exposed to temperature  $85 \pm 5^\circ\text{C}$  for  $96 \pm 2$  hours and 1~2 hours recovery time under normal temperature.

## 9.8 Low Temperature Endurance

Place  $96 \pm$  in a temperature of  $-40^\circ\text{C} \pm 5^\circ\text{C}$  and recover for 1~2 hours as specified in Table 8.1~8.4.


The device should also satisfy the electrical characteristics specified in paragraph 8.1~8.4 after exposed to the temperature  $-40^\circ\text{C} \pm 5^\circ\text{C}$  for  $96 \pm 2$  hours and to 2 hours recovery time under normal temperature.


## 9.9 Temperature Cycle Test

At  $-40^\circ\text{C}$  for 30 minutes and  $+85^\circ\text{C}$  for 30 minutes, after 5 cycles and 1 to 2 hours in room temperature, the test conforms to Table 8.1~8.4.

The device should also satisfy the electrical characteristics specified in paragraph 8.1~8.4 after exposed to the low temperature  $-40^\circ\text{C}$  and high temperature  $+85^\circ\text{C}$  for  $30 \pm 2$  min each by 5 cycles and 1 to 2 hours recovery time under normal temperature.


## 10 Reflow Soldering Standard Condition



**Specification****11 Packaging and Dimensions****11.1 Plastic Tape****Packaging description: Remarks for Package**

The length of the tail hole of the carrier is 150~200mm, the length of the carrier head is 250~300mm, and the cover of the head is 250mm longer.

Reserve a length of 150~200mm for the trailer of the carrier and 250~300 mm for the leader of the carrier and further 250mm of cover tape at the leading part of the carrier.

**11.2 Reel (3000 pcs/Reel)****11.3, Storage Period**

The product shall be used up within half a year after being received.

Product should be used within six months of receipt.

Wet sensitivity level 1 / Storage temperature and humidity:

MSL 1 / Storage Temperature Range : <30 degree C , Humidity : <85%RH