



REPORT No.: SZ25020189W03

TEST REPORT

APPLICANT : FJ Dynamics Co.,Ltd.

PRODUCT NAME : FJD Trion S2 LiDAR Scanner

MODEL NAME : S2

BRAND NAME : FJD Trion

FCC ID :

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2025-02-24

TEST DATE : 2025-04-18 to 2025-06-25

ISSUE DATE : 2025-07-21

Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	11
2.4. Test Configuration of EUT	12
2.5. Test Conditions	12
2.6. Test Setup Layout Diagram	13
3. Test Results	16
3.1. Antenna Requirement	16
3.2. Duty Cycle of Test Signal	17
3.3. Maximum Peak and Average Conducted Output Power	18
3.4. 6 dB Bandwidth	19
3.5. Conducted Spurious Emissions and Band Edge	20
3.6. Power Spectral Density	21
3.7. Conducted Emission	22
3.8. Restricted Frequency Bands	23
3.9. Radiated Emission	24
Annex A Test Data and Result	26



REPORT No.: SZ25020189W03

Change History		
Version	Date	Reason for change
1.0	2025-07-21	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Apr. 18, 2025	Li Xinpeng	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Apr. 18, 2025	Li Xinpeng	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Apr. 18, 2025	Li Xinpeng	PASS	/
5	15.247(a)	Bandwidth	Apr. 18, 2025	Li Xinpeng	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	May 12, 2025	Li Xinpeng	PASS	/
7	15.247(e)	Power Spectral Density	May 12, 2025	Li Xinpeng	PASS	/
8	15.207	Conducted Emission	Jun. 24, 2025	Fan Shengquan	PASS	/
9	15.247(d)	Restricted Frequency Bands	Jun. 25, 2025	Zhong Xiangyun	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Jun. 25, 2025	Zhong Xiangyun	PASS	/

Note 1: All test items are tested and evaluated in the worse mode with reference to output power results.

Note 2: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 3: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
Power Sensor	MY54180008	U2021XA	Agilent	2024.09.11	2025.09.10
Attenuator	MTJ6004-20	VAT-10+	MTJ Cooperation	N/A	N/A
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2024.06.03	2025.06.02
				2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	R&S	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.20	2026.06.19
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
				2025.06.16	2026.06.15
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.20	2026.06.19
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
				2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.09.11	2025.09.10
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	FJ Dynamics Co.,Ltd.
Applicant Address:	21F, Das Tower, No. 28, 1st South Keji Road, Nanshan District , Shenzhen, China
Manufacturer:	FJ Dynamics Co.,Ltd.
Manufacturer Address:	21F, Das Tower, No. 28, 1st South Keji Road, Nanshan District , Shenzhen, China

2.2. Information of EUT

Product Name:	FJD Trion S2 LiDAR Scanner	
Sample No.:	5#, 9#	
Hardware Version:	V2.1	
Software Version:	V1.0.1	
Modulation Technology:	DSSS, OFDM, OFDMA	
Modulation Type:	Refer to section 2.4.1	
Wireless Technology:	802.11b, 802.11g, 802.11n (HT20), 802.11ax (HEW20)	
Operating Frequency Range:	2412MHz–2462MHz	
Antenna Type:	FPC Antenna	
Antenna Gain (dBi):	5.53dBi	
Accessory Information:	Battery	
	Brand Name:	FJD Trion
	Model No.:	BP0030-3
	Serial No.:	N/A
	Rated Capacity:	3000mAh
	Rated Voltage:	10.8V
	Charge Limit:	12.6V
	Manufacturer:	FJ Dynamics Technology (Fujian) Co., Ltd.
	AC Adapter	
	Brand Name:	Huizhou Fujia
	Model No.:	FJ-GN265C87N
	Serial No.:	N/A
	Rated Output:	5V=3A, 9V=3A, 12V=3A, 15V=3.2A, 20V=5A



REPORT No.: SZ25020189W03

	Rated Input:	100-240V~50/60Hz, 1.5A
	Manufacturer:	Huizhou Fujia Appliance Tech. Co.,Ltd.

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate	RU Size
802.11b	20	DSSS	DBPSK	1/2/5.5/11Mbps	N/A
			DQPSK		
			CCK		
802.11g	20	OFDM	BPSK	6/9/12/18/24/36/48/54Mbps	N/A
			QPSK		
			16QAM		
			64QAM		
802.11n	20 (HT20)	OFDM	BPSK	MCS0~MCS7	N/A
			QPSK		
			16QAM		
			64QAM		
802.11ax	20 (HEW20)	OFDM/ OFDMA	BPSK	MSC0~MCS11	N/A
			QPSK		
			16QAM		
			64QAM		
			256QAM		
			1024QAM		

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

Note2: The RF signal transmission of EUT is controlled by the build-in engineering mode which is provided by the manufacturer. The recorded power setting value is the maximum that the engineering mode has configuration during testing.


Note3: The RU allocation of 802.11ax mode, only full ru is supported.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement



2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☒ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☐ On-board antenna	☒ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak and Average Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum conducted output power of the intentional radiator shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in above of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2. Test Procedures

The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 and A.3 in this report.



3.4.6 dB Bandwidth

3.4.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.4.1.Test Procedures

KDB 558074 Section 8.2 was used in order to prove compliance.

3.4.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.3.Test Result

Refer to Annex A.4 in this report.



3.5. Conducted Spurious Emissions and Band Edge

3.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.5.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.6. Power Spectral Density

3.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 30kHz
- d) Set VBW to 100kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level and recorded as PD
- j) Use below formula to calculate the Conducted PSD value that at specified RBW:

Conducted PSD = PD - 10lg(30k/3k)

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.7 in this report.

3.7. Conducted Emission

3.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.7.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.7.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.7.4. Test Result

Refer to Annex A.8 in this report.

3.8. Restricted Frequency Bands

3.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.8.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.8.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.8.4. Test Result

Refer to Annex A.9 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4.Test Result

Refer to Annex A.10 in this report.



Annex A Test Data and Result


A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	99.83	0.01	0.12
NVNT	b	2437	Ant1	98.9	0.05	0.12
NVNT	b	2462	Ant1	98.92	0.05	0.12
NVNT	g	2412	Ant1	98.66	0.06	0.48
NVNT	g	2437	Ant1	98.66	0.06	0.48
NVNT	g	2462	Ant1	98.66	0.06	0.48
NVNT	n20	2412	Ant1	93.04	0.31	0.76
NVNT	n20	2437	Ant1	93.04	0.31	0.76
NVNT	n20	2462	Ant1	92.9	0.32	0.76
NVNT	ax20	2412	Ant1	91.25	0.4	0.98
NVNT	ax20	2437	Ant1	91.25	0.4	0.98
NVNT	ax20	2462	Ant1	91.25	0.4	0.98




Test Graphs


Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1




Duty Cycle NVNT g 2412MHz Ant1






Duty Cycle NVNT g 2437MHz Ant1




Duty Cycle NVNT g 2462MHz Ant1







Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2437MHz Ant1




Duty Cycle NVNT n20 2462MHz Ant1




Duty Cycle NVNT ax20 2412MHz Ant1



Duty Cycle NVNT ax20 2437MHz Ant1



Duty Cycle NVNT ax20 2462MHz Ant1




**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	22.08	0	22.08	0.16144	30	Pass
NVNT	b	2437	Ant1	22.44	0	22.44	0.17539	30	Pass
NVNT	b	2462	Ant1	23.14	0	23.14	0.20606	30	Pass
NVNT	g	2412	Ant1	27.29	0	27.29	0.5358	30	Pass
NVNT	g	2437	Ant1	27.66	0	27.66	0.58345	30	Pass
NVNT	g	2462	Ant1	28.13	0	28.13	0.65013	30	Pass
NVNT	n20	2412	Ant1	27.15	0	27.15	0.5188	30	Pass
NVNT	n20	2437	Ant1	27.54	0	27.54	0.56754	30	Pass
NVNT	n20	2462	Ant1	27.93	0	27.93	0.62087	30	Pass
NVNT	ax20	2412	Ant1	28.21	0	28.21	0.66222	30	Pass
NVNT	ax20	2437	Ant1	28.36	0	28.36	0.68549	30	Pass
NVNT	ax20	2462	Ant1	28.98	0	28.98	0.79068	30	Pass




Test Graphs


Peak Power NVNT b 2412MHz Ant1




Peak Power NVNT b 2437MHz Ant1




Peak Power NVNT b 2462MHz Ant1




Peak Power NVNT g 2412MHz Ant1




Peak Power NVNT g 2437MHz Ant1




Peak Power NVNT g 2462MHz Ant1



Peak Power NVNT n20 2412MHz Ant1




Peak Power NVNT n20 2437MHz Ant1







Peak Power NVNT n20 2462MHz Ant1




Peak Power NVNT ax20 2412MHz Ant1



Peak Power NVNT ax20 2437MHz Ant1



Peak Power NVNT ax20 2462MHz Ant1




**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	19.53	0.01	19.54	0.08995	30	Pass
NVNT	b	2437	Ant1	19.92	0.05	19.97	0.09931	30	Pass
NVNT	b	2462	Ant1	20.61	0.05	20.66	0.11641	30	Pass
NVNT	g	2412	Ant1	19.66	0.06	19.72	0.09376	30	Pass
NVNT	g	2437	Ant1	20.02	0.06	20.08	0.10186	30	Pass
NVNT	g	2462	Ant1	20.48	0.06	20.54	0.11324	30	Pass
NVNT	n20	2412	Ant1	19.22	0.31	19.53	0.08974	30	Pass
NVNT	n20	2437	Ant1	19.6	0.31	19.91	0.09795	30	Pass
NVNT	n20	2462	Ant1	20.08	0.32	20.4	0.10965	30	Pass
NVNT	ax20	2412	Ant1	19.37	0.4	19.77	0.09484	30	Pass
NVNT	ax20	2437	Ant1	19.65	0.4	20.05	0.10116	30	Pass
NVNT	ax20	2462	Ant1	20.19	0.4	20.59	0.11455	30	Pass




Test Graphs


Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1




Average Power NVNT b 2462MHz Ant1




Average Power NVNT g 2412MHz Ant1



Average Power NVNT g 2437MHz Ant1




Average Power NVNT g 2462MHz Ant1







Average Power NVNT n20 2412MHz Ant1




Average Power NVNT n20 2437MHz Ant1




Average Power NVNT n20 2462MHz Ant1




Average Power NVNT ax20 2412MHz Ant1



Average Power NVNT ax20 2437MHz Ant1



Average Power NVNT ax20 2462MHz Ant1



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	8.041	0.5	Pass
NVNT	b	2437	Ant1	7.563	0.5	Pass
NVNT	b	2462	Ant1	7.521	0.5	Pass
NVNT	g	2412	Ant1	16.33	0.5	Pass
NVNT	g	2437	Ant1	16.34	0.5	Pass
NVNT	g	2462	Ant1	16.34	0.5	Pass
NVNT	n20	2412	Ant1	16.94	0.5	Pass
NVNT	n20	2437	Ant1	17.55	0.5	Pass
NVNT	n20	2462	Ant1	17.55	0.5	Pass
NVNT	ax20	2412	Ant1	18.55	0.5	Pass
NVNT	ax20	2437	Ant1	18.4	0.5	Pass
NVNT	ax20	2462	Ant1	18.55	0.5	Pass



Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1




-6dB Bandwidth NVNT g 2437MHz Ant1




-6dB Bandwidth NVNT g 2462MHz Ant1




-6dB Bandwidth NVNT n20 2412MHz Ant1




-6dB Bandwidth NVNT n20 2437MHz Ant1




-6dB Bandwidth NVNT n20 2462MHz Ant1




-6dB Bandwidth NVNT ax20 2412MHz Ant1



-6dB Bandwidth NVNT ax20 2437MHz Ant1



-6dB Bandwidth NVNT ax20 2462MHz Ant1



**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-40.58	-20	Pass
NVNT	b	2437	Ant1	-40.51	-20	Pass
NVNT	b	2462	Ant1	-41.27	-20	Pass
NVNT	g	2412	Ant1	-36.78	-20	Pass
NVNT	g	2437	Ant1	-37.35	-20	Pass
NVNT	g	2462	Ant1	-36.86	-20	Pass
NVNT	n20	2412	Ant1	-37.06	-20	Pass
NVNT	n20	2437	Ant1	-36.45	-20	Pass
NVNT	n20	2462	Ant1	-36.97	-20	Pass
NVNT	ax20	2412	Ant1	-36.49	-20	Pass
NVNT	ax20	2437	Ant1	-37.36	-20	Pass
NVNT	ax20	2462	Ant1	-37.86	-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref




Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref




Tx. Spurious NVNT b 2437MHz Ant1 Emission




Tx. Spurious NVNT b 2462MHz Ant1 Ref




Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref




Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref




Tx. Spurious NVNT g 2437MHz Ant1 Emission



Tx. Spurious NVNT g 2462MHz Ant1 Ref




Tx. Spurious NVNT g 2462MHz Ant1 Emission



Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission



Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Tx. Spurious NVNT n20 2437MHz Ant1 Emission




Tx. Spurious NVNT n20 2462MHz Ant1 Ref




Tx. Spurious NVNT n20 2462MHz Ant1 Emission



Tx. Spurious NVNT ax20 2412MHz Ant1 Ref




Tx. Spurious NVNT ax20 2412MHz Ant1 Emission



Tx. Spurious NVNT ax20 2437MHz Ant1 Ref




Tx. Spurious NVNT ax20 2437MHz Ant1 Emission



Tx. Spurious NVNT ax20 2462MHz Ant1 Ref



Tx. Spurious NVNT ax20 2462MHz Ant1 Emission



**A.6. Band Edge**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-47.86	-20	Pass
NVNT	b	2462	Ant1	-55.81	-20	Pass
NVNT	g	2412	Ant1	-27.45	-20	Pass
NVNT	g	2462	Ant1	-37.03	-20	Pass
NVNT	n20	2412	Ant1	-28.58	-20	Pass
NVNT	n20	2462	Ant1	-36.32	-20	Pass
NVNT	ax20	2412	Ant1	-27.07	-20	Pass
NVNT	ax20	2462	Ant1	-33.16	-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref




Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission



Band Edge NVNT ax20 2412MHz Ant1 Ref



Band Edge NVNT ax20 2412MHz Ant1 Emission



Band Edge NVNT ax20 2462MHz Ant1 Ref



Band Edge NVNT ax20 2462MHz Ant1 Emission



**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-1.53	0	-1.53	8	Pass
NVNT	b	2437	Ant1	-2.9	0	-2.9	8	Pass
NVNT	b	2462	Ant1	-2.58	0	-2.58	8	Pass
NVNT	g	2412	Ant1	-5.44	0	-5.44	8	Pass
NVNT	g	2437	Ant1	-5.87	0	-5.87	8	Pass
NVNT	g	2462	Ant1	-5.15	0	-5.15	8	Pass
NVNT	n20	2412	Ant1	-5.07	0	-5.07	8	Pass
NVNT	n20	2437	Ant1	-6.29	0	-6.29	8	Pass
NVNT	n20	2462	Ant1	-6.11	0	-6.11	8	Pass
NVNT	ax20	2412	Ant1	-6.38	0	-6.38	8	Pass
NVNT	ax20	2437	Ant1	-6.24	0	-6.24	8	Pass
NVNT	ax20	2462	Ant1	-5.92	0	-5.92	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1



PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1





PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



PSD NVNT ax20 2412MHz Ant1





PSD NVNT ax20 2437MHz Ant1



PSD NVNT ax20 2462MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+DATA Cable+WIFI TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1905	48.67	30.90	79.00	66.00	Line	PASS
2	0.5685	39.38	32.33	73.00	60.00		PASS
3	1.2119	25.07	19.49	73.00	60.00		PASS
4	3.7272	17.73	9.40	73.00	60.00		PASS
5	10.2753	16.60	10.31	73.00	60.00		PASS
6	23.7636	13.47	8.32	73.00	60.00		PASS



(N Phase)


No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1770	43.84	26.62	79.00	66.00	Neutral	PASS
2	0.5550	23.37	18.57	73.00	60.00		PASS
3	1.9004	21.86	16.09	73.00	60.00		PASS
4	5.1274	15.90	9.72	73.00	60.00		PASS
5	10.5129	16.03	10.02	73.00	60.00		PASS
6	20.4895	14.03	8.38	73.00	60.00		PASS

A.9. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Vertical) was recorded in this test report.

Note 2 All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.


802.11b Mode



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2362.98	8.7	46.14	37.470	54.00	7.86	150	322	AV	PASS
2368.84	24.6	62.10	37.470	74.00	11.90	150	322	PK	PASS
2371.22	8.7	46.15	37.470	54.00	7.85	150	219	AV	PASS
2378.12	26.1	63.53	37.480	74.00	10.47	150	331	PK	PASS
2387.58	8.6	46.09	37.490	54.00	7.91	150	265	AV	PASS
2388.43	25.0	62.46	37.490	74.00	11.54	150	270	PK	PASS



Plot for Channel 11



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2485.28	22.1	60.32	38.270	74.00	13.68	150	310	PK	PASS
2486.05	9.5	47.78	38.280	54.00	6.22	150	284	AV	PASS
2487.56	10.5	48.76	38.270	54.00	5.24	150	284	AV	PASS
2489.36	10.2	48.48	38.260	54.00	5.52	150	291	AV	PASS
2490.18	21.7	59.99	38.270	74.00	14.01	150	322	PK	PASS
2493.88	20.8	59.08	38.250	74.00	14.92	150	298	PK	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis (X axis) test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded.




802.11b Mode

Plot for Channel 1




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
36.31	56.7	27.22	-29.500	40.00	12.78	150	19	PK	PASS
90.48	57.9	26.41	-31.470	43.50	17.09	150	86	PK	PASS
300.01	59.0	33.53	-25.450	46.00	12.47	150	134	PK	PASS
449.98	66.2	44.67	-21.540	46.00	1.33	150	60	PK	PASS
749.97	52.1	37.29	-14.840	46.00	8.71	150	236	PK	PASS
830.63	49.7	35.19	-14.460	46.00	10.81	150	284	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2411.48	47.4	52.77	5.390	-	-	150	268	AV	NA
3762.02	50.5	42.07	-8.420	74.00	31.93	150	23	PK	PASS
4158.46	45.9	37.99	-7.900	54.00	16.01	150	354	AV	PASS
4824.48	51.6	46.59	-4.990	54.00	7.41	150	314	AV	PASS
6432.53	39.6	40.98	1.390	54.00	13.02	150	116	AV	PASS
14689.62	27.7	48.30	20.570	54.00	5.70	150	128	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
34.75	56.5	26.48	-29.970	40.00	13.52	150	344	PK	PASS
130.40	59.5	27.64	-31.850	43.50	15.86	150	73	PK	PASS
300.01	64.2	38.77	-25.450	46.00	7.23	150	269	PK	PASS
449.98	60.2	38.70	-21.540	46.00	7.30	150	324	PK	PASS
593.99	52.0	34.39	-17.650	46.00	11.61	150	87	PK	PASS
750.02	55.1	40.29	-14.840	46.00	5.71	150	337	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1950.59	38.4	40.63	2.200	54.00	13.37	150	286	AV	PASS
2411.48	40.1	45.49	5.390	-	-	150	318	AV	NA
3450.44	45.8	36.40	-9.420	54.00	17.60	150	279	AV	PASS
4824.48	50.3	45.26	-4.990	54.00	8.74	150	266	AV	PASS
7187.26	35.0	40.03	4.990	54.00	13.97	150	318	AV	PASS
14687.91	27.3	47.90	20.570	54.00	6.10	150	266	AV	PASS

Plot for Channel 6




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
90.53	57.1	25.64	-31.450	43.50	17.86	150	97	PK	PASS
300.01	58.4	32.97	-25.450	46.00	13.03	150	50	PK	PASS
449.98	66.1	44.53	-21.540	46.00	1.47	150	267	PK	PASS
593.99	51.7	34.00	-17.650	46.00	12.00	150	144	PK	PASS
749.97	50.8	35.91	-14.840	46.00	10.09	150	247	PK	PASS
899.99	44.3	32.75	-11.580	46.00	13.25	150	130	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1650.53	31.9	31.78	-0.070	54.00	22.22	150	77	AV	PASS
2434.29	45.4	51.12	5.740	-	-	150	289	AV	NA
4158.46	44.4	36.49	-7.900	54.00	17.51	150	9	AV	PASS
4874.62	57.7	52.77	-4.970	54.00	1.23	150	314	AV	PASS
7310.27	39.6	43.79	4.180	54.00	10.21	150	234	AV	PASS
14783.05	27.8	47.70	19.880	54.00	6.30	150	234	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
90.48	57.4	25.96	-31.470	43.50	17.54	150	199	PK	PASS
129.87	60.5	28.60	-31.930	43.50	14.90	150	199	PK	PASS
300.01	67.2	41.79	-25.450	46.00	4.21	150	6	PK	PASS
449.98	63.8	42.24	-21.540	46.00	3.76	150	302	PK	PASS
593.99	58.2	40.51	-17.650	46.00	5.49	150	6	PK	PASS
749.97	58.8	43.97	-14.840	46.00	2.03	150	289	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)


Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
1950.59	38.5	40.69	2.200	54.00	13.31	150	291	AV	PASS
2434.29	38.1	43.88	5.740	-	-	150	318	AV	NA
3762.45	49.4	40.95	-8.420	54.00	13.05	150	157	AV	PASS
4158.46	45.9	37.95	-7.900	54.00	16.05	150	104	AV	PASS
4874.20	57.4	52.48	-4.960	54.00	1.52	150	264	AV	PASS
7310.27	39.0	43.19	4.180	54.00	10.81	150	237	AV	PASS
14691.76	27.3	47.87	20.580	54.00	6.13	150	264	AV	PASS

Plot for Channel 11




(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
36.35	57.1	27.61	-29.480	40.00	12.39	150	256	PK	PASS
90.53	56.9	25.41	-31.450	43.50	18.09	150	195	PK	PASS
132.92	58.6	26.75	-31.880	43.50	16.75	150	2	PK	PASS
300.01	53.0	27.56	-25.450	46.00	18.44	150	229	PK	PASS
449.98	63.2	41.67	-21.540	46.00	4.33	150	86	PK	PASS
593.99	53.0	35.32	-17.650	46.00	10.68	150	290	PK	PASS
990.01	52.3	41.83	-10.510	54.00	12.17	150	201	PK	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2461.49	46.9	52.81	5.940	-	-	150	286	AV	NA
3450.44	43.1	33.66	-9.420	54.00	20.34	150	48	AV	PASS
3693.45	42.7	33.51	-9.210	54.00	20.49	150	246	AV	PASS
4924.34	55.4	50.45	-4.980	54.00	3.55	150	326	AV	PASS
7388.27	38.7	43.41	4.690	54.00	10.59	150	314	AV	PASS
14691.33	26.9	47.45	20.580	54.00	6.55	150	167	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
36.31	54.7	25.19	-29.500	40.00	14.81	150	288	PK	PASS
90.48	54.0	22.57	-31.470	43.50	20.93	150	173	PK	PASS
150.00	61.2	29.77	-31.460	43.50	13.73	150	336	PK	PASS
300.01	56.8	31.34	-25.450	46.00	14.66	150	98	PK	PASS
593.99	50.0	32.38	-17.650	46.00	13.62	150	194	PK	PASS
750.02	53.3	38.48	-14.840	46.00	7.52	150	281	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2461.49	38.6	44.53	5.940	-	-	150	323	AV	NA
3150.43	47.4	36.97	-10.390	54.00	17.03	150	103	AV	PASS
3762.45	46.1	37.67	-8.420	54.00	16.33	150	23	AV	PASS
4158.46	45.5	37.59	-7.900	54.00	16.41	150	23	AV	PASS
4924.34	56.3	51.35	-4.980	54.00	2.65	150	262	AV	PASS
7387.41	38.0	42.63	4.680	54.00	11.37	150	235	AV	PASS
14689.62	26.7	47.30	20.570	54.00	6.70	150	222	AV	PASS

END OF REPORT