

TEST REPORT

Product Name : LED Wash Light
Model Number : NEO fx
FCC ID : 2A2LS-NEOFX

Prepared for : ROXX GmbH
Address : Hansestrasse No. 91 | 51149 Cologne | Germany

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2506270156E02102R
Date(s) of Tests : April 09, 2025 to July 28, 2025
Date of issue : July 28, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. FACILITIES AND ACCREDITATIONS	6
FACILITIES	6
LABORATORY ACCREDITATIONS AND LISTINGS	6
4. TEST REQUIREMENT	7
RF EXPOSURE EVALUATION	7
FRIIS TRANSMISSION FORMULA: $Pd = (P_{out} * G) \backslash (4 * \pi * R^2)$	7
5. MEASUREMENT RESULT	8



1. TEST RESULT CERTIFICATION

Applicant : ROXX GmbH
Address : Hansestrasse No. 91 | 51149 Cologne | Germany
Manufacturer : ROXX GmbH
Address : Hansestrasse No. 91 | 51149 Cologne | Germany
EUT : LED Wash Light
Model Name : NEO fx
Trademark : 

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093, 1.1307(b)(1)	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093, 1.1307(b)(1).

The test results of this report relate only to the tested sample identified in this report

Date of Test : April 09, 2025 to July 28, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2506270156E02102R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	LED Wash Light
Model Number:	NEO fx
Sample:	1#
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	-2.21 dBm(0.000601 W)
Antenna Gain:	2.45 dBi
Power supply:	AC 100-240V~50/60Hz
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at:

EMTEK (SHENZHEN) CO., LTD.

Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description	
EMC Lab.	: Accredited by CNAS The Certificate Registration Number is L2291. The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017) Accredited by FCC Designation Number: CN1204 Test Firm Registration Number: 882943 Accredited by A2LA The Certificate Number is 4321.01. Accredited by Industry Canada The Conformity Assessment Body Identifier is CN0008
Name of Firm	: EMTEK (SHENZHEN) CO., LTD.
Site Location	: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

4. Test Requirement

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

5. Measurement Result

Antenna gain:
2.4G: 2.45 dBi

Mode	Frequen cy (MHz)	Output Power(dB m)	E.I.R.P(dB m)	Target Power W/toleran ce (dBm)	Max tune up power(dB m) tolerance	Max tuneup power(m W) tolerance	Power Density at R=20cm (mW/cm2)	Limit (mW/ cm2)
GFSK	2402	-0.7	1.75	1±1	2	1.58	0.000554	1
	2441	-1.84	0.61	0±1	1	1.26	0.000440	1
	2480	-3.6	-1.15	-2±1	-1	0.79	0.000278	1

According to KDB 447498, no stand-alone required for Thread & BLE antenna, and no simultaNEO fxus SAR measurement is required.

*** End of Report ***