

FCC ID: 2A2LV-AG40

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

Operation Frequency: 2402MHz~2480MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: FPCB antenna

WIFI antenna gain: -0.7dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(-0.7/10)}=0.85$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm^2)	(mW/cm ²)
				(dBm)	(mW)	Numeric		
2402	GFSK	3.011	4±1	5	3.162278	0.85	0.00053	1
2441		4.208	4±1	5	3.162278	0.85	0.00053	1
2480		3.049	4±1	5	3.162278	0.85	0.00053	1
2402	π/4-DQPSK,	3.959	4.5±1	5.5	3.548134	0.85	0.00060	1
2441		5.059	4.5±1	5.5	3.548134	0.85	0.00060	1
2480		3.98	4.5±1	5.5	3.548134	0.85	0.00060	1
2402	8DPSK	3.351	4±1	5	3.162278	0.85	0.00053	1
2441		4.388	4±1	5	3.162278	0.85	0.00053	1
2480		3.63	4±1	5	3.162278	0.85	0.00053	1
2402	BLE(GFSK)	-2.886	-2±1	-1	0.794328	0.85	0.00013	1
2440		-1.838	-2±1	-1	0.794328	0.85	0.00013	1
2480		-3.561	-3±1	-2	0.630957	0.85	0.00011	1

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

WIFI 802.11n HT40:2422-2452MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: FPCB antenna

WIFI antenna gain: -0.7dBi;

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

antenna gain Numeric= $10^{(\text{dBi}/10)}=10^{(-0.7/10)}=0.85$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm^2)	(mW/cm ²)
				(dBm)	(mW)	Numeric		
2412	802.11b	13.23	14±1	15	31.62278	0.85	0.00535	1
2437		14.06	14±1	15	31.62278	0.85	0.00535	1
2462		13.65	14±1	15	31.62278	0.85	0.00535	1
2412	802.11g	12.35	12±1	13	19.95262	0.85	0.00337	1
2437		12.87	12±1	13	19.95262	0.85	0.00337	1
2462		12.66	12±1	13	19.95262	0.85	0.00337	1
2412	802.11n H20	12.31	12±1	13	19.95262	0.85	0.00337	1
2437		12.87	12±1	13	19.95262	0.85	0.00337	1
2462		12.69	12±1	13	19.95262	0.85	0.00337	1
2422	802.11n H40	13.01	13±1	14	25.11886	0.85	0.00425	1
2437		12.35	13±1	14	25.11886	0.85	0.00425	1
2452		12.44	13±1	14	25.11886	0.85	0.00425	1

5G WIFI:

Operation Frequency: WIFI 802.11a/ac/n(HT20): 5180-5240MHz; 5745-5825MHz;
WIFI 802.11ac/n(HT40): 5190-5230MHz; 5755-5795MHz; WIFI 802.11ac80:5210-5210MHz;
5775-5775MHz

Power density limited: 1mW/ cm

Antenna Type: FPCB antenna

WIFI Antenna gain: 3dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(3/10)}=2$

5.2G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	Numeric		
5180	802.11a	11.12	12±1	13	19.95262	2	0.00794	1
5200		11.28	12±1	13	19.95262	2	0.00794	1
5240		12.1	12±1	13	19.95262	2	0.00794	1
5180	802.11n H20	11.05	11±1	12	15.84893	2	0.00631	1
5200		10.22	11±1	12	15.84893	2	0.00631	1
5240		11.19	11±1	12	15.84893	2	0.00631	1
5190	802.11n H40	10.07	11±1	12	15.84893	2	0.00631	1
5230		11.08	11±1	12	15.84893	2	0.00631	1
5180	802.11ac 20	10.03	10±1	11	12.58925	2	0.00501	1
5200		10.22	10±1	11	12.58925	2	0.00501	1
5240		10.96	10±1	11	12.58925	2	0.00501	1
5190	802.11ac 40	9.98	10.5±1	11.5	14.13	2	0.00562	1
5230		11.23	10.5±1	11.5	14.13	2	0.00562	1
5210	802.11ac 80	11.43	11±1	12	15.84893	2	0.00631	1

5.8G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	Numeric		
5745	802.11a	11.01	11±1	12	15.84893	2	0.00631	1
5785		10.62	11±1	12	15.84893	2	0.00631	1
5825		11.01	11±1	12	15.84893	2	0.00631	1
5745	802.11n20	9.62	9±1	10	10	2	0.00398	1
5785		9.58	9±1	10	10	2	0.00398	1
5825		9.91	9±1	10	10	2	0.00398	1
5755	802.11n40	9.55	9±1	10	10	2	0.00398	1
5795		9.69	9±1	10	10	2	0.00398	1
5745	802.11ac 20	9.329	9±1	10	10	2	0.00398	1
5785		9.301	9±1	10	10	2	0.00398	1
5825		9.087	9±1	10	10	2	0.00398	1
5755	802.11ac 40	8.297	8±1	9	7.943282	2	0.00316	1
5795		8.771	8±1	9	7.943282	2	0.00316	1
5775	802.11ac 80	13.437	13±1	14	25.12	2	0.00999	1

5.3G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	Numeric		
5260	802.11a	10.44	10±1	11	12.58925	2	0.00501	1
5280		10.43	10±1	11	12.58925	2	0.00501	1
5320		10.86	10±1	11	12.58925	2	0.00501	1
5260	802.11n H20	9.78	9±1	10	10	2	0.00398	1
5280		9.43	9±1	10	10	2	0.00398	1
5320		9.74	9±1	10	10	2	0.00398	1
5270	802.11n H40	9.23	10±1	11	12.58925	2	0.00501	1
5310		10.19	10±1	11	12.58925	2	0.00501	1
5260	802.11ac 20	9.68	9±1	10	10	2	0.00398	1
5280		9.42	9±1	10	10	2	0.00398	1
5320		9.61	9±1	10	10	2	0.00398	1
5270	802.11ac 40	9.3	10±1	11	12.58925	2	0.00501	1
5310		10.16	10±1	11	12.58925	2	0.00501	1
5290	802.11ac 80	10.31	10±1	11	12.58925	2	0.00501	1

5.6G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain	Power density(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	Gain		
5500	802.11a	10.33	10±1	11	12.58925	2	0.00501	1
5600		10.33	10±1	11	12.58925	2	0.00501	1
5700		10.07	10±1	11	12.58925	2	0.00501	1
5500	802.11n H20	9.23	10±1	11	12.58925	2	0.00501	1
5600		10.31	10±1	11	12.58925	2	0.00501	1
5700		9.97	10±1	11	12.58925	2	0.00501	1
5510	802.11n H40	9.99	9±1	10	10	2	0.00398	1
5590		9.63	9±1	10	10	2	0.00398	1
5670		9.49	9±1	10	10	2	0.00398	1
5500	802.11ac 20	9.13	9±1	10	19.95	2	0.00627	1
5600		9.2	9±1	10	19.95	2	0.00627	1
5700		8.97	9±1	10	19.95	2	0.00627	1
5510	802.11ac 40	9.11	9±1	10	19.95	2	0.00627	1
5590		9.8	9±1	10	19.95	2	0.00627	1
5670		9.67	9±1	10	19.95	2	0.00627	1
5530	802.11ac 80	9.53	9±1	9	19.95	2	0.00627	1
5610		9.25	9±1	9	19.95	2	0.00627	1

Conclusion:

For the max result : $0.00999 \leq 1.0$ for Max Power Density, Compliance the RF Exposure requirement.

Signature:

Date: 2021-07-12



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E,
Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.