

Cover Letter for Wireless Charger

Data:2022-06-19

Dear Sir/Madam,

There's a [socket](#) that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below Wireless Charger with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5 b) requirements.

Applicant:	Cixi Mingye Communication and Electronic Co., Ltd.
Product Description:	Portable multiple socket outlets, non-rewirablewith USB charging and wireless charging
Model No:	AA10704J-4AC1Q2UC AvA1704J-1Q2UC, AvA1704J-1H1Q1R2UC, AsA1704J-4AC1Q2UC, AsA1704J-1Q2UC, AsA1704J-1H1Q1R2UC
FCC ID:	2A2N8-171Q2UC

Requirement	Technical	Result
1) Power transfer frequency is less than 1 MHz	111-200kHz	Complied
2) Output power from each primary coil is less than 15 watts	5W	Complied
3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils	Model "AA10704J-4AC1Q" contains one wireless charging module, the module contains only one coil.	Complied
4) Client device is inserted in or placed directly in contact with the transmitter	Placed directly in transmitter	Complied
5) Mobile exposure conditions only	Mobile	Complied
6) Aggregate leakage fields at 15 cm surrounding the device and 20cm above the top surface from all simultaneous transmitting coils	H-field strengths at 15 cm surrounding the device and 20cm above the top surface	Complied

are demonstrated to be less than 50% of the MPE limit.	from all simultaneous transmitting coils is less than 50% of the MPE limit.	
--	---	--

Sincerely,

By:

Iris.yu

(Signature)

Iris.yu

(Print name)