

Cixi Mingye Communication and Electronic Co.,Ltd.

RF TEST REPORT

Report Type:

FCC Part 15C RF report

Model:

53-2AC1Q,53-2AC1Q-01

REPORT NUMBER:

240400243SHA-001

ISSUE DATE:

July 5, 2024

DOCUMENT CONTROL NUMBER:

TTRFFCCPART15C_V1 © 2018 Intertek



Applicant : Cixi Mingye Communication and Electronic Co.,Ltd.
West Industrial District,Guanhaiwei Town,CIXI CITY Zhejiang Province
315315

Manufacturer : Cixi Mingye Communication and Electronic Co.,Ltd.
West Industrial District,Guanhaiwei Town,CIXI CITY Zhejiang Province
315315

Manufacturer Site : Cixi Mingye Communication and Electronic Co.,Ltd.
West Industrial District,Guanhaiwei Town,CIXI CITY Zhejiang Province
315315

Type/Model: : 53-2AC1Q,53-2AC1Q-01

FCC ID : 2A2N8-532AC1Q

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2023): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:

Project Engineer
Dylan Tang

REVIEWED BY:

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 TECHNICAL SPECIFICATION.....	6
1.3 DESCRIPTION OF TEST FACILITY	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST.....	8
2.5 TEST ENVIRONMENT CONDITION:.....	8
2.6 INSTRUMENT LIST	9
2.7 MEASUREMENT UNCERTAINTY.....	10
3 RADIATED EMISSIONS	11
3.1 LIMIT	11
3.2 MEASUREMENT PROCEDURE	11
3.3 TEST CONFIGURATION	12
3.4 TEST RESULTS OF RADIATED EMISSIONS	14
4 CONDUCTED EMISSIONS	17
4.1 LIMIT	17
4.2 TEST CONFIGURATION	17
4.3 MEASUREMENT PROCEDURE	18
4.4 TEST RESULTS OF CONDUCTED EMISSIONS.....	19

Revision History

Report No.	Version	Description	Issued Date
240400243SHA-001	Rev. 01	Initial issue of report	July 5, 2024

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Radiated emissions	15.209	Pass
Conducted emissions	15.207	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Wireless charger
Type/Model:	53-2AC1Q,53-2AC1Q-01
Description of EUT:	The EUT is a Wireless charger which supports Wireless Charger function. 53-2AC1Q-01 has input type C cable, and 53-2AC1Q does not have input type C cable, the PCB is the same, so choose 53-2AC1Q-01 to test as representative.
Rating:	Input:5.0V 3A, 9.0V 2.22A,12.0V 1.67A Output Type A + Type C: 5VDC, 3A Wireless Charger:15W
EUT type:	☒ Table top ☐ Floor standing
Software Version:	V1.1
Hardware Version:	V2.0 for 53-2AC1Q-01 V1.1 for 53-2AC1Q
Sample received date:	December 1, 2023
Date of test:	December 1, 2023 ~ May 22, 2024

1.2 Technical Specification

Frequency Range:	111kHz – 205kHz
Modulation:	FSK
Antenna:	Coil antenna

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2023)

ANSI C63.10 (2020)

2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Brand and Model	Description
1	Wireless load	Iphone X	100% power level
2	Wireless load	Iphone X	50% power level
3	Wireless load	Iphone X	0% power level

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	25°C	54% RH
Power line conducted emission	24°C	54% RH

TEST REPORT

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESR7	EC 6194	2024-02-08
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2024-11-10
☐	A.M.N.	R&S	ENV4200	EC 3558	2024-06-05
☒	Attenuator	Huaxiang	Ts5-10db-6g	EC 6194-1	2024-12-08
☒	Shielded room	Zhongyu	-	EC 2838	2024-01-11
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2024-08-24
☒	Test Receiver	R&S	ESR	EC6501	2024-09-05
☒	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2024-08-23
☐	Horn antenna	Tonscend	bha9120d	EC 6432-2	2024-02-15
☐	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2024-12-08
☐	Horn antenna	ETS	3117	EC 4792-1	2024-08-28
☐	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2024-07-29
☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2024-07-16
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2024-07-08
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2024-03-24
☒	Pressure meter	YM3	Shanghai Mengde	EC 3320	2024-08-16

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Expanded Uncertainty (k=2)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.90 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

TEST REPORT

3 Radiated emissions

Test result: Pass

3.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

3.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are

TEST REPORT

set to make the measurement.


- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were evaluated and the worst-case emissions were reported

3.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:



TEST REPORT


3.4 Test Results of Radiated Emissions

EUT was tested with empty load, half load and full load, the full load is the worst case and we listed the results in the report.


Test data below 30MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector	Remark
X	0.1254	73.9	20.1	105.6	31.7	PK	Fundamental
X	0.0729	57.2	20.1	110.3	53.1	PK	Spurious
X	0.5055	63.1	20.2	73.5	10.4	PK	Spurious
X	0.6585	58.7	20.2	71.2	12.5	PK	Spurious
X	0.7845	54.3	20.1	69.7	15.5	PK	Spurious
X	0.9375	43.5	20.1	68.2	24.7	PK	Spurious
X	10.356	44.0	20.4	69.5	25.5	PK	Spurious
Y	0.1254	71.4	20.1	105.6	34.2	PK	Fundamental
Y	0.0099	67.3	20.1	127.7	60.3	PK	Spurious
Y	0.5100	62.7	20.2	73.5	10.7	PK	Spurious
Y	0.6090	61.2	20.2	71.9	10.8	PK	Spurious
Y	0.7935	55.1	20.1	69.6	14.5	PK	Spurious
Y	1.118	39.7	20.1	66.7	27.0	PK	Spurious
Y	7.526	37.9	20.4	69.5	31.6	PK	Spurious
Z	0.1254	73.0	20.1	105.6	32.6	PK	Fundamental
Z	0.0733	54.2	20.1	110.3	56.1	PK	Spurious
Z	0.5370	62.7	20.2	73.0	10.3	PK	Spurious
Z	0.6270	57.7	20.2	71.7	14.0	PK	Spurious
Z	0.7305	52.9	20.1	70.3	17.4	PK	Spurious
Z	0.8745	46.5	20.1	68.8	22.2	PK	Spurious
Z	7.332	44.9	20.4	69.5	24.6	PK	Spurious

Horizontal



Vertical



TEST REPORT

Test data from 30MHz to 1000MHz:

Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
H	35.238	19.1	13.0	40.0	20.9	QP
H	84.902	23.4	9.9	40.0	16.6	QP
H	168.128	30.6	14.0	43.5	12.9	QP
H	180.447	25.4	13.1	43.5	18.1	QP
H	202.951	27.8	11.4	43.5	15.7	QP
H	875.743	31.9	25.9	46.0	14.1	QP
V	31.067	29.0	12.2	40.0	11.0	QP
V	35.044	32.5	12.9	40.0	7.5	QP
V	44.744	32.8	14.1	40.0	7.2	QP
V	97.609	27.5	9.8	43.5	16.0	QP
V	165.994	37.0	14.1	43.5	6.5	QP
V	177.052	31.3	13.3	43.5	12.2	QP

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

4 Conducted emissions


Test result: **PASS**

4.1 Limit

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

4.2 Test Configuration



TEST REPORT**4.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.



The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT

4.4 Test Results of Conducted Emissions

EUT was tested with empty load, half load and full load, the full load is the worst case and we listed the results in the report.

Test Curve:



TEST REPORT

Test Data:

No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Phase
1	150.000kHz	66.0	44.4	21.6	38.2	6.2	QP	L1
2	181.500kHz	64.4	48.4	16.0	42.2	6.2	QP	L1
3	217.500kHz	62.9	43.0	19.9	36.7	6.3	QP	L1
4	514.500kHz	56.0	40.8	15.2	34.6	6.2	QP	L1
5	564.000kHz	56.0	43.7	12.3	37.4	6.3	QP	L1
6	3.152MHz	56.0	37.1	18.9	30.8	6.3	QP	L1
7	154.500kHz	65.8	45.0	20.7	38.7	6.3	QP	N
8	181.500kHz	64.4	48.7	15.7	42.5	6.2	QP	N
9	541.500kHz	56.0	43.0	13.0	36.8	6.2	QP	N
10	672.000kHz	56.0	37.4	18.6	31.1	6.3	QP	N
11	1.163MHz	56.0	35.4	20.6	29.1	6.3	QP	N
12	10.343MHz	60.0	42.1	17.9	35.7	6.4	QP	N
13	550.500kHz	46.0	38.1	7.9	31.8	6.3	AV	L1
14	2.396MHz	46.0	35.1	10.9	28.8	6.3	AV	L1
15	3.152MHz	46.0	31.6	14.4	25.3	6.3	AV	L1
16	3.908MHz	46.0	32.0	14.0	25.6	6.4	AV	L1
17	4.538MHz	46.0	31.2	14.8	24.8	6.4	AV	L1
18	10.838MHz	50.0	36.6	13.4	30.2	6.4	AV	L1
19	559.500kHz	46.0	36.6	9.4	30.4	6.2	AV	N
20	2.270MHz	46.0	34.5	11.5	28.2	6.3	AV	N
21	2.900MHz	46.0	35.3	10.7	29.0	6.3	AV	N
22	3.534MHz	46.0	34.9	11.1	28.6	6.3	AV	N
23	4.164MHz	46.0	35.1	10.9	28.7	6.4	AV	N
24	4.794MHz	46.0	34.7	11.3	28.3	6.4	AV	N

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Reading = Original Receiver Reading + Factor

3. Margin = Limit - Level

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

***** END *****