

MPE ESTIMATION

FCC ID: 2A20E-R3

1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)		
300MHz1.5GHz	F/1500	30		
1.5GHz100GHz	1.0	30		

Note: F= Frequency in MHz

2, Estimation Result

Mode	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm²)
2.4G WiFi	2422	20.33	20±1(21)	125.893	1.2	1.318	0.03301
5.2G WiFi	5190	11.84	11±1(12)	15.849	1.2	1.318	0.00416
5.8G WiFi	5825	12.15	12±1(13)	19.953	1.2	1.318	0.00523

$$Pd = \frac{Pout * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK2105261651-1E/2E/3E, antenna gain=1.2dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.03301 mW/cm² which is< 1.0mW/cm², RF Exposure testing is not required.

Note: the device could not transmit simultaneously in 2.4G and 5G.

----The End-----