

**Cover Letter-Wireless Charger Approval**

Date: 2021-12-27

Gentlemen:

There's a SCX Design Wireless Charger & 4 Hub 2.0 that would like to have your authorization as an Inductive wireless power transfer applications approval.

The specific product as below, SCX Design Wireless Charger & 4 Hub 2.0, with its designed features and specified description, meets special requirements for KDB 680106 D01 section 5.2 requirements.

<b>Company:</b>	SCX DESIGN
<b>Product Name:</b>	SCX Design Wireless Charger & 4 Hub 2.0
<b>Model Number:</b>	H16/32469
<b>FCC ID:</b>	2A2OH-H1630L

<b>KDB 680106 D01 Section 5.2 Requirements</b>	<b>Product Technical Specification</b>	<b>Result</b>
a) Power transfer frequency is less than 1 MHz	120.0KHz – 194.0KHz	Complied
b) Output power from each primary coil is less than or equal to 15 watts.	5W	Complied
c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils		Complied
d) Client device is placed directly in contact with the transmitter.		Complied
e) Mobile exposure conditions only	For inductive applications where the primary does not physically attach to the client, and it is intended for desktop use, the desktop guidance in KDB 680106 D01 may be applied	Complied
f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Please refer to RF exposure report	Complied

Sincerely,

Print Name: Caroline Vanderschooten

Title: purchasing and marketing manager



Signature:

On behalf of Company: SCX DESIGN

Telephone: +33.1.86.95.99.88

E-mail: caroline@scx.design.com