

APPROVAL SHEET

MODEL	FREQUENCY
HW-LORA-N-RSMA	902 ~ 928 MHz



HANWOOL TECHNOLOGY CO., LTD
#1002 IT303-DONG, BUCHONTECHNOPARK III 36-1
SAMJUNG-DONG, OHJUNG-GU, KYOUNG GI-DO, KOREA
TEL.: 032) 624-2555
FAX: 032) 624-2559

ANTENNA SPECIFICATION

1. MODEL: HW-LORA-N-RSMA

2. APPLICATION: This specification is provided for LORA DIPOLE ANTENNA

3 ANTENNA used condition

☐ Portable ☒ Fixing ☐ Movement ☒ Out-door ☒ In-door ☒ Etc()

4. ANTENNA Drawing

Attached Drawing paper

5. Electrical specification and performance

Satisfied next data with real used or similar environment conditions.

No.	ELECTRICAL DATA	SPECIFICATIONS	REMARK
5. 1	FREQUENCY RANGE	902 ~ 928 MHz	
5. 2	IMPEDANCE	50 Ω NOMINAL	
5. 3	V. S. W. R	LESS THAN 1:2.5	
5. 4	GAIN(MAX.)	2.7 dBi	
5. 5	RADIATION PATTERN	OMNI - DIRECTIONAL	
5. 6	POLARIZATION	VERTICAL	

6. Hardware specification and mechanical

No.	MECHANICAL	SPECIFICATIONS	REMARK
6. 1	SLEEVE	NYLON GRASS	BLACK-COLOR
6. 2	COVER	NYLON GRASS	BLACK-COLOR
6. 3	SMA(Male) CONNECTOR	BRASS	Ni-PLATING
6. 4	ANTENNA TOTAL LENGTH	154 $\pm$ 2.0 mm	

7. Reliability test and standards


NO	TEST	TEST Method	Decision
1	High Tem. storage	Temp.: 70℃, 48 Hour	* No transform about antenna
2	High Humidity storage	Temp.: 70℃, Humidity : 95% 72 Hour	
3	Low Tem. storage	Temp.: -40℃, 48 Hour	


8. TEST and Q/C

This specification is according to fixed demands and suitable Hanwool technology Q/C provision.

But it is possible to skip No. 7 demands, after consultation with buyer.

-. VSWR → 902 ~ 928 Mhz





· GAIN → 902Mhz ~ 928Mhz

