

Applicant		MoMagic Technologies Private Limited	
FCC ID :		2A2OT-MMT1211	
Section 15.212 Modular Transmitters			
Request for Single Modular Approval	Yes	Request for Limited Modular Approval	No
SL. No	Requirement	EUT Condition	Comply (Yes/No)
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements	All elements except antenna is inside the Shield CAN	YES
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation	The data rate is 2Mbps with GPSK modulation	YES
3	The modular transmitter must have its own power supply regulation	The MCU on board has its own regulation datasheet of MCU attached	YES
4	The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section	The antenna used is CHIP antenna which is permanently attached to the EUT. No connectors is available on EUT to attach external antenna	YES
5	The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be	EUT is stand alone device. No ferrites is used on powerlines. For testing, adapter board is used which is available commercially.	YES

MoMAGIC Technologies Pvt. Ltd.

I-9, LGF, Lajpat Nagar-3, New Delhi 110 024

Phone: +91-11-49400900, Fax: +91-11-29842450

www.momagic.com Email: rishnik@momagic.com

CIN No. U72200DL2011PTC215210

	unmodified and commercially available (see §15.31(i))		
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number	The EUT is affixed with sticker with FCC ID Label.	YES
A full modular approval may be granted for single or split modular transmitters that do not comply with all of the above requirements, e.g., shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured			

By _____

Signature

Name: Arun Kumar Gupta

Title: Director

On behalf of: MoMAGIC Technologies Private Limited

Phone: +91-11-49400900

MoMAGIC Technologies Pvt. Ltd.

I-9, LGF, Lajpat Nagar-3, New Delhi 110 024

Phone: +91-11-49400900, Fax: +91-11-29842450

www.momagic.com Email: rishnik@momagic.com

CIN No. U72200DL2011PTC215210