


Prüfbericht-Nr.: <i>Test report no.:</i>	IN2500H5 001	Auftrags-Nr.: <i>Order no.:</i>	146989299 0010	Seite 1 von 38 Page 1 of 38
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	2339983	Auftragsdatum: <i>Order date:</i>	2024-11-26	
Auftraggeber: <i>Client:</i>	MOMAGIC TECHNOLOGIES PRIVATE LIMITED 206, FF, PLOT NO. 190-191, NEELKANTH PALACE, 252-A, SANT NAGAR, NEW DELHI 110 065.			
Prüfgegenstand: <i>Test item:</i>	TW1318 BLE MODULE			
Bezeichnung <i>Identification</i>	TW1318	Serien -Nr.: <i>Serial no.:</i>	TW02AC000025010000001	
Auftrags-Inhalt: <i>Order content:</i>	Testing and issue of Test Report with Grant Certificate			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C 15.247, 15.207, 15.205 & 15.209			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2024-12-02			
Prüfmuster-Nr.: <i>Test sample no:</i>	A003878404-001 A003878404-002			
Prüfzeitraum: <i>Testing period:</i>	2024-12-06 - 2024-12-09			
Ort der Prüfung: <i>Place of testing:</i>	Wireless laboratory, Bangalore			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (India) Pvt. Ltd. 27/B, 2nd cross road, Electronic city Phase1, Bangalore-560100, India FCC Test Site Registration No: 496599			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i> 2025-02-05	Ausstellatum: <i>Issue date:</i> 2025-02-05			
Stellung / Position:	Likhithesh M D Senior Engineer	Stellung / Position:	Madhu K.N Assistant Manager	
Sonstiges / Other:	FCC ID: 2A2OT-TW1318			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

v05

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 2 von 38
Page 2 of 38

- | | |
|---|---|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird.</p> <p><i>The decision rule for statements of conformity in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report.</i></p> |

Prüfbericht - Nr.:

Test Report No.:

IN25O0H5 001

Seite 3 von 38

Page 3 of 38

TEST SUMMARY

Test Item	FCC	Result
Maximum conducted (Peak) output power	15.247 (b)(3)	Pass
Maximum Power Spectral Density	FCC 15.247(e)	Pass
DTS Bandwidth	FCC 15.247(a)(2)	Pass
Emissions in non-restricted frequency bands	15.247 (d)	Pass
Spurious Radiated Emissions and Restricted Bands of Operation	15.247 (d) /FCC 15.209 / FCC 15.205	Pass
Conducted Spurious Emission on AC Power lines	FCC 15.207	Pass

Product Category: Electronics Testing

Test Discipline: EMC Test Facility

Prüfbericht - Nr.:
Test Report No.:

IN25O0H5 001

Seite 4 von 38
Page 4 of 38

REVISION HISTORY OF THIS REPORT

Report Number	Version	Description	Issue date
IN25O0H5 001	01	Initial issue of report	2025-02-05

Prüfbericht - Nr.:
Test Report No.:

IN25O0H5 001

Seite 5 von 38
Page 5 of 38

Table of Contents

1	GENERAL REMARKS	6
1.1	Attachments	6
2	TEST SITES	7
2.1	Testing Facilities	7
2.2	List of Test and Measurement Instruments.....	7
3	GENERAL PRODUCT INFORMATION.....	9
3.1	Product Function and Intended Use	9
3.2	Ratings and System Details of Equipment under Test	9
4	TEST SET-UP AND OPERATION MODE.....	10
4.1	Principle of Configuration Selection	10
4.2	Test Operation and Test Software	10
4.3	Special Accessories and Auxiliary Equipment	10
4.4	Simultaneous Transmission	10
4.5	Countermeasures to achieve EMC Compliance	10
4.6	List of frequencies	10
4.7	TUV Sample Identification.....	10
5	OPERATIONAL DESCRIPTION.....	11
6	TEST METHODOLOGY	12
6.1	Radiated Emission Test	12
7	TEST RESULTS FOR BLE.....	14
7.1	Maximum Peak Conducted Output Power	14
7.2	DTS Bandwidth & 99% Bandwidth.....	16
7.3	Power Spectral Density.....	19
7.4	Emissions in non-restricted frequency bands and Conducted Spurious Emission.....	21
7.5	Spurious Radiated Emissions & Restricted Bands of Operation	25
8	AC Power lines Conducted Emission	35
9	LIST OF TABLES.....	38
10	List of Figures.....	38

Prüfbericht - Nr.:

Test Report No.:

IN25O0H5 001

Seite 6 von 38

Page 6 of 38

1 GENERAL REMARKS

1.1 Attachments

All attachments are part of this test report and are issued in separate document.

1. Test Setup Photos
2. EUT External Photos
3. EUT Internal Photos
4. FCC Label and Label Location
5. Block Diagram
6. Specification of EUT
7. Schematic Diagrams
8. Bill of Material
9. User Manual
10. Maximum Permissible Exposure Information

2 TEST SITES

2.1 Testing Facilities

- | | |
|---|--|
| <p>1. TÜV Rheinland (India) Pvt.Ltd.,
27/B, 2nd Cross,
ElectronicCityPhase1
Bangalore – 560 100,
India
Radiated Measurement site type:
Fully anechoic chamber (used for above 1 GHz
measurements)</p> | <p>2. TUV Rheinland (India) Pvt.Ltd.,
108, Beside ISBR Business School,
Electronic city Phase I
Bangalore - 560 100.
India
Radiated Measurement site type:
Semi anechoic chamber (used for below 1 GHz
measurements)</p> |
|---|--|

2.2 List of Test and Measurement Instruments

Table 1: List of test and measurement instruments

Equipment	Manufacturer	Model Name	Serial Number	Firmware Versions	Calibration Due Date	Periodicity	Test Facility
EMI Receiver	Rohde & Schwarz	ESW 44	101733	1.72 SP5	26.01.2025	Yearly	Radiated Spurious Emission
Active loop antenna	Frankonia	LAX-10	LAX-10-800	-	23.03.2025	Yearly	
Balun & Biconical Antenna	Schwarzbeck Mess-Elektronik	BBA 9106+VHBB 9124	9124-1117	-	03.06.2025	Yearly	
Log Periodic Antenna	Schwarzbeck Mess-Elektronik	VUSLP 9111B	9111B-324	-	31.05.2025	Yearly	
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1944	-	12-11-2025	Yearly	
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA 9170-0904	-	15.01.2025	Yearly	
EMI Test Receiver	Rohde & Schwarz	ESW44	101773	1.72.SP1	10.05.2025	Yearly	
Semi Anechoic Chamber	Frankonia	-	-	-	-	-	
Fully Anechoic Chamber	Albatross	-	-	-	-	-	Conducted Test Parameters
Spectrum Analyzer	Agilent	E4407B	ESA-E	A.14.07	04-01-2025	Yearly	
EMI Receiver	Rohde & Schwarz	ESR7	101133	3.48 SP3	16-09-2025	Yearly	Conducted AC Power line Test
Line Impedance Stabilization Network	Rohde & Schwarz	ENV 216	101434	-	15-04-2025	Yearly	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100811	-	08-07-2025	Yearly	

Prüfbericht - Nr.:

Test Report No.:

IN25O0H5 001

Seite 8 von 38

Page 8 of 38

Table 2: Instrument application Software versions

SL. No.	Test Type	Application software	Version
1	Radiated spurious emission measurement in FAC	EMC 32	10.60.20
2	Radiated spurious emission measurement in 10mtr SAC	BAT EMC	3.20.0.17

3 GENERAL PRODUCT INFORMATION

3.1 Product Function and Intended Use

The TW1318 BLE Module, powered by ST cutting-edge BlueNRG technology, offers seamless wireless connectivity with exceptional efficiency. Compact and robust, this module is designed for IoT applications, ensuring low power consumption without compromising performance. With its extended range and reliable data transmission, the TW1318 simplifies integration into wearables, smart devices, and industrial systems. Pre-certified for global use, it accelerates your product's time-to-market while delivering enhanced security and scalability for the future of connected technology.

3.2 Ratings and System Details of Equipment under Test

Table 3: Ratings and System Details as declared by Client*

Radio Protocol		BLE
Operating Frequency Range		2402MHz to 2480MHz
No. of Channels		40 (Refer Table 5)
Channel Spacing		2MHz
Maximum Measured Peak Output Power		7.64 dBm @ 2440MHz
Modulation		GFSK
Number of antennas		1
Antenna Gain & Type		0.5dBi & Chip Antenna
Supply Voltage to Product		3.3V through USB
Environmental conditions	Storage	-40° C to 85° C
	Operating	-40° C to 85° C
EUT Dimension		(L)11.5mm x (W)13.5mm x (H) 2.30mm

***Disclaimer:** The information/data is supplied by the client and the same is considered to arrive at the final value. Any changes made apart from the specified specification, can directly impact on the tests results. Refer the products user manual for more details.

4 TEST SET-UP AND OPERATION MODE

4.1 Principle of Configuration Selection

Transmission was enabled with highest possible duty cycle transmission on low, mid and high channel.

4.2 Test Operation and Test Software

Hardware Version Identification number (HVIN): TW1318
Software version : TW1318 Ver 0.0.1

4.3 Special Accessories and Auxiliary Equipment

Test laptop & USB Cable

4.4 Simultaneous Transmission

- None

4.5 Countermeasures to achieve EMC Compliance

- None

4.6 List of frequencies

Frequency Band (MHz)	Channel No.	Channel Frequency (MHz)
2402 – 2480	0	2402
	1	2404
	2	2406
	3	2408
	:	:
	11	2424
	12	2426
	:	:
	19	2440
	20	2442
	:	:
	:	:
	:	:
	:	:
	36	2474
	37	2476
	38	2478
	39	2480

Table 4: List of BLE Centre frequencies

Channel used for BLE testing.

Channel low: 2402MHz

Channel mid: 2440MHz

Channel high : 2480MHz

4.7 TUV Sample Identification

- TUV Sample Identification number: A003878404-001 – Radiated test Sample
A003878404-002 – Conducted test Sample

5 OPERATIONAL DESCRIPTION

The TW1318 module is an ultra-low power programmable Bluetooth® Low Energy wireless solution. It embeds Arm® Cortex®-M0+ microcontroller that can operate up to 64 MHz and the BlueNRG core co-processor (DMA based) for Bluetooth Low Energy timing critical operations. It is compliant with Bluetooth® Low Energy SIG core specification version 5.3 addressing point-to-point connectivity and Bluetooth Mesh networking and allows large-scale device networks to be established in a reliable way. The TW1318 module is also suitable for 2.4 GHz proprietary radio wireless communication to address ultra-low latency applications.

- High performance and ultra-low power Arm® Cortex®-M0+ 32-bit, running up to 64MHz.
- Low Energy system-on-chip supporting Bluetooth 5.3 with 2mbps data rate.
- Ultra-low power radio performance.
- The MCU provides On-chip non-volatile Flash memory of 192 kB and On-chip RAM of 24 kB + 4 kB PKA RAM.
- Operating supply voltage: from 1.7 to 3.6 V
- Output power up to +8 dBm (at antenna connector)
- RX sensitivity level: -97 dBm @ Mbps, -104 dBm @ 125 kbps (long range)
- Embedded MLPF-NRG-01D3 integrated matched balun with harmonic filter.
- Interfaces 1xUART, 7xGPIO, SWD debug interface
- Integrated with high performance small form factor chip antenna.
- Small module form factor: **(L)**11.5mm x **(W)**13.5mm x **(H)** 2.30mm

6 TEST METHODOLOGY

6.1 Radiated Emission Test

The radiated emission measurement was performed according to the procedures in ANSI C63.10-2013. The equipment under test (EUT) was placed at the middle of the 80 cm high turntable for below 1 GHz & 1.5 m height for above 1 GHz measurement, and the EUT is 3 meters far from the measuring antenna. The turntable was rotated 360° for obtaining the maximum emission. The height of the measuring antennas was scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained. The measurement above 1000 MHz was performed by horn antenna, the measurement below 30 MHz was performed by loop antenna, Measurement from 30 MHz to 200 MHz was performed by Balloon and Biconical Antenna, and measurement from 200 MHz to 1 GHz was performed by Log-Periodic Antenna.

The EUT was rotated around the X-, Y-, and Z-Axis and the results from worst case axis are recorded.

6.1.1 Test Setup Configuration




Figure 1: Frequency Range 9 kHz- 30 MHz




Figure 2: Frequency Range 30 MHz – 200 MHz




Figure 3: Frequency Range 200 MHz - 1GHz




Figure 4: Frequency Range above 1 GHz

Prüfbericht - Nr.:
Test Report No.:

IN25O0H5 001

Seite 14 von 38
Page 14 of 38


7 TEST RESULTS FOR BLE

7.1 Maximum Peak Conducted Output Power

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (b)(3)
Test Method	Subclause 11.9.1.1 of ANSI C63.10
Measurement Bandwidth	1MHz
Detector	Peak
Port of testing	Antenna port
Requirement	Power $\leq$ 1 W (30 dBm)



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.1 °

Voltage: 3.3V through USB

Relative humidity: 65%

KDB Guidelines applied:

Measurements were made as per section 8.3.1 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:

Test Report No.:

IN2500H5 001

Seite 15 von 38

Page 15 of 38


Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report
2. Total Peak Output power (dBm) = Measured Peak power (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB).
3. This product does not support additional beamforming gain / directional gain, it uses single antenna and hence Directional gain of the single antenna is 0.5 dBi.

Data Rate (Mbps)	Channel Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Power Limit (dBm)
1	2402	7.72	30
	2440	7.64	30
	2480	7.26	30

Test Plots:



Prüfbericht - Nr.:
Test Report No.:

IN25O0H5 001

Seite 16 von 38
Page 16 of 38


7.2 DTS Bandwidth & 99% Bandwidth

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (a) (2)
Test Method	Subclause 11.8.1 & 6.9.3 of ANSI C63.10
Measurement Bandwidth	100 kHz for x dB bandwidth 1 to 5% of OCB for 99% bandwidth
Detector	Peak
Port of testing	Antenna port
Requirement	The minimum 6 dB bandwidth shall be at least 500 kHz

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.1 °

Voltage: 3.3V through USB

Relative humidity: 65%

KDB Guidelines applied:

Measurements were made as per section 8.2 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. This product does not support additional beamforming gain / directional gain, it uses single antenna and hence directional gain of the single antenna is 0 dBi.

Data Rate (Mbps)	Channel Frequency (MHz)	99% Occupied bandwidth (MHz)	6dB BW (MHz)	Limit (kHz)
1Mbps	2402	1.026	692.77	0.5
	2440	1.029	700.59	0.5
	2480	1.010	691.67	0.5


Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001


Seite 17 von 38
Page 17 of 38

Test Plots:


6dB DTS Plots



Channel Frequency 2402MHz



Channel Frequency 2440MHz




Channel Frequency 2480MHz

Prüfbericht - Nr.:
Test Report No.:


IN2500H5 001

Seite 18 von 38
Page 18 of 38


99% OBW plots



Channel Frequency 2402MHz



Channel Frequency 2440MHz



Channel Frequency 2480MHz

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 19 von 38
Page 19 of 38


7.3 Power Spectral Density

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (e)
Test Method	Subclause 11.10.2 of ANSI C63.10
Measurement Bandwidth	3 kHz
Detector	Peak
Port of testing	Antenna port
Requirement	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.1 ° Voltage: 3.3V through USB Relative humidity: 65%

KDB Guidelines applied:

Measurements were made as per section 8.4 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Test results:

Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Total Peak PSD (dBm) = Measured Peak PSD (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)


Data Rate (Mbps)	Channel Frequency (MHz)	Measured PSD (dBm/kHz)	PSD Limit (dBm/kHz)
1Mbps	2402	-10.11	8.00
	2440	-10.13	8.00
	2480	-11.97	8.00

Prüfbericht - Nr.:
Test Report No.:


IN2500H5 001

Seite 20 von 38
Page 20 of 38


Test Plots:



Channel Frequency 2402MHz



Channel Frequency 2440MHz



Channel Frequency 2480MHz

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 21 von 38
Page 21 of 38

7.4 Emissions in non-restricted frequency bands and Conducted Spurious Emission

Result

Pass

Test Specification

FCC part 15 Subpart C 15.247 (d)

Test Method

Subclause 11.11.3 of ANSI C63.10

Measurement Bandwidth

100 kHz

Detector

Peak

Port of testing


Antenna port

Requirement

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 db.

Test Method:



Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.1 °

Voltage: 3.3V through USB

Relative humidity: 65%

KDB Guidelines applied:

Measurements were made as per section 8.5 in KDB 558074 D01 15.247 Measurement Guidance v05r02.

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 22 von 38
Page 22 of 38

Test results:


Note:

1. All the losses are included during measurement and final values are mentioned in the test report.
2. Final Value (dBm) = Measured Value (dBm) + Attenuator factor (10dB) + Cable loss (0.5dB)
3. This product do not support additional beamforming gain / directional gain, it uses signal antenna and hence directional gain of the single antenna is 0.5 dBi

7.4.1 Band Edge

Channel Frequency (MHz)	Band edge frequency (MHz)	Value at band edge (A) (dBm)	Reference value (B) (dBm)	A-B (dBc)	Minimum Limit (dBc)
2402.00	2390.00	-51.99	7.70	-59.69	-20.00
2480.00	2483.50	-48.15	7.25	-55.40	-20.00

Reference Plots:



Prüfbericht - Nr.:


Test Report No.:

IN2500H5 001


Seite 23 von 38

Page 23 of 38

Bandedge Plots:




Channel Frequency:2402MHz




Channel Frequency:2480MHz


7.4.2 Out-Of-Band Emissions




Channel Frequency: 2402MHz Frequency Range 30MHz – 1GHz




Channel Frequency: 2402MHz Frequency Range 1GHz – 26.5GHz




Channel Frequency: 2440MHz Frequency Range 30MHz – 1GHz



Channel Frequency: 2440MHz Frequency Range 1GHz – 26.5GHz



Channel Frequency: 2480MHz Frequency Range 30MHz – 1GHz



Channel Frequency: 2480MHz Frequency Range 1GHz – 26.5GHz

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 25 von 38
Page 25 of 38

7.5 Spurious Radiated Emissions & Restricted Bands of Operation

Result

Pass

Test Specification	FCC part 15 Subpart C 15.247 (d) / (15.209 & 15.205)
Test Method	ANSI C63.10
Measurement Location	Semi Anechoic Chamber 9kHz - 1 GHz Fully Anechoic Chamber 1 GHz - 40GHz
Measurement Bandwidth	100 kHz for frequency range < 1GHz 1 MHz for Frequency range >1GHz
Detector	Refer remarks below
Measuring Distance	3 m
Requirement	As per the limits mentioned in the below table
Test setup	Refer TEST METHODOLOGY

Table 5: Transmitter limits for Radiated emission

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Distance of Measurement (m)
0.009 – 0.490	2400/F(kHz)	48.50 – 13.80	300*
0.490 – 1.705	24000/F(kHz)	33.80 – 23.00	30*
1.705 -30	30	29.54	30*
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Remark: * The limit shows in the table above of frequency range 0.009 – 0.490, 0.490 – 1.705 MHz and 1.705-30MHz is at 300-meter, 30 meter and 30-meter range respectively, which corresponds to 128.51 – 93.80, 73.80 – 62.96 and 69.54 dBμV/m at 3m range by extrapolation calculation and the measurement of loop antenna.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Condition

Normal Test Condition:

Temperature (Norm) = + 22.1 °

Voltage: 3.3V through USB

Relative humidity: 65%

Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 26 von 38
Page 26 of 38

Test results:

Note: All the losses are included during measurement and final values are mentioned in the test report. Refer TEST METHODOLOGY for more details.


Test results for frequency range 9 kHz – 30MHz

No emissions found in frequency range 9 kHz to 30 MHz, and measured levels are below 20dB from the limit line, hence not reported.

Table 6: Test results for frequency range 30MHz – 200MHz

Antenna Polarization	Measured Frequency (MHz)	Measured Peak Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	42.78	9.58	40.00	-30.42
	71.82	8.99	40.00	-31.01
	108.00	21.30	43.50	-22.20
	120.00	14.00	43.50	-29.50
	156.00	15.50	43.50	-28.00
Horizontal	42.72	8.98	40.00	-31.02
	70.26	13.10	40.00	-26.90
	79.98	14.10	40.00	-25.90
	108.06	15.70	43.50	-27.80
	174.00	13.30	43.50	-30.20

Frequency Range 30MHz – 200MHz _Vertical Polarization



Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 27 von 38
Page 27 of 38

Frequency Range 30MHz – 200MHz _Horizontal Polarization




Table 7: Test results for frequency range 200MHz – 1GHz


Antenna Polarization	Measured Frequency (MHz)	Measured Peak Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Vertical	222.02	17.30	46.00	-28.70
	257.99	15.10	46.00	-30.90
	432.05	19.50	46.00	-26.50
	499.97	21.00	46.00	-25.00
	812.51	24.60	46.00	-21.40
Horizontal	221.99	25.80	46.00	-20.20
	312.50	19.10	46.00	-26.90
	408.02	21.10	46.00	-24.90
	687.50	22.60	46.00	-23.40
	812.51	24.30	46.00	-21.70

Prüfbericht - Nr.:
Test Report No.:


IN2500H5 001

Seite 28 von 38
Page 28 of 38

Frequency Range 200MHz – 1GHz_Vertical Polarization



Frequency Range 200MHz – 1GHz_Horizontal Polarization



Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 29 von 38
Page 29 of 38

Table 8: Test results for the frequencies above 1GHz:

Channel Frequency (MHz)	Measured Frequency (MHz)	Antenna Polarization	Measured Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
2402	2402(Pk)	Vertical	81.49	-	-
	2402(Av)		79.15	-	-
	2390(Pk)		42.18	74.00*	-31.82
	2390(Av)		24.57	54.00*	-29.43
	4804(Pk)		47.70	74.00	-26.30
	4804(Av)		39.31	54.00	-14.69
	7206(Pk)		51.40	74.00	-22.60
	7206(Av)		40.98	54.00	-13.02
	2402(Pk)	Horizontal	74.41	-	-
	2402(Av)		72.04	-	-
	2390(Pk)		37.62	74.00*	-36.38
	2390(Av)		24.33	54.00*	-29.67
	4804(Pk)		43.47	74.00	-30.53
	4804(Av)		31.70	54.00	-22.30
	7206(Pk)		52.98	74.00	-21.02
	7206(Av)		43.57	54.00	-10.43
2440	2440(Pk)	Vertical	80.46	-	-
	2440(Av)		78.11	-	-
	4880(Pk)		44.21	74.00	-29.79
	4880(Av)		34.23	54.00	-19.77
	7320(Pk)		51.78	74.00	-22.22
	7320(Av)		40.61	54.00	-13.39
	2440(Pk)	Horizontal	73.19	-	-
	2440(Av)		70.8	-	-
	4880(Pk)		41.85	74.00	-32.15
	4880(Av)		30.97	54.00	-23.03
	7320(Pk)		52.22	74.00	-21.78
	7320(Av)		43.16	54.00	-10.84
2480	2480(Pk)	Vertical	78.26	-	-
	2480(Av)		75.89	-	-
	2483.5(Pk)		36.97	74.00*	-37.03
	2483.5(Av)		24.55	54.00*	-29.45
	4960(Pk)		44.42	74.00	-29.58
	4960(Av)		33.88	54.00	-20.12
	7440(Pk)		50.47	74.00	-23.53
	7440(Av)		39.20	54.00	-14.80
	2480(Pk)	Horizontal	69.89	-	-
	2480(Av)		67.81	-	-
	2483.5(Pk)		37.11	74.00*	-36.89
	2483.5(Av)		24.07	54.00*	-29.93
	4960(Pk)		41.91	74.00	-32.09
	4960(Av)		31.21	54.00	-22.79
	7440(Pk)		53.24	74.00	-20.76
	7440(Av)		43.66	54.00	-10.34

_ → Fundamental Frequency

*→ Restricted Band edges

Pk: Peak Detector.

Av: Average Detector.

Prüfbericht - Nr.:
Test Report No.:


IN2500H5 001

Seite 30 von 38
Page 30 of 38


Worst Case Test Plots:

Data Rate: 1 Mbps


Channel Frequency: 2402MHz_Vertical Polarization




Channel Frequency: 2402MHz_Horizontal Polarization



Frequency Range: 1GHz – 18GHz_Vertical Polarization



Frequency Range: 1GHz – 18GHz_Horizontal Polarization



Prüfbericht - Nr.:


Test Report No.:

IN2500H5 001


Seite 32 von 38

Page 32 of 38


Channel Frequency: 2480MHz_Vertical Polarization




Channel Frequency: 2480MHz_Horizontal Polarization



Frequency Range: 1GHz – 18GHz_Vertical Polarization



Frequency Range: 1GHz – 18GHz_Horizontal Polarization




Prüfbericht - Nr.:
Test Report No.:


IN25O0H5 001

Seite 34 von 38
Page 34 of 38

Frequency Range: 18GHz – 26GHz_Vertical Polarization



Frequency Range: 18GHz – 26GHz_Horizontal Polarization



Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 35 von 38
Page 35 of 38

8 AC Power lines Conducted Emission

Result

Pass

Test Specification	FCC Part 15 Section 15.207
Test Method	ANSI C 63.10-2013
Testing Location	Screened room
Measurement Bandwidth	9kHz
Frequency Range	150kHz – 30MHz
Supply Voltage	110VAC,60Hz
Test Method	Refer TEST METHODOLOGY

Table 9: Limits for Conducted power line emission

Frequency of emission (MHz)	QP Limit (dBμV)	AV Limit (dBμV)
0.15 – 0.5	66 – 56*	56 – 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency

Test Conditions:

Temperature (Norm) = + 22.1 °

Voltage: 3.3V through USB Adaptor

Relative humidity: 65%

Prüfbericht - Nr.:

Test Report No.:

IN2500H5 001


Seite 36 von 38

Page 36 of 38

Test Results:

Line:

Trace	Frequency	Level (dBµV)	Phase	Detector	Delta Limit/dB
2	778.000000000 kHz	31.86		Average	-14.14
2	390.000000000 kHz	32.90		Average	-15.16
2	302.000000000 kHz	32.80		Average	-17.39
1	762.000000000 kHz	36.73		Quasi Peak	-19.27
1	294.000000000 kHz	39.96		Quasi Peak	-20.45
1	350.000000000 kHz	36.74		Quasi Peak	-22.22
2	12.150000000 MHz	27.17		Average	-22.83
1	11.706000000 MHz	35.78		Quasi Peak	-24.22
2	3.614000000 MHz	19.43		Average	-26.57
1	150.000000000 kHz	38.99		Quasi Peak	-27.01
2	5.610000000 MHz	22.25		Average	-27.75
2	2.670000000 MHz	17.04		Average	-28.96
1	3.658000000 MHz	26.24		Quasi Peak	-29.76
1	3.194000000 MHz	25.07		Quasi Peak	-30.93
1	2.662000000 MHz	24.63		Quasi Peak	-31.37




Prüfbericht - Nr.:
Test Report No.:

IN2500H5 001

Seite 37 von 38
Page 37 of 38

Neutral:

Trace	Frequency	Level (dBµV)	Phase	Detector	Delta Limit/dB
2	722.000000000 kHz	35.31		Average	-10.69
2	778.000000000 kHz	35.25		Average	-10.75
2	662.000000000 kHz	32.28		Average	-13.72
1	778.000000000 kHz	40.78		Quasi Peak	-15.22
2	618.000000000 kHz	28.97		Average	-17.03
2	562.000000000 kHz	27.98		Average	-18.02
2	302.000000000 kHz	32.02		Average	-18.17
1	294.000000000 kHz	38.66		Quasi Peak	-21.75
1	11.674000000 MHz	33.09		Quasi Peak	-26.91
1	154.000000000 kHz	38.50		Quasi Peak	-27.28
2	11.690000000 MHz	22.48		Average	-27.52
2	2.678000000 MHz	18.37		Average	-27.63
1	2.722000000 MHz	22.98		Quasi Peak	-33.02
1	3.674000000 MHz	22.65		Quasi Peak	-33.35
1	2.158000000 MHz	19.90		Quasi Peak	-36.10
1	2.158000000 MHz	19.78		Quasi Peak	-36.22



9 LIST OF TABLES

Table 1: List of test and measurement instruments	7
Table 2: Instrument application Software versions	8
Table 3: Ratings and System Details as declared by Client*	9
Table 4: List of BLE Centre frequencies	10
Table 5: Transmitter limits for Radiated emission	25
Table 6: Test results for frequency range 30MHz – 200MHz	26
Table 7: Test results for frequency range 200MHz – 1GHz	27
Table 8: Test results for the frequencies above 1GHz:	29
Table 9: Limits for Conducted power line emission	35

10 List of Figures

Figure 1: Frequency Range 9 kHz- 30 MHz	12
Figure 2: Frequency Range 30 MHz – 200 MHz	12
Figure 3: Frequency Range 200 MHz - 1GHz	13
Figure 4: Frequency Range above 1 GHz	13

End of test report