

承認書

APPROVAL SHEET

客 户 朗芯微
:

品 名 规格 YD-N9206(H01)-TX-V1.0-天线
DESCRIPTION:

料 号
PART NO.:

客 户 料 号
CUS PART NO.:

日 期 2024.12.13
D A T E:

呈样签章

工 程 ENGINEERING DEPARTMENT	品 保 Q C DEPARTMENT	业 务 SALES DEPARTMENT

客户承认签章


工 程 ENGINEERING DEPARTMENT	品 保 Q C DEPARTMENT	采 购 PURCHASING DEPARTMENT

※ 承认书一式 三份，惠蒙贵司承认签章

※ Approval in duplicate, please signed by your company.

1. 测项目与设备


	测试项目	设备
1. S11 参 数 (S-parameter)	1. 回波损耗 (Return Loss) 2. 电压驻波比 (VSWR)	网络分析仪: Agilent E5071B HP 8753D
2. 有源测试 (Active)	1. 发射功率 (TRP) 2. 接收灵敏度 (TIS)	1. 暗室: ETS 7x4x3 m (3D) Chamber ETS 5x3x3 m (3D) Chamber 2.综合测试仪: Agilent 8960 E5515B ×2 StarPoint SP6011 Cmw500
3.无源测试 (Passive)	1. 天 线 增 益 (Gain) 2. 天 线 效 率 (Efficiency)	1. 暗室: ETS 7x4x3 m (3D) Chamber ETS 5x3x3 m (3D) Chamber 2. 网络分析仪: Agilent E5071B HP 8753D




2. 天线效率与增益

Passive Test For WIFI2.4		
Freq (MHz)	Effi (%)	Gain (dBi)
2400	53.24	-0.65
2410	51.94	-0.7
2420	50.81	-0.66
2430	50.26	-0.71
2440	51.83	-0.55
2450	54.02	-0.35
2460	53.06	-0.37
2470	52.93	-0.32
2480	52.5	-0.33
2490	53.79	0
2500	52.96	-0.18


2400.000MHz




2400.000MHz H




2500.000MHz




2500.000MHz H




2400.000MHz E1




2400.000MHz E2




2500.000MHz E1



2500.000MHz E2



3. 天线结构图：



电器技术参数

电 性 能 指 标		Electrical Specifications	
频率范围	2400~2500MHz	Frequency Range	2400~2500MHz
输入阻抗	50 Ω	Input Impedance	50 Ω
最大增益	0 DBI	Maximum gain	0 DBI
最大输入功率	50W	Maximum Input Power	50W
机 械 指 标		Mechanical Specifications	
天线颜色	黑色	Antenna Color	BLACK
工作温度	-40℃~+85℃	Working Temperature	-40℃~+85℃
工作湿度	20~80%	Working Humidity	20~80%

环境性能测试（Environment performance test）：

项目	测试条件	测试结果
储存环境	在没有指定的情况下测试温度、湿度、气压如下： 1. 温度为-30℃~+80℃ 2. 相对湿度为45%-85% 3. 气压为86kpa-106kpa	电气机械性能正常
高低温试验	在70℃与-40℃之间进行5次循环，然后在正常条件下1-2H，检查外观质量。	尺寸应满足规定并应满足于机械、电气性能
耐恒定湿热试验	相对湿度95±3%，试验温度：40℃.持续2H作用后，试品取出后5min之内测定电气性能，试品在正常条件下1-2H，检查外观质量	尺寸应满足规定并应满足于机械、电气性能
振动试验	振频范围10-55HZ，位移幅值：0.35MM，加速度幅值：50.0M/S，扫频循环次数：30次	电气机械性能正常
跌落试验	1M高空按照互相垂直的轴方向自由跌落3次	电气机械性能正常

Project	Test condition	Test results
Storage environment	Test temperature, humidity, pressure without stated condition as follwings:1.Temperature: -30℃ ~ +80℃ ;2.Relative humidity: 45%-85%;3, Pressure: 86kpa-106kpa	Electrical and mechanical performance normal
High and low temperature test	Having 5 times cycle between -40℃ to 70℃,Then in common condition 1-2 hours test exterior quality.	Measurement satisfied with electrical and mechanical performance normal.
Resistance constant hot and humid test	Relative humidity:95±3%,Test temperature: 40℃,last 2 hours ,put it after 5 min test the electrical function .Test products during common condition 1-2 hours ,Then test exterior quality.	Measurement satisfied with electrical and mechanical performance normal.
Vibration test	Vibrate Frequency:10-55HZ; Distance :0.35mm;Acceleration :50.0m/s;Sweep frequency cycle:30 times	Electrical and mechanical performance normal
Fall test	From 1m height fall down 3 times freely (vertical direction)	Electrical and mechanical performance normal