



#### FCC RF EXPOSURE REPORT

For

**EcoFlow OCEAN Pro Hybrid Inverter** 

**MODEL NUMBER: EF-PCS-24** 

REPORT NUMBER: 4791889722.1-2

**ISSUE DATE: July 30, 2025** 

FCC ID: 2A2P9-HLKLD1030

Prepared for

**EcoFlow Inc.** 

RM 401, Plant #1, Runheng Industrial Zone, Fuhai Street, Bao'an District, Shenzhen, 518000, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China

Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4791889722.1-2 Page 2 of 8

**Revision History** 

Rev.Issue DateRevisionsRevised ByV0July 30, 2025Initial Issue



# **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4.	DESCRIPTION OF EUT	6
5	REQUIREMENT	7



REPORT NO.: 4791889722.1-2 Page 4 of 8

# 1. ATTESTATION OF TEST RESULTS

**Applicant Information** 

Company Name: EcoFlow Inc.

Address: RM 401, Plant #1, Runheng Industrial Zone, Fuhai Street, Bao'an

District, Shenzhen, 518000, China

**Manufacturer Information** 

Company Name: EcoFlow Inc.

Address: RM 401, Plant #1, Runheng Industrial Zone, Fuhai Street, Bao'an

District, Shenzhen, 518000, China

**EUT Description** 

Stephen Guo

Operations Manager

EUT Name: EcoFlow OCEAN Pro Hybrid Inverter

Model: EF-PCS-24
Brand Name: ECOFLOW
Sample Status: Normal
Sample ID: 8682812-1
Sample Received Date: July 8, 2025
Date of Tested: July 10~28, 2025

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC 47CFR§2.1093	PASS		
KDB-447498 D01 V06	PASS		

Prepared By:	Checked By:
Janny Huang	kebo. zhanz
Fanny Huang	Kebo Zhang
Engineer Project Associate	Senior Project Engineer
Approved By:	
Stephen Luo	



REPORT NO.: 4791889722.1-2 Page 5 of 8

### 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1093&1.1310 and KDB 447498 D01 General RF Exposure Guidance v06.

#### 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.  FCC (FCC Designation No.: CN1187)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320)
Accreditation Certificate	FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject
	Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202
	Shielding Room B, the VCCI registration No. is C-20153 and T-20155

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



# 4. DESCRIPTION OF EUT

EUT Name	EcoFlow OCEAN Pro Hybrid Inverter
Model	EF-PCS-24

Frequency Range:	10.5 ~ 10.55 GHz
Channel Number:	1
Center frequency	10.5268 GHz
Type of Modulation:	CW
Antenna Type:	Linear Antenna
Antenna Gain:	3.33 dBi
Normal Test Voltage:	AC 120 V, 60 Hz

REPORT NO.: 4791889722.1-2 Page 7 of 8

# 5. REQUIREMENT

#### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1093, Portable devices that transmit at frequencies above 6 GHz shall be evaluated in terms of the MPE limits specified in Table 1 to § 1.1310(e)(1) of this chapter.

Limits for General Population/Uncontrolled Exposure

### **RF EXPOSURE LIMIT**

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

# **CALCULATION METHOD**

S=PG/4πR<sup>2</sup>

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4791889722.1-2 Page 8 of 8

## **CALCULATED RESULTS**

Radio Frequency Radiation Exposure Evaluation

(Worst case)				
Operating	Max. Power	Antenna Gain	Power density	Limit
Mode	(dBm)	(dBi)	(mW/ cm <sup>2</sup> )	Liiik
CW	0.85	3.33	0.00052	1

#### Note:

- 1. The calculated distance is 5mm.
- 2. The power comes from operation description.

EIRP = 99.38 dBuV/m in 3m = (99.38-95.2) dBm= 4.18 dBm

Max. Conducted power= 4.18 - 3.33 = 0.85 dBm

3.WIFI 2.4GHz+ WIFI 5G + CW=

=0.05156+0.05062 + 0.00052=0.1027 (mW/ cm2 )

Therefor the maximum calculations of above situations are less than the "1" limit.

For the WIFI module PD, refer to report "4791873944.1-RF-4"

**END OF REPORT**