

CONNECTS TO PHONE via Bluetooth™

A/C PRO®

EXTREME CONDITIONS

+ SMART CHARGE™

R-134A REFRIGERANT

A / C R E C H A R G E

- GUARDS AGAINST EXTREME TEMPERATURES
- PROTECTS AGAINST HIGH USE
- RESTORES MAXIMUM, COLD, DRY AIR
- SEALS LEAKS
- HYBRID/ELECTRIC COMPATIBLE

WARNING! CONTENTS UNDER PRESSURE.
Carefully read precautions on rear panel

WARNING! CONTENTS UNDER PRESSURE.
Carefully read precautions on rear panel

NET WT 22 OZ (1.37 LB) 623 g

To get started, download the A/C Pro App available on all app stores. Then Connect Smart Charge to phone via Bluetooth. The app will walk you through the entire process.

Below is an outline of the instructional steps to expect:

Always wear protective gloves and Eyewear before starting Check hoses and ports for leaks and repair before recharging

- After Bluetooth connection has been established, select vehicle Year make and model.
- With engine off, open hood and locate the low-pressure A/C service port. Remove the plastic cap from port and save.
- Start car and turn on A/C. Set fan to highest setting and temperature to coldest setting. Make sure Recirculation Mode is selected.
- Attach quick-connect fitting on end of recharge hose to low-pressure service port by pressing the back of the fitting onto the port.
- App will confirm if refrigerant level is low and will indicate next step based on PSI.
- If refrigerant is low, detach gauge from vehicle by pulling back on the connection ring to release the coupler. Unscrew and remove plastic spacer between trigger assembly and can.
- Shake can well, and screw can onto gauge/trigger assembly. Reattach the quick-connect back on the low-side port. Make sure to always hold the can upright (12 o'clock position) before starting to charge. Squeeze the trigger to charge the A/C system. While charging, shake the can up and down, alternating between an upright and sideways position. Every 15 seconds release trigger, and check the PSI reading on the screen.
- STOP CHARGING WHEN PSI IN GREEN RANGE. BE CAREFUL NOT TO OVERCHARGE YOUR SYSTEM — DO NOT LET PSI READING MAKE IT INTO THE RED RANGE.** Once PSI makes it anywhere between 25–30 PSI, check vent temperature. If vent temp is colder than charging is complete. Do not try to get it to the highest part of the green zone or you risk overcharging. Remove hose from service port and replace plastic cap when finished. Store any unused refrigerant in a cool, dry place.

To get started, download the A/C Pro App available on all app stores. Then Connect Smart Charge to phone via Bluetooth. The app will walk you through the entire process.

Below is an outline of the instructional steps to expect:

Always wear protective gloves and Eyewear before starting Check hoses and ports for leaks and repair before recharging

- After Bluetooth connection has been established, select vehicle Year make and model.
- With engine off, open hood and locate the low-pressure A/C service port. Remove the plastic cap from port and save.
- Start car and turn on A/C. Set fan to highest setting and temperature to coldest setting. Make sure Recirculation Mode is selected.
- Attach quick-connect fitting on end of recharge hose to low-pressure service port by pressing the back of the fitting onto the port.
- App will confirm if refrigerant level is low and will indicate next step based on PSI.
- If refrigerant is low, detach gauge from vehicle by pulling back on the connection ring to release the coupler. Unscrew and remove plastic spacer between trigger assembly and can.
- Shake can well, and screw can onto gauge/trigger assembly. Reattach the quick-connect back on the low-side port. Make sure to always hold the can upright (12 o'clock position) before starting to charge. Squeeze the trigger to charge the A/C system. While charging, shake the can up and down, alternating between an upright and sideways position. Every 15 seconds release trigger, and check the PSI reading on the screen.
- STOP CHARGING WHEN PSI IN GREEN RANGE. BE CAREFUL NOT TO OVERCHARGE YOUR SYSTEM — DO NOT LET PSI READING MAKE IT INTO THE RED RANGE.** Once PSI makes it anywhere between 25–30 PSI, check vent temperature. If vent temp is colder than charging is complete. Do not try to get it to the highest part of the green zone or you risk overcharging. Remove hose from service port and replace plastic cap when finished. Store any unused refrigerant in a cool, dry place.

CONTENTS: Approximately 18 oz refrigerant and 4 oz dyes

WARNING: Contains 1,1,1,2-tetrafluoroethane (R11-97-2). KEEP OUT OF REACH OF CHILDREN. DO NOT STORE CAN IN VEHICLE (MAY EXPLODE). Do not store above 120°F or in direct sunlight. Keep away from any source of electricity. Do not puncture. Incandescent lamp contains. Exposure to skin may cause frostbite. Use only with adequate ventilation. ALWAYS WEAR PROTECTIVE GLASSES AND RESISTANCE BURNED ALICE CAP. NEVER CHARGE WITH OPEN FLAME OR HOT SURFACES. Get medical attention at symptoms persist. Skin: Flush with warm water. Inhalation: Move to fresh air. Get medical attention if irritation or other symptoms develop.

ADVERTENCIA: Contiene 1,1,1,2-tetrafluoroetano (R11-97-2). MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS. NO ALMACENE LA LATA EN EL VEHÍCULO (PUEDE EXPLOTAR). No almacenar en lugares con luz solar directa ni temperaturas superiores a 120 °F. Manténgase la lata alejada de cualquier fuente de electricidad. No perforar ni incinerar. Evitar el contacto con lámparas incandescentes. La exposición a la piel puede causar quemaduras. Nunca almacenar con ventilación adecuada. SIEMPRE USE GUANTES PROTECTORES Y PROTECCIÓN OCULAR. PRÓTEJASE LAS OÍDAS. Nunca cargue nunca con fuego abierto o superficies calientes. Siempre use casco y gorra resistentes al fuego. Si los síntomas persisten, lávelos con agua tibia. Si inhalara: Muévase a un lugar con aire fresco. Si causa irritación u otros síntomas, obtenga atención médica.

REQUIRES ADAPTER

OF COMPLIANT HOSE

\$10 REFUNDABLE DEPOSIT if returned within 90 days of purchase.

CALIFORNIA

DEPÓSITO RECUPERABLE DE \$10 si es regresado en menos de 90 días después de la compra.

For more information, visit www.apcpro.com

Do Not Throw In Trash

APPROVED FOR USE IN CA

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

CAUTION: Equipment A/C PRO is a trademark of Ecobuilt. Made in USA by Ecoproducts LLC, St. Louis, MO 63141.
 Dimensions: 8" x 7" x 4.5" (203mm x 178mm x 114mm)
 Company NA: 1-800-258-3322
 Dimension: 8" x 7" x 4.5" (203mm x 178mm x 114mm)
 Made in USA by Ecoproducts LLC, St. Louis, MO 63141.
 Dimensions: 8" x 7" x 4.5" (203mm x 178mm x 114mm)
 Company NA: 1-800-258-3322
 Dimension: 8" x 7" x 4.5" (203mm x 178mm x 114mm)



Energizer Holdings, Inc.
533 Maryville University Drive
St. Louis, MO 63141
FOR QUESTIONS, CONTACT:
creative.services@energizer.com

PROCESS COLOR:



PANTONE:



OTHER:



COATING: N/A

SPECIAL FINISH: N/A

SUBSTRATE: N/A

DIELINES (DO NOT PRINT):

| | | |
|-------------|------------|--------|
| Die cut | Score/Fold | Margin |
| Perforation | Bleed | |

SPECIAL INSTRUCTIONS

Set elements to knockout or overprint as necessary.
Apply appropriate trapping.

UPN:

UPN-XXXXX

TYPENAME:

DESCRIPTION: CA A/C PRO EXTREME 220Z BLUETOOTH DIGITAL GAUGE

SPEC/WMD# XXXXXXX

REPLACES: XXXXXXXX

BARCODE: FPO

UPC SCALE: 100%

PACK CODE: N/A

SAP#: N/A

WF#: 224937

CATEGORY: AUTO CARE

BRAND: A/C PRO

DESIGNER: LL/JA

MARKETING: MS

VERSION: 4

DATE: 06/17/2021

LIMITATION OF LIABILITY | Do not approve without proper inspection. It is the responsibility of the recipient to examine and proofread all digital files, film, plates, and proofs immediately upon receipt prior to any printing. Should the work be found to be incorrect upon the inspection described above, email create.services@energizer.com, ask for the production manager or graphic designer managing this job, and ensure that corrections are made prior to using this product. The liability of Energizer Holdings, Inc. shall be limited to correcting its own errors in design and printing. Energizer Holdings, Inc. shall not be liable for any other loss or damage including, but not limited to, costs of printing plates or cylinders, overtime, any press time, or delays and/or mission of the production dates.