

RADIO TEST REPORT

FCC ID: 2A2RI-RF012Q

Product : Remote control

Trade Mark : N/A

Model Name : RF012Q-LJD-001

Family Model : N/A

Report No. : S23041903603001

Prepared for

SHENZHEN NICENT ELECTRONICS CO.,LTD

5th floor, building C, No. 2, jiazitang community, Second Industrial Zone, Guangming
Fenghuang street, Shenzhen China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China

Tel.: 400-800-6106,0755-2320 0050 / 2320 0090

Website:<http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : SHENZHEN NICENT ELECTRONICS CO.,LTD
Address..... : 5th floor, building C, No. 2, jiazitang community, Second Industrial Zone, Guangming Fenghuang street, Shenzhen China
Manufacturer's Name : SHENZHEN NICENT ELECTRONICS CO.,LTD
Address..... : 5th floor, building C, No. 2, jiazitang community, Second Industrial Zone, Guangming Fenghuang street, Shenzhen China

Product description

Product name : Remote control
Model and/or type reference : RF012Q-LJD-001
Family Model..... : N/A
Rating(s) : DC 3V from Battery

Standards : FCC Part15.249

Test procedure ANSI C63.10-2013

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test:

Date (s) of performance of tests.....: 21 Apr. 2023 ~ 27 May. 2023

Date of Issue: 27 May. 2023

Test Result: **Pass**

Testing Engineer :



(Allen Liu)

Authorized Signatory :



(Alex Li)

Table of Contents

Page

1 . SUMMARY OF TEST RESULTS	4
1.1 TEST FACILITY	5
1.2 MEASUREMENT UNCERTAINTY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . ANTENNA REQUIREMENT	13
3.1 STANDARD REQUIREMENT	13
3.2 EUT ANTENNA	13
3.3 CONDUCTED EMISSION MEASUREMENT	14
3.3.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.3.2 TEST PROCEDURE	14
3.3.3 DEVIATION FROM TEST STANDARD	14
3.3.4 TEST SETUP	15
3.2.5 TEST RESULT	16
3.4 RADIATED EMISSION MEASUREMENT	17
3.4.1 RADIATED EMISSION LIMITS	17
3.4.2 TEST PROCEDURE	18
3.4.3 DEVIATION FROM TEST STANDARD	18
3.4.4 TEST RESULTS (BELOW 30MHZ)	21
3.4.5 TEST RESULTS (BELOW 1000 MHZ)	22
3.4.6 TEST RESULTS (ABOVE 1000 MHZ)	24
3.4.7 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	28
4. BANDWIDTH TEST	34
4.1 TEST PROCEDURE	34
4.2 DEVIATION FROM STANDARD	34
4.3 TEST SETUP	34
5. TEST RESULTS	35

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.249)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.203	Antenna Requirement	Pass	
15.249 15.209	Radiated Spurious Emission	Pass	
15.249(2)	Frequency Tolerance	N/A	
15.249(a)	Fundamental Measurement	Pass	
15.205	Band Edge Emission	Pass	
15.249	Occupied Bandwidth	Pass	

1.1 TEST FACILITY

Shenzhen NTEK Testing Technology Co., Ltd
 Add. : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.
 FCC FRN Registration No.:463705; IC Registration No.:9270A-1
 CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Remote control	
Trade Mark	N/A	
Model Name	RF012Q-LJD-001	
Family Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Remote control	
	Operation Frequency:	2406MHz-2433MHz
	Modulation Type:	FSK
	Antenna Designation:	PCB Antenna
	Antenna Gain(Peak)	1.5dBi
	Based on the application, features, or specification exhibited in User's Manual. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Rating	DC 1.5V*2 AAA Battery	
Battery	DC 3V	
Hardware version:	Ver1.0	
Firmware version:	Ver1.0	
Software version:	Ver1.0	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel No.	Frequency
1	2406MHz
2	2424MHz
3	2433MHz

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.5	Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX 2406MHz
Mode 2	TX 2424MHz
Mode 3	TX 2433MHz
Mode 4	Normal link

For Radiated Spurious Emission	
Pretest Mode	Description
Mode 1	TX 2406MHz
Mode 2	TX 2424MHz
Mode 3	TX 2433MHz

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX 2406MHz
Mode 2	TX 2424MHz
Mode 3	TX 2433MHz
Mode 4	Normal link

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Mode

EUT

Radiated Spurious Emission Test

EUT

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2023.03.27	2024.03.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2022.06.17	2023.06.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2023.03.27	2024.03.26	1 year
4	Test Receiver	R&S	ESPI7	101318	2023.03.27	2024.03.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2023.03.27	2024.03.26	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2023.03.27	2024.03.26	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2022.11.08	2023.11.07	1 year
9	Amplifier	EMC	EMC051835SE	980246	2022.06.17	2023.06.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2022.11.08	2023.11.07	1 year
11	Power Meter	DARE	RPR3006W	15100041SN084	2022.11.08	2023.11.07	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2022.11.08	2023.11.07	1 year
16	Filter	TRILTHIC	2400MHz	29	2022.11.08	2023.11.07	1 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2023.03.27	2024.03.26	1 year
2	LISN	R&S	ENV216	101313	2023.03.27	2024.03.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2023.03.27	2024.03.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is permanent attached PCB antenna(Gain:1.5dBi). It comply with the standard requirement.

3.3 CONDUCTED EMISSION MEASUREMENT

3.3.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.3.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.
Margin=Measure-ment-Limits, Measure-ment=Reading level+Correct Factor

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.2.5 TEST RESULT

EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N/A
Test Voltage :	N/A	Test Mode :	N/A

Note: Not Applicable

3.4 RADIATED EMISSION MEASUREMENT

3.4.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
Frequency (MHz)	Limit (dBuV)	
30~88	40	3
88~216	43.5	3
216~960	46	3
960 -10000	54.00	3
*902 - 928	94.00	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).
- (3) *Note: This is the limit for the fundamental frequency.

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.249)

Frequency of Emission (MHz)	Field Strength of fundamental ((millivolts /meter)	Field Strength of Harmonics (microvolts/meter)
2400-2483.5	50	500

Notes:

- (1) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.4.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.4.3 DEVIATION FROM TEST STANDARD


No deviation

(A) Radiated Emission Test-Up Frequency Below 30MHz


(a)



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.4.4 TEST RESULTS (BELOW 30MHz)

EUT :	Remote control	Model Name. :	RF012Q-LJD-001
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Remark:1. Emission level in dBuV/m= $20 \log (\mu\text{V/m})$

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor = $40 \log (\text{Specific distance/ test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor = $20 \log (\text{Specific distance/ test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.


3.4.5 TEST RESULTS (BELOW 1000 MHz)

EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	Model 4	Polarization :	Vertical

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	30.9618	5.67	25.93	31.60	40.00	-8.40	QP
V	75.1821	7.09	14.50	21.59	40.00	-18.41	QP
V	150.5378	6.56	18.51	25.07	43.50	-18.43	QP
V	191.7450	8.87	16.44	25.31	43.50	-18.19	QP
V	375.9384	6.69	22.71	29.40	46.00	-16.60	QP
V	511.8351	6.15	25.03	31.18	46.00	-14.82	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	31.7313	4.89	25.51	30.40	40.00	-9.60	QP
H	43.3534	6.24	19.10	25.34	40.00	-14.66	QP
H	135.9822	6.42	18.77	25.19	43.50	-18.31	QP
H	160.3456	6.90	18.04	24.94	43.50	-18.56	QP
H	191.7450	8.24	16.44	24.68	43.50	-18.82	QP
H	366.8231	6.32	22.45	28.77	46.00	-17.23	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



3.4.6 TEST RESULTS (ABOVE 1000 MHZ)


Note: For above 18GHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2406MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2400.000	61.66	9.99	71.65	74.00	-2.35	peak
2400.000	40.21	9.99	50.20	54.00	-3.80	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2406MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2400.000	58.39	9.99	68.38	74.00	-5.62	peak
2400.000	26.25	9.99	36.24	54.00	-17.76	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission above 18GHz.




Note: EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report(X orientation).

EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2433MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	42.70	10.28	52.98	74.00	-21.02	peak
2483.500	29.74	10.28	40.02	54.00	-13.98	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2433MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.500	34.92	10.28	45.20	74.00	-28.80	peak
2483.500	25.02	10.28	35.30	54.00	-18.70	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Note: EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report(X orientation).


3.4.7 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2406MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2406.000	90.38	10.00	100.38	114.00	-13.62	peak
2406.000	81.25	10.00	91.25	94.00	-2.75	AVG
4808.000	57.13	16.26	73.39	74.00	-0.61	peak
4808.000	25.31	16.26	41.57	54.00	-12.43	AVG
7222.000	38.40	22.05	60.45	74.00	-13.55	peak
7222.000	23.16	22.05	45.21	54.00	-8.79	AVG
8922.000	33.13	24.46	57.59	74.00	-16.41	peak
8922.000	10.90	24.46	35.36	54.00	-18.64	AVG
13291.000	32.01	28.56	60.57	74.00	-13.43	peak
13291.000	11.66	28.56	40.22	54.00	-13.78	AVG
16198.000	35.68	26.53	62.21	74.00	-11.79	peak
16198.000	16.16	26.53	42.69	54.00	-11.31	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2406MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2406.000	82.97	10.00	92.97	114.00	-21.03	peak
2406.000	70.22	10.00	80.22	94.00	-13.78	AVG
4808.000	40.27	16.26	56.53	74.00	-17.47	peak
4808.000	24.99	16.26	41.25	54.00	-12.75	AVG
7222.000	39.46	22.05	61.51	74.00	-12.49	peak
7222.000	20.31	22.05	42.36	54.00	-11.64	AVG
8514.000	34.31	23.64	57.95	74.00	-16.05	peak
8514.000	14.38	23.64	38.02	54.00	-15.98	AVG
11914.000	32.18	26.96	59.14	74.00	-14.86	peak
11914.000	12.37	26.96	39.33	54.00	-14.67	AVG
14022.000	32.84	28.34	61.18	74.00	-12.82	peak
14022.000	15.76	28.34	44.10	54.00	-9.90	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2424MHz	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2424.000	90.12	10.05	100.17	114.00	-13.83	peak
2424.000	80.17	10.05	90.22	94.00	-3.78	AVG
4859.000	53.25	16.48	69.73	74.00	-4.27	peak
4859.000	25.89	16.48	42.37	54.00	-11.63	AVG
7307.000	38.55	22.14	60.69	74.00	-13.31	peak
7307.000	23.57	22.14	45.71	54.00	-8.29	AVG
11710.000	32.77	26.71	59.48	74.00	-14.52	peak
11710.000	18.59	26.71	45.30	54.00	-8.70	AVG
14022.000	32.89	28.34	61.23	74.00	-12.77	peak
14022.000	16.88	28.34	45.22	54.00	-8.78	AVG
15892.000	35.59	26.93	62.52	74.00	-11.48	peak
15892.000	13.10	26.93	40.03	54.00	-13.97	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2424MHz	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2424.000	82.58	10.05	92.63	114.00	-21.37	peak
2424.000	73.97	10.05	84.02	94.00	-9.98	AVG
4859.000	45.43	16.48	61.91	74.00	-12.09	peak
4859.000	26.18	16.48	42.66	54.00	-11.34	AVG
7307.000	37.69	22.14	59.83	74.00	-14.17	peak
7307.000	23.07	22.14	45.21	54.00	-8.79	AVG
11744.000	32.86	26.72	59.58	74.00	-14.42	peak
11744.000	9.58	26.72	36.30	54.00	-17.70	AVG
13427.000	32.56	28.70	61.26	74.00	-12.74	peak
13427.000	13.80	28.70	42.50	54.00	-11.50	AVG
16589.000	35.57	27.14	62.71	74.00	-11.29	peak
16589.000	18.06	27.14	45.20	54.00	-8.80	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2433MHz	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2433.000	90.49	10.08	100.57	114.00	-13.43	peak
2433.000	77.03	10.08	87.11	94.00	-6.89	AVG
4842.000	57.35	16.41	73.76	74.00	-0.24	peak
4842.000	26.03	16.41	42.44	54.00	-11.56	AVG
7273.000	38.30	22.13	60.43	74.00	-13.57	peak
7273.000	22.08	22.13	44.21	54.00	-9.79	AVG
8684.000	33.18	24.12	57.30	74.00	-16.70	peak
8684.000	15.21	24.12	39.33	54.00	-14.67	AVG
10792.000	32.83	26.26	59.09	74.00	-14.91	peak
10792.000	15.59	26.26	41.85	54.00	-12.15	AVG
13512.000	32.91	28.64	61.55	74.00	-12.45	peak
13512.000	15.13	28.64	43.77	54.00	-10.23	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	25 °C	Relative Humidity :	51%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	TX 2433MHz	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2433.000	85.46	10.08	95.54	114.00	-18.46	peak
2433.000	72.22	10.08	82.30	94.00	-11.70	AVG
4842.000	43.82	16.41	60.23	74.00	-13.77	peak
4842.000	23.73	16.41	40.14	54.00	-13.86	AVG
7273.000	38.39	22.13	60.52	74.00	-13.48	peak
7273.000	22.43	22.13	44.56	54.00	-9.44	AVG
9330.000	33.36	24.73	58.09	74.00	-15.91	peak
9330.000	12.71	24.73	37.44	54.00	-16.56	AVG
13461.000	32.10	28.68	60.78	74.00	-13.22	peak
13461.000	14.34	28.68	43.02	54.00	-10.98	AVG
15620.000	35.01	27.31	62.32	74.00	-11.68	peak
15620.000	17.80	27.31	45.11	54.00	-8.89	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. BANDWIDTH TEST


4.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW $\geq$ RBW, Sweep time = Auto.

4.2 DEVIATION FROM STANDARD

No deviation.

4.3 TEST SETUP



5. TEST RESULTS


EUT :	Remote control	Model Name :	RF012Q-LJD-001
Temperature :	26 °C	Relative Humidity :	53%
Pressure :	1020 hPa	Test Power :	DC 3V
Test Mode :	TX(2406MHz/2424MHz/2433MHz)		

Test Frequency (MHz)	20 dBc Bandwidth (MHz)
2406	2.496
2424	2.474
2433	2.387

2406 MHz



20 dBc Bandwidth 2424MHz



20 dBc Bandwidth 2433MHz



END OF REPORT