

EXHIBIT C - RF EXPOSURE EVALUATION

Maximum Permissible Exposure (MPE)

Applicable Standard

According to subpart §1.1310,15.247(i) systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | / | / | f/1500 | 30 |
| 1500–100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

| Mode | Frequency (MHz) | Antenna Gain ▲ | | Conducted output power including Tune-up Tolerance ▲ | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|------|-----------------|----------------|-----------|--|--------|--------------------------|-------------------------------------|---------------------------------|
| | | (dBi) | (numeric) | (dBm) | (mW) | | | |
| WiFi | 2412-2462 | 2.27 | 1.69 | 23.0 | 199.53 | 20.00 | 0.067 | 1.0 |
| NFC | 13.56 | / | / | -27.64 | 0.002 | 20.00 | <<0.001 | 0.98 |

Note:
NFC field strength is 67.56dB μ V/m @ 3m = -27.64 dBm EIRP. That equal to antenna gain is 0dBi and used the EIRP value as conducted power.

Note:

The Antenna Gain and Conducted output power including Tune-up Tolerance provided by manufacturer.

NFC and WiFi can transmit simultaneously, it is too small to calculated.

Result: The device meet FCC MPE at 20 cm distance

***** END OF REPORT *****