

TEST REPORT

Applicant: ShenZhen FLYSKY Technology Co.,Ltd

Address of Applicant: 16F, Huafeng Building, No. 6006 Shennan Road, Futian District, Shenzhen, Guangdong, China

Manufacturer: ShenZhen FLYSKY Technology Co.,Ltd

Address of Manufacturer: 16F, Huafeng Building, No. 6006 Shennan Road, Futian District, Shenzhen, Guangdong, China

Factory: Dongguan Flysky RC Model technology Co.,Ltd

Address of Factory: West building 3, Huangjinyuan Ind Park, Qiaoli North Gate, Changping Town, Dongguan, China

Equipment Under Test (EUT)

Product Name: 8-Channel Receiver

Model No.: EMr

Trade Mark: FLYSKY

FCC ID: 2A2UNEMR000000

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: March 11, 2024

Date of Test: March 12, 2024-October 30, 2024

Date of report issued: October 30, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	October 30, 2024	Original

Prepared By:



Date:

October 30, 2024

Project Engineer

Check By:



Reviewer

Date:

October 30, 2024

3 Contents

Page

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
4.1	MEASUREMENT UNCERTAINTY	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE	7
5.3	TEST FACILITY	7
5.4	TEST LOCATION	7
5.5	DESCRIPTION OF SUPPORT UNITS	7
5.6	DEVIATION FROM STANDARDS	7
5.7	ABNORMALITIES FROM STANDARD CONDITIONS	7
5.8	ADDITIONAL INSTRUCTIONS	7
6	TEST INSTRUMENTS LIST	8
7	TEST RESULTS AND MEASUREMENT DATA	10
7.1	ANTENNA REQUIREMENT	10
7.2	CONDUCTED EMISSIONS	11
7.3	CONDUCTED PEAK OUTPUT POWER	14
7.4	CHANNEL BANDWIDTH	15
7.5	CARRIER FREQUENCIES SEPARATION	16
7.6	HOPPING CHANNEL NUMBER	17
7.7	DWELL TIME	18
7.8	SPURIOUS EMISSION	19
7.8.1	Conducted Emission Method	19
7.8.2	Radiated Emission Method	20
8	TEST SETUP PHOTO	35
9	EUT CONSTRUCTIONAL DETAILS	35

4 Test Summary

Test Item	Section	Result
Antenna Requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(2)(3)	Pass
Channel Bandwidth	15.247 (a)(1)(2)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)(iii)	Pass
Dwell Time	15.247(a)(1)(i)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.10:2013.

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz~30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	8-Channel Receiver
Model No.:	EMr
Serial No.:	RD1001579
Test sample(s) ID:	GTS2024030127-1
Sample(s) Status	Engineer sample
Operation Frequency:	905.1MHz~926.4MHz
Channel numbers:	143
Modulation technology:	FHSS
Modulation type:	FLRC
Antenna Type:	ANT 1: T- Antenna ANT 2: T- Antenna
Antenna gain:	ANT 1: 1.03dBi ANT 2: 1.03dBi
Power supply:	DC 3.5-9V

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

The test frequencies are below:

Channel	Frequency(MHz)
The lowest channel	905.1
The middle channel	915.75
The Highest channel	926.4

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905.1	37	910.5	73	915.9	109	921.3
2	905.25	38	910.65	74	916.05	110	921.45
3	905.4	39	910.8	75	916.2	111	921.6
4	905.55	40	910.95	76	916.35	112	921.75
5	905.7	41	911.1	77	916.5	113	921.9
6	905.85	42	911.25	78	916.65	114	922.05
7	906	43	911.4	79	916.8	115	922.2
8	906.15	44	911.55	80	916.95	116	922.35
9	906.3	45	911.7	81	917.1	117	922.5
10	906.45	46	911.85	82	917.25	118	922.65
11	906.6	47	912	83	917.4	119	922.8
12	906.75	48	912.15	84	917.55	120	922.95
13	906.9	49	912.3	85	917.7	121	923.1
14	907.05	50	912.45	86	917.85	122	923.25
15	907.2	51	912.6	87	918	123	923.4
16	907.35	52	912.75	88	918.15	124	923.55
17	907.5	53	912.9	89	918.3	125	923.7
18	907.65	54	913.05	90	918.45	126	923.85
19	907.8	55	913.2	91	918.6	127	924
20	907.95	56	913.35	92	918.75	128	924.15
21	908.1	57	913.5	93	918.9	129	924.3
22	908.25	58	913.65	94	919.05	130	924.45
23	908.4	59	913.8	95	919.2	131	924.6
24	908.55	60	913.95	96	919.35	132	924.75
25	908.7	61	914.1	97	919.5	133	924.9
26	908.85	62	914.25	98	919.65	134	925.05
27	909	63	914.4	99	919.8	135	925.2
28	909.15	64	914.55	100	919.95	136	925.35
29	909.3	65	914.7	101	920.1	137	925.5
30	909.45	66	914.85	102	920.25	138	925.65
31	909.6	67	915	103	920.4	139	925.8
32	909.75	68	915.15	104	920.55	140	925.95
33	909.9	69	915.3	105	920.7	141	926.1
34	910.05	70	915.45	106	920.85	142	926.25
35	910.2	71	915.6	107	921	143	926.4
36	910.35	72	915.75	108	921.15		

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode. New battery used
-------------------	---

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC —Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● ISED —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing. ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.4 Test Location

All other tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number
ShenZhen FLYSKY Technology Co.,Ltd	Remote control	Noble NB4 Pro+	N/A
GW	DC POWER SUPPLY	GPR-6030D	EF924756

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Jun. 22, 2024	Jun. 21, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 11, 2024	Apr. 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Mar. 19, 2023	Mar. 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 17, 2023	Apr. 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Apr. 11, 2024	Apr. 10, 2025
8	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 13, 2023	Nov.12, 2024
9	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2024	Apr. 10, 2025
10	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2024	Apr. 10, 2025
11	Horn Antenna (15GH-40GHz)	SCHWARZBECK	01296	GTS691	Mar. 07, 2024	Mar. 06, 2025
12	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 12, 2024	Mar. 11, 2025
13	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2024	Apr. 10, 2025
14	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 08, 2023	Nov. 07, 2024
15	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2024	Apr. 10, 2025
16	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 18, 2024	Apr. 17, 2025
17	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
23	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
24	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 11, 2024	Apr. 10, 2025
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2024	Apr. 10, 2025
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
6	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 18, 2024	Apr. 17, 2025
7	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 11, 2024	Apr. 10, 2025
8	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2024	Apr. 10, 2025
9	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2024	Apr. 10, 2025
10	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2024	Apr. 10, 2025

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 13, 2024	Apr. 12, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 13, 2024	Apr. 12, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 13, 2024	Apr. 12, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 13, 2024	Apr. 12, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 13, 2024	Apr. 12, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 13, 2024	Apr. 12, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 13, 2024	Apr. 12, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 13, 2024	Apr. 12, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 18, 2024	Apr. 17, 2025
10	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 03, 2023	Nov. 02, 2024

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Apr. 18, 2024	Apr. 17, 2025

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is T- antenna, reference to the appendix II for details.	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane 40cm LISN AUX Equipment E.U.T. Test table/Insulation plane 80cm 40cm LISN Filter AC power EMI Receiver Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test results:	Pass					
Test voltage:	AC 120V					

Measurement data


Pre-scan all test modes, found worst case at 905.1MHz@Ant 1, and so only show the test result of it.

Line:



Freq	Reading	LISN/ISN	Cable		Limit	Over	
	level	factor	loss	Level	level	limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.23	27.17	9.51	0.01	36.69	62.44	-25.75	QP
0.23	3.34	9.51	0.01	12.86	52.44	-39.58	Average
0.44	16.27	9.49	0.01	25.77	57.15	-31.38	QP
0.44	-2.35	9.49	0.01	7.15	47.15	-40.00	Average
0.84	8.74	9.49	0.03	18.26	56.00	-37.74	QP
0.84	1.80	9.49	0.03	11.32	46.00	-34.68	Average
2.84	-1.48	9.54	0.05	8.11	56.00	-47.89	QP
2.84	-6.05	9.54	0.05	3.54	46.00	-42.46	Average
6.19	-1.38	9.38	0.08	8.08	60.00	-51.92	QP
6.19	-5.91	9.38	0.08	3.55	50.00	-46.45	Average
16.84	12.41	9.74	0.17	22.32	60.00	-37.68	QP
16.84	7.08	9.74	0.17	16.99	50.00	-33.01	Average

Neutral:




Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.17	28.33	9.55	0.01	37.89	65.16	-27.27	QP
0.17	4.81	9.55	0.01	14.37	55.16	-40.79	Average
0.32	23.55	9.56	0.01	33.12	59.80	-26.68	QP
0.32	10.01	9.56	0.01	19.58	49.80	-30.22	Average
0.63	17.25	9.56	0.02	26.83	56.00	-29.17	QP
0.63	7.70	9.56	0.02	17.28	46.00	-28.72	Average
1.74	-2.05	9.55	0.04	7.54	56.00	-48.46	QP
1.74	-4.90	9.55	0.04	4.69	46.00	-41.31	Average
5.77	-1.24	9.55	0.07	8.38	60.00	-51.62	QP
5.77	-5.90	9.55	0.07	3.72	50.00	-46.28	Average
17.02	9.21	9.85	0.17	19.23	60.00	-40.77	QP
17.02	3.73	9.85	0.17	13.75	50.00	-36.25	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247(b)(2)(3)
Test Method:	ANSI C63.10:2013
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix.

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(2)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a table labeled 'Non-Conducted Table'. Below this table is a shaded area labeled 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix.

7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix.

7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=50kHz, VBW=150kHz, Frequency range=902MHz-928MHz, Detector=Peak
Limit:	Report for Use
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both devices are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix.


7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247(a)(1)(i)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=300KHz, VBW=300KHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix.


7.8 Spurious Emission


7.8.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.
Test Instruments:	Refer to section6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix.

7.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 18GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP/PK/AV	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
5000		Peak			
Test setup:	Below 30MHz				
					
	Below 1GHz				



Above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments:

Refer to section 5.8 for details

Test mode:

Refer to section 5.2 for details

Temp. / Hum.

Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
--------	-------	---------	-----	---------	-----------

Test results:	Pass
Test voltage:	AC 120V

Remark:


1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement data:**■ Below 30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


- 30MHz ~ 1GHz
- All antennas have test, only the worst case ANT 1 report.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.437	29.53	14.29	1.25	32.30	12.77	40.00	-27.23	QP
68.631	33.03	10.94	1.63	32.37	13.23	40.00	-26.77	QP
186.441	34.78	10.96	2.76	32.41	16.09	43.50	-27.41	QP
429.523	39.11	15.49	3.98	32.24	26.34	46.00	-19.66	QP
902.000	37.56	23.10	5.74	31.10	35.30	46.00	-10.70	QP
928.000	26.06	23.36	5.81	31.10	24.13	46.00	-21.87	QP

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.510	46.77	12.50	1.13	32.30	28.10	40.00	-11.90	QP
69.600	47.48	10.84	1.64	32.38	27.58	40.00	-12.42	QP
167.824	35.39	13.62	2.62	32.43	19.20	43.50	-24.30	QP
428.019	35.47	15.46	3.97	32.24	22.66	46.00	-23.34	QP
902.000	35.85	23.10	5.74	31.10	33.59	46.00	-12.41	QP
928.000	28.57	23.36	5.81	31.10	26.64	46.00	-19.36	QP

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.576	29.56	14.32	1.25	32.30	12.83	40.00	-27.17	QP
71.330	41.14	10.67	1.65	32.39	21.07	40.00	-18.93	QP
186.441	35.56	10.96	2.76	32.41	16.87	43.50	-26.63	QP
425.028	37.55	15.40	3.96	32.24	24.67	46.00	-21.33	QP
902.000	28.78	23.10	5.74	31.10	26.52	46.00	-19.48	QP
928.000	26.78	23.36	5.81	31.10	24.85	46.00	-21.15	QP

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.399	45.19	12.50	1.13	32.30	26.52	40.00	-13.48	QP
68.391	45.62	10.96	1.62	32.37	25.83	40.00	-14.17	QP
103.080	37.46	9.92	1.97	32.50	16.85	43.50	-26.65	QP
155.910	33.02	14.80	2.52	32.44	17.90	43.50	-25.60	QP
902.000	27.39	23.10	5.74	31.10	25.13	46.00	-20.87	QP
928.000	26.90	23.36	5.81	31.10	24.97	46.00	-21.03	QP

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.715	29.01	14.34	1.26	32.30	12.31	40.00	-27.69	QP
130.379	39.33	13.24	2.28	32.47	22.38	43.50	-21.12	QP
186.441	36.21	10.96	2.76	32.41	17.52	43.50	-25.98	QP
428.019	36.12	15.46	3.97	32.24	23.31	46.00	-22.69	QP
902.000	30.36	23.10	5.74	31.10	28.10	46.00	-17.90	QP
928.000	39.90	23.36	5.81	31.10	37.97	46.00	-8.03	QP


Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
68.391	44.75	10.96	1.62	32.37	24.96	40.00	-15.04	QP
155.910	33.00	14.80	2.52	32.44	17.88	43.50	-25.62	QP
426.521	31.86	15.43	3.97	32.24	19.02	46.00	-26.98	QP
694.417	33.47	20.49	5.06	31.49	27.53	46.00	-18.47	QP
902.000	29.76	23.10	5.74	31.10	27.50	46.00	-18.50	QP
928.000	41.00	23.36	5.81	31.10	39.07	46.00	-6.93	QP


- Above 1GHz
- All antennas have test, only the worst case ANT 1 report.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1810.000	41.46	25.85	8.01	38.55	36.77	54.00	-17.23	Average
1810.000	54.65	25.85	8.01	38.55	49.96	74.00	-24.04	Peak
2715.000	45.65	27.92	4.46	38.60	39.43	54.00	-14.57	Average
2715.000	56.36	27.92	4.46	38.60	50.14	74.00	-23.86	Peak
3620.000	43.35	28.77	4.95	38.43	38.64	54.00	-15.36	Average
3620.000	52.44	28.77	4.95	38.43	47.73	74.00	-26.27	Peak
4525.000	37.85	30.27	7.79	38.31	37.60	54.00	-16.40	Average
4525.000	48.58	30.27	7.79	38.31	48.33	74.00	-25.67	Peak
5430.000	37.96	32.20	7.03	38.57	38.62	54.00	-15.38	Average
5430.000	45.47	32.20	7.03	38.57	46.13	74.00	-27.87	Peak
6335.000	39.65	33.71	9.37	38.77	43.96	54.00	-10.04	Average
6335.000	50.68	33.71	9.37	38.77	54.99	74.00	-19.01	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1810.000	49.56	25.85	8.01	38.55	44.87	54.00	-9.13	Average
1810.000	61.29	25.85	8.01	38.55	56.60	74.00	-17.40	Peak
2715.000	42.85	27.92	4.46	38.60	36.63	54.00	-17.37	Average
2715.000	53.46	27.92	4.46	38.60	47.24	74.00	-26.76	Peak
3620.000	40.66	28.77	4.95	38.43	35.95	54.00	-18.05	Average
3620.000	50.77	28.77	4.95	38.43	46.06	74.00	-27.94	Peak
4525.000	35.77	30.27	7.79	38.31	35.52	54.00	-18.48	Average
4525.000	45.79	30.27	7.79	38.31	45.54	74.00	-28.46	Peak
5430.000	34.29	32.20	7.03	38.57	34.95	54.00	-19.05	Average
5430.000	46.25	32.20	7.03	38.57	46.91	74.00	-27.09	Peak
6335.000	40.45	33.71	9.37	38.77	44.76	54.00	-9.24	Average
6335.000	52.48	33.71	9.37	38.77	56.79	74.00	-17.21	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1831.000	42.76	25.95	7.57	38.54	37.74	54.00	-16.26	Average
1831.000	53.82	25.95	7.57	38.54	48.80	74.00	-25.20	Peak
2746.500	43.39	27.99	4.49	38.60	37.27	54.00	-16.73	Average
2746.500	54.27	27.99	4.49	38.60	48.15	74.00	-25.85	Peak
3662.000	41.91	28.83	5.27	38.40	37.61	54.00	-16.39	Average
3662.000	52.79	28.83	5.27	38.40	48.49	74.00	-25.51	Peak
4577.500	36.94	30.42	8.46	38.32	37.50	54.00	-16.50	Average
4577.500	48.69	30.42	8.46	38.32	49.25	74.00	-24.75	Peak
5493.000	35.43	32.29	6.95	38.60	36.07	54.00	-17.93	Average
5493.000	47.64	32.29	6.95	38.60	48.28	74.00	-25.72	Peak
6408.500	38.55	33.97	9.43	38.78	43.17	54.00	-10.83	Average
6408.500	50.75	33.97	9.43	38.78	55.37	74.00	-18.63	Peak

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1831.000	48.47	25.95	7.57	38.54	43.45	54.00	-10.55	Average
1831.000	61.66	25.95	7.57	38.54	56.64	74.00	-17.36	Peak
2746.500	46.47	27.99	4.49	38.60	40.35	54.00	-13.65	Average
2746.500	60.34	27.99	4.49	38.60	54.22	74.00	-19.78	Peak
3662.000	45.46	28.83	5.27	38.40	41.16	54.00	-12.84	Average
3662.000	53.66	28.83	5.27	38.40	49.36	74.00	-24.64	Peak
4577.500	36.80	30.42	8.46	38.32	37.36	54.00	-16.64	Average
4577.500	47.38	30.42	8.46	38.32	47.94	74.00	-26.06	Peak
5493.000	35.81	32.29	6.95	38.60	36.45	54.00	-17.55	Average
5493.000	46.48	32.29	6.95	38.60	47.12	74.00	-26.88	Peak
6408.500	40.46	33.97	9.43	38.78	45.08	54.00	-8.92	Average
6408.500	52.94	33.97	9.43	38.78	57.56	74.00	-16.44	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1853.000	43.47	26.06	7.11	38.52	38.12	54.00	-15.88	Average
1853.000	52.46	26.06	7.11	38.52	47.11	74.00	-26.89	Peak
2779.500	45.64	28.07	4.53	38.60	39.64	54.00	-14.36	Average
2779.500	54.56	28.07	4.53	38.60	48.56	74.00	-25.44	Peak
3706.000	41.43	28.89	5.61	38.38	37.55	54.00	-16.45	Average
3706.000	51.73	28.89	5.61	38.38	47.85	74.00	-26.15	Peak
4632.500	36.90	30.57	8.53	38.33	37.67	54.00	-16.33	Average
4632.500	48.59	30.57	8.53	38.33	49.36	74.00	-24.64	Peak
5559.000	36.45	32.32	6.86	38.61	37.02	54.00	-16.98	Average
5559.000	48.46	32.32	6.86	38.61	49.03	74.00	-24.97	Peak
6485.500	37.96	34.25	9.43	38.80	42.84	54.00	-11.16	Average
6485.500	49.49	34.25	9.43	38.80	54.37	74.00	-19.63	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
1853.000	47.88	26.06	7.11	38.52	42.53	54.00	-11.47	Average
1853.000	58.63	26.06	7.11	38.52	53.28	74.00	-20.72	Peak
2779.500	45.88	28.07	4.53	38.60	39.88	54.00	-14.12	Average
2779.500	56.50	28.07	4.53	38.60	50.50	74.00	-23.50	Peak
3706.000	41.48	28.89	5.61	38.38	37.60	54.00	-16.40	Average
3706.000	53.16	28.89	5.61	38.38	49.28	74.00	-24.72	Peak
4632.500	36.81	30.57	8.53	38.33	37.58	54.00	-16.42	Average
4632.500	47.68	30.57	8.53	38.33	48.45	74.00	-25.55	Peak
5559.000	37.90	32.32	6.86	38.61	38.47	54.00	-15.53	Average
5559.000	48.14	32.32	6.86	38.61	48.71	74.00	-25.29	Peak
6485.500	42.15	34.25	9.43	38.80	47.03	54.00	-6.97	Average
6485.500	51.65	34.25	9.43	38.80	56.53	74.00	-17.47	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

---End---