



FCC TEST REPORT

For

NAHOU (GUANGZHOU) INTELLIGENT MANUFACTURING CO., LTD

BLUE LAVA AirFlow Wireless Charger

Test Model: AirFlow Wireless Charger

Additional Model No.: Please Refer to Page 6

Prepared for

: NAHOU (GUANGZHOU) INTELLIGENT MANUFACTURING
CO., LTD

Address

: Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District,
Guangzhou, Guangdong, China

Prepared by

: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address

: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,
Baoan District, Shenzhen, China

Tel

: (+86)755-82591330

Fax

: (+86)755-82591332

Web

: www.LCS-cert.com

Mail

: webmaster@LCS-cert.com

Date of receipt of test sample

: October 22, 2021

Number of tested samples

: 2

Serial number

: 211018109A-1(Engineer sample), 211018109A-2(Normal sample)

Date of Test

: October 22, 2021 ~ November 23, 2021

Date of Report

: November 25, 2021



FCC TEST REPORT
FCC CFR 47 PART 15C

Report Reference No. : LCS211018109AEA

Date Of Issue : November 25, 2021

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China

Testing Location/ Procedure..... :
Full application of Harmonised standards
Partial application of Harmonised standards
Other standard testing method

Applicant's Name : NAHUO (GUANGZHOU) INTELLIGENT MANUFACTURING CO., LTD

Address..... : Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China

Test Specification

Standard..... : FCC CFR 47 PART 15C

Test Report Form No..... : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : BLUE LAVA AirFlow Wireless Charger

Trade Mark : LAVA ME /BLUE LAVA

Test Model..... : AirFlow Wireless Charger

Power Supply : Input: 9V=2A MAX
Output: 5V=2A MAX 10W

Result : Positive

Compiled by:

Jack Liu/ Administrator

Supervised by:

Jin Wang/ Technique principal

Approved by:

Gavin Liang/ Manager



FCC TEST REPORT

Test Report No. : LCS211018109AEA	<u>November 25, 2021</u> Date of issue
--	---

Test Model.....	: AirFlow Wireless Charger
EUT.....	: BLUE LAVA AirFlow Wireless Charger
Applicant.....	: NAHUO (GUANGZHOU) INTELLIGENT MANUFACTURING CO., LTD Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Address.....	: Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: NAHUO (GUANGZHOU) INTELLIGENT MANUFACTURING CO., LTD Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Address.....	: Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Telephone.....	: /
Fax.....	: /
Factory.....	: NAHUO (GUANGZHOU) INTELLIGENT MANUFACTURING CO., LTD Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Address.....	: Room103, No.4 Yuanxiadi Road, Jiangxia, Baiyun District, Guangzhou, Guangdong, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Revision History

Revision	Issue Date	Revisions	Revised By
000	November 25, 2021	Initial Issue	Gavin Liang



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1 Description of Device (EUT)	6
1.2 Support equipment List	6
1.3 External I/O Cable.....	6
1.4 Description of Test Facility	6
1.5 Statement of the Measurement Uncertainty	7
1.6 Measurement Uncertainty	7
1.7 Description of Test Modes	7
2. TEST METHODOLOGY.....	8
2.1 EUT Configuration.....	8
2.2 EUT Exercise	8
2.3 General Test Procedures.....	8
2.3.1 Conducted Emissions	8
2.3.2 Radiated Emissions	8
2.4. Test Sample	8
3. SYSTEM TEST CONFIGURATION	9
3.1 Justification	9
3.2 EUT Exercise Software	9
3.3 Special Accessories	9
3.4 Block Diagram/Schematics	9
3.5 Equipment Modifications	9
3.6 Test Setup.....	9
4. SUMMARY OF TEST EQUIPMENT	10
5. SUMMARY OF TEST RESULT.....	11
6. POWER LINE CONDUCTED MEASUREMENT	12
7. RADIATED EMISSION MEASUREMENT.....	15
7.1. Block Diagram of Test Setup	15
7.2. Radiated Emission Limit	16
7.3. EUT Configuration on Measurement	16
7.4. Operating Condition of EUT	16
7.5. Measuring Setting	16
7.6. Test Procedure.....	17
7.7. Test Results	18
8. PHOTOGRAPHS OF TEST SETUP	22
9. EXTERNAL PHOTOGRAPHS OF THE EUT	22
10. INTERNAL PHOTOGRAPHS OF THE EUT	22



1. GENERAL INFORMATION

1.1 Description of Device (EUT)

EUT : BLUE LAVA AirFlow Wireless Charger

Test Model : AirFlow Wireless Charger

Additional Model No. : AirFlow Wireless Charger 2, AirFlow Wireless Charger 3, AirFlow Wireless Charger 4, AirFlow Wireless Charger 5

Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested

Power Supply : Input: 9V==2A MAX
Output: 5V==2A MAX 10W

Hardware Version : /

Software Version : /

Wireless Charging :

Operating Frequency : 110.3~205.0KHz

Modulation Type : Continuous Wave

Antenna Type : Coil Antenna

1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Shenzhen REMAX Co., Ltd	Adapter	RP-U70	--	FCC

Note: Adapter is supplied by lab and only used test.

1.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Port	1	Cable: 2.0m, unshielded

1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.



1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

Charging and communication mode

Modulation Type: CW (Continuous Wave)

Test Modes		
Mode 1	AC/DC Adapter (9V/2A) + EUT + Guitar (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter (9V/2A) + EUT + Guitar (Battery Status: <50%)	Pre-tested
Mode 3	AC/DC Adapter (9V/2A) + EUT + Guitar (Battery Status: 100%)	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR PART 15C 15.207.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the normal operating mode for Hopping Numbers and Dwell Time test and a continuous transmits mode for other tests.

According to its specifications, the EUT must comply with the requirements of the Section 15.207 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

2.4. Test Sample

The application provides 2 samples to meet requirement;

Sample Number	Description
Sample 1(211018109A-1)	Engineer sample – continuous transmit
Sample 2(211018109A-2)	Normal sample – Intermittent transmit



3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a normal condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
/	/	/	/	/	/	/	/

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.



4. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100040	2021-06-21	2022-06-20
2	SPECTRUM ANALYZER	R&S	FSP40	100503	2021-11-16	2022-11-15
3	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2021-06-21	2022-06-20
4	Positioning Controller	MF	MF7082	MF78020803	2021-06-21	2022-06-20
5	EMI Test Software	AUDIX	E3	/	N/A	N/A
6	EMI Test Receiver	R&S	ESR 7	101181	2021-06-21	2022-06-20
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-07-25	2024-07-24
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-07-25	2024-07-24
9	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-07-01	2024-06-30
10	EMI Test Receiver	R&S	ESPI	101840	2021-06-21	2022-06-20
11	Artificial Mains	R&S	ENV216	101288	2021-06-21	2022-06-20
12	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2021-06-21	2022-06-20



5. SUMMARY OF TEST RESULT


FCC Rules	Description of Test	Test Sample	Result
§15.209	<i>Radiated Spurious Emissions</i>	<i>Sample 1</i>	<i>Compliant</i>
§15.207(a)	<i>AC Conducted Emissions</i>	<i>Sample 1</i>	<i>Compliant</i>

Remark: The measurement uncertainty is not included in the test result.

N/A – Not Applicable!!!

6. POWER LINE CONDUCTED MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Standard Applicable

According to §15.207: For all the consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

6.3 Test Results


PASS

The test data please refer to following page.

Temperature	22.5°C	Humidity	53.7%
Test Engineer	Kay Hu	Configurations	Transmit

AC Power Line Conducted Emission (Power input to adapter @ AC 120V/60Hz (Worst Case))


Line



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.6270	23.71	19.81	43.52	56.00	-12.48	QP	
2		0.6270	17.53	19.81	37.34	46.00	-8.66	AVG	
3		1.7250	25.41	19.83	45.24	56.00	-10.76	QP	
4		1.7250	19.93	19.83	39.76	46.00	-6.24	AVG	
5		2.0400	26.87	19.84	46.71	56.00	-9.29	QP	
6		2.0400	20.70	19.84	40.54	46.00	-5.46	AVG	
7		3.1426	28.04	19.88	47.92	56.00	-8.08	QP	
8		3.1426	20.22	19.88	40.10	46.00	-5.90	AVG	
9		4.2451	27.18	19.90	47.08	56.00	-8.92	QP	
10	*	4.2451	21.29	19.90	41.19	46.00	-4.81	AVG	
11		24.2386	17.43	20.76	38.19	60.00	-21.81	QP	
12		24.2386	12.65	20.76	33.41	50.00	-16.59	AVG	



Neutral





No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
1		0.4246	28.14	19.76	47.90	57.36	-9.46	QP	
2	*	0.4246	25.58	19.76	45.34	47.36	-2.02	AVG	
3		0.7935	21.18	19.77	40.95	56.00	-15.05	QP	
4		0.8565	16.16	19.77	35.93	46.00	-10.07	AVG	
5		2.0400	23.35	19.83	43.18	56.00	-12.82	QP	
6		2.0400	16.39	19.83	36.22	46.00	-9.78	AVG	
7		3.1426	24.77	19.87	44.64	56.00	-11.36	QP	
8		3.1426	16.62	19.87	36.49	46.00	-9.51	AVG	
9		10.5406	20.29	20.13	40.42	60.00	-19.58	QP	
10		10.5406	14.79	20.13	34.92	50.00	-15.08	AVG	
11		24.2476	15.44	20.63	36.07	60.00	-23.93	QP	
12		24.2476	12.09	20.63	32.72	50.00	-17.28	AVG	

***Note: Pre-scan all modes and recorded the worst case results in this report.

Margin=Reading level + Correct - Limit

7. RADIATED EMISSION MEASUREMENT

7.1. Block Diagram of Test Setup





7.2. Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

7.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

- (1) Setup the EUT as shown in Section 7.1.
- (2) Let the EUT work in worst test mode (Mode 1) and measure it.

7.5. Measuring Setting



The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/Average
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/Average
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

7.6. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 ° to 315 ° using 45 ° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0 ° to 360 °) and by rotating the elevation axes (0 ° to 360 °).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 ° to 315 ° using 45 ° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45 °) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.7. Test Results


PASS.

Only report the worst test data (Mode 1) in test report;

The test data please refer to following page:

Temperature	23.7°C	Humidity	52.3%
Test Engineer	Kay Hu	Configurations	Transmit


0.009 MHz – 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.1682	41.43	20.40	61.83	103.06	-41.23	QP
2	0.3353	13.48	20.37	33.85	97.09	-63.24	QP
3 *	0.5030	15.48	20.32	35.80	73.57	-37.77	QP
4	0.6736	11.01	20.40	31.41	71.04	-39.63	QP
5	1.7975	30.91	-21.94	8.97	69.54	-60.57	QP
6	10.5358	10.09	-22.34	-12.25	69.54	-81.79	QP

Remark: 1). Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.


2). Margin=Reading level + Correct - Limit

**Below 1GHz****Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	36.3814	53.18	-30.40	22.78	40.00	-17.22	QP
2	143.8295	66.84	-31.61	35.23	43.50	-8.27	QP
3	216.0240	65.47	-29.29	36.18	46.00	-9.82	QP
4 *	239.9874	67.31	-28.48	38.83	46.00	-7.17	QP
5	455.9058	52.40	-25.87	26.53	46.00	-19.47	QP
6	656.5300	48.99	-22.10	26.89	46.00	-19.11	QP



Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	36.3814	57.01	-30.40	26.61	40.00	-13.39	QP
2	84.7019	58.41	-29.28	29.13	40.00	-10.87	QP
3 !	119.8556	67.29	-29.41	37.88	43.50	-5.62	QP
4 *	167.8243	71.18	-31.16	40.02	43.50	-3.48	QP
5 !	239.9874	69.24	-28.48	40.76	46.00	-5.24	QP
6	480.5276	53.65	-25.64	28.01	46.00	-17.99	QP

1). Emission level (dBuV/m) = 20 log Emission level (uV/m).

2). Margin=Reading level + Correct - Limit



8. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

9. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

10. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----