

Functional description of Ridepad

Function: 3 motors 7 modes with charging, manual and remote control for different modes (manual for combination mode, remote control mode 3 motors can be controlled independently).

I. Receiver:

1. A button, long press 2S to boot, and then short press conversion mode; Press and hold for 2S again to shut down the machine.
2. Boot LED1, LED2 (white light, two LED synchronization) flashing, remote standby state, at this time, press the button, LED1, LED2 long bright, the motor vibrates in the first mode, and press the conversion mode again (that is, 0-1-2-3-4-5-6-7-1.....) ; Leds, whether shiny or long, can be remote controlled.
4. The low voltage detection value is 3.2V; Two LED flash prompts when the battery voltage is lower than 3.2V;
5. Charging function: A=1, B=0 start charging, two leds shine at the same time; A=1, B=1 full, both leds are long and bright; When charging, the motor stops and the button has no function.
6. Automatic shutdown without operation for 30 minutes (effective when 3 motors have no output).

Transmitter: 3 keys,1 LED

- 1.K1 control the vibration mode of M1, and press the button to turn on M1 (ON1-2-3-4-5-6-7-1.....) Press for 1.5S to turn off vibration.
2. K2 control the vibration mode of M2, press and turn on M2 (ON1-2-3-4-5-6-7-1.....) Press for 1.5S to turn off vibration.
3. K3 Control M3 vibration mode, short press to open M3 (ON1-2-3-4-5-6-7-1.....) Press for 1.5S to turn off vibration.
4. Any function is turned on, LED is long bright state; When the button is pressed short, the LED will flash once; when the button is pressed long, the LED will flash twice. If there are other functions open, then shine twice to restore long bright; Extinguish if all functions are turned off).
5. Pressing K1 and K3 at the same time can quickly shut down the machine.
6. Automatic shutdown without operation for 30 minutes (only turn off the transmitter, do not send the shutdown code).

Three, the conversion relationship between remote control and manual: press the receiver button for manual mode, press the remote control button for remote control mode.

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction

FCC ID: 2A2W8-05599890000

Function	Operation Frequency	Max RF outputpower	Limit
SRD	433.88MHz	3.58 dBm	10dBm.

This product can be used across EU member states.

Receiver Category: 1

Applicant's name: ORION VERSAND GMBH & CO.KG.

Address: SCHAEFERWEG 14, D-24941 FLENSBURG, GERMANY

Importer: xxxxxx

Manufacturer's Name: TOPARC TECHNOLOGY (SHENZHEN) CO.,LTD.

Ridepad

Model number: 05599890000_163

Operating Temperature: -10° C to 40° C

This device is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU. All essential radio test suites have been carried out.

1. CAUTION : RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS
2. The device complies with RF Exposure.

