

## User's Manual

Applicant:	Taizhou Huitian Metal Products Co., LTD.			Model:	RXC-918A
Product Name:	Remote Controller for Iron flowerpot holder			Number of Keys:	2 PCS
Voltage:	3Vdc	Current:	4~5mA	TX Distance:	100m
Environment:	Indoor	Frequency:	433.92MHZ	Frequency Offset:	-50kHz/+30kHz



1. Press the button  , and the candle lamp installed on the Iron flowerpot holder will be lit. The candle lamp has a 433.92MHz chip receiver.
2. Press the button  , and the candle lamp installed on the Iron flowerpot holder will be turned off.
3. Note: This Remote Controller for Iron flowerpot holder can only be used if the manufacturer matches the candle lamp with the corresponding 433.92MHz receiver chip.

### Federal Communications Commission Notice:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.