

Model: HEATCURE 400  
Battery Capacity: 384.8Wh, 14.8V/26000mAh  
Interface: 2 x Type-C, 4 x USB-A, 2 x AC, 1 x Car Charger  
**DC Input**  
DC(5525): 19.0V=3.42A (65W Max)  
Type-C1: 5V=3A/ 9V=3A/ 12V=3A/ 15V=3A/ 20V=3A (60W Max)  
**AC Output**  
105V-120V~60Hz(300W Max)  
**DC Output**  
Type-C 1: 5V=3A/ 9V=3A/ 12V=3A/ 15V=3A/ 20V=3A (60W Max)  
Type-C 2: 5V=3A/ 9V=2A/ 12V=1.5A (18W Max)  
USB1&USB2: 5V=3A/ 9V=2A/ 12V=1.5A(QC 3.0)(Total 5V=3A)  
USB3&USB4: 5V=2.4A (Total 5V=3A)  
Car Charger: 12V=10A (120W Max)  
Wireless output 1&2: 5W/7.5W/10W

Charging Temperature: 0°C-40°C  
Discharge Temperature: -10°C-40°C  
FCC ID: 2A2Y7-HEATCURE400

This device complies with part 15 of the FCC Rules.  
Operation is subject to the following two conditions:  
(1) This device may not cause harmful interference, and  
(2) this device must accept any interference received, including  
interference that may cause undesired operation.  
CAUTION: Risk of Electric Shock. Do not remove cover

Eastway (Shanghai) Co., Ltd.  
Made in China

D/C: 3621



120mm

98mm

注: D/C: WWYY 前两码代表周, 后两码代表年份

**要求:**

1. 消银龙表面覆哑膜
2. 耐高温>80°C
3. 粘性加强



## Label Location