

# SAR TEST EXCLUSION EVALUATION REPORT

**Product Name:** Wireless Earbuds  
**Trade Mark:** N/A  
**Model No.:** AthlosLive-01  
**Report Number:** 210809012RFC-3  
**Test Standards:** FCC 47 CFR Part 2.1093  
**FCC ID:** 2A2YB-ALA  
**Test Result:** PASS  
**Date of Issue:** September 6, 2021

Prepared for:

**UniRAM Technology, Inc.**  
**19925 Stevens Creek Blvd. Suite 100, Cupertino, CA 95014, USA**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Prepared by: Gavin Xu  
Gavin Xu  
Project Engineer

Reviewed by: Henry Lu  
Henry Lu  
Team Leader

Approved by: Kevin Liang  
Kevin Liang  
Assistant Manager



Date: September 6, 2021

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

**Version**

Version No.	Date	Description
V1.0	September 6, 2021	Original



## CONTENTS

<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1 CLIENT INFORMATION .....	4
1.2 EUT INFORMATION .....	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD .....	4
1.4 OTHER INFORMATION.....	5
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	5
1.6 DEVIATION FROM STANDARDS .....	5
1.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	5
<b>2. EQUIPMENT LIST</b> .....	<b>6</b>
<b>3. SAR TEST EXCLUSION EVALUATION</b> .....	<b>6</b>
3.1 REFERENCE DOCUMENTS FOR EVALUATION .....	6
3.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION .....	6
3.2.1 SAR TEST EXCLUSION THRESHOLD.....	6
3.2.2 TEST PROCEDURE .....	7
3.3 MPE CALCULATION RESULTS .....	7
3.3.1 FOR BT.....	7
<b>APPENDIX 1 PHOTOS OF TEST SETUP</b> .....	<b>8</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b> .....	<b>8</b>

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	UniRAM Technology, Inc.
<b>Address of Applicant:</b>	19925 Stevens Creek Blvd. Suite 100, Cupertino, CA 95014, USA
<b>Manufacturer:</b>	UniRAM Technology, Inc.
<b>Address of Manufacturer:</b>	19925 Stevens Creek Blvd. Suite 100, Cupertino, CA 95014, USA
<b>Factory:</b>	Yuzhuo Technology Limited
<b>Address of Factory:</b>	Room 1806, No 2095, Bixin Road, Longgang District, Shenzhen, China

### 1.2 EUT INFORMATION

<b>Product Name:</b>	Wireless Earbuds	
<b>Model No.:</b>	AthlosLive-01	
<b>Add. Model No.:</b>	AL-001, AL-002, AL-003, AL-101, AL-102, AL-103, ALG-001, ALJ-001, ALW-001	
<b>Trade Mark:</b>	N/A	
<b>DUT Stage:</b>	Identical Prototype	
<b>EUT Supports Function:</b>	2.4 GHz ISM Band:	Bluetooth V4.2
<b>Sample Received Date:</b>	August 17, 2021	
<b>Sample Tested Date:</b>	August 22, 2021 to August 26, 2021	
<b>Note:</b> The additional model AL-001, AL-002, AL-003, AL-101, AL-102, AL-103, ALG-001, ALJ-001, ALW-001 is identical with the test model AthlosLive-01 except the model number for marketing purpose.		

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For BT_LE	
<b>Frequency Band:</b>	2400 MHz to 2483.5 MHz
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Bluetooth Version:</b>	Bluetooth LE
<b>Type of Modulation:</b>	GFSK
<b>Number of Channels:</b>	40
<b>Channel Separation:</b>	2 MHz
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	1.75 dBi
<b>Maximum Peak Power:</b>	0.88 dBm

For BT_EDR	
<b>Frequency Band:</b>	2400 MHz to 2483.5 MHz
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Bluetooth Version:</b>	Bluetooth BR + EDR
<b>Modulation Technique:</b>	Frequency Hopping Spread Spectrum(FHSS)
<b>Type of Modulation:</b>	GFSK, $\pi/4$ DQPSK, 8DPSK
<b>Number of Channels:</b>	79
<b>Channel Separation:</b>	1 MHz
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	1.75 dBi
<b>Maximum Peak Power:</b>	4.48 dBm

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS102-V1.1

### 1.4 OTHER INFORMATION

Test channels for BT_LE				
Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

Test channels for BT_EDR				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
$\pi/4$ DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

### 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

**FCC 47 CFR Part 2.1093**

All test items have been performed and recorded as per the above standards

### 1.6 DEVIATION FROM STANDARDS

None.

### 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

### 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

## 3. SAR TEST EXCLUSION EVALUATION

### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices.
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

### 3.2 EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION

#### 3.2.1 SAR Test Exclusion Threshold

##### 3.2.1.1 KDB 447498 D01 v06

#### Appendix A

#### *SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm*

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

MHz	30	35	40	45	50	mm
150	232	271	310	349	387	<i>SAR Test Exclusion Threshold (mW)</i>
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

**Note:** 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3.3 MPE CALCULATION RESULTS

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.3.1 For BT

For BT\_LE function, operating at 2402MHz to 2480 MHz for GFSK and

For BT\_EDR function, operating at 2402MHz to 2480 MHz for GFSK,  $\pi/4$  DQPSK, 8DPSK

#### 3.3.1.1 Antenna Type:

PCB Antenna

#### 3.3.1.2 Antenna Gain:

2402MHz to 2480 MHz: 1.75 dBi

#### 3.3.1.3 Results for BT

Operating Mode	Frequency (MHz)	Maximum conducted output power (dBm)	Antenna Gain (dBi)	Maximum EIRP		Separation Distance (mm)	SAR Test Exclusion Threshold (mW)
				(dBm)	(mW)		
BR+EDR	2402-2480	4.48	1.75	6.23	4.1976	5	10
LE	2402-2480	0.88	1.75	2.63	1.8323	5	10

## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

---

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---

---