



■ Report No.: DDT-R21090214-1E02

■ Issued Date: Sep. 13, 2021

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Bei Jing DeepCool Industries Co.,Ltd.
<b>Address</b>	:	No.101-30, Floor 1-4, Building 10, Dijin Road 9, Haidian Dist., Beijing China
<b>Equipment under Test</b>	:	Mouse
<b>Model No.</b>	:	MG510
<b>Trade Mark</b>	:	N/A
<b>FCC ID</b>	:	2A2YC-MG510
<b>Manufacturer</b>	:	Bei Jing DeepCool Industries Co.,Ltd.
<b>Address</b>	:	No.101-30, Floor 1-4, Building 10, Dijin Road 9, Haidian Dist., Beijing China

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add.:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel.:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## Table of Contents

Test report declares.....	3
1. General Information.....	5
1.1. Description of equipment.....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC .....	5
3. Estimtions Result.....	6

## Test Report Declare

<b>Applicant</b>	:	Bei Jing DeepCool Industries Co.,Ltd.
<b>Address</b>	:	No.101-30, Floor 1-4, Building 10, Dijin Road 9, Haidian Dist., Beijing China
<b>Equipment under Test</b>	:	Mouse
<b>Model No.</b>	:	MG510
<b>Trade mark</b>	:	N/A
<b>Manufacturer</b>	:	Bei Jing DeepCool Industries Co.,Ltd.
<b>Address</b>	:	No.101-30, Floor 1-4, Building 10, Dijin Road 9, Haidian Dist., Beijing China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R21090214-1E02		
<b>Date of Receipt:</b>	Sep. 03, 2021	<b>Date of Test:</b>	Sep. 03, 2021~Sep. 10, 2021

**Prepared By:**

*Johnny Wang*

**Johnny Wang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 13, 2021	

## 1. General Information

### 1.1. Description of equipment

EUT* Name	:	Mouse
Model Number	:	MG510
EUT function description	:	Please reference user manual of this device
Power Supply	:	DC 3.7V Polymer Li-ion built-in battery
Radio Specification	:	2.4G Digitally Modulated
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	:	GFSK
Data Rate	:	2 Mbps
Antenna Gain	:	-1.0 dBi
Serial Number	:	N/A

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### 3. Estimation Result

GFSK (Peak)			
Channel	Channel 1	Channel 3	Channel 16
Target (dBm)	1	1	1
Tolerance $\pm$ (dB)	1	1	1

Worse case is as below: [2480 MHz, 2 dBm, 1.58 mW] output power]

$$(1.58/5) \cdot [\sqrt{2.48(\text{GHz})}] = 0.50 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

**END OF REPORT**