

TEST REPORT

Product Name : Bone Conduction Headphones
Model Number : M3301
FCC ID : 2A2YH-M3301

Prepared for : Suzhou Mojawa Intelligent Electronic Co., Ltd
Address : Room F1-A-1028, Building A2, No. 8, Qicun Road,
Suzhou, Jiangsu Province, Suzhou, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2503250083E08903R
Date of sample receipt : March 25,2025
Date(s) of Tests : March 25,2025 to April 25,2025
Date of issue : April 25,2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Suzhou Mojawa Intelligent Electronic Co., Ltd
Address : Room F1-A-1028, Building A2, No. 8, Qicun Road, Suzhou, Jiangsu Province, Suzhou, China
Manufacturer : Suzhou Mojawa Intelligent Electronic Co., Ltd
Address : Room F1-A-1028, Building A2, No. 8, Qicun Road, Suzhou, Jiangsu Province, Suzhou, China
Factory : Ganzhou Ouxiang Electronics Co., Ltd.
Address : No. 66, Baokuang Road, Shangou Industrial Park, Yudu County, Ganzhou City, Jiangxi Province, P.R. China
EUT : Bone Conduction Headphones
Model Name : M3301
Trademark : **Mojawa**

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD.. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : March 25,2025 to April 25,2025

Prepared by : Warren Deng

Warren Deng /Editor

Reviewer : Tim Dong

Tim Dong /Supervisor

Approve & Authorized Signer : Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2503250083E08902R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Bone Conduction Headphones
Model Number:	M3301
Sample:	1#
Data Rate:	BLE: 1Mbps for GFSK modulation 2Mbps for GFSK modulation BT: 1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	BLE: GFSK BT: GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	2.6 dBm(0.001820 W) for BT 1.30 dBm(0.001349 W) for BLE
Antenna Gain:	3.0 dBi
Power supply:	DC5V from USB, DC3.8V from battery
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{24} \text{ where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

gain:	3.0 dBi	BT EMF						
Mode	Channel Frequency (MHz)	Measured Power (dBm)	E.I.R.P(dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR	Verdict
GFSK	2402	1.60	4.60	-3±1	5	0.9802041	3	PASS
	2441	1.24	4.24	-4±1	5	0.9881295	3	PASS
	2480	1.05	4.05	-3±1	5	0.9959920	3	PASS
π/4-DQPSK	2402	2.21	5.21	-2±1	6	1.2340038	3	PASS
	2441	1.89	4.89	-3±1	5	0.9881295	3	PASS
	2480	1.74	4.74	-3±1	5	0.9959920	3	PASS
8QPSK	2402	2.60	5.60	-2±1	6	1.2340038	3	PASS
	2441	2.29	5.29	-3±1	6	1.2439814	3	PASS
	2480	2.07	5.07	-2±1	6	1.2538796	3	PASS

gain:	3.0 dBi	BLE EMF						
Mode	Frequency (MHz)	Measured Power (dBm)	E.I.R.P(dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR	Verdict
1M	2402	1.30	4.30	-3±1	5	0.9802041	3	PASS
	2441	1.06	4.06	-4±1	5	0.9881295	3	PASS
	2480	0.79	3.79	-3±1	4	0.7911445	3	PASS
2M	2402	1.22	4.22	-2±1	5	0.9802041	3	PASS
	2441	0.98	3.98	-3±1	4	0.7848992	3	PASS
	2480	0.85	3.85	-3±1	4	0.7911445	3	PASS

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement

*** End of Report ***