



Report No.: PTC21111606601E-FC02

# FCC TEST REPORT

## FCC ID: 2A33H-12018

Product	:	CCTV CAMERA
Model Name	:	EM-TY3903W06
Brand	:	Psennikow®  CM
Report No.	:	PTC21111606601E-FC02

### Prepared for

Shenzhen Pasensi Technology Co.,Ltd

20-2-201, Waijing Ind. Zone, Fuqian Road, Fucheng Street, Longhua Dist., Shenzhen, Guangdong

### Prepared by

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China



## TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Pasensi Technology Co.,Ltd.  
Address : 20-2-201, Waijing Ind. Zone, Fuqian Road, Fucheng Street, Longhua Dist., Shenzhen, Guangdong  
Manufacturer's name : Shenzhen Pasensi Technology Co.,Ltd.  
Address : 20-2-201, Waijing Ind. Zone, Fuqian Road, Fucheng Street, Longhua Dist., Shenzhen, Guangdong  
Product name : CCTV CAMERA  
Model name : EM-TY3903W06  
Test procedure : KDB 447498 D01 General RF Exposure Guidance v06  
Test Date : Dec. 17, 2021 to Dec. 24, 2021  
Date of Issue : Dec. 24, 2021  
Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads 'Abel Yu'.

Abel Yu / Engineer

Technical Manager:

A handwritten signature in black ink that reads 'Wu Weimin'.

Wu Weimin /Manager



## Contents

	<b>Page</b>
<b>2 TEST SUMMARY.....</b>	4
<b>3 GENERAL INFORMATION.....</b>	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
<b>4 RF EXPOSURE.....</b>	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT.....	6
4.3 MPE CALCULATION METHOD.....	7
4.4 TEST RESULT.....	7



## 2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name	:	CCTV CAMERA
Model Name	:	EM-TY3903W06
Additional model	:	N/A
Specification	:	802.11b/g/n HT20/HT40
Operation Frequency	:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452 MHz for 802.11 n(HT40)
Number of Channel	:	11 channels for 802.11b/g; n(HT20) 7 channels for 802.11; n(HT40)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	Glue stick antenna
Antenna Gain	:	5 dBi
Power supply	:	Adapter model:GQ18-120100-AC Input:100-240V~0.5A,50-60Hz;Output: 12V/1.0A
Hardware Version	:	N/A
Software Version	:	N/A



## 4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



#### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

#### 4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
WIFI	3.16	17.824	60.59	0.03809	1	Pass

\*\*\*\*\*THE END REPORT\*\*\*\*\*