



RF EXPOSURE Test Report

Report No.: MTi221101001-01E4

Date of issue: 2023-03-16

Applicant: Shenzhen Teneth Technology Co., Ltd

Product: CUTTING PLOTTER

Model(s): X5PRO-230GB, X5PRO-180GB, X5PRO-180BT,
X5PRO-230BT

FCC ID: 2A33R-X5PRO

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



Instructions

1. The report shall not be partially reproduced without the written consent of the laboratory;
2. The test results of this report are only responsible for the samples submitted;
3. This report is invalid without the seal and signature of the laboratory;
4. This report is invalid if transferred, altered or tampered with in any form without authorization;
5. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.



Test Result Certification	
Applicant:	Shenzhen Teneth Technology Co., Ltd
Address:	No.161, Pinghu Street, Pinghu Town, Longgang District, Shenzhen City, Guangdong, China.
Manufacturer:	Shenzhen Teneth Technology Co., Ltd
Address:	No.161, Pinghu Street, Pinghu Town, Longgang District, Shenzhen City, Guangdong, China.
Factory:	Shenzhen Teneth Technology Co., Ltd
Address:	Building A-2, No. 8, Baolong 1st Road, Baolong Community, Baolong Street, Longgang District, Shenzhen City, Guangdong province, China
Product description	
Product name:	CUTTING PLOTTER
Trademark:	TENETH
Model name:	X5PRO-230GB
Serial Model:	X5PRO-180GB, X5PRO-180BT, X5PRO-230BT
Standards:	N/A
Test procedure:	KDB 447498 D01 v06
Date of Test	
Date of test:	2023-01-13 ~ 2023-03-16
Test result:	Pass

Test Engineer :

Yanice Xie

(Yanice Xie)

Reviewed By :

Leon Chen

(Leon Chen)

Approved By :

Tom Xue

(Tom Xue)



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BT/BLE:

Operation Frequency: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

BT/BLE antenna gain: -0.1dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(-0.1/10)}=0.98$

2.4GWiFi:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna;

WIFI antenna gain: 3.06dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(3.06/10)}=2.02$

BR+EDR:

Channe l Freq. (MHz)	modulation	conducted power	Tune- up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-3.19	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2441		-3.79	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2480		-3.12	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2402	π/4- DQPSK	-2.83	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2441		-3.47	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2480		-2.87	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2402	8DPSK	-2.42	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2441		-3.06	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1
2480		-2.43	(-3)±1	-2	0.631	-0.1	0.98	0.0001	1



BLE:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power	Gain		(mW/cm²)	(mW/cm²)	
				(dBm)	(mW)	(dBi)			Numeric
2402	BLE-1M	-1.54	(-1)±1	0	1.000	-0.1	0.98	0.0002	1
2440		-1.64	(-1)±1	0	1.000	-0.1	0.98	0.0002	1
2480		-1.42	(-1)±1	0	1.000	-0.1	0.98	0.0002	1

2.4GWiFi:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna		Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power		Gain		Power density(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	(dBi)	Numeric		
		Ant A	Ant A	Ant A	Ant A	Ant A	Ant A	Ant A	
2412	802.11b	17.68	17±1	18	63.096	3.06	2.02	0.02539	1
2437		16.89	17±1	18	63.096	3.06	2.02	0.02539	1
2462		17.28	17±1	18	63.096	3.06	2.02	0.02539	1
2412	802.11g	15.67	15±1	16	39.811	3.06	2.02	0.01602	1
2437		14.83	15±1	16	39.811	3.06	2.02	0.01602	1
2462		15.09	15±1	16	39.811	3.06	2.02	0.01602	1
2412	802.11n H20	15.47	15±1	16	39.811	3.06	2.02	0.01602	1
2437		15.22	15±1	16	39.811	3.06	2.02	0.01602	1
2462		15.39	15±1	16	39.811	3.06	2.02	0.01602	1
2422	802.11n H40	15.49	15±1	16	39.811	3.06	2.02	0.01602	1
2437		15.09	15±1	16	39.811	3.06	2.02	0.01602	1
2452		14.93	15±1	16	39.811	3.06	2.02	0.01602	1

Conclusion:

The device can transmitter simultaneously.

BR&EDR+2.4G WIFI =0.0001+0.02539=0.02549

BLE+2.4G WIFI=0.0002+0.02539=0.02559

For the max result: 0.02559≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----