













3.7. Spurious Emission (Radiated)

Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance Meters(at 3m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m).


Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=1MHz Peak detector for Peak value.
RBW=1MHz, VBW=10Hz Peak detector for Average value.

Test Mode

Please refer to the clause 2.2

Test Result

9 KHz~30 MHz and 18GHz~25GHz

From 9 KHz~30 MHz and 18GHz~25GHz: Conclusion: PASS


Note:


- 1) Measurement = Reading level + Correct Factor
Correct Factor=Antenna Factor + Cable Loss -Preamplifier Factor
- 2) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
- 3) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 4) The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 5) Pre-scan 802.11b/g/n(HT20/HT40) modulation, found 802.11n20_2412MHz which it is worse case for 30MHz-1GHz , the 802.11n20 modulation which it is worse case for above 1GHz, so only show the test data for worse case.

BELOW 30MHZ


No emission found between lowest internal used/generated frequencies to 30MHz.


30MHz-1GHz






Adobe 1GHz







Test Voltage:	DC 3.3V
Ant. Pol.	Horizontal
Test Mode:	TX 802.11b Mode 2437MHz




No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		5154.800	42.96	-5.24	37.72	74.00	-36.28	peak
2		6875.200	42.45	-1.06	41.39	74.00	-32.61	peak
3		8626.200	42.32	1.92	44.24	74.00	-29.76	peak
4		11152.400	41.05	6.05	47.10	74.00	-26.90	peak
5		13263.800	38.91	10.28	49.19	74.00	-24.81	peak
6	*	17464.500	37.75	13.37	51.12	74.00	-22.88	peak

Measurement = Reading level + Correct Factor







Note:

1. All test modes had been tested. The 802.11b modulation is the worst case and recorded in the report.
2. 18GHz-26.5GHz is the background of the site, there is no radiated spurious.

3.8. Conducted Emission

Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Configuration



Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 0.1m above the conducting ground plane. The vertical conducting plane was located 80 cm to the rear of the EUT. All other surfaces of EUT were at least 0.8m from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.


Test Mode:

Please refer to the clause 2.2.

Test Results

Pre-scan 802.11b/g/n(HT20/HT40) modulation, and found the 802.11b modulation 2412MHz which it is worse case, so only show the test data for worse case.


Test Voltage:	AC 120V/60Hz
Terminal:	Line
Test Mode:	2.4G WIFI



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1700	24.71	10.73	35.44	64.96	-29.52	QP
2		0.1700	11.43	10.73	22.16	54.96	-32.80	AVG
3		0.4580	16.36	10.45	26.81	56.73	-29.92	QP
4	*	0.4580	8.18	10.45	18.63	46.73	-28.10	AVG
5		0.7539	6.92	10.44	17.36	56.00	-38.64	QP
6		0.7539	-3.39	10.44	7.05	46.00	-38.95	AVG
7		2.5819	11.40	10.58	21.98	56.00	-34.02	QP
8		2.5819	-2.53	10.58	8.05	46.00	-37.95	AVG
9		5.2259	3.71	10.63	14.34	60.00	-45.66	QP
10		5.2259	-3.85	10.63	6.78	50.00	-43.22	AVG
11		15.9859	10.00	10.74	20.74	60.00	-39.26	QP
12		15.9859	0.55	10.74	11.29	50.00	-38.71	AVG

Remarks:
1.Measurement = Reading Level+ Correct Factor
2.Over = Measurement -Limit

Test Voltage:	AC 120V/60Hz
Terminal:	Neutral
Test Mode:	2.4G WIFI



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1737	24.59	10.74	35.33	64.78	-29.45	QP
2		0.1737	9.56	10.74	20.30	54.78	-34.48	AVG
3		0.4339	13.67	10.51	24.18	57.18	-33.00	QP
4	*	0.4339	9.22	10.51	19.73	47.18	-27.45	AVG
5		0.7620	5.60	10.43	16.03	56.00	-39.97	QP
6		0.7620	-1.46	10.43	8.97	46.00	-37.03	AVG
7		2.5819	9.85	10.55	20.40	56.00	-35.60	QP
8		2.5819	-2.41	10.55	8.14	46.00	-37.86	AVG
9		6.0819	2.67	10.58	13.25	60.00	-46.75	QP
10		6.0819	-4.42	10.58	6.16	50.00	-43.84	AVG
11		15.9859	13.45	10.79	24.24	60.00	-35.76	QP
12		15.9859	4.86	10.79	15.65	50.00	-34.35	AVG


Remarks:
1.Measurement = Reading Level+ Correct Factor
2.Over = Measurement -Limit

4.EUT TEST PHOTOS


Radiated Measurement (Below 1GHz)




Radiated Measurement (Above 1GHz)



Conducted Emission



RF Conducted



5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL

External Photographs

Photo 1




Photo 2




Photo 3




Photo 4




Photo 5




Photo 6





Photo 7



Internal Photographs

Photo 1




Photo 2




Photo 3




Photo 4




Photo 5




Photo 6




Photo 7




Photo 8




Photo 9




Photo 10




Photo 11




Photo 12





Photo 13



--THE END--