



Report No.: E01A22060794F00102

1 of 67

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

4" Wifi Led Recessed Lights, 6" Wifi Led Recessed Lights

Model No.: EPCL-WIFI-RGBCW-WC-4INCH, EPCL-WIFI-RGBCW-WC-6INCH

FCC ID: 2A358CLWC

Trademark: N/A

Report No.: E01A22060794F00102

Issue Date: July 21, 2022

Prepared for

Shenzhen Ephan Technology Co., Ltd

**Rm. 306-308, Fl. 3, No. 2 Bldg. CHENGHEDE Industrial Zone,
HENGLANG Community, DALANG residential district, LONGHUA Town,
Shenzhen City.**

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

**1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake
Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr.,
China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Eleaactronic Technology Co., Ltd.**

VERIFICATION OF COMPLIANCE


Applicant:	Shenzhen Ephan Technology Co., Ltd. Rm. 306-308, Fl. 3, No. 2 Bldg. CHENGHEDE Industrial Zone, HENGLANG Community, DALANG residential district, LONGHUA Town, Shenzhen City.
Manufacturer:	Dongguan Ephan Intelligent Technology Co.,Ltd Rm. 601, No. 1 Bldg., No.136 YongJun Rd., DaLingShan Town, DongGuan city, China.
Product Description:	4" Wifi Led Recessed Lights, 6" Wifi Led Recessed Lights
Trade Mark:	N/A
Model Number:	EPCL-WIFI-RGBCW-WC-4INCH, EPCL-WIFI-RGBCW-WC-6INCH (The two models have the same circuit principle, PCB, and LED driver, the difference is that the number of lamp beads is different, resulting in different power. We choose model: EPCL-WIFI-RGBCW-WC-6INCH for all tests, model: EPCL-WIFI-RGBCW-WC-4INCH for radiation and conducted emission difference tests.)

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2022).


Date of Test :

July 06, 2022 to July 19, 2022



Prepared by :

Tomas Yang/Supervisor

Reviewer & Authorized
Signer :

Tiger /Supervisor

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A22060794F00102

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
1.2 TEST METHODOLOGY	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3. DESCRIPTION OF TEST MODES	9
4. SUMMARY OF TEST RESULTS.....	10
5. TEST FACILITY.....	13
6. CONDUCTED EMISSIONS TEST	14
6.1 MEASUREMENT PROCEDURE:	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
6.3 MEASUREMENT EQUIPMENT USED:	14
6.4 CONDUCTED EMISSION LIMIT	14
6.5 MEASUREMENT RESULT:	15
6.5 CONDUCTED MEASUREMENT PHOTOS:	19
7. RADIATED EMISSION TEST	20
7.1 MEASUREMENT PROCEDURE	20
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	21
7.3 MEASUREMENT EQUIPMENT USED.....	22
7.4 RADIATED EMISSION LIMIT	23
7.5 MEASUREMENT RESULT	24
7.6 RADIATED MEASUREMENT PHOTOS:.....	32
8. 6DB BANDWIDTH TEST	33
8.1 MEASUREMENT PROCEDURE	33
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	33
8.3 MEASUREMENT EQUIPMENT USED.....	33
8.4 MEASUREMENT RESULTS	33
9. MAXIMUM PEAK OUTPUT POWER TEST	42
9.1 MEASUREMENT PROCEDURE	42
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	42
9.3 MEASUREMENT EQUIPMENT USED.....	42
9.4 PEAK POWER OUTPUT LIMIT	42
9.5 MEASUREMENT RESULTS	42
10. BAND EDGE TEST	43
10.1 MEASUREMENT PROCEDURE	43
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	44
10.3 MEASUREMENT EQUIPMENT USED	44
10.4 MEASUREMENT RESULTS.....	44
11. POWER DENSITY	50
11.1 TEST EQUIPMENT	50
11.2 MEASURING INSTRUMENTS AND SETTING.....	50
11.3 TEST PROCEDURES.....	50
11.4 BLOCK DIAGRAM OF TEST SETUP.....	50



11.5 LIMIT.....	51
11.6 TEST RESULT.....	51
12. ANTENNA PORT EMISSION	57
12.1 TEST EQUIPMENT	59
12.2 MEASURING INSTRUMENTS AND SETTING.....	59
12.3 TEST PROCEDURES.....	59
12.4 BLOCK DIAGRAM OF TEST SETUP	59
12.5 TEST RESULT.....	59
13. ANTENNA APPLICATION	66
13.1 ANTENNA REQUIREMENT.....	66
13.2 RESULT	66
APPENDIX (PHOTOS OF EUT) (3 PAGES)	

1. General Information

1.1 Product Description

Characteristics	Description
Product Name	4" Wifi Led Recessed Lights, 6" Wifi Led Recessed Lights
Model number	EPCL-WIFI-RGBCW-WC-4INCH, EPCL-WIFI-RGBCW-WC-6INCH
Power Supply	AC 120V, 60Hz
Test Power Supply	AC 120V 60Hz
Modulation	802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM)
Operating Frequency Range	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Transmit Power Max	802.11b: 13.06Bm 802.11g: 10.98dBm 802.11n(HT20): 10.81dBm 802.11n(HT40): 9.41dBm
Antenna Type	PCB antenna
Antenna Gain	1.3dBi
Date of Received	July 06, 2022

Note: for more details, please refer to the User's manual of the EUT.

1.2 Test Methodology

All the test program has follow FCC new test procedure KDB 558074 D01 15.247 Meas Guidance v05r02 and in accordance with the procedures given in ANSI C63.10-2013.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	4" Wifi Led Recessed Lights, 6" Wifi Led Recessed Lights	N/A	EPCL-WIFI-RGBCW-W C-4INCH, EPCL-WIFI-RGBCW-W C-6INCH	2A358CLWC	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition and Only the worst case data were reported. The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed. EUT is connected by com port, and transmit the control instruction via test software(Wifi Test Tool v1.6.0 release).

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):


Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

Report No.: E01A22060794F00102
 Operated Mode for Worst Duty cycle:
 Duty Cycle:


10 of 67

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
802.11b	2412	100	0
802.11b	2437	100	0
802.11b	2462	100	0
802.11g	2412	100	0
802.11g	2437	100	0
802.11g	2462	100	0
802.11n(HT20)	2412	100	0
802.11n(HT20)	2437	100	0
802.11n(HT20)	2462	100	0
802.11n(HT40)	2422	100	0
802.11n(HT40)	2437	100	0
802.11n(HT40)	2452	100	0

All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages:




Duty Cycle NVNT 802.11b 2437MHz



Date: 8.JUL.2022 20:03:45

Duty Cycle NVNT 802.11b 2462MHz



Date: 8.JUL.2022 20:05:35

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass
N/A (Not Applicable).		

5. Test Facility

Site Description


Name of Firm : Dong Guan Anci Electronic Technology Co., Ltd.
Site Location : 1-2 Floor, Building A, No.11, Headquarters 2 Road,
Songshan, Lake Hi-tech Industrial Development
Zone, Dongguan City, Guangdong Pr., China.

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

Conducted Emission Test Site				
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2023-05-12
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2023-05-12
RF Cable	N/A	N/A	2#	2023-05-12
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2023-05-12
Shielded Room	chengyu	8m*4m*3m	N/A	2023-05-12
Test Software	Farad	EZ-EMC Ver:ANCI-8A1	N/A	N/A

6.4 Conducted Emission Limit

(7) Conducted Emission Frequency(MHz)

0.15-0.5
0.5-5.0
5.0-30.0

Quasi-peak

66-56
56
60


Average

56-46
46
50

Note:


1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.5 easurement Result:




Site:		Phase: L1	Temperature(C): 23.5(C)
Limit:	FCC Part 15 C Conduction(QP)		Humidity(%): 52.6%
EUT:	6" Wifi Led Recessed Lights	Test Time:	2022-07-12
M/N.:	EPCL-WIFI-RGBCW-WC-6INCH	Power Rating:	AC 120V/60Hz
Mode:	WIFI Mode	Test Engineer:	Sunshine
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Margin (dB)	Detector	Comment
1	0.5860	40.34	9.75	50.09	56.00	-5.91	QP	
2	0.5860	28.60	9.75	38.35	46.00	-7.65	AVG	
3	1.0700	39.65	9.33	48.98	56.00	-7.02	QP	
4	1.0700	29.30	9.33	38.63	46.00	-7.37	AVG	
5	1.7140	37.80	10.41	48.21	56.00	-7.79	QP	
6	1.7140	29.82	10.41	40.23	46.00	-5.77	AVG	
7	2.0579	38.03	10.42	48.45	56.00	-7.55	QP	
8 *	2.0579	30.81	10.42	41.23	46.00	-4.77	AVG	
9	4.5700	36.46	10.53	46.99	56.00	-9.01	QP	
10	4.5700	30.51	10.53	41.04	46.00	-4.96	AVG	
11	20.7820	39.59	11.50	51.09	60.00	-8.91	QP	
12	20.7820	32.06	11.50	43.56	50.00	-6.44	AVG	




Site:		Phase: N	Temperature(C): 23.5(C)
Limit:	FCC Part 15 C Conduction(QP)		Humidity(%): 52.6%
EUT:	6" Wifi Led Recessed Lights	Test Time:	2022-07-12
M/N.:	EPCL-WIFI-RGBCW-WC-6INCH	Power Rating:	AC 120V/60Hz
Mode:	WIFI Mode	Test Engineer:	Sunshine
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Margin (dB)	Detector	Comment
1	0.5860	38.76	9.75	48.51	56.00	-7.49	QP	
2	0.5860	26.75	9.75	36.50	46.00	-9.50	AVG	
3	1.8340	35.71	10.46	46.17	56.00	-9.83	QP	
4	1.8340	28.29	10.46	38.75	46.00	-7.25	AVG	
5	2.5780	35.35	10.47	45.82	56.00	-10.18	QP	
6	2.5780	28.32	10.47	38.79	46.00	-7.21	AVG	
7	4.5180	35.81	10.51	46.32	56.00	-9.68	QP	
8 *	4.5180	29.01	10.51	39.52	46.00	-6.48	AVG	
9	18.5180	39.19	11.41	50.60	60.00	-9.40	QP	
10	18.5180	31.59	11.41	43.00	50.00	-7.00	AVG	
11	23.0500	39.25	11.64	50.89	60.00	-9.11	QP	
12	23.0500	31.48	11.64	43.12	50.00	-6.88	AVG	



Site:		Phase: L1	Temperature(C): 23.5(C)
Limit:	FCC Part 15 C Conduction(QP)		Humidity(%): 52.6%
EUT:	4" Wifi Led Recessed Lights	Test Time:	2022-07-12
M/N.:	EPCL-WIFI-RGBCW-WC-4INCH	Power Rating:	AC 120V/60Hz
Mode:	WIFI Mode	Test Engineer:	Sunshine
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Margin (dB)	Detector	Comment
1	0.5860	38.48	9.75	48.23	56.00	-7.77	QP	
2	0.5860	28.07	9.75	37.82	46.00	-8.18	AVG	
3	0.8700	38.31	9.54	47.85	56.00	-8.15	QP	
4	0.8700	28.01	9.54	37.55	46.00	-8.45	AVG	
5	1.2980	39.22	9.11	48.33	56.00	-7.67	QP	
6	1.2980	29.63	9.11	38.74	46.00	-7.26	AVG	
7	2.4980	36.73	10.44	47.17	56.00	-8.83	QP	
8	2.4980	28.85	10.44	39.29	46.00	-6.71	AVG	
9	4.6500	35.13	10.53	45.66	56.00	-10.34	QP	
10	4.6500	28.56	10.53	39.09	46.00	-6.91	AVG	
11	20.8860	39.45	11.50	50.95	60.00	-9.05	QP	
12	20.8860	32.97	11.50	44.47	50.00	-5.53	AVG	
*								



Site:	FCC Part 15 C Conduction(QP)	Phase:N	Temperature(C):23.5(C)
Limit:	4" Wifi Led Recessed Lights	Test Time:	Humidity(%):52.6%
EUT:	EPCL-WIFI-RGBCW-WC-4INCH	Power Rating:	2022-07-12
M/N.:	WIFI Mode	Test Engineer:	AC 120V/60Hz
Note:			Sunshine

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Margin (dB)	Detector	Comment
1	0.5860	37.06	9.75	46.81	56.00	-9.19	QP	
2	0.5860	26.15	9.75	35.90	46.00	-10.10	AVG	
3	1.2980	37.28	9.14	46.42	56.00	-9.58	QP	
4	1.2980	27.49	9.14	36.63	46.00	-9.37	AVG	
5	2.6460	35.02	10.47	45.49	56.00	-10.51	QP	
6	2.6460	27.97	10.47	38.44	46.00	-7.56	AVG	
7	4.8420	34.34	10.52	44.86	56.00	-11.14	QP	
8	4.8420	27.97	10.52	38.49	46.00	-7.51	AVG	
9	20.1500	39.25	11.48	50.73	60.00	-9.27	QP	
10	20.1500	32.50	11.48	43.98	50.00	-6.02	AVG	
11	21.9940	39.13	11.58	50.71	60.00	-9.29	QP	
12	21.9940	32.57	11.58	44.15	50.00	-5.85	AVG	
*								

6.5 Conducted Measurement Photos:

7. Radiated Emission Test

7.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022-11-12
2.	Pre-Amplifier	HP	8447D	2727A06172	2023-05-12
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2023-05-12
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022-11-12
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
6.	Low noise Amplifiers	A-INFO	LA1018N4009	J101313052400 1	2023-05-12
7.	Horn antenna	A-INFO	LB-10180-SF	J203109061212 3	2023-05-12
8.	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX10 0KHz-40GHz	J101313052400 1	2022-11-12
9.	DRG Horn Antenna	A.H.SYSTEMS	SAS-574	J203109061212 3	2022-11-12
10.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-2m	N/A	2022-11-12
11.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-0.3m	N/A	2022-11-12
12.	RF Cable	N/A	N/A	6#	2023-05-12
13.	RF Cable	N/A	N/A	1-1#	2023-05-12
14.	RF Cable	N/A	N/A	1-2#	2023-05-12
15.	RF Cable	N/A	N/A	7#	2023-05-12
16.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2023-05-12
17.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	2022-07-19
Frequency Range:	9KHz~30MHz	Temperature :	26℃
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	Ellie

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b 2437MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



Site:	LAB	Antenna::Horizontal	Temperature(C):26(C)
Limit:	FCC Part 15 C 3m Radiation		Humidity(%):60%
EUT:	6" Wifi Led Recessed Lights	Test Time:	2022-07-19
M/N.:	EPCL-WIFI-RGBCW-WC-6INCH	Power Rating:	AC 120V/60Hz
Mode:	TX2437	Test Engineer:	Ellie
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	46.3402	23.49	-4.29	19.20	40.00	-20.80	QP	
2 *	59.8588	27.32	-4.78	22.54	40.00	-17.46	QP	
3	109.0286	29.59	-4.53	25.06	43.50	-18.44	QP	
4	123.2655	31.01	-6.09	24.92	43.50	-18.58	QP	
5	199.2855	23.48	-5.23	18.25	43.50	-25.25	QP	
6	284.9767	22.51	-2.52	19.99	46.00	-26.01	QP	


Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor



Site:	LAB	Antenna::Vertical	Temperature(C):26(C)
Limit:	FCC Part 15 C 3m Radiation		Humidity(%):60%
EUT:	6" Wifi Led Recessed Lights	Test Time:	2022-07-19
M/N.:	EPCL-WIFI-RGBCW-WC-6INCH	Power Rating:	AC 120V/60Hz
Mode:	TX2437	Test Engineer:	Ellie
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	30.1054	39.51	-7.62	31.89	40.00	-8.11	QP	
2 *	53.5052	36.78	-4.39	32.39	40.00	-7.61	QP	
3	60.2801	37.03	-4.90	32.13	40.00	-7.87	QP	
4	74.1351	35.81	-9.68	26.13	40.00	-13.87	QP	
5	119.8556	31.96	-5.55	26.41	43.50	-17.09	QP	
6	138.3873	36.33	-8.66	27.67	43.50	-15.83	QP	

Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor




Site: LAB
Limit: FCC Part 15 C 3m Radiation
EUT: 4" Wifi Led Recessed Lights
M/N.: EPCL-WIFI-RGBCW-WC-4INCH
Mode: TX2437
Note:

Antenna::Horizontal
Temperature(C):26(C)
Humidity(%):60%
Test Time: 2022-07-19
Power Rating: AC 120V/60Hz
Test Engineer: Ellie

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	53.6932	28.27	-4.41	23.86	40.00	-16.14	QP	
2	85.2980	31.58	-9.23	22.35	40.00	-17.65	QP	
3	108.2667	30.07	-4.56	25.51	43.50	-17.99	QP	
4	128.1130	33.87	-6.86	27.01	43.50	-16.49	QP	
5	162.0414	33.93	-9.62	24.31	43.50	-19.19	QP	
6 *	199.2855	32.98	-5.23	27.75	43.50	-15.75	QP	

Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor



Site:	LAB	Antenna::Vertical	Temperature(C):26(C)
Limit:	FCC Part 15 C 3m Radiation		Humidity(%):60%
EUT:	4" Wifi Led Recessed Lights	Test Time:	2022-07-19
M/N.:	EPCL-WIFI-RGBCW-WC-4INCH	Power Rating:	AC 120V/60Hz
Mode:	TX2437	Test Engineer:	Ellie
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	30.1054	41.30	-7.62	33.68	40.00	-6.32	QP	
2 *	54.0711	40.43	-4.43	36.00	40.00	-4.00	QP	
3 !	59.8588	40.56	-4.78	35.78	40.00	-4.22	QP	
4	83.5222	36.74	-9.85	26.89	40.00	-13.11	QP	
5	119.8556	32.90	-5.55	27.35	43.50	-16.15	QP	
6	143.3261	37.32	-9.44	27.88	43.50	-15.62	QP	

Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor

Above 1GHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits. The frequency range from 1GHz to 25GHz is investigated.

Operation Mode: 802.11b Lowest Test Date : 2022-07-12
Test Voltage: AC 120V/60Hz Test by: Ellie

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	63.85	43.54	74	54	-10.15	-10.46
7236	V	63.97	42.15	74	54	-10.03	-11.85
9648	V	62.15	43.05	74	54	-11.85	-10.95
12060	V	62.64	44.15	74	54	-11.36	-9.85
14472	V	63.05	40.36	74	54	-10.95	-13.64
16884	V	63.15	41.55	74	54	-10.85	-12.45
4824	H	62.78	42.19	74	54	-11.22	-11.81
7236	H	62.64	42.64	74	54	-11.36	-11.36
9648	H	61.45	42.87	74	54	-12.55	-11.13
12060	H	60.69	42.63	74	54	-13.31	-11.37
14472	H	60.12	41.45	74	54	-13.88	-12.55
16884	H	59.88	40.32	74	54	-14.12	-13.68

Operation Mode: 802.11b Middle Test Date : 2022-07-12
Test Voltage: AC 120V/60Hz Test by: Ellie

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	64.15	44.12	74	54	-9.85	-9.88
7311	V	62.15	43.64	74	54	-11.85	-10.36
9688	V	62.35	43.15	74	54	-11.65	-10.85
12185	V	63.87	43.05	74	54	-10.13	-10.95
14622	V	63.46	43.19	74	54	-10.54	-10.81
17059	V	62.59	42.64	74	54	-11.41	-11.36
4874	H	63.05	42.54	74	54	-10.95	-11.46
7311	H	61.11	41.78	74	54	-12.89	-12.22
9688	H	62.15	41.97	74	54	-11.85	-12.03
12185	H	63.05	40.52	74	54	-10.95	-13.48
14622	H	61.59	40.69	74	54	-12.41	-13.31
17059	H	60.96	39.87	74	54	-13.04	-14.13

Operation Mode: 802.11b Highest

Test Date : 2022-07-12

Test Voltage: AC 120V/60Hz

Test by: Ellie

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	63.88	44.87	74	54	-10.12	-9.13
7386	V	63.54	43.64	74	54	-10.46	-10.36
9848	V	63.12	42.15	74	54	-10.88	-11.85
12310	V	62.69	42.85	74	54	-11.31	-11.15
14772	V	62.36	43.05	74	54	-11.64	-10.95
17234	V	62.54	43.16	74	54	-11.46	-10.84
4924	H	64.42	42.57	74	54	-9.58	-11.43
7386	H	63.58	42.55	74	54	-10.42	-11.45
9848	H	62.49	41.77	74	54	-11.51	-12.23
12310	H	61.33	40.28	74	54	-12.67	-13.72
14772	H	61.39	38.95	74	54	-12.61	-15.05
17234	H	60.25	39.16	74	54	-13.75	-14.84

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Report No.: E01A22060794F00102

31 of 67

7.6 Radiated Measurement Photos:




8. 6dB Bandwidth Test

8.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02 .

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Measurement Results

6db Bandwidth Test Data Chart:


Refer to attached data chart.

Spectrum Detector: PK
Test By: Best
Humidity : 60%

Test Date : 2022-07-08
Temperature : 26°C

IEEE 802.11b			
Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)	Result
2412	12.404	>500	Pass
2437	9.836	>500	
2462	10.064	>500	


OBW NVNT 802.11b 2412MHz Ant1



Date: 8.JUL.2022 20:02:12


IEEE 802.11g			
Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)	Result
2412	15.088	>500	Pass
2437	16.588	>500	
2462	15.1	>500	

OBW NVNT 802.11g 2412MHz Ant1




Date: 8.JUL.2022 20:11:29

OBW NVNT 802.11g 2437MHz Ant1




OBW NVNT 802.11g 2462MHz Ant1




IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)	Result
2412	16.612	>500	Pass
2437	13.208	>500	
2462	12.624	>500	

OBW NVNT 802.11n(HT20) 2412MHz Ant1




OBW NVNT 802.11n(HT20) 2437MHz Ant1



Date: 8.JUL.2022 20:36:03


OBW NVNT 802.11n(HT20) 2462MHz Ant1



Date: 8.JUL.2022 20:37:42


IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (MHz)	Required Limit (KHz)	Result
2422	35.104	>500	Pass
2437	30.656	>500	
2452	34.088	>500	

OBW NVNT 802.11n(HT40) 2422MHz Ant1




Date: 8.JUL.2022 20:39:28

OBW NVNT 802.11n(HT40) 2437MHz Ant1



Date: 8.JUL.2022 20:41:17

OBW NVNT 802.11n(HT40) 2452MHz Ant1



Date: 8.JUL.2022 20:45:36

9. Maximum Peak Output Power Test

9.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used

EQUIPMENT TYPE	Manufacturer	Model No.	Serial Number	Calibrated until.
USB RF Power sensor	RadiPower	RPR3006W	17I00015SNO88	2022-11-12
RF Test Software	MAIWEI	MTS 8310	N/A	N/A

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results

Spectrum Detector:	PK	Test Date :	2022-07-08
Test By:	Best	Temperature :	26°C
Test Result:	PASS	Humidity :	60%

Test Channel	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	12.81	10.37	10.09	9.3	30	Pass
Middle	13.06	10.98	10.81	9.41		
Highest	12.9	10.81	10.6	9.15		

10. Band Edge Test

10.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 5558074 D01 15.247 Meas Guidance v05r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 5558074 D01 15.247 Meas Guidance v05r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Results

1. Conducted Test


Please refer to the following pages.

Band Edge 802.11b 2412MHz Ant1 Emission




Date: 8.JUL.2022 20:03:01

Band Edge 802.11b 2462MHz Ant1 Emission




Date: 8.JUL.2022 20:06:15

Band Edge 802.11g 2412MHz Ant1 Emission




Date: 8.JUL.2022 20:27:02

Band Edge 802.11g 2462MHz Ant1 Emission




Date: 8.JUL.2022 20:33:08

Band Edge 802.11n(HT20) 2412MHz Ant1 Emission



Date: 8.JUL.2022 20:34:51

Band Edge 802.11n(HT20) 2462MHz Ant1 Emission



Date: 8.JUL.2022 20:38:14





Report No.: E01A22060794F00102

49 of 67

2. Radiated emission Test

Spectrum Detector:

PK/AV

Test Date :

2022-07-08

Test By:

Best

Temperature :

28 °C

Humidity :

65 %

IEEE 802.11b SISO Ant1										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	84.2	65.32	-26.3	57.9	39.02	74	54	-16.1	-14.98
<2400	V	83.69	65.14	-26.1	57.59	39.04	74	54	-16.41	-14.96
>2483.5	H	83.14	66.32	-26.3	56.84	40.02	74	54	-17.16	-13.98
>2483.5	V	83.74	64.25	-26.1	57.64	38.15	74	54	-16.36	-15.85

IEEE 802.11g SISO Ant1										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	83.32	65.2	-26.3	57.02	38.9	74	54	-16.98	-15.1
<2400	V	83.41	64.63	-26.1	57.31	38.53	74	54	-16.69	-15.47
>2483.5	H	84.11	65.14	-26.3	57.81	38.84	74	54	-16.19	-15.16
>2483.5	V	83.59	66.32	-26.1	57.49	40.22	74	54	-16.51	-13.78

IEEE 802.11n(HT20) SISO										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	82.63	63.47	-26.3	56.33	37.17	74	54	-17.67	-16.83
<2400	V	82.41	63.52	-26.1	56.31	37.42	74	54	-17.69	-16.58
>2483.5	H	82.63	64.23	-26.3	56.33	37.93	74	54	-17.67	-16.07
>2483.5	V	82.74	64.11	-26.1	56.64	38.01	74	54	-17.36	-15.99

IEEE 802.11n(H40) SISO										
Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<2400	H	80.32	61.39	-26.3	54.02	35.09	74	54	-19.98	-18.91
<2400	V	80.14	61.27	-26.1	54.04	35.17	74	54	-19.96	-18.83
>2483.5	H	79.63	60.23	-26.3	53.33	33.93	74	54	-20.67	-20.07
>2483.5	V	78.61	60.47	-26.1	52.51	34.37	74	54	-21.49	-19.63

11. Power Density

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

11.2 Measuring Instruments and Setting

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3kHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

11.3 Test Procedures

The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02.

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set analyzer center frequency to DTS channel center frequency.
- Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- Set the RBW ≥ 3 kHz. Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

11.4 Block Diagram of Test Setup



11.5 Limit


The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

11.6 Test Result

Spectrum Detector:	PK	Test Date :	2022-07-08
Test By:	Best	Temperature :	26°C
Test Result:	PASS	Humidity :	60%


IEEE 802.11b			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-11.43	8	Pass
2437	-11.1		
2462	-11.91		

PSD NVNT 802.11b 2412MHz Ant1




Date: 8.JUL.2022 20:02:49

PSD NVNT 802.11b 2437MHz Ant1



Date: 8.JUL.2022 20:04:54


PSD NVNT 802.11b 2462MHz Ant1



Date: 8.JUL.2022 20:05:59


IEEE 802.11g			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-14.88	8	Pass
2437	-14.33		
2462	-14.37		

PSD NVNT 802.11g 2412MHz Ant1




Date: 8.JUL.2022 20:26:41

PSD NVNT 802.11g 2437MHz Ant1



Date: 8.JUL.2022 20:31:04


PSD NVNT 802.11g 2462MHz Ant1



Date: 8.JUL.2022 20:32:56


IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-16.21	8	Pass
2437	-15.51		
2462	-15.70		

PSD NVNT 802.11n(HT20) 2412MHz Ant1




Date: 8.JUL.2022 20:34:38

PSD NVNT 802.11n(HT20) 2437MHz Ant1



Date: 8.JUL.2022 20:36:22


PSD NVNT 802.11n(HT20) 2462MHz Ant1




Date: 8.JUL.2022 20:38:01

IEEE 802.11n(HT40)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2422	-18.24	8	Pass
2437	-18.16		
2452	-18.29		

PSD NVNT 802.11n(HT40) 2422MHz Ant1




PSD NVNT 802.11n(HT40) 2437MHz Ant1



Date: 8.JUL.2022 20:41:35

PSD NVNT 802.11n(HT40) 2452MHz Ant1



Date: 8.JUL.2022 20:45:53

12. Antenna Port Emission

12.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-12
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-12

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

12.2 Measuring Instruments and Setting

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

12.3 Test Procedures

The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02 .

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

12.4 Block Diagram of Test setup




12.5 Test Result


PASS.

Please refer to following pages.


Tx. Spurious 802.11b 2412MHz Ant1 Emission




Tx. Spurious 802.11b 2437MHz Ant1 Emission




Tx. Spurious 802.11b 2462MHz Ant1 Emission




Tx. Spurious 802.11g 2412MHz Ant1 Emission




Tx. Spurious 802.11g 2437MHz Ant1 Emission




Tx. Spurious 802.11g 2462MHz Ant1 Emission




Tx. Spurious 802.11n(HT20) 2412MHz Ant1 Emission




Tx. Spurious 802.11n(HT20) 2437MHz Ant1 Emission




Tx. Spurious 802.11n(HT20) 2462MHz Ant1 Emission




Tx. Spurious 802.11n(HT40) 2422MHz Ant1 Emission



Tx. Spurious 802.11n(HT40) 2437MHz Ant1 Emission



Tx. Spurious 802.11n(HT40) 2452MHz Ant1 Emission



13. Antenna Application

13.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result

The EUT'S antenna is an PCB antenna. The antenna's gain is 1.3dBi and meets the requirement.

14. Photos of EUT

-----The end of report-----