

NOTES: UNLESS OTHERWISE SPECIFIED

PURCHASED LABEL

1. PRINT PER LABEL CONTENT SHOWN.


2 PRINTING SPECIFICATION:

INK COLOR - BLACK
BACKGROUND - WHITE
MATERIAL - 2mil POLYESTER with 1 mil CLEAR OVERCOAT
ADHESIVE - 1.8 mil #350 ACRYLIC

LABEL SIZE - 2.0 x 1.0 ± .02
CORNER RADIUS - .05 ± .02
ROLL SIZE - 500, MAX

3 INNER DIE CUT: 1.25 x 0.5 ± .02

4. DIE CUT TO LINER.
PERFORATE LINER BETWEEN LABELS.
PART NUMBER TO BE PRINTED ON THE WASTE MATRIX.
5. LABEL MUST CONFORM TO UL 969 AND CSA 22.2 NO. 0.15-95 AND
SHALL BE UL APPROVED MATERIAL, WITH SUPPLIER NAME AND
LABEL NAME OR DESIGNATION ON INSIDE OF ROLL CORE.
6. LABEL MUST BE PROCURED FROM UL AUTHORIZED
SUPPLIER.
7. REFERENCE S14913.
8. THIS PART IS A U.L. CRITICAL PART. ANY CHANGES TO THIS PART
MUST BE REVIEWED BY EMC/SAFETY GROUP. LABEL TO BE U.L.
RECOGNIZED COMPONENT CATEGORY PGDQ2/PGDQ8.
EMC/SAFETY GROUP MUST REVIEW ALL SUPPLIERS.
9. THIS PART/ASSEMBLY SHALL BE COMPLIANT PER THE
LATEST REVISION OF ABBOTT SPECIFICATION S205053.




CONFIDENTIAL INFORMATION

CONTAINS TRADE SECRET AND/OR CONFIDENTIAL INFORMATION
WHICH IS THE PROPERTY OF ABBOTT LABORATORIES. AS PROVIDED
BY 21CFR 20.61. DO NOT DISCLOSE TO THE PUBLIC.

UNLESS OTHERWISE SPECIFIED:	DWN BY: S. Goldston	DATE: 03/03/23	 ABBOTT DIAGNOSTIC DIVISION ABBOTT LABORATORIES 1921 HURD DRIVE IRVING, TEXAS 75038, USA			
	MATERIAL: 2		TITLE: LABEL, SPR FCC - IC ID			
	APPLIED FINISH: None					
DIMENSIONS IN INCHES TOLERANCES .XX ± .02 .XXX ± .010 ANGULAR ± 2° 63 ✓ THREADS CLASS 2A OR 2B REMOVE BURRS AND SHARP EDGES .02 MAX.	SCALE 1/1 SIZE B DWG NO. 80005174-101 REV. A					
			DO NOT SCALE DRAWING		SHEET 1 OF 1	

1 2 3 4

ACHTUNG VORENTWURF! Nur zur Information.



Fonts:

1) Calibri 8 normal

2) Calibri 7 normal

C

D

*: Deviating dimensions require the consent of Abbott /
*: Abweichende Maße bedürfen der Zustimmung durch Abbott

E

Material requirements:
self-adhesive, abrasion-proof, temperature-resistant from -20 to +80°C /
Materialanforderungen:
Selbstklebend, abriebfest und temperaturbeständig von -20 bis +80°C

		General tolerances		Surface finish		Scale 1:1		Weight: 0.00 g		
		DIN ISO 2768 - mK		DIN ISO 1302		Material		Sale No. 12879	Revision B01	
		Date		Signature		Title Component Label SpiralSwitch				
		Cre. Part 03.12.2020		kiw						
		Cre. Drw. 03.12.2020		kiw						
		Appv'd								
		Standard								
				Sachsenkamp 5, 20097 Hamburg		Article No. 20037086			Sheet 1 / 1	
						A4				
B	Size Code changed	28.07.2023	kiw							
Rev.	Change	Date	Name	Refer to protection notice ISO 16016		Replacement for:		Replaced by:		

1

2

3

4

F

FCC/IC label location
(Permanent acrylic adhesive)

Component label
IC HVIN location

